NOT MEASUREMENT SENSITIVE

MIL-I-3575/44E
23 May 1995
SUPERSEDING
MIL-I-3575/44D
22 June 1994

MILITARY SPECIFICATION SHEET


INSIGNIA, SERVICE CAP, WARRANT OFFICERS, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-3575.



PIERCED



DASH NO.
-1: Male
-2: Female

MATERIAL: Red Brass

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT (Overall): 1-1/2 inches (3.81 cm) (REF)
WIDTH (Overall): 2-1/32 inches (5.16 cm) (REF)
THICKNESS (At Wing Tips): 0.047 inch + 0.016 inch - 0 (0.119 cm + 0.04 cm -0)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:25Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to measurements taken from the Government furnished hub or die.

2. Pierced areas shall be as indicated.

3. A forcer may be used to bring up the design provided the use of the forcer does not result in a thickness of the breast of less than 0.060 inch (0.152 cm).

4. Attaching device for Dash -1 shall be screw post with thumb nut and two registering prongs located as indicated. The screw post shall be 1/2 inch + 1/32 inch - 0 inch (1.27 cm + 0.08 cm - 0 cm) in length. The registration prongs shall 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) in length and shall be located 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm) from the top of the wings, 3/8 inch ± 1/64 inch (0.95 cm ± 0.04 cm) from each side and 1 inch ± 1/64 inch (2.54 cm ± 0.04 cm) apart. Attaching device for Dash -2 shall be two prong and clutch located on horizontal center line of both sides of the wreath. A registration prong shall not be required for Dash -2.

5. Insignia shall be dapped in the horizontal direction along a 4 inch ± 1/64 inch (10.16 cm ± 0.04 cm) radius.

6. Insignia may be manufactured using 22 karat gold plate with nickel underplating for commercial sale only which shall match TIOH Metal Finish Chip Number 11.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0794)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:25Z
Check the source to verify that this is the current version before use.