MIL-C-48258 (PA)
24 March 1975

MILITARY SPECIFICATION

CARTRIDGE, 40MM, PRACTICE, M407A2;

PROJECTILE METAL PARTS

FOR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts for one type of cartridge designated as Cartridge, 40MM, Practice, M407A2.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-C-5541	- Chemical Film and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS

PICATINNY ARSENAL

9287443 - Body and Skirt Assembly

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117-73 - Standard Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (Dwg. 9287443), all associated drawings, and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents. All marking and stamping shall be neat and sharply defined.

3.4 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (See 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

3.5 First Article Inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions.-Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 (PA) shall apply and are hereby made a part of this detail specification.

4.2 Classification of Inspections.-The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection.-

4.3.1 Submission.-The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Skirts	8886344	50
Bodies	9287444	50
Body and Skirt Assemblies	9287443	50

4.3.2 Inspections to be Performed.-See MIL-A-48078 (PA) and Table 1 herein.

4.3.3 Rejection.-See MIL-A-48078 (PA)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

TABLE 1 - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48258 (PA)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER
	Body and Skirt Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Skirt (Dwg. 8886344)				
	Examination for Defects	50		3.2	4.4.2.1
	Salt Spray	4		3.2	4.5.4
	Body (Dwg. 9287444)				
	Examination for Defects	50		3.2	4.4.2.2
	Body and Skirt Assembly (Dwg. 9287443)				
	Examination for Defects	50		3.2	4.4.2.3
	Push out test	50		3.2	4.5.2
	Air pressure test	50		3.2	4.5.3

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation.-Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (PA).

4.4.2 Examination.-See MIL-A-48078 (PA).

a. Sampling Plans.-Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48258 (PA)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8886344
4.4.2.1	Skirt				NEXT HIGHER ASSEMBLY 9287443
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special	None defined				
Major A	None defined				
Major B					
131	Distance between fuze seating surface and body seating surface		0.40%	3.2	Gage
132	Perpendicularity of fuze seating surface with bourrelet		0.40%	3.2	Gage
133	Perpendicularity of body seating surface with bourrelet		0.40%	3.2	Gage
134	Salt spray test	(a)	(a)	3.2	4.5.4
Minor					
201	Total length		0.65%	3.2	Gage
202	Evidence of poor workmanship		0.65%	3.3	Visual

(a) Sampling and AQL shall be in accordance with MIL-C-5541.

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48258 (PA)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9287444
4.4.2.2	Body				NEXT HIGHER ASSEMBLY 9287443
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined	See 4.5.1			
Special	None defined				
Major A	None defined				
Major B					
131	Weight improper		0.40%	3.2	Balance
132	Crack		0.40%	3.2	Visual
Minor					
201	Large outside diameter		0.65%	3.2	Gage
202	Body identification missing		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-48258 (PA)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9287443
4.4.2.3	Body and Skirt Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Special	None defined				
Major A					
101	Push out test	32 per shift	0.65%	3.2	4.5.2
102	Air pressure test		100%	3.2	4.5.3
103	Bourrelet diameter		0.40%	3.2	Gage
104	Diameter between rotating bands		0.40%	3.2	Gage
105	Diameter of rotating bands		0.40%	3.2	Gage
106	Profile of rotating bands		0.40%	3.2	Gage
Major B					
131	Distance from curved surface to rotating bands		0.40%	3.2	Gage
132	Diameter of fuze cavity		0.40%	3.2	Gage
133	Gap, maximum (max.)		0.40%	3.2	Gage
Minor					
201	Skirt color incorrect		0.65%	3.2	Visual
202	Adhesive not full 360°		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.-Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection Equipment.-The inspection equipment required to perform the examinations and tests prescribed herein is described in the Paragraph Reference/Inspection Method column in the tables starting with Paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.-

4.5.1 Dimensional control of molded or plastic parts.-In place of the normal sampling and inspections associated with the Classification of Defects, and after a curing time for the parts has been approved (See Note 1) a sample of three (3) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4.2.2 after continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request. Contractor designs of gages and test equipment required to perform the inspections listed herein shall be forwarded to Commander, Picatinny Arsenal, Dover, New Jersey 07801, Attn: SARPA-QA-T for approval prior to manufacture of equipment. The noted sub-paragraphs identify those items and minimum inspections subject to the requirements of this paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

NOTE 1: In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60 etc mins) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Picatinny Arsenal, Dover, New Jersey 07801 Attn: SARPA-QA-A-S. If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

4.5.2 Push out test of body and skirt assembly.-The body and skirt assembly shall be placed in a Government approved fixture and the load specified on Dwg. 9287443 shall be applied. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.5.3 Air pressure of body and skirt assembly.-The body and skirt assembly shall be placed in a Government approved fixture and the required air pressure specified on Dwg. 9287443 shall be applied. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.5.4 Salt Spray.-This test shall be conducted in accordance with ASTM B 117 except as noted on applicable drawing. This test is a destructive test. Parts so tested shall not be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level C.-See 5.2.1

5.2 Packing.-

5.2.1 Level C.-The assemblies shall be packed in accordance with MIL-STD-1169.

5.3 Marking.-Marking of the carton shall comply with MIL-STD-1169.

5.4 Shipping.-When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended Use.-The components covered by this specification are intended for use on the Cartridge, 40MM, Practice, M407A2.

6.2 Ordering Data.-See MIL-A-48078 (PA).

6.3 Submission of Inspection Equipment Designs for Approval.-See MIL-A-48078 (PA). Submit equipment designs as required to Commander, Attn: SARPA-QA-T, Picatinny Arsenal, Dover, NJ 07801.

6.4 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations and tests to Commander, Picatinny Arsenal, Attn: SARPA-QA-A-S.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1310-A036

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:19Z
Check the source to verify that this is the current version before use.