MILITARY SPECIFICATION

CARTRIDGE, 152MM, TP-T, M411A3
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-50902A (PA) dated 9 August 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

*Delete 3.12.1 in its entirety and substitute the following:
"3.12.1 Maximum (max.) projected areas and dimensions of cavities outside Segment A (See Figure 1) shall be:

Sum of areas of all cavities (square inches) 1.5

Max. dimension of any cavity (inches) 1.5"

Delete 3.12.2 in its entirety.

*4.4.2.13, Defect 103: Change "100%" to read "1.0%"

*4.4.3.6 Add: "If any skid document indicates time in the conditioning bay greater than the maximum total requirement, the cartridges on the skid represented by that document shall be considered rejected, and removed from the lot."

*Delete 4.4.3.7 and substitute:
"4.4.3.7 Moisture Content of Cartridge Case.-

4.4.3.7.1 Cartridge Cases and Bases, Prior to Assembly.-A continuous record shall be kept of temperature (°F) and relative humidity (RH) in any and all areas where cartridge cases or bases are held after removal from the inner-most protective pack. If either temperature or RH goes outside the applicable requirements, all cases and bases exposed to the nonconforming environment shall be conditioned in accordance with the applicable requirement, prior to assembly. Any cartridge assembled with cases or bases so exposed, and not so con-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

ditioned, shall have 3 hours added to the total min. conditioning requirement for that skid which includes such cartridges. Any such addition shall be conspicuously noted on the skid document.

4.4.3.7.2 Cartridges in Conditioning Bay.-Just prior to removing each skid of cartridges from the conditioning bay, the temperature and RH in the conditioning bay shall be checked and recorded on the skid document. The skid shall not be removed from the conditioning bay if the temperature or RH has been outside the applicable requirements at any point in time during the min. total conditioning requirement for that skid (i.e. over the last 1 or 4 hours, as applicable). Instead, the temperature and RH in the conditioning bay must be corrected to reach an acceptable level and the moisture test specified in MIL-STD-286B, Method 101.4, must be performed on one cartridge selected at random from the skid which was scheduled for removal. This cartridge will represent all cartridges in the conditioning bay at the time the discrepancy was observed, having a min. total conditioning requirement less than, or equal to, that of the representative cartridge. The samples required for the test shall be prepared as follows: Two .025 gm (approximate) samples shall be sectioned from the case body at random locations and two .025 gm (approximate) samples shall be sectioned from the case base. The temperature control shall be set at 100 degrees C with a timer setting of 15 minutes. Any cartridges in the conditioning bay during this test sequence, and in compliance with applicable conditioning requirements, may be removed. Cartridges represented by the samples, and not in compliance with applicable conditioning requirements, shall remain identified until successful performance during the moisture content test is indicated. Acceptable performance during the moisture test will qualify the skid for removal from the conditioning bay and shall reinstate normal inspection for temperature and RH. If the samples fail to comply with the applicable requirement, all cartridges represented by that sample, not otherwise qualified for removal from the conditioning bay, will remain in the bay an additional 2 hours + 1/2 hour (in addition to the required conditioning time for each skid of cartridges). Any such addition shall be conspicuously noted on the document of each skid affected. One hour prior to completion of the additional curing time, samples shall again be taken from the cartridge originally selected and subjected to

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:43Z
Check the source to verify that this is the current version before use.

testing as specified above. Failure of these samples to comply with the applicable requirement shall reject the skid originally scheduled for removal and will require moisture testing as above on one cartridge selected at random from each subsequent skid of cartridges until acceptable performance is demonstrated. Skids indicating non-conformance shall also be rejected. Normal inspection may be reinstated coincident with determination of acceptable moisture content. Upon return to normal inspection, all cartridges remaining in the oven and represented by the original moisture sample shall be considered acceptable as long as the deviation from RH or temperature requirements does not exceed the amount of such deviation at the time the acceptable moisture sample was taken.

4.4.3.7.3 Cartridges.-A continuous record shall be kept of temperature and relative humidity in any and all areas where cartridges are held prior to or after completion of required conditioning. If either temperature or relative humidity goes outside the applicable requirement, or if the length of time between completion of conditioning and assembly of barrier bag exceeds the applicable requirement, all cartridges in non-conformance shall be subject to additional conditioning in accordance with the applicable requirement. Any such addition shall be conspicuously noted on the skid document."

4.5.6.6 Delete the last sentence and substitute the following:

"In addition, the gun tube and breech shall be visually inspected after the cameras stop and prior to chambering of the next round, or cleaning. Any residue, excluding normal soot, shall be recovered and placed in a suitable envelope labeled with lot and test round numbers and approximate location from which the residue was recovered. All residue recovered shall be forwarded to Picatinny Arsenal, SARPA-QA-A-A for evaluation."

* From prior Amendments

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number 1320-A- 338

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:43Z
Check the source to verify that this is the current version before use.