NOT MEASUREMENT SENSITIVE

MIL-PRF-83495B
AMENDMENT 1
16 March 1998

PERFORMANCE SPECIFICATION
TECHNICAL MANUALS—ON-EQUIPMENT MAINTENANCE
MANUAL SET

This amendment forms a part of MIL-PRF-83495B, dated 1 March 1996, and is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

1. The attached insertable replacement pages listed below are replacements for stipulated pages. When the new pages have been inserted in the document, insert the amendment as the cover sheet to the specification.

NEW PAGE	DATE	SUPERSEDED PAGE	DATE
29	16 March 1998	29	1 March 1996
30	16 March 1998	30	1 March 1996
31	16 March 1998	31	1 March 1996
32	16 March 1998	32	1 March 1996

2. Text substitutions shall be accomplished as follows:

PAGE 11

Paragraph 3.4.2.2: Add to paragraph, “Function and task title text shall not be underlined.”

PAGE 12

Paragraph 3.4.2.4: Replace last sentence with, “If the proposed JG manual exceeds these page limitations, it shall be divided at lowest level nearest the complete function. Tasks shall not be divided unless absolutely necessary. The contractor’s recommended breakout shall be approved by the acquiring activity on a case-by-case basis.”

AMSC F6846 **AREA TMSS**

Distribution Statement A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

Paragraph 3.4.3.1.1:

Add, to the first sentence, between the words "...for the listed LRU or item" and before the comma, "(if a function consists of only one task, only the function shall be listed)".

Add to sentence ending, "...manuals in that series." the words, "...; page numbers shall not be listed for other manuals."

Add to the last sentence, "...; paragraph or task numbers shall not be listed

PAGE 14

Paragraph 3.4.3.2.1.1: Add, before the last sentence, "Optional headings shall not be listed if not used."

PAGE 15

Paragraph 3.4.3.2.1.1.7: After the title, "Checklist requirements." add, "(Optional)."

PAGE 15

Paragraph 3.4.3.2.1.2: Add new first sentence, "Tasks shall begin on a left-hand page."

PAGE 16

Paragraph 3.4.3.2.1.2.1 e: In "Step 7, SPECIAL INSTRUCTION." change the word "insure" to "ensure".

Paragraph 3.4.3.2.1.2.2: Add sentence to the end of the paragraph, "To conserve space, follow-on maintenance reference information may be listed on the same page and immediately following the last task text, space permitting."

PAGE 17

Paragraph 3.4.3.2.1.3 e: Delete and substitute, "Figure numbers shall not be used for JG task illustrations.

Paragraph 3.5.2.3: Change the end of the sentence reading, "... the chapters shall be subsystem oriented." to read, "... the chapters shall be sectionalized by subsystem."

PAGE 18

Paragraph 3.5.5.1: To the sentence ending with, "...contents shall refer to SSSNs" delete the period and add, "or page numbers as required, e.g., single manual: SSSNs; system oriented manuals: page numbers."

PAGE 21

Paragraph 3.5.5.6: Last sentence, delete, "or manual."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

MIL-PRF-83495B (USAF)
AMENDMENT 1

NOTE: Updated standard generalized markup language (SGML) documents supporting this amendment are available from the PA or on the World Wide Web page: http://wpcdso1.wpafb.af.mil.

CONCLUDING MATERIAL

Custodian:
Air Force - 16

Review Activities:
Air Force - 01, 10, 99

Preparing Activity:
Air Force - 16
(Project No. TMSS-F638)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

2-2. ELECTRONIC EQUIPMENT COOLING SET MODULATING VALVE ASSEMBLY, 2121FV1, REMOVAL AND INSTALLATION.

INPUT CONDITIONS

Applicability: All

Required Conditions:

- Aircraft safe for maintenance (JG10-30-01)
- Gun barrels removed (JG94-51-02)
- Gun trough access cover B removed (General Maintenance)
- Cockpit cold air check valve removed (JG21-22-11)
- UHF radio control removed (JG23-22-06)
- Closeout panel A removed (General Maintenance)
- Gun trough access cover A removed (General Maintenance)

SAMPLE PAGE
NOT TO SCALE

Personnel Recommended: Two

- Technician A performs removal and installation of valve.
- Technician B assists in removal and installation of valve (access panel 2405).

FIGURE 2. *Example jog guide input conditions page.*

Supersedes page 29
of MIL-PRF-83495B
of 1 March 1996.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

TO 1F-1A-2-21JG-20-1

2-2. (Contd)

Support Equipment:

Adapter Hose, Part No. 16A41006-1

Generator Set, Type A/M32A-60A or equivalent

Maintenance Platform, Type B-1 or equivalent

Torque Wrench (torque range 0-80 inch-pounds)

Consumables:

Nomenclature	Specification/ PN	CAGE Code	Use	Reference
Cheesecloth or equivalent	CCC-C-123	20999	AR	2-2-2
Grease, Pneumatic	MIL-G-1234	81349	AR	2-2-2
Leak Detection Compound	MIL-L-12345	81349	AR	2-2-2
Packing	MS1234-04	81352	1	2-2-2
Tape, Electrical Lacing	DPS 3CL AR	00768	1	2-2-2

SAMPLE PAGE
NOT TO SCALE

Safety Conditions: None

Additional Data:

Reference	Purpose
TO 1F-1A-2-00GE-00-1	To prepare surfaces for electrical bonding

21-21-02

2-10

FIGURE 2. *Example job guide input condition page - Continued.*

Supersedes page 30
of MIL-PRF-83495B
of 1 March 1996.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.

2-2. ELECTRONIC EQUIPMENT COOLING SET MODULATING VALVE ASSEMBLY, 2121FV1, REMOVAL AND INSTALLATION.

INPUT CONDITIONS

Applicability: All

Required Conditions:

- Aircraft safe for maintenance (JG10-30-01)
- Gun barrels removed (JG94-51-02)
- Gun trough access cover B removed (General Maintenance)
- Cockpit cold air check valve removed (JG21-22-11)
- UHF radio control removed (JG23-22-06)
- Closeout panel A removed (General Maintenance)
- Gun trough access cover A removed (General Maintenance)

SAMPLE PAGE
NOT TO SCALE

Personnel Recommended: Two

- Technician A performs removal and installation of valve.
- Technician B assists in removal and installation of valve (access panel 2405).

FIGURE 3. *Example job guide task.*

Supersedes page 31
of MIL-PRF-83495B
of 1 March 1996.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.




FIGURE 3. *Example job guide task - Continued.*

Supersedes page 32
of MIL-PRF-83495B
of 1 March 1996.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:18Z
Check the source to verify that this is the current version before use.