MIL-F-60311 (MU)
17 December 1964
SUPERSEDING
MIL-F-12578B (MU)
29 July 1963
(See Section 6)

MILITARY SPECIFICATION

FUZE, POINT DETONATING, M508A1,
METAL PARTS FOR

1. SCOPE

1.1 This specification covers the metal parts for one type of fuze designated as Fuze, Point Detonating, M508A1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for.
MIL-P-10025 - Packaging, Packing and Marking for Interplant shipment of Inert Ammunition Components, General Specification for.
MIL-I-45208 - Inspection Requirements, General Specification for.
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

7549042 - Body Assembly
7549044 - Head, Metal Parts Assembly
7549050 - Ogive
7549055 - Screw, Detonator Retaining
7549056 - Screw, Detonator Retaining
7549060 - Tube, Flash

PUBLICATIONS

ORDNANCE CORPS

IEL-7155541 - Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The parts shall comply with all requirements specified on Drawing (dwg.) 7549042; 7549044; 7549050; 7549060; 7549055 and 7549056, as applicable, and with all requirements specified in applicable specifications.

3.3 Firing pin assembly load.-The firing pin assembly shall not chip, crack, or break when subjected to a minimum (min.) tension load of 70 pounds in the test specified in 4.4.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

3.4 Spring embrittlement.-The interrupter spring shall not break when extended to the min. point of permanent distortion in the test specified in 4.4.2.

3.5 Workmanship.-All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Contractor inspection system.-The contractor shall provide and maintain an effective inspection system in compliance with the requirements of Specification MIL-I-45208. The contractor's quality assurance system shall contain a procedure for the reporting of critical defectives found during the course of his inspection and during inspection by the Government. Any critical defect encountered, unless annotated by an asterisk (*) to the right of the characteristic code number (see 6.2), will be reported within 48 hours. A monthly summary report covering those critical defects annotated by an asterisk will be furnished. The agencies to whom the reports will be furnished are identified in paragraph 6.6. The reports shall contain, as a minimum, the following information:

a. Contractor and contract number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

b. Number and revision date of specification.
c. Characteristic code number.
d. Lot or serial number.
e. Number of defectives found.
f. Assignable cause or analysis of occurrence.
g. Corrective action taken or recommended. When the corrective action is beyond the control of the contractor or the scope of the contract, the report shall contain the contractor's recommendation to the Government.

4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:
a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.
b. Number of units of product inspected.
c. Results obtained for all inspection performed.
d. Drawing, specification number and date, together with an identification and date of changes.
e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.
f. Number of items in the lot.
g. Date submitted.
The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL-I-45208

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Initial production inspection.

4.2.1 Prior to the start of regular production, the contractor shall submit an initial production sample to a government facility as designated by the contracting officer (see 6.4) for evaluation in accordance with the provisions of 4.2.2. The initial production sample shall consist of 25 complete sets of parts (i.e., 25 each of every component and every subassembly), plus 25 firing pin assemblies for load testing, 25 springs for embrittlement testing, 25 cups for load testing, 50 body assemblies for arming and non-arming testing which have been produced or purchased by the contractor and which have been manufactured using the same production process, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of compliance for materials. An initial production sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, materials used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer.

4.2.2 Inspections to be performed.-The components and subassemblies will be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.2.3 Rejection.-If any sub-assembly or component fails to comply with any of the applicable requirements, the initial production sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new initial production sample or portion thereof. Until an initial production sample is accepted, the contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the contracting officer.

4.3 Inspection provisions.

4.3.1 Lot formation.-A lot shall consist of metal parts of one fuze designation produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government shall not necessitate changing the lot interfix number.

4.3.2 Examination.-Inspection for Critical defects shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Cup, support (see dwg. 7549057 covering a detail of dwg. 7549044).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Crack	Visual	01001*
Minor:	AQL 2.5 percent		
201.	Outside diameter of flange, min.	Gage	01002
202.	Depth to the bottom	Gage	01003
203.	Outside diameter under flange, min.	Gage	01004
204.	Outside diameter, maximum (max.)	Gage	01005
205.	Diameter of hole, max.	Gage	01006
206.	Evidence of poor workmanship (see 3.5)	Visual	01007

4.3.2.2 Screw, detonator retaining (see dwgs. 7549055 or 7549056)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Pitch diameter of thread, min.	Gage	02001
102.	Major diameter of thread,	Gage	02002
103.	Slot missing	Visual	02003
Minor:	AQL 4.0 percent		
201.	Width of hexagonal opening (when applicable)	Gage	02004
202.	Total length	Gage	02005
203.	Diameter of hole (when applicable)	Gage	02006
204.	Pitch diameter of thread, max.	Gage	02007
205.	Width of the slot	Gage	02008
206.	Distance from top to the thread (when applicable)	Gage	02009
207.	Evidence of poor workmanship (see 3.5)	Visual	02010
208.	Thread damaged	Visual	02011

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.3.2.3 Firing pin assembly (see dwg. 7549058, covering a detail of dwg. 7549044).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Length from point to flange, max	Gage	03001
102.	Total length	Gage	03002
103.	Thickness of flange	Gage	03003
104.	Diameter and profile of pin point	Gage	03004
105.	Pin loose	Manual	03005
Minor:	AQL 1.5 percent		
201.	Diameter under flange	Gage	03006
202.	Diameter of flange	Gage	03007
203.	Evidence of poor workmanship (see 3.5)	Visual	03008

4.3.2.4 Spring, interrupter (see dwg. 7549047, covering a detail of dwg. 7549042)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Solid height	Gage	04001
102.	Outside diameter, max	Gage	04002
Minor:	AQL 1.5 percent		
201.	Inside diameter, min	Gage	04003
202.	Ends not closed	Visual	04004
203.	Evidence of poor workmanship (see 3.5)	Visual	04005

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.3.2.5 Interrupter (see dwg. 7549046, covering a detail of dwg. 7549042)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Diameter	Gage	05001
102.	Small outside diameter	Gage	05002
103.	Length	Gage	05003
104.	Length of small outside diameter	Gage	05004
105.	Finish improper on outside diameter	Visual	05005
Minor:	AQL 1.5 percent		
201.	Diameter of spring cavity	Gage	05006
202.	Depth of spring cavity	Gage	05007
203.	Protective coating missing or contains bare spot	Visual	05008
204.	Evidence of poor workmanship (see 3.5)	Visual	05009

4.3.2.6 Tube, flash (see dwg. 7549060)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Pitch diameter of thread	Gage	06001
102.	Major diameter of thread	Gage	06002
103.	Length to end of thread, min	Gage	06003
104.	Thread damaged	Visual	06004
Minor:	AQL 2.5 percent		
201.	Total length	Gage	06005
202.	Outside diameter	Gage	06006
203.	Length of thread pilot	Gage	06007

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

204.	Diameter of flash hole for total length, min	Gage	06008
205.	Diameter of thread pilot	Gage	06009
206.	Evidence of poor workmanship (see 3.5)	Visual	06010

4.3.2.7 Ogive (see dwg. 7549050)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Wall thickness	Gage	07001
102.	Crack, deep scratch or dent	Visual	07002
Minor:	AQL 4.0 percent		
201.	Inside diameter of body seat surface	Gage	07003
202.	Total length	Gage	07004
203.	Outside diameter of head end	Gage	07005
204.	Inside diameter of head end	Gage	07006
205.	Outside diameter at body end	Gage	07007
206.	Location of inside projections	Gage	07008
207.	Distance between inside projections	Gage	07009
208.	Profile of inside projections	Gage	07010
209.	Angle on body	Gage	07011
210.	Marking misleading or unidentifiable	Gage	07012
211.	Evidence of poor workmanship (see 3.5)	Visual	07013

4.3.2.8 Body (see dwg. 7548045, covering a detail of dwg. 7549042)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Major:		AQL 1.0 percent	
101.	Pitch diameter of external thread	Gage	08001
102.	Major diameter of external thread min	Gage	08002
103.	Minor diameter of flash tube thread, max	Gage	08003
104.	Pitch diameter of flash tube thread	Gage	08004
105.	True position of interrupter cavity with flash hole	Gage	08005
106.	Length of interrupter cavity protrusion beyond centerline	Gage	08006
Minor:		AQL 6.5 percent	
201.	Thickness of boss	Gage	08007
202.	Thickness of flange	Gage	08008
203.	Diameter across wrench slots	Gage	08009
204.	Width of wrench slots, min	Gage	08010
205.	Location of interrupter cavity	Gage	08011
206.	Small diameter of interrupter cavity	Gage	08012
207.	Diameter of interrupter closing disc	Gage	08013
208.	Total length	Gage	08014
209.	Length from base end to bottom of flash tube cavity	Gage	08015
210.	Length from base end to flange	Gage	08016
211.	Length of external thread undercut, max	Gage	08017
212.	Length of external thread pilot, max	Gage	08018
213.	Depth of small interrupter cavity	Gage	08019
214.	Depth of large interrupter cavity	Gage	08020
215.	Diameter of flange	Gage	08021
216.	Angle of base	Gage	08022
217.	Diameter of external thread undercut, min	Gage	08023
218.	Diameter of flash hole	Gage	08024
219.	Diameter of ogive seat	Gage	08025
220.	Diameter of shoulder below flange	Gage	08026

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

221.	Length from rear end to shoulder below flange	Gage	08027
222.	Depth of relief cavity in base	Gage	08028
223.	Diameter of safety disc cavity	Gage	08029
224.	Plug gage fails to pass through flash hole	Gage	08030
225.	Finish improper	Visual	08031
226.	Evidence of poor workmanship (see 3.5)	Visual	08032
227.	Protective coating missing or contains bare spot	Visual	08033

4.3.2.9 Head (see dwg. 7549061, covering a detail of dwg. 7549044)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.0 percent		
101.	Minor diameter flash tube thread, max	Gage	09001
102.	Pitch diameter flash tube thread	Gage	09002
103.	Minor diameter detonator retaining screw thread	Gage	09003
104.	Pitch diameter detonator retaining screw thread	Gage	09004
105.	Diameter of firing pin assembly cavity	Gage	09005
Minor:	AQL 4.0 percent		
201.	Depth of flash tube thread, min	Gage	09006
202.	Depth of flash tube cavity	Gage	09007
203.	Depth to bottom of detonator retaining screw thread, min	Gage	09008
204.	Diameter of detonator cavity	Gage	09009
205.	Diameter of support cup counterbore, max	Gage	09010
206.	Length to ogive seat flange from face	Gage	09011

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

207.	Concentricity of firing pin hole with firing pin assembly civity...Gage		09012
208.	Major outside diameter of flange, min.....Gage		09013
209.	Depth to bottom of firing pin assembly cavity.....Gage		09014
210.	Diameter of ogive seat surface....Gage		09015
211.	Diameter of firing pin hole.....Gage		09016
212.	Total length.....Gage		09017
213.	Outside diameter at rear end.....Gage		09018
214.	Wrench hole or ogive staking hole missing.....Visual		09019
215.	Evidence of poor workmanship (see 3.5).....Visual		09020

4.3.2.10 Disc, body closing (see dwg. 7549049, covering a detail of dwg. 7549042)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Hole, crack, or fracture.....Visual		10001
Minor:	AQL 2.5 percent		
201.	Thickness.....Gage		10002
202.	Diameter.....Gage		10003
203.	Evidence of poor workmanship (see 3.5).....Visual		10004

4.3.2.11 Body assembly (see dwg. 7549042)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Interrupter spring missing (as determined by tapping assembly lightly against solid object and then sighting through flash hole).Manual	Visual-	11001*

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

2.	Interrupter missing	Visual	11002*
3.	Interrupter in armed or partly armed position (does not completely obstruct flash hole)	Visual	11003*
4.	Body sealing cup or body closing disc crimp less than 360 degrees	Visual	11004*
5.	Body sealing cup or body closing disc punctured or cracked	Visual	11005*
Major:	AQL 0.40 percent		
101.	Thread damaged	Visual-Gage	11006
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	11007

4.3.2.12 Head metal parts assembly (see dwg. 7549044)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Length from firing pin point to detonator cavity	Gage	12001*
Major:	AQL 0.65 percent		
101.	Closing disc damaged	Visual	12002
102.	Firing pin point damaged	Visual	12003
103.	Firing pin assembly missing	Visual	12004
Minor:	AQL 2.5 percent		
201.	Length to ogive seat, max	Gage	12005
202.	Total length, max	Gage	12006
203.	Wrench hole missing	Visual	12007
204.	Closing disc crimp less than 360 degrees	Visual	12008
205.	Evidence of poor workmanship (see 3.5)	Visual	12009

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.3.3 Testing

4.3.3.1 Firing pin assembly load (see 3.3) Major defect, Code No. 03009.-The sampling plan shall be in accordance with Standard MIL-STD-105 using a sampling plan with an AQL of 0.40 percent. The test shall be performed as specified in 4.4.1.

4.3.3.2 Spring embrittlement (see 3.4) Major defect, Code No. 04006.-Thirty interrupter springs shall be randomly selected for this test. If one or more springs fail to comply with the specified requirements the lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.3 Support cup load (see dwg. 7549057) Major defect, Code No. 01008.-The sampling plan shall be in accordance with Standard MIL-STD-105 using a sampling plan with an AQL of 0.40 percent. The test shall be performed as specified in 4.4.3.

4.3.3.4 Arming (see dwg. 7549042) Major defect, Code No. 11008.-The sampling plan shall be in accordance with Standard MIL-STD-105 using a sampling plan with an AQL of 0.40 percent. The test shall be performed as specified in 4.4.4.

4.3.3.5 Non-Arming (see dwg. 7549042) Critical defect, Code No. 11009*.-This test shall be performed 100 percent in accordance with the procedure specified in 4.4.5. If any body assembly fails to comply with the requirements, it shall be classed defective and removed from the lot.

4.3.4 Inspection Equipment.-Index of Inspection Equipment Number IEL-7155541 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.3.4.3 Government use of contractor's inspection equipment.-The contractor shall as required make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor, as required by the Government in performance of its examination or test.

4.4 Test methods and procedures.

4.4.1 Firing pin assembly load.-The firing pin assembly shall be assembled in equipment that is in accordance with 4.3.4. The required load shall be applied, without impact, and the assembly observed for compliance with the requirement. Assemblies subjected to this test shall be scrapped.

4.4.2 Spring embrittlement.-The spring shall be pulled to the minimum point of permanent distortion using equipment in accordance with 4.3.4. Springs subjected to this test shall be scrapped.

4.4.3 Support cup load.-The support cup shall be placed in equipment that is in accordance with 4.3.4 and the required loads applied without impact. The cup shall be observed for compliance with the requirements. Support cups subjected to this test shall be scrapped.

4.4.4 Arming test of body assembly.-The unarmed body assembly shall be assembled in the test fixture in a vertical position, with the end containing the flash tube threads up, and be rotated counterclockwise (as viewed from the top) at the prescribed arming speed. The spindle shall be of the continuously operating type or it shall start from rest for each test. The rate of acceleration imparted to the body assembly

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

shall be as nearly uniform as practicable for each assembly tested. No assembly, prior to acceptance in the arming test, shall be rotated at a speed greater than that specified. If this test is performed on automatic equipment, it shall be performed prior to the assembly of the body closing disc in the body, after which the closing disc will be crimped in position. The assembly will be classed defective if any part of the interrupter is visible in the flash hole during the arming test.

4.4.5 Non-Arming test of body assembly.-The body assembly shall be tested as specified in 4.4.4 except that rotation shall be at the non-arming speed. If the interrupter does not completely obstruct the flash hole during and following the non-arming test, the assembly shall be classed defective. This test shall be performed subsequent to performance of the non-arming test.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packaging, packing and marking of fuze metal parts assemblies shall be in accordance with Specification MIL-P-10025.

5.2 Data cards.-Data card information shall be prepared for each lot in accordance with information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of tl contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action requi by the contractor with respect to commercial inspection equipment i described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contracto designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approva as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipme as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designed in the IEL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contracto need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspectio equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equip-ment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be sub-mitted for approval as specified in 6.3.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above.

6.3.7 Submission of contractor designs.-Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 Submission of initial production.-Instructions as to the location for the evaluation of the initial production sample shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal, and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal, Dover, New Jersey.

6.5 Supersession data.-This specification supersedes in part Military Specification MIL-F-12578B (MU).

6.6. Critical defect report

6.6.1 Submission of critical defect reports.-For U. S. Army Munitions Command procurement, one copy of each critical defect report will be furnished the cognizant Government inspection agency; the Army Ammunition Procurement and Supply Agency, ATTN: SMUAP-RO; Picatinny Arsenal, ATTN: SMUPA-ND.

6.6.2 Reporting to other services.-For other than U. S. Army Munitions Command procurements, critical defect reporting shall be as prescribed by the contracting officer.

Custodian:
Army-MU

Preparing Acitivity:
Army-MU

Project No. 1390-A423

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.