MILITARY SPECIFICATION

# LIFE RAFTS, INFLATABLE, LRU-16/P AND LRU-17/P

This specification is approved for use by the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers two types of life rafts which are designated LRU-16/P and LRU-17/P (see 6.2).

## 2. APPLICABLE DOCUMENTS

2.1 issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-B-636 | Boxes, Shipping, Fiberboard |
| PPP-C-795 | Cushioning Material, Flexible, Cellular, Plastic Film for Packing Applications |

MILITARY

| | |
|---|---|
| MIL-P-116 | Preservation-Packaging, Methods of |
| MIL-A-3339 | Anchors, Sea, Life Raft |
| MIL-I-6903 | Ink, Marking (for Parachutes and Other Textile Items) |
| MIL-O-81375 | Oral inflation Assemblies, Survival Equipment, Inflatable |
| MIL-C-83489 | Cloth, Coated, Nylon, polyurethane Coated |
| MIL-I-87108 | Inflation Assembly, FLU-2A/P |

STANDARDS

FEDERAL

| | |
|---|---|
| FED-STD-595 | Colors |

Bencficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: ASD/ENESS, Wright-Patterson AFB, OH 45433 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) at the end of this document or by letter.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

MILITARY

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-129 | Marking for Shipment and Storage |

DRAWINGS

AIR FORCE

| | |
|---|---|
| 64D2169 | Patterns - Storage Pockets, Life Raft |
| 64C2170 | Pocket, Storage - Life Raft Assembly |
| 76212 | Life Rafts, Inflatable, LRU-16/P and LRU-17/P |

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

* 3.1 First articles. When specified (see 4.4 and 6.2), the contractor shall furnish samples for first article inspection and approval .

3.2 Materials

* 3.2.1 Coated nylon cloth. The material for the primary buoyancy tube, the canopy, and the floor shall be coated nylon cloth and shall approximately match 35042 [Lusterless Blue) of FED-STD-595. The coated nylon cloth for the primary buoyancy tube of the LRU-16/P life raft, the primary buoyancy tube of the LRU-17/P life raft, and the floor of the LRU-l7/P life raft shall conform to type I of MIL-C-84389. The coated nylon cloth for the canopy of the LRU-16/P life raft and the floor of the LRU-l6/P life raft shall conform to type II of MIL-C-83489.

3.3 Design and construction. The design and construction of the life raft shall conform to Drawing 76212 and the detail drawings applicable thereto. In the event of conflict between the drawings and the text of this specification, the text of this specification shall govern.

3.3.1 Storage pockets. The parts of the storage pockets of the life raft shall conform to the patterns referenced on Drawing 64D2169 and shall be assembled in accordance with Drawing 64C2170.

3.3.2 Inflation assembly. The FLU-2A/P inflation assembly, which is a component of this life raft, shall not be furnished by the contractor.



Source: https://assist.dla.mil -- Downloaded: 2026l0-23T08:16Z
Check the source to verify that this is the currentversion before use.

* 3.5.3 Oral inflation tube clamp. The clamp that secures the oral inflation tube assembly to the oral tube shall be covered with protective tape or shrink tubing.

3.4 Performance

* 3.4.1 Operation. The life raft shall inflate to its design shape within 50 seconds after actuation of the FLU-2A/P inflation assembly and shall not show any evidence of constructional or material failure.

* 3.4.2 Pressure. A minimum of 10 minutes after the primary buoyancy tube of the life raft has been inflated to 5.0 pounds per square inch (PSIg) , the primary buoyancy tube shall still retain a pressure of not less than 4.75 psig and shall not show any evidence of constructional or material failure.

3.4.3 Leakage. A minimum of 6 hours after the primary buoyancy tube of the life raft has been inflated to a pressure of 2.0 psig, the primary buoyancy tube shall still retain a pressure of not less than 1.5 psi.

X 3.4.4 Canopy and floor inflation. Three hours after the inflatable floor and the inflatable canopy sections of the LRU-16/P life raft have been inflated through the oral inflation valve assembly to the design shape (10 inches of water pressure), the inflatable floor and the inflatable canopy sections of the LRU-16/P life raft shall have a retained pressure of 5 inches of water and shall not show any evidence of separation of any point of attachment of the “quilts” or of any seam.

3.4.5 Burst strength

*3.4.5.1 Floor and canopy. The inflatable floor and the inflatable canpoy sections of the LRU-16/P life raft shall not burst nor show any evidence of constructional or material failure at pressure less than 3.

* 3.4.5.2 Primary buoyancy tube. The primary buoyancy tube of the life raft shall not burst nor show any evidence of constructional or material failure at pressure less than 9.0 psig.

3.4.6 Oral inflation valve assembly. The oral inflation valve assembly shall conform to all of the performance requirements described in MIL-O-81375.

* 3.4.7 Primary buoyancy tube inflation. There shall be no restriction of flow of air into the primary buoyancy tube. There shall be no malfunction nor incompatibility of the inlet check valve. There shall be no malfunction of the oral inflation valve.

Source: https://assist.dla.mil -- Downloaded: 202610-23T08:16Z
Check the source to verify that this is the current version before use.

3.5 Weight . The maximum weight of the LRU-16/P life raft, excluding the FLU-2A/P inflation assembly, shall be 5.9 pounds, The maximum weight of the LRU-17/P life raft, excluding the FLU-2.A/P inflation assembly, shall be 3.0 pounds.

3.6 Volume . The volume of the packaged LRU-16/P life raft, excluding the FLU-2A/P inflation assembly, shall not exceed 400 cubic inches. The volume of the packaged LRU-17/P life raft, excluding the FLU-2A/P inflation assembly, shall not exceed 210 cubic inches.

3.7 Operational marking. The life raft shall be marked with the information specified in 3.7.1 through 3.7.3. This marking shall be silk screen and shall be made with white washproof ink. The marking specified in 5. .1.1, 3.7.1.2, 3.7.2, and 3.7.3 shall be in l/4-inch-lettering. The marking specified in 3.7.1.3 shall be in i-inch lettering.

3.7.1 Primary buoyancy tube

3.7.1.1 Inboard side. The inboard side of the primary buoyancy tube of the life raft, adjacent to the oral inflation valve pocket, shall be marked with the following information:

TO INCREASE PRESSURE, UNSCREW KNURLED RING.
PUSH VALVE MOUTHPIECE DOWN AND IMMEDIATELY
BLOW THROUGH INLET.

* 3.7.1.2 Outboard side. The outboard side of the cylinder sling of the life raft shall be marked with the following information:

TO REMOVE CYLINDER WITHOUT WRENCH, SPLIT
POCKET, ROTATE CYLINDER COUNTERCLOCKWISE
TO BREAK SEAL, UNCOUPLE.

3,7.1.3 Stern end. The upper portion of the stern end of the primary buoyancy tube of the life raft shall be marked with the following information:

CLIMB IN HERE.
CLOSE PARACHUTE CLIPS.

3.7.2 Large storage pocket. The large storage pocket of the life raft shall be marked with the following word: BEACON.

3.7.3 Small storage pocket. The small storage pocket of the life raft shall be marked with the following word: LIGHT.

* 3.8 Identification of product, The bottom of the life raft and the sea anchor shall be marked for identification.



Source: https://assist.dla.mil -- Downloaded: 2026l0-23T08:16Z
Check the source to verify that this is the currenversion before use.

* 3.8.1 Life raft. The marking of the bottom of the life raft shall be shall be made with white washproof ink, shall be l/2-inch and shall include the following information:

NSN 1/ 2/
LIFE RAFT. INFLATABLE
TYPE 1/
SERIAL NO. 1/ 3/ 4/
MANUFACTURE'S INDENTIFICATION 1/
CONTRACT NO. 1/ 4/
DATE OF MANUFACTURE (YEAR AND MONTH 1/ 4/

1/ The manufacturer shall include the applicable information.
2/ The national stock number for the LRU-16/P life raft is 4220-01-003-6763LS. The national stock number for the LRU-17/P life raft is 4220-NC-410689PLS.
3/ The procuring activity (see 6.2) will furnish the serial number to the manufacture.
4/ As an option to the requirement for silk screen, the information may be stenciled using white washproof ink that conforms to type IV of MIL-I-6903.

* 3.8.2 Sea anchor. The sea anchor shall be marked for identification in accordance with MIL-A-5339.

3.9 Workmanship. Workmanship shall be in accordance with high grade manufacturing practice covering this class of work. Because of the emergency use of the life raft, the details of workmanship shall be the highest quality to insure proper functioning of the life raft at all times.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.4)

(b) Quality conformance inspection (see 4.5).

4.3 Test conditions

4.3.1 Atmospheric conditions. Unless otherwise specified, all tests shall be made at an atmospheric pressure of 28 to 32 inches of mercury, at a temperature of 77 degrees ‘(plus or minus 18 degrees) Fahrenheit, and at a relative humidity of 80 percent or less.

4.3,1.1 Temperature correction. If the temperature at the conclusion of a test differs from the temperature at start of the test, correction shall be made for the change in value as follows: Subtract 0.031 psi for each degree Fahrenheit rise in temperature from the final pressure reading, Add 0.031 psi for each degree Fahrenheit drop in temperature from the final pressure reading.

4.3.1.2 Barometric pressure correction. If the atmospheric pressure at the conclusion of a test differs from the atmospheric pressure at the start of the test, correction shall be made for the change in value as follows: Add 0.049 psi for each 0.1 inch of mercury rise in barometric pressure to the final temperature-corrected pressure reading. Subtract 0.049 psi for each 0.1 inch of mercury drop in barometric pressure from the final tc~nperature-corrected pressure reading.

4.3.2 Sequence of inspection. The individual inspection shall be performed in the sequence listed in 4,5.1. The inspection specified for sampling plan A shall be performed in the sequence listed in 4.5.2.1.

* 4.3.3 Inflation assemblies, The inflation assemblies required to accomplish the tests specified herein shall be furnished by the manufacturer of the life raft . Each inflation assembly shall be a fully charged carbon dioxide cylinder and valve assembly that conforms to MIL-I-87108.

* 4.4 First article inspection. The first article inspection shall consist of all of the methods of inspection described herein. The first article samples shall be subjected to the first article inspection as follows: The LRU-16/P life raft shall be subjected to all of the methods of inspection described herein except the burst strength tests described in 4.6.6.1 and 4.6.6.2. The LRU-17/P life raft shall be subjected to all of the methods of inspection described herein except the burst strength tests described in 4.6.6.1 and 4.6,6.2 and the canopy and floor inflation test described in 4.6.5. The



Source: https://assist.dla.mil -- Downloaded: 2026t0-23T08:16Z
Check the source to verify that this is the currentversion before use.

inflatable canopy and the inflatable floor sections of the LRU-16/P life raft shall be subjected to the burst strength test described in 4.6.6,1. The primary bouyancy tube of the LRU-16/P life raft and the primary buoyancy tube of the LRU-17/P life raft shall be subjected to the burst strength test described in 4.6.6.2.

* 4.4.1 First article samples. The first article samples shall consist of one LRU-16/P life raft, the inflatable canopy and the inflatable floor sections of one LRU-16/P life raft, and the primary buoyancy tube of one LRU-16/P life raft or shall consist of one LRU-17/P life raft and the primary bouyancy tube of one LRU-17/P life raft. The first article samples shall be representative of the materials and the workmanship to be used in the production items.

4.4.2 First article report. The data requirements for the first article inspection shall be as specified vy the procuring activity (see 6.2).

4.5 Quality conformance inspection. The quality conformance inspection shall consist of the following:

(a) Individual inspection

(b) Sampling inspection.

* 4.5.1 Individual inspection. Each life raft shall be subjected to the following:

(a) Primary buoyancy tube inflation (see 4.6.8)

(b) Leakage (see 4.6.4)

(c) Canopy and floor inflation (see 4.6.5) 1/

(d) Visual examination (see 4.6.1.1].

1/ The canopy and floor inflation test shall not apply to the LRU-17/P life raft.

4.3.2 Sampling inspection. The sampling inspection specified for plans C and D shall be performed by the contractor. The selection of the samples for plans A and B shall be performed by the contractor. The inspection specified for plans A and B shall be performed by a commercial laboratory that has been selected by the procuring activity (see 6.2). The serial numbers of. the life rafts represented by each sample selected in accordance with plans A and B shall be furnished to the commercial laboratory by the contractor (see 3.8.1 and 6.2). A lot of life rafts shall not be shipped until after the samples selected from the lot have been approved and the lot has been accepted by the procuring activity (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 202610-23T08:16Z
Check the source to verify that this is the current version before use.

4.5.2.1 Plan A. The inspection level for plan A shall be S-1 of MIL-STD-105, The sample unit for the expression of the lot size for plan A shall be one life raft, The sample size for plan A shall be based only on the applicable sample size code letter corresponding to inspection level S-1 of MIL-STD-105. Each life raft that is selected as asample in accordance with plan A shall be subjected to the following:

(a) Operation (see 4.6.2)

(b) Pressure (see 4.5.3)

[c) Leakage (see 4.6.4)

(d) Canopy and floor inflation (see 4.6.5) 1/.

1/ The canopy and floor inflation test shall not apply to the LRU-l7/B life raft.

4.5.2.2 Plan B. In addition to the life raft selected from each lot in accordance with plan A, the contractor shall furnish the commercial laboratory with one primary. buoyancy tube for each lot of life rafts. The primary buoyancy tubes shall not be specially prepared primary byoyancy tubes but shall be representative of the workmanship and the heat sealing used during production. The primary buoyancy tubes shall be selected prior to completion of the lot. The primary buoyancy tubes selected as samples in accordance with plan B shall be subjected to the burst strength test described in 4.6.6.2.

4.5.2.3 Plan C. The inspection level for plan C shall be S-4 of MIL-STD-105. The sample unit for the expression of the lot size for plan C shall be one life raft. The acceptable quality level for plan C shall be accept zero, reject one, Life rafts that are selected as samples in accordance with plan C shall be subjected to the pressure test described in 4.6.3.

4.5.2.4 Plan D. A primary buoyancy tube section that is representative of the workmanship and heat scaling to be used in production shall be manufactured at the start of production each day; after each change in machine setting; and after each change of operator. The primary buoyancy tube section shall immediately be subjected to the burst strength test desrcibed in 4.6.6.2 If any primary buoyancy tube section is rejected, corrective action shall be taken before continuing production.

4.5.2.5 Rejection and retest (plan D). If an item selected from a production run in accordance with plan D fails to meet the specification, no items later produced shall be accepted until the extent and cause of failure have been determined and appropriately corrected. The contractor shall explain fully



Source: https://assist.dla.mil -- Downloaded: 2026l0-23T08:16Z
Check the source to verify that this is the currentversion before use.

to the Government representative and notify the procuring activity in writing the cause of failure, the action taken to preclude recurrence, and the impact the failure may have on scheduled deliveries.

4.5.2.5.1 Continuation of tests. For production reasons, individual tests or other sampling plans may be continued pending the investigation of a sampling plan D test failure. Final acceptance of items produced later shall not be made until it is determined that all items meet all of the requirements of the specification.

4.5.3 Defects in items already accepted The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and the method of correcting them.

4.6 Methods of inspection

4.6.1 Examination of product

4.6.1.1 Visual examination. The life raft shall be visually examined for the defects listed in table I. The acceptable quality level for minor defects shall be 15.0 defects per 100 units. Any life raft that contains a critical defect shall be rejected.

4.6.1.2 Examination of weight and packed volume. The life raft shall be examined for conformance to the weight specified in 3.5 and the packed volume specified in 3.6. If the weight or the packed volume of the life raft is not as specified, the life raft shall be rejected.

4.6.1.3 Examination of dimensions. The life raft shall be inspected for conformance to the applicable drawings with the respect to dimensions. If any dimension of the life raft is not as specified on the drawings, the life raft shall be rejected.

* 4.6.2 Operation. An inflation assembly (see 4.5.3) shall be attached to the life raft. The valve shall be activated and shall inflate the life raft to its design shape within 30 seconds. The carbon dioxide shall enter the primary buoyancy tube through the inlet valve without any evidence of hindrance to the flow of gas or restriction by any component. The life raft shall be examined. There shall be no evidence of leakage and no evidence of constructional or material failure in any respect. All of the seams, sealed areas, and attachments shall remain perfectly intact and shall show no indication of separation. The oral inflation valve shall open without difficulty and shall shut off completely. There shall be no evidence that the carbon dioxide gas being discharged from the primary buoyancy tube is hindered by the misplacement of the oral inflation tube base, by damage to the oral inflation valve due to the clamping together of the oral inflation tube and valve, or by blockage of the oral inflation assembly (tube and valve) by any foreign matter. After this operation test has been completed, the primary buoyancy tube shall be completely deflated.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects.

| No. | Defect | Critical | Minor |
|---|---|---|---|
| 1 | Any fabric damaged, bruised, abraded; fabric containing imperfections; or fabric otherwise defective (seriously affecting serviceability or function) | X | |
| * 2 | Oral tube clamp not securrly installed on primary buoyancy tube and taped or covered | X | |
| 3 | Voids in any cementing operation more than l/4-inch diameter or more than two voids in any cementing operations per life raft | X | |
| * 4 | Excessive bias in fabric resulting in twisting of primary buoyancy tube 1/ | X | |
| 201 | Cement not visible on cloth surface around any patch or attachment | | X |
| 202 | Cement visible on cloth surface around any patch or attachment in excess of 1 inch | | X |
| 203 | Gage of stitching irregular | | X |
| 204 | Stitches per inch more or less than stitches per inch specified | | Y |
| 205 | Three or more spots or stains | | X |
| 206 | Seam tape overlap more than 1-1/4 inches or less than 3/4 inch | | X |
| 207 | Voids in any cementing operation but not more than two per life raft and less than l/4-inch diameter | | X |
| 208 | Any seam tape, patch, or attachment (including edge lifts) separating | | X |
| 209 | Any marking missing, incorrect, illegible, or incomplete *or* not located as specified | | X |
| 210 | Any stitched seam containing excessive pucker or containing pleats or any part caught in unrelated operation or seam | | X |



Source: https://assist.dla.mil -- Downloaded: 2026l0-23T08:16Z
Check the source to verify that this is the currentversion before use.

TABLE I. Classification of defects. - Continued

| No. | Defect | Critical | Minor |
|---|---|---|---|
| 211 | Any knot not tightly drawn | | X |
| 212 | Location of any cemented attachment or subassembly not as specified | | X |
| 213 | Powder omitted on exterior cemented surfaces of life raft | | X |
| 214 | Any fabric damaged, bruised, or abraded; fabric containing imperfections; or fabric otherwise defective (not seriously affecting serviceability or function) | | X |
| 215 | Inlet check valve cement on threads or not as specified on drawings | | X |
| 216 | Oral inflation assembly mismated, bent, distorted, or not operable | | X |
| 217 | Oral tube clamp in floor not securely installed and taped or covered | | X |
| 218 | Oral tube clamp in canopy not securely installed and taped or covered | | X |
| 219 | Any line or cord missing or not securely attached as specified | | X |
| 220 | Any component part missing or operation not performed | | X |

* 1/ If excessive twisting of the primary buoyancy tube is evident, the life raft shall be examined as follows: With the primary buoyancy tube inflated to 2.0 psig and with the floor and the canopy (if applicable) deflated, the life raft shall be placed on a horizontal surface. A 3-inch-block shall be placed under the life raft adjacent to each of two diagonally opposite retaining tab locations. A gap between the bottom of the primary buoyancy tube and the 3-inch-high block is evidence of excessive bias in the fabric and shall be classified as a critical defect.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

4. 6.3 Pressure. The completely deflated life raft shall be placed in a horizontal position. All the pressure readings shall be taken with the life raft in this position. The primary buoyancy tube shall be inflated with oil and water free air to a pressure of 5.0 psig. The air supply shall be securely shut off; after minimum of 10 minutes, the pressure in the primary buoyancy tube shall be checked and readjusted, if necessary, to the original pressure of 5.0 psi. At the end of a minimum of 10 minutes after the readjustment period, the pressure in the primary buoyancy tube shall be not less than 4.75 psig. The primary buoyancy tube, while held under pressure, shall be examined. There shall not be any evidence of constructional or material failure in any respect. All of the seams, the sealed areas, and the attachments shall remain perfectly intact and shall not show any sign of separation. The life raft shall be deflated. The life raft shall then be inflated to 5.0 psig and deflated four more times for a total of five cycles each of inflation and deflation. During the fifth inflation cycle, the primary buoyancy. tube shall still retain a pressure of not less than 4.75 psig and shall show no evidence of constructional or material failure.

4.6,4 Leakage. The completely deflated life raft shall be placed in a horizontal position. All the temperature and pressure readings shall be taken with the life raft in this position. The primary buoyancy tube shall be inflated, with oil and water free air, to a pressure of 2.0 psig. The air supply shall be securel shut off, After a minimum of 15 minutes, the pressure in the primary buoyancy tube shall be checked and readjusted, if necessary, to the original pressure of 2.0 psig. The temperature and the barometric pressure shall be recorded at this time. At the end of a minimum of 6 hours after the readjustment period, the pressure shall be measured and corrected for any change in the temperature or the barometric pressure. The corrected pressure in the primary buoyancy tube shall be not less than 1.5 psig. The life rafts may be stacked one upon another, during the inspection waiting period, providing the following conditions are met:

(a) The temperature shall be recorded at a level comparable to the height at which the life raft being inspected was stowed during the 6 hours of the inspection waiting period.

(b) At the end of a minimum of 6 hours from the readjustment periods, the life raft to be checked for pressure shall be removed from the stacking and placed in a horizontal position, The barometric pressure of the inspection area shall be recorded. The pressure in the life raft shall be measured and corrected for any change in the temperature or the barometric pressure. In any event, the pressure in a life raft shall not be determined while another life raft is stacked upon it.



Source: https://assist.dla.mil -- Downloaded: 2026l0-23T08:16Z
Check the source to verify that this is the currentversion before use.

* 4.6.5 Canopy and floor inflation. The inflatable sections of the canopy and the floor of the LRU-16/P life raft shall be inflated through the oral inflation valve assembly until the design shape (10 inches of water pressure) is attained. After a minimum 3-hour period, there shall be 5 inches of water pressure still retained in the inflatable sections of the canopy and the floor and no evidence of separation at any point of attachment of the "quilts" or of any seam. Correction for any change in temperature or barometric pressure is not required. This canopy and floor inflation test may be conducted concurrently with the leakage test described in 4.6.4 provided the floor and the canopy are not inflated when the pressure measurement of the primary buoyancy tube is made.

4.6.6 Burst strength

4.6.6.1 Floor and canopy. The inflatable floor and indlatable canopy sections of the LRU-16/P life raft shall be inflated to a pressure sufficient to cause failure of the material or the seam areas. The pressure at which failure occurs and the type of failure shall be recorded. Failure at a pressure Less than 3,0 psig shall be cause for rejection.

* 4.6.6.2 Primary buoyancy tube. The primary buoyancy tube of the life raft shall be inflated to a pressure sufficient to cause failure of the material or the seam areas. The pressure at which failure occurs and the type of failure shall be recorded. Failure at a pressure less than 9.0 psig shall be cause for rejection. The contractor may utilize material salvaged from burst tubes to fabricate subassembly components.

4.6.7 Oral inflation valve assembly. The oral inflation valve assembly shall be tested in accordance with the test requirements specified in MIL-D-81575 to determine conformance to the performance requirements specified for the oral inflation valve assembly.

* 4.6.8 Primary buoyancy tube inflation. The primary buoyancy tube shall be inflated to design shape within 30 seconds with oil and water free air admitted through an inflation valve of the type used with the FLU-2A/P inflation assembly attached to the inlet check valve. The threads of the inlet check valve shall be clean and compatible with the inflation valve. Air shall flow freely into the life raft. The oral inflation valve shall open without difficulty and shall shut off completely.

* 5. PREPARATION FOR DELIVERY

* 5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

* 5. 1.1 Level A. Each life raft shall be packaged in accordance with method III of MIL-P-116, cushioned with material that conforms to PPP-C-795 to prevent movement within the box, and placed in a snug-fitting box that conforms to grade W6c of PPP-B-6.36.

* 5.1.2 Level C. Life rafts shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard commercial practice provided it meets these requirements.

* 5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

* 5.2.1 Level A. Life rafts that have been packaged as specified shall be packed in a shipping container that conforms to class weather-resistant of PPP-B-636. As far as practical, the shipping containers shall be of uniform shape and size, shall be of minimum cube and tare consistent with the protection required, and shall contain identical quantities. The gross weight of each shipping container shall not exceed the limitations of the shipping container specification. The closure of the shipping container shall be in accordance with the appendix of PPP-B-636.

* 5.2.2 Level B. Life rafts that have been packaged as spepcified shall be packed in a shipping container that conforms to class domestic of PPP-B-636. As far as practical, the shipping containers shall be of uniform shape and size, shall be of minimum cube and tare consistent with the protection required, and shall contain identical quantities. The gross weight of each shipping container shall not exceed the limitations of the shipping container specification. The closurec of the shipping container shall be in accordance with the appendix of PPP-B-636.

* 5.2.3 Level C. Life rafts that have been packaged as specified shall be packed in a shipping container that will be acceptable to the carrier and in a manner that will ensure safe transportation, at the lowest rates, to the point of delivery. The shipping containers shall conform to the rules and regulations applicable to the mode of transporation.

* 5.3 Marking. In addition to any other markings required by the order or contract, interior containers and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The life rafts colored by this specification are intended for use as emergency and life support equipment for personnel in aircraft forced down at sea.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification

(b) Specify type of life raft required (see 1.1)

(c) Requirements for first article inspection including test data (see 5.1 and 4.4)

(d) Requirements for inspection by commercial laboratory and instructions for return of tested samples to contractor (see 4.5.2)

(e) Serial numbers for life rafts (see 3.8.1 and 41.5.2)

(f) Packaging (see 5.1 and 5.2).

6.3 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Air Force - 11

Reviewer:
Air Force - 99

Preparaing activity:
Air Force - 11

Project No. 4220-F237



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

**DD FORM 1 OCT 76 1426** PREVIOUS EDITION WILL BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.

FOLD

ASD/ENESS
Wright-Patterson AFB, O 45433

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF AIR FORCE
DOD-318




ASD/ENESS
Wright-Patterson AFB, O 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:16Z
Check the source to verify that this is the current version before use.