MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M250 FRAGMENTS FOR

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains the quality assurance provisions and special requirements for the fabrication and purchase of tungsten fragments for use in the CHAPARRAL Warhead designated as Warhead, GM, HE, M250.

2. APPLICABLE DOCUMENTS

2.1 Issues of Documents. - The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-21014	- Tungsten Base, High Density Metal (Sintered or Hot Pressed)
MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-1169	- Packaging, Packing and Marking for Shipment of Inert Ammunition Components

FSC: 1336

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

9256694 - Fragment

(Copies of Specifications, standards, drawings and publications required by suppliers in connection with specific propurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Materials. - Material used in manufacture of the fragments shall be in accordance with all applicable specifications. Fragment ingredients shall be certified as being in compliance with MIL-T-21014.

3.2 Fragments. - Fragments shall comply with all the requirements specified on drawing 9256694, this specification, and all applicable specifications.

3.3 First Article Inspection. - This specification makes provisions for First Article Inspection. Requirements for submission of First Article Samples by the contractor shall be as specified in the contract.

3.4 Workmanship. - Fragments shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, cracks, surface defects, dirt, grease, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection and Standard Quality Assurance Provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this specification.

4.2 Classification of Inspection. - The following types of inspection shall be conducted on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First Article Inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of material certification, a test bar, and one inspection lot as defined in paragraph 4.4.1.

4.3.2 Inspections to be Performed. - See MIL-A-48078.

4.3.3 Rejection. - See MIL-A-48078.

4.4 Quality Conformance Inspection

4.4.1 Inspection Lot Formation. - An inspection lot shall contain the fragments of one sinter heat, and shall be limited in quantity to 3900 - 4100 fragments.

4.4.2 Examination. - Examination is described in the Quality Conformance Inspection Table 1. (See 4.4.2.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

TABLE 1
QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-63465 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9256694
4.4.2.1	Fragment				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Mechanical Properties	NOTE	NOTE	3.2	4.5.1/Gage
102	Mean Weight	NOTE	NOTE	3.2	4.5.2.1/Gage
103	Individual Weight	NOTE	NOTE	3.2	4.5.2.2/Gage
104	Shape	NOTE	NOTE	3.2	4.5.3/Gage
105	Certificate of Conformance	NOTE	NOTE	3.1	Visual
MINOR					
201	Packing and Marking improper	1/lot	100%	3.2	5.1/Visual
202	Evidence of poor workmanship	NOTE	NOTE	3.4	4.5.4/Visual

NOTES:
See paragraph 4.5 and subparagraphs for sampling and acceptance criteria.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the Quality Conformance Inspection Table 1. (See 4.4.2.1)

4.4.4 Inspection Equipment. - The inspection equipment required to perform the examination and tests prescribed in this specification is identified, either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the Quality Conformance Inspection Table herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. (see 6.3)

4.5 Test Methods and Procedures

4.5.1 Mechanical Properties. - A test bar conforming to the dimensions specified in Figure 1 of MIL-T-21014 shall be fabricated and sintered along with each quantity of 40,000 fragments (i.e., one test bar for every tenth lot or sinter). The test bar shall be submitted to the Government for Quality Conformance Testing. Failure of the test bar to exhibit mechanical properties in accordance with those specified on the drawing, when tested in accordance with the test method for mechanical properties specified in MIL-T-21014 shall result in rejection of the represented fragments.

4.5.2 Weight

4.5.2.1 Mean Weight. - A sample of 200 fragments shall be taken from each lot for determination of the mean weight. This shall be accomplished by weighing the sample as a group and dividing by 200 to determine the mean weight. Failure to meet the mean weight of 30 $\pm$ 0.5 grains shall be cause for rejection of the lot.

4.5.2.2 Individual Weight. - From the sample of 200, a group of 32 fragments shall be randomly selected and individually weighed. Failure of any one fragment to be within the limits of 30 $\pm$ 1.0 grains shall be cause for rejection of the lot.

4.5.3 Shape. - Thirty-two (32) fragments from the sample of 200 shall be randomly selected and measured for conformance to the shape requirements of drawing 9256694. Failure of any one fragment to comply with the shape requirements of 9256694 shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

4.5.4 Workmanship - Thirty-two (32) fragments shall be randomly selected from each lot. Failure of two or more fragments to meet the workmanship requirements shall be cause for rejection of the lot.

5. PACKAGING.

5.1 Packaging and Marking. - Lots shall be packaged and marked individually and shall be sealed in moisture proof containers. An approved moisture proof container would be a heavy duty plastic bag capable of holding 4000 tungsten alloy fragments in a moisture free (as per paragraphs 3.2.1.2.2 and 3.3.2.2 of MIL-STD-1169) environment.

6. NOTES

6.1 Intended Use. - The fragments covered by this specification are intended for use on the M250 Chaparral Warhead.

6.2 Ordering Data. - See MIL-A-48078 (PA).

6.3 Submission of Inspection Equipment Designs For Approval. - See MIL-A-48078 - Submit equipment designs, as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Drawings. - Drawings listed in Section 2 of this specification under heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1336-A349

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-63465 Warhead, Guided Missile, HE, M250 Fragments for

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

7

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:57Z
Check the source to verify that this is the current version before use.