MIL-B-12264A(CmlC)
27 March 1961
SUPERSEDING
MIL-B-12264 (CmlC)
10 October 1952

MILITARY SPECIFICATION

BEAM, HOISTING, LIQUID GAS TANK, M1

1. SCOPE

1.1 This specification covers a beam used for the handling of one ton liquid gas tanks when filling airplane spray tanks.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

CHEMICAL CORPS

C28-10-4 - Beam, Grab, M1, Assembly and Bill of Material.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:37Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing C28-10-4 or on the subsidiary drawings shall conform to the specifications thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the beam shall conform to the specifications and drawings listed on Drawing C28-10-4 and subsidiary drawings.

3.2 Assembly. The beam shall be assembled as shown on Drawing C28-10-4.

3.3 Workmanship. The beam shall be free from surface defects, such as burrs and sharp edges; also free from foreign matter, such as chips, oil, and cutting compounds.

4. QUALITY ASSURANCE PROVISIONS

4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Special provisions.

4.2.1 Alternative inspection (including testing) procedures. The supplier may utilize any alternative inspection procedure which will insure equal or better quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 Supplemental evidence. The supplier shall provide evidence acceptable to the contracting officer that the requirements of 3.1 have been satisfied. (See 6.1.1)

4.3 Regular production lot. A lot shall consist of the beam assemblies produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions, and offered for delivery at one time.

4.4 Sampling for nondestructive examination. Sampling shall be conducted in accordance with Standard MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:37Z
Check the source to verify that this is the current version before use.

4.5 Examination. Sample beam assemblies shall be inspected in accordance with the classification of defects and with Standard MIL-STD-105.

4.5.1 Classification of defects.

4.5.1.1 Beam, grab, M1, assembly (Dwg C28-10-4).

Categories		Defects
Critical:		None defined
Major:	AQL 1.0 percent defective	
101		Component missing or incorrectly assembled
*102		Yoke and hook profile or thickness incorrect
Minor:	AQL 4.0 percent defective	
201		Yoke to hook support bolt length incorrect
202		Channel length or section profile incorrect
203		Marking missing, incorrect, or illegible
204		Coating missing or incorrect
205		Damage (3.3)

*Inspect prior to assembly.

5. PREPARATION FOR DELIVERY

5.1 Packing, level A. No packing is required. The hoisting beam shall be shipped loose with the hook secured against the hoisting beam to prevent movement.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Whether shipment to assembly plants or as spare parts is required.
(c) Supplemental evidence required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:37Z
Check the source to verify that this is the current version before use.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:

Army - CmlC

Preparing activity:

Army - CmlC

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:37Z
Check the source to verify that this is the current version before use.