MIL-S-12285D(AT)
AMENDMENT 1
7 April 1992

MILITARY SPECIFICATION
SWITCHES, THERMOSTATIC

This amendment forms a part of MIL-S-12285D(AT), dated 20 December 1989, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1: Delete and substitute:

"1.1 Scope. This specification covers a level high coolant temperature switch which is designed to generate an alarm by light or audible sound when fluid temperature exceeds predetermined conditions (see 6.1)."

PAGE 3

3.5.1: Delete and substitute:

"3.5.1 Calibration. The switch shall operate within the temperature ranges specified in MIL-S-12285/1 and/or MIL-S-12285/2 (see 4.9.3)."

PAGE 4

3.5.2, line 2: Delete "and pressure ranges".

DISTRIBUTION STATEMENT A. Approved for public release; Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:39Z
Check the source to verify that this is the current version before use.

PAGE 6

4.4: Delete and substitute:

"4.4: Testing apparatus. Testing shall include a mounting manifold, an oil bath circulating through the manifold, a 3 candlepower (cp), 24-volt indicating lamp connected to a 28-volt direct current (dc) source of electrical energy, and laboratory thermometers. separate temperature controls and heating or cooling apparatus shall be provided for the mounting manifold and oil bath. Instruments such as voltmeters, ammeters and thermometers shall be of the laboratory type and shall be accurate to within 0.5 percent of full scale deflection and within one percent of indicated values."

PAGE 9

4.9.7, line 5: Delete "(5.4°C)", and substitute "(5.4°F)".

PAGE 10

4.9.9, line 8: Delete "(5.4°C)", and substitute "(5.4°F)".

Custodian:
Army - AT

Preparing activity:
Army - AT

(Project 5930-A717)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T22:39Z
Check the source to verify that this is the current version before use.