MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, SAMPLE AND HOLD CIRCUITS
MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/125, dated 3 November 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1, line 2: Delete "Three" and substitute "Two".

PAGE 3

TABLE I, series change resistance: Delete "change" and substitute "charge".

TABLE I, R_{SC} minimum limits column: Delete "100" and substitute "75".

PAGE 4

TABLE I, $I_{HL(+)}$; $I_{HL(-)}$, conditions column: Delete "T_J" and "7/" and substitute "T_A" respectively (4 places each).

Acquisition time (0.01% error): Delete "0.01%" and substitute "0.1%".

PAGE 5

4/, line one: Delete "change" and substitute "charge".

7/: Delete in its entirety.

PAGE 6

3.6: Delete the second sentence in its entirety.

4.2d: Delete lines 1 and 2 and substitute the following:

"The percent defective allowable (PDA) for class S and class B devices shall be as specified in MIL-M-38510,".

PAGE 7

TABLE II: Delete "Class C devices" column in its entirety. Also delete all references to "class C devices" from the remaining text of the document.

PAGE 8

FIGURE 1, lower diagram: Connect the top ends of each diode together and add a " - " (minus sign) to the left amplifier's upper input.

PAGE 9

FIGURE 1: Connect the top ends of each diode together and add a " - " (minus sign) to the left amplifier's upper input.

PAGE 13

FIGURE 5: Delete "T_A = 125°C". (2 places)

FIGURE 6: Delete "T_A > 150°C". (2 places)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:28Z
Check the source to verify that this is the current version before use.

PAGE 16

FIGURE 9, top portion of the figure (test circuit) lower right of circuit: Delete "10 μΩ" and substitute "10 MΩ".

PAGE 20

FIGURE 13, NOTES, 1/, line two: Delete "1 mV" and ".1 V" and substitute "10 mV" and "1 V", respectively.

PAGE 27

FIGURE 20, NOTES, 2/: Delete "1 μs" and substitute "2 μs)".

PAGE 29

FIGURE 22: Delete ".01 kΩ" and substitute ".01 μF".

PAGE 31

TABLE III, test number 29, minimum limits column: Delete "100" and substitute "75".

TABLE III, test number 31, adapter pin numbers column 5: Delete "0 V" and substitute "5.5 V".

TABLE III, test number 32, adapter pin numbers column 4: Delete "0 V" and substitute "5.5 V".

PAGE 33

TABLE III, test number 67, minimum limits column: Delete "100" and substitute "75".

TABLE III, test number 70, adapter pin numbers column 5: Delete "0 V" and substitute "5.5 V".

TABLE III, test number 71, adapter pin numbers columns 4 and 5: Delete "0 V" and substitute "5.5 V" to column 4 and in column 5: Add "0 V".

PAGE 34

TABLE III, test number 106, minimum limits column: Delete "100" and substitute "75".

TABLE III, test number 109, adapter pin numbers column 5: Delete "0 V" and substitute "5.5 V".

TABLE III, test number 110, adapter pin numbers columns 4 and 5: Delete "0 V" and substitute "5.5 V" in column 4 and add "0 V" to column 5.

PAGE 35

TABLE III, test number 131 and 132, unit column: Delete "mV rms" and substitute "μV rms".

Footnote 4, line 1: Delete "2.5 V" and substitute "5 V".

Footnote 20, line 1: Delete "100" and substitute "10,000".

PAGE 36

4.5.2, delete and substitute the following:

"4.5.2 Life test and burn-in cooldown procedure When devices are measured at +25°C following application of the steady-state life or burn-in test condition, they shall be cooled within 10°C of their power stable condition at room temperature prior to removal of the bias."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:28Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Navy - EC
Air Force - 17
NASA - NA

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-1108)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:28Z
Check the source to verify that this is the current version before use.