MILITARY SPECIFICATION

MICROCIRCUITS, LINEAR, CMOS MULTIPLYING D/A CONVERTERS,
MONOLITHIC SILICON

This amendment forms a part of MIL-M-38510/127A, dated 28 February 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Table I, Zero-scale current (I_{ZS} and $I_{ZS'}$), delete and substitute:

"

Zero-scale current	I_{ZS}	V_{IL} = 0.8 V Measured at I_{OUT1} T_A = +125°C	01-06 07	-100 -50	100 50	nA nA
	$I_{ZS'}$	V_{IH} = 2.4 V Measured at I_{OUT2} T_A = +125°C	01-06 07	-100 -50	100 50	nA nA

"

PAGE 23

Table III, tests for I_{ZS} and $I_{ZS'}$, device type 04 only, for T_A = 125°C: Limits shall be ±100 nA.

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 11, 19, 85, 99
DLA - ES

User activities:
Army - SM
Navy - AS, CG, MC

Civil Agency Coordinating Activity:
NASA - NA

Preparing activity:
Air Force - 17

Agent:
DLA - ES

(Project 5962-0943)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T13:29Z
Check the source to verify that this is the current version before use.