MILITARY SPECIFICATION SHEET

ELECTRON TUBE, CROSS FIELD AMPLIFIER

1/ TYPE 8129F

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Broadband, pulsed, integral magnet, liquid cooled, 2,900 to 3,100 MHz, 2.6 MW rated peak power output.

ABSOLUTE RATINGS: See note 25

Parameter:	epy	epx	ib	tp	Du	VSWR	Waveguide pressurization	T(bushing)	TA
Unit:	kv	kv	a	us	---	---	psia	°C	°C
Maximum:	60	20	66	29	0.00756	-1.3	55	200	-54
Minimum:	---	---	30	---	0.00424	---	40	---	+65
						(Note 1)	(Note 2)		

ABSOLUTE RATINGS: See note 25

Parameter:	Coolant inlet Temperature	Coolant pressure Window	Coolant pressure Anode	Coolant flow rate Window	Coolant flow rate Anode	Alt	F
Unit:	°C	psia	psia	gpm	gpm	ft	MHz
Maximum:	65	55	75	---	---	10,000	H3
Minimum:	---	---	---	0.4	3.0	---	F1
	(Note 3)			(Note 3)			

PHYSICAL CHARACTERISTICS:

Dimensions:	See figure 1	Cooling:	Forced liquid
Mounting position:	Cathode axis vertical	Handling:	See note 5
Input connection:	See note 4	Weight:	130 lb (max)
RF connectors:	Mates with UG-548/U type flange per MIL-F-3922/26	Magnet isolation:	12 inches (see note 5)

TEST CONDITIONS: See notes 6, 12, and 13

Parameter:	Ib	Du	tp	VSWR	pd	Waveguide pressurization	F
Unit:	mAdc	---	us	---	kw	psia	MHz
Tolerance:	---	---	±1	---	Max	Min	---
Test condition 1:	330 (max) (Note 26)	0.0053	28	1.1	550	45	F1,F2,F3
Test condition 2:	Note 27 (Notes 18, 20,28)	0.0063	28 (Note 8)	1.1 (Note 1)	550 (Notes 9, 10)	45 (Note 21)	F1,F2,F3 (Note 12)
Test condition 3:	Note 27	0.00424	28	1.1	550	45	F1,F2,F3
Test condition 4:	303	0.00756	28	1.1	550	45	F1,F2,F3

GENERAL:

Qualifications - Required

1/ Replaces - Raytheon type QKS-1541
ITT Gilfillan part number 183005

FREQUENCY	
F	MHz
1	2,900
2	3,000
3	3,100

8129F

FSC 5960

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	TESTS	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1	6,11, 12	-					
4003	Pressurization (rf window)	2	-	55 psia (max)	---	---	---	---
4306	Pulse voltage	8	1,2	F1, F3	epy	44	56	kv
4250	Power output	13,14	1		Po	13,780	---	W
		13,14	2	F3	Po	16,380	---	W
		13,14	3	F3	Po	11,024	---	W
4279	Reverse directed power	13,19	1	VSWR = 1.3:1 (min)	Pr	---	2,400	W
			2		Pr	---	2,850	W
---	Stability	13,15, 16	2	F1 to F2	MP	---	35	Pulses
			3	F2 to F3	MP	---	35	Pulses
			4		MP	---	35	Pulses
---	Rumup	13,16, 7	1	F2 to F3; Ib (start) = 0	MP	---	35	Pulses
---	Amplifier insertion loss	17	1	F1, F3; pd = 550 kw (see figure 2)	Li	---	1.0	dB
1261	Electrode voltage (getter)	-	-	$I_{(getter)}$ = 15 A; t = 300 (min)	E (getter)	1.0	5.0	V
---	Inhibit	13,16 29	1	F2 to F3	---	---	---	---
	Quality conformance inspection, part 2							
4266	Direct-interelectrode capacitance	-	-		C	---	50	pF
---	Voltage variation	24	1		$\frac{\Delta V}{V}$	---	15	%
1155	Coolant-pressure drop versus coolant flow	3	-					
	Anode	-	-	Water Flow rate = 3 gpm	ΔP	6	20	psi
	Window	-	-	Flow rate = 0.4 gpm	ΔP	0.5	6	psi
1105	Permanence of marking	-	-		---	---	---	---

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	TESTS	CONDITIONS	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 3							
---	Life test	30,31, 32	1	Group D	t	1,000	---	hrs
---	Life-test end points:							
4250	Power output	13,14	2		Po	11,024	---	W
---	Stability	13,15, 16	2,3,4		MP	---	35	Pulses
	Periodic-check tests							
1032	Vibration, mechanical	21,22	-	No voltages	---	---	---	---
1042	Shock, specified pulse	22,23	-	Test condition A	---	---	---	---
				Test condition J	---	---	---	---
4278	Phase sensitivity	-	1	i_D = 42 a (min) to 62 a (max)	$\frac{\Delta\phi}{I_D \Delta I_D}$	---	0.5	deg/a

NOTES:

1. The system match looking away from the input and output flanges shall have a VSWR less than 1.5:1 for the frequency range of 2,800 to 3,200 MHz. The VSWR shall be less than 1.3:1 for the operating range of F1 to F3.

2. The pressurization gas shall provide insulating properties which are the equivalent of oil-filtered and particle-filtered air dried to a dew point below 40°F. The oil trap may be activated alumina, the filter may be 20 to 30 micron size and the desiccant may be silica gel.

3. Demineralized water with a maximum inlet temperature of +65°C shall be used with, (1) specific resistivity maintained greater than 0.5 meg-cm, (2) oxygen content maintained less than 0.5 ppm, (3) an organic filter, and (4) a 3 to 4 micron filter.

4. The cathode terminal and high-voltage bushing shall be insulated by immersion in oil that have the electrical characteristics specified in VV-I-530.

5. Extreme caution shall be used in the storage, handling, and installation of the tube to avoid imparting vibration or shock in excess of the values specified herein. To prevent demagnetization, ferromagnetic materials or energized magnets shall not be exposed to the tube magnet at a distance less than 12 inches.

6. Government owned equipment installed at the contractors manufacturing facility shall be made available to perform all required tests specified herein. A transmitter test fixture with necessary microwave and modulator components, as specified in note 15, shall be used for these tests. Appropriate terminations shall be used where the TUT is required to operate into a 1.3:1 VSWR.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

7. The runup test shall be performed while sweeping the operating frequency from F2 to F3 at a rate of 1 sec/sweep. Reduce the high voltage to zero for a minimum period of 1 minute. The runup test shall be performed by raising the high voltage from zero manually or automatically to the normal operating level at a rate of approximately 8 amp/sec. This test is to be conducted three times. Tube sparking is permissible but it shall not be acceptable if a series of four successive modulator inhibits occurs during the test.

8. The pulse characteristics determined in accordance with method 4304, shall be as follows:

trv: 1.0 µs (max) at 20 to 85 percent.
tfv: 5.0 µs (max) at 20 to 85 percent.

9. The following relationships shall exist between the TUT rf input and the rf output pulse:

(a) t1 is the time interval between the leading edge of the rf input pulse and the leading edge of the TUT rf output which shall be between zero (minimum) and 1.0 µs (maximum).
(b) The TUT rf envelopes shall be positioned to be totally contained within the rf drive (pd) pulse.
(c) The minimum isolation specified below shall be provided between the TUT and rf input source:

Frequency (MHz)	Isolation (dB)
2,600 to 3,100	20
3,100 to 3,200	15

10. The average rf drive (pd) to the TUT shall be adjusted to a value corresponding to 550 kw (peak) at the frequency of lowest drive power. The operating frequency shall be manually changed to each test frequency without readjustment of rf drive power.

11. Unless otherwise specified, the AQL for all tests listed under quality conformance inspection, part 1, shall be 1.0, inspection level II.

12. The TUT shall be capable of satisfying all requirements specified herein at any frequency over the range F1 thru F3, even though specific frequencies are specified for these tests.

13. The tests shall be performed in a test circuit as shown on figure 3, with the TUT installed in a pulse transformer with a cavity damping sleeve and socket configuration as shown on figure 4, to overcome the effects of rf generated in the cathode well. The network impedance shall be within 5 percent of the specified value. The pulse width shall be the value specified minus zero +1 µs. (see note 6.)

14. The TUT shall be capable of rated power output not less than the specified limit at any frequency in the range F1 through F3.

15. The operating frequency shall be swept from F1 through F3 at a rate of 100 sec/sweep. The duration of this test shall not exceed 5 minutes. The TUT shall be rejected for:


(a) Repeated waveguide breakdown, or
(b) Four successive inhibits of the modulator.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

16. Stability shall be measured in terms of the average number of output pulses missing, normally expressed as a percentage of the number of input pulses applied during the period of observation. Output (rf) pulses are considered to be "missing" if, due to any causes, the average rf pulse energy, within a ±1 percent frequency range of the normal operating frequency is less than 70 percent of the energy of a normal pulse. No more than the specified number of pulses shall be missing during any 18-second sample period as described below:

    Count 1 initiates the first 8-second sample gate, count 2 must occur within the 8-second sample gate, count 3 must occur within the first 5-second sample gate and count 4 must occur within the second 5-second sample gate. When count 4 is reached, the tube is considered unacceptable. The integrated value of missing pulses equivalent to 70 full width missing pulses shall cause the modulator to inhibit for 5 seconds and register count.



>70 Abnormal inverse pulses/gate

17. The insertion loss will be the difference between input power, measured by the coupler and the feed-through power with the TUT passive, measured by the water-load, minus the loss of the miscellaneous microwave components.

18. The TUT shall be operated at F3, then manually swept to F2 and F1 without readjustment of the high voltage.

19. The phase of the mismatched load shall be adjusted for maximum reverse directed power at the input of the TUT.

20. The indicated values apply at F3 only when the TUT is tuned from F3 to F1, under test condition 1, the maximum change in average current shall be 60 mA.

21. The TUT shall be mounted with the cathode axis vertical and vibrated as follows:

Exploratory:	Frequency	Amplitude (peak to peak)
	5 to 15 Hz	0.075 ±0.012 (0.150 total displacement)
	16 to 25 Hz	0.050 ±0.008 (0.100 total displacement)
	25 to 33 Hz	0.025 ±0.004 (0.050 total displacement)

Variable: As specified in the exploratory test except that the dwell time at each frequency with observed resonances shall be 5 minutes (approximately).

Endurance: As specified in the variable test except that the dwell time shall be 2 hours (minimum).

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

22. After the completion of this test, the TUT shall exhibit no mechanical failures and shall satisfy all requirements of the power output and stability tests of quality conformance inspection, part 1.

23. The TUT shall be mounted with the cathode axis vertical and shocked in accordance with condition A in a direction along the cathode axis. The TUT shall then be shocked in accordance with condition J (except 25 G) along the other two mutually perpendicular axes.

24. The TUT voltage variation shall be less than 15 percent based on the voltage at F3, when the frequency is swept from F1 through F3. Relative voltage indication may be used for this test. The voltage variation shall be computed as follows:

$$\frac{VF3 - VF1}{VF2} < 15\%$$

25. In addition to the MIL-E-1 symbols, the following shall apply:

p	Pressure
ppm	Parts per million
Pr	Reverse power
ΔP	Pressure drop
$\Delta\phi$	Phase change

26. The average current for this test shall be that current at F3 necessary to insure minimum specified power from F1 to F3. This average current shall be designated on the tube.

27. The average current for test condition 2 shall be 119 percent of the average current at F3 for test condition 1. The average current for test condition 3 shall be 80 percent of the average current at F3 for test condition 1.

28. The tube shall be capable of the performance specified herein at any frequency between the limits specified herein.

29. Inhibit test shall be performed while sweeping the operating frequency from F2 to F3 at a rate of 1 sec/sweep. The pulse voltage shall be removed for a minimum period of 5 seconds and reapplied. The pulse voltage may be removed by interrupting the trigger to the modulator. This test shall be conducted 3 times at an interval of not less than 30 seconds between tests. Tube sparking is permissible but shall not be acceptable if a series of four successive modulator inhibits occurs during the test.

30. Life tests shall be conducted using the TUT in cascade with a driver tube type 8129D. The applied voltage pulses shall be programmed such that the final amplifier is pulsed only on alternate pulses of the driver tube.

31. A life-test cycle shall consist of the following schedule:

Condition	Duration
High voltage "ON"	7.5 hours
High voltage "OFF"	0.5 hour

The frequency shall be varied from F1 to F3 and repeated after each 100 hours of operating time.

32. Service-life guarantee may be acceptable if specifically authorized by contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

Custodian:
Navy - EC

Review activity:
DSA - ES

User activities:
Navy - AS, CG, MC, OS, SH

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-N990)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube type 8129F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube type 8129F - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube type 8129F - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

L.	DIMENSIONS			
T	INCHES		MILLIMETERS	
R	MIN	MAX	MIN	MAX
Quality conformance inspection, part 1 (see note 1)				
D		2.750		69.85
E	1.990	2.010	50.55	51.05
F	14.845	14.905	377.06	378.59
H	.552	.572	14.02	14.53
K		2.687		68.25
M	8.360	8.460	212.34	214.88
N	3.115	3.135	79.12	79.63
P	1.990	2.010	50.55	51.05
S	15.845	15.905	402.46	403.99
T	14.302	14.322	363.27	363.78
U		15.937		404.80
V		17.500		444.50
W	.576	.585	14.63	14.86
X	.593	.602	15.06	15.29
AB	.275	.291	6.99	7.39
AC	7.407	7.467	188.14	189.66
AD	.490	.510	12.45	12.95
AF	3.500	3.870	88.90	98.30
AG		14.500		368.30
AH		18.600		472.44
AJ	.425	.525	10.80	13.34
AL	10.410	10.590	264.41	268.99
AM	4.581	4.661	116.36	118.39
AQ	.435		11.05	
AR	10.430	10.490	264.92	266.45
AS	.812		20.62	
AT	6.400	6.650	162.56	168.91
BB		3.500		88.90
BD	2.910	3.090	73.91	78.49
BE	4.115	4.135	104.52	105.03
BF	.452	.459	11.48	11.66
Quality conformance inspection, part 2				
A		2.750		69.85
B		5.562		141.27
C		6.312		160.32
G	4.812		122.22	
J		1.062		26.97
L	.275	.325	6.99	8.26
Q	12.500		317.50	
R	4.052		102.92	
Y	5.300	5.325	134.62	135.28
Z	2.183	2.205	55.45	56.01
AA	.898	.920	22.81	23.37
AE		2.875		73.03
AK		3.250		82.55
AN	2.177	2.197	55.30	55.80
AW	.780		19.81	
AY	2.348	2.372	59.64	60.25
BA	4.485	4.515	113.92	114.68
BC	1.375	1.625	34.93	41.28

FIGURE 1. Outline drawing of electron tube type 8129F - Continued.


Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

NOTES:

a. Reference plane "A" is defined as a plane passing along the face of the mounting surface as shown.
b. Reference plane "B" is defined as a plane perpendicular to reference plane "A" passing through the ℄ of holes XX and ZZ at reference plane "A" as shown.
c. Reference plane "C" is defined as a plane mutually perpendicular to reference planes "A" and "B" passing through the ℄ of "XX" at reference plane "A" as shown.
d. This flange shall mate with UG-54B/U in accordance with MIL-F-3922/26.
e. The axis of this feature shall be parallel with or inclined away from reference plane "A".
f. Getter connections UG-106/U in accordance with REB 49236: Getter connections (red cap) and ground (black cap).
g. Wiggins BP1700 series nipple, or equivalent.
h. These dimensions apply to the ℄ of diameter "Y".
k. These dimensions include angular as well as lateral deviation.
m. These surfaces shall be flat within .015 in. (.38 mm).
n. These holes shall lie on a plane parallel to reference plane "A" within .025 in. (.64 mm).
p. Applies to uncoated area of magnet.
q. Cathode connection.
r. These surfaces shall be coplanar within .020 in. (.51 mm).
s. rf output.
t. rf input.
u. Mounting fixtures.
v. These surfaces shall be parallel with reference plane "B" within .050 in.(1.27 mm).
w. The axis of this diameter shall lie on reference plane "B" within .030 in.(.76 mm).
x. These couplings shall be AN815-4, or equivalent (stainless steel).
y. These couplings shall be AN815-8, or equivalent (stainless steel).
z. "O" ring shall be in accordance with MS28778-8 per MIL-G-5510.
aa. "O" ring shall be in accordance with MS28778-4 per MIL-G-5510.

FIGURE 1. Outline drawing of electron tube type 8129F - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.



EQUIPMENT REQUIRED

1 - Cross-guide coupler (30-40 dB directivity)
1 - Microwave power meter
1 - Thermistor mount, 200 ohms negative
1 - Matched load
1 - Termination

NOTE: Use transmitter test fixture (notes 6 and 13).

FIGURE 2. Insertion loss test circuit.





FIGURE 3. Electrical test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.



INCHES	MM	INCHES	MM
2.400	60.96	4.52	114.81
3.09	78.49	4.62	117.35
3.15	80.01	4.66	118.36
3.185	80.90	4.91	124.71
3.205	81.41	5.14	130.56
4.10	104.14	5.59	141.99
4.14	105.16	5.65	143.51
4.25	107.95	6.72	170.69

FIGURE 4. Pulse transformer socket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.

NOTES:

The following describes the general characteristics of the rf pulse transformer to be used in conjunction with the testing of the TUT.

ELECTRICAL CHARACTERISTICS:

Turns ratio	1:5
Primary voltage (peak)	11 kV
Current (peak)	310A
Secondary voltage (peak)	55 kV
Current (peak)	62A

PULSE CHARACTERISTICS:

Pulse width (90 percent points)	27.5 μs
Rise time (10 percent to 90 percent)	1.5 μs max
Fall time (90 percent to 10 percent)	3.5 μs max
Overshoot and ripple	3 percent max
Droop	5 percent max

INSULATION:

Oil	In accordance with VV-I-530

MECHANICAL:

Sleeve, cavity damping	See figure Height 4.00 in. O.D. 4.66 in. I.D. 4.10 in. Composition: 23 PBW EPON 828 Resin, Shell Chemical Corp., or equal. 5 PBW Methane Diamine Catalyst. Shell Chemical Corp., or equal. 72 PBW No. 325 Mesh Powdered Iron. Van Waters and Rogers, Inc. No. 2226, or equal.
Choke assembly, cathode	28 turns #16 AWG wire. MIL-W-16878, type EE, @ .100 pitch on 3 inch dia. coil form. Coil form material: Epoxy resin laminated tubing, Nema Grade G-10, or equal.
Coil assembly, cathode cooling	7 turns of 3/8 O.D. seamless tubing. Cres 304, or equal.

FIGURE 4. Pulse transformer socket - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.