MILITARY SPECIFICATION SHEET

ELECTRON TUBE, POWER

TYPE 8122

This amendment forms a part of Military Specification Sheet MIL-E-1/1748, dated 24 April 1974, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 3

Quality conformance inspection, part 2, Method 2214, RF useful power output, under Conditions column: Delete "Ic1 = 30 mAdc".

Page 4

Quality conformance inspection, part 3, Requirement or test column: Delete title heading "Periodic-check tests" and in NOTES column, delete note "11".

Quality conformance inspection, part 3, under NOTES column, add note "11" to the following test methods:

1032	Vibration, mechanical
1042	Shock, specified pulse

Page 5

NOTE 9, delete and substitute new note 9 as follows:

"9. Vibrate along each of the three mutually perpendicular axes (X, Y, and Z), see figure 1. Vibrate at 0.080 inch (2.03 mm) double amplitude at constant displacement to the 60.5 Hz crossover frequency and at a constant acceleration of 15 G to 2,000 Hz."

NOTE 11, delete and substitute new note 11 as follows:

"11. This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of two. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level D, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted."

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 80
DSA - ES

User activities:
Army - ME, MU
Navy - AS, OS, MC, CG, SH
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-2917)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:29Z
Check the source to verify that this is the current version before use.