Metric

A-A-59106A
4 August 2014
SUPERSEDING
A-A-59106
26 August 1998

COMMERCIAL ITEM DESCRIPTION

ETHYLENE GLYCOL MONOETHYL ETHER, TECHNICAL

The General Services Administration has authorized the use of this commercial item for all federal agencies.

1. SCOPE. This commercial item description covers technical grade ethylene glycol monoethyl ether.

2. SALIENT CHARACTERISTICS

2.1 Appearance. Ethylene glycol monoethyl ether shall be clear and uniform when visually inspected using transmitted light.

2.2 Chemical and physical characteristics. Ethylene glycol monoethyl ether shall conform to the chemical and physical characteristics of Table I when tested as specified therein.

2.3 Spot test. Support a piece of 125 millimeter (mm) diameter filter paper (Whatman No. 2 or equal) on a crystallizing dish, which is 70 mm in diameter. Using a small pipette or burette, place five drops of the specimen the center of the paper. Allow the liquid to evaporate at 21° C to 32° C, away from both sunlight and strong drafts. After 30 minutes examine the filter paper for the presence of any stains or residual oiliness.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to: STDZNMGT@dla.mil or DLA Aviation VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.dla.mil/

FSC 6810

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

TABLE I. Chemical and physical characteristics.

Characteristics	Requirements		Test Method
	Min	Max	
Color, Pt-Co Scale	---	Number 15	ASTM D1209
Odor	---	Mild, Non-residual	ASTM D1296
Water content, percent by weight	---	0.1	ASTM D1364
Specific gravity at 20° C /20° C	0.929	0.932	ASTM D891
Nonvolatile matter (g/100 ml sample)	---	0.005	ASTM D1353
Acidity (free acid as acetic acid), percent by weight	---	0.01	ASTM D1613
Distillation range, °C	134.0	136.0	ASTM D1078[(1)]
Flash Point, °C	38.0	---	ASTM D56
Evaporation rate (n-butyl acetate = 1.0)	---	0.34	ASTM D3539
Spot test	---	none	para 2.3 of this description
Sulfur	---	none	ASTM D4952

[(1)] Using ASTM Solvents Distillation Thermometer 102C, with a range from 123°C to 177°C.

3. REGULATORY REQUIREMENTS

3.1 Labeling, packaging and marking. Item shall be labeled, packed and marked in accordance with Title 49 Code of Federal Regulations (CFR), Parts 171 to 199.

3.2 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR). Unless otherwise specified herein, all equipment, material, and articles incorporated in the work covered by this CID are to be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

intended use. The term “recovered materials” means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. Unless otherwise specified, none of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this CID.

3.3 Safety data sheets (SDSs). SDSs shall be prepared and furnished in accordance with 29 CFR 1910.1200 and submitted as directed in the contract or order at time of acquisition award.

4. QUALITY ASSURANCE PROVISIONS

4.1 Product conformance. The product provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The government reserves the right to require proof of such conformance.

4.2 Market acceptability. The item offered must have been sold to the government or commercial market.

5. PACKAGING. Preservation, packing, labeling, and marking shall be as specified in the contract or order.

6. NOTES.

6.1 Source of documents.

6.1.1 Copies of ASTM document are available online at http://www.astm.org/ or from ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959.)

6.1.2 Copies of the CFR and FAR may be obtained from the U.S. Government Printing Office, 732 North Capital Street NW, Washington, DC 20401-0001 or online at www.gpo.gov.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, name, and date of this CID.
b. Unit quantity required.
c. Packaging requirements.

6.3 National stock numbers (NSNs). The following NSNs correspond to this CID. This list may not be indicative of all possible NSNs associated with this document.

6810-00-222-2751
6810-00-285-4309

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:
Army - EA
Air Force - 68
DLA - GS

Reviewers:
Army - MD1

CIVIL AGENCY COORDINATING ACTIVITIES:
GSA - FAS

Preparing Activity:
DLA – GS3
(Project No: 6810-2014-051)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:01Z
Check the source to verify that this is the current version before use.