INCH-POUND
A-A-59126 /5A
31 May 2011
SUPERSEDING
A-A-59126 /5
26 September 1997

COMMERCIAL ITEM DESCRIPTION SHEET

TERMINALS, FEEDTHRU (INSULATED)
STYLE FT05

The General Services Administration has authorized the use of this commercial item description (CID) as a replacement for Style FT05 of MIL-T-55155/5 for all federal agencies.

The requirements for acquiring the product described herein shall consist of this sheet and CID A-A-59126.

REQUIREMENTS:

Dimensions and configuration: see Figure 1.



Figure 1. Configuration and Dimensions

Comments, suggestions, or questions on this document should be should be emailed to michael.g.williams31.civ@mail.mil Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil/

AMSC N/A FSC 5940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.

.

Part Number	DIMENSIONS							
	A	B	C +.002 -0.000	D	E	F	G	H
AA59126/05--01	.225	.040	.093	.040	.125	.060	.030	.010 x 45°
AA59126/05--02	.310	.050	.120		.130	.053		.015 x 45°
AA59126/05--03	.367		.148	.085	.172	.110	.063	

Figure 1. Configuration and Dimensions (continued)

Figure 1 Notes:

1. Dimensions are in inches.
2. Unless otherwise specified, tolerances are ±0.015inch and ±3° on angles.
3. Drawing depicts only general design characteristics and is not intended to limit specific manufacturing processes.
4. Terminals shall have no less than 0.040 inch of the insulated portion protruding beyond the mounting panel or board.

Insulation material: Polytetrafluoroethylene.

For test mounting hole dimensions, see Figure 2.



Figure 2. Test Mounting Hole.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.

PART NUMBER	DIMENSIONS			
	A		B	
	MAX	MIN	MAX	MIN
AA59126/05--01	0.088	0.081	0.115	0.110
AA59126/05--02	0.109	0.105	0.135	0.130
AA59126/05--03	0.138	0.134	0.165	0.160

Figure 2. Test Mounting Hole (continued)

Figure 2 Notes:

1. Dimensions are in inches.
2. For panels less than .040 thick, the countersink angle shall be 82°.

Table I. Dielectric withstanding voltage.

Pressure	Volts ac (rms) (min)
Atmospheric	1,500
Reduced barometric	650

Pull: 8 pounds minimum.
Torque: 3 ounce-inches, minimum.
Type of mounting Compression.

Table II. Substitutability data.

Part number in A-A-59126/5 1/	Part number in MIL-T-55155/5C 1/
AA59126/05--01	M55155/05--01
AA59126/05--02	M55155/05--02
AA59126/05--03	M55155/05--03

1/ The complete part number shall include the symbol for the insulation color (first dash) and symbol for the conductor material and finish (second dash).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodian:
Army - CR
Navy – EC
Air Force – 85

Reviewer:
DLA – GS

CIVIL AGENCY COORDINATING ACTIVITY

GSA-7FXE

Preparing activity:
Army – CR

(Project No. 5940-2011-063)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T10:03Z
Check the source to verify that this is the current version before use.