MILITARY SPECIFICATION SHEET

**AIRCREW ESCAPE PROPULSION SYSTEMS (AEPS)
ROCKET MOTORS, UNDERSEAT, GAS INITIATED, (MARK 74 MOD 0, MARK 75 MOD 0, MARK 76 MOD 0, MARK 77 MOD 0, MARK 86 MOD 0, MARK 87 MOD 0, MARK 88 MOD 0, MARK 92 MOD 0, MARK 100 MOD 0, AND MARK 101 MOD 0) (LOADED ASSEMBLY)**

This amendment forms a part of MIL-A-85097/8B(AS), dated 24 August 1984, and is approved for use within the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Delete table I and substitute new table I as follows:

TABLE I. Ballistic performance requirements for Mk 74/75/76/77/86/87/88 Mod 0 Rocket Motors.

Parameter	−40° ± 5°F		160° ± 5°F	
	Minimum	Maximum	Minimum	Maximum
Ignition delay (ms)	-	17.0	-	17.0
Thrust (lbf)	4,085	4,890	5,010	6,270
Impulse (lbf-s)	1,190	1,305	1,210	1,335
Action time (ms)	280	340	245	285

NOTE: The margin of this amendment is marked with a vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity:
Navy (AS)
(Project 1377-N922)

Distribution Statement A: Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:23Z
Check the source to verify that this is the current version before use.