MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, RECTANGULAR, RECEPTACLE, MICROMINIATURE, POLARIZED SHELL, SOCKET CONTACTS, CLASS M, CRIMP TYPE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the connectors described herein shall consist of this specification and the latest issue of MIL-C-83513.




FIGURE 1. Connector, receptacle (.050 spacing).

Ⓓ denotes change

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.




FIGURE 1. Connector, receptacle (.050 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connector, receptacle (.050 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.


Number cavities	A ±.010 (.25)	B BSC	C ±.010 -.018 +(.25) -(.46)	D BSC	CONFIG. LETTER
9	.775 (19.68)	.3342 (8.489)	.390 (9.91)	.565 (14.35)	A
15	.925 (23.50)	.4842 (12.299)	.540 (13.72)	.715 (18.16)	A
21	1.075 (27.30)	.6342 (16.109)	.690 (17.53)	.865 (21.97)	A
25	1.175 (29.84)	.7342 (18.649)	.790 (20.07)	.965 (24.51)	A
31	1.325 (33.66)	.8842 (22.459)	.940 (23.88)	1.115 (28.32)	A
37	1.475 (37.46)	1.0342 (26.269)	1.090 (27.69)	1.265 (32.13)	A
51	1.425 (36.20)	.9842 (25.00)	1.040 (26.42)	1.215 (30.86)	B
100	2.160 (54.86)	1.3842 (35.159)	1.432 (36.37)	1.800 (45.72)	C

INCHES	MM	INCHES	MM
.002	0.05	.096	2.44
.003	0.08	.100	2.54
.0035	0.089	.1141	2.898
.0038	0.097	.117	2.97
.004	0.10	.123	3.12
.005	0.13	.130	3.30
.006	0.15	.144	3.66
.007	0.18	.145	3.68
.008	0.20	.150	3.81
.010	0.25	.180	4.57
.014	0.36	.1852	4.704
.018	0.46	.189	4.80
.020	0.51	.193	4.90
.022	0.56	.195	4.95
.023	0.58	.200	5.08
.025	0.64	.2282	5.796
.030	0.76	.232	5.89
.032	0.81	.239	6.07
.033	0.84	.270	6.86
.045	1.14	.2712	6.888
.050	1.27	.275	6.99
.067	1.702	.281	7.14
.0671	1.704	.298	7.57
.069	1.75	.310	7.87
.070	1.78	.322	8.18
.088	2.24	.341	8.66
.090	2.29	.360	9.14
.093	2.36	.384	9.75
.094	2.39	.419	10.64
.095	2.41	1.438	36.53

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is .005 (0.13 mm).
4. Metric equivalents are in parentheses or columns.
5. Point from which lead length is measured.
6. Dimension line at point D locates the point of intersection of the two adjacent sides of the receptacle interface.

FIGURE 1. Connector, receptacle (.050 spacing) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.



NOTE: Engaging face of socket insert shown cavity identification numbers are for reference only and do not appear on part.

FIGURE 2. Insert arrangement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1. This specification sheet describes the socket side of a rectangular metal shell connector. This connector uses reverse gender contacts, i.e., the live pin recessed in the insulator with the static socket protruding from a shrouded interface.

Material and finish:
Interfacial seal: Silicone rubber or fluorosilicone rubber.

Contact identification: See figure 2 for contact layout numbering.

Contact connection: The pin contact (being recessed in the insulator) is normally connected to the live side of the circuit.

Current rating, maximum: 3 amperes per contact.

Ⓓ Mounting and mating hardware: Mounting hardware is to be ordered separately. For insert arrangements A thru G, use MIL-C-83513/5, configurations A and B. For insert arrangement H, use MIL-C-83513/5, configuration C (see figure 2).

Mating plug: Shall conform to MIL-C-83513/1 or MIL-C-83513/3.

Part number: Consists of the letter M, the basic number of the specification sheet, and a dash number compiled from the code.

M83513/04- A 01 1/ C

- M83513/04- : Specification sheet number
- A : Insert arrangement (see fig. 2)
  - A = 9
  - B = 15
  - C = 21
  - D = 25
  - E = 31
  - F = 37
  - G = 51
  - H = 100
- 01 : Wire type
  - 01 = M22759/11-26-9, 18 inches long 5/
  - 02 = M22759/11-26-9, 36 inches long 5/
  - 03 = M22759/11-26-( ), 18 inches long 2/ 6/
  - 04 = M22759/11-26-( ), 36 inches long 2/ 6/
  - 05 = QQ-W-343, Type S, 25 AWG, except shall be gold plated 10 microinches; 0.5 inch long
  - 06 = QQ-W-343, Type S, 25 AWG, except shall be gold plated 10 microinches; 1.0 inch long
  - 07 = QQ-W-343, Type S, 25 AWG, tin plated 100 microinches; 0.5 inch long
  - 08 = QQ-W-343, Type S, 25 AWG, tin plated 100 microinches; 1.0 inch long

  (01 through 04: 3/; 05 through 08: 4/)
- C : Shell finish
  - C = Cadmium or zinc (preferred)
  - N = Electroless nickel (Space applications only)

1/ These connectors have leads attached of which wire type, wire size, wire color, and lead length is specified in part number.

Ⓓ 2/ Color coding in accordance with MIL-STD-681, system I, except the appropriate color code shall be the individual contact cavity number minus 1. For example, for contact cavity number one, color code is 1-1 or 0 (black) for contact positions 1 thru 10 only.

3/ Lead length tolerance +1.0, -0.0 inch.

4/ Lead length tolerance +0.2, -0.0 inch.

5/ For connectors with shell finish N, wire shall be M22759/19-26-9.

6/ For connectors with shell finish N, wire shall be M22759/19-26-( ).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - MI
Navy - AS, SH
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, ME
Navy - CG, MC

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5935-3477-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:27Z
Check the source to verify that this is the current version before use.