INCH-POUND


MIL-DTL-83517/8A
w/AMENDMENT 2
19 April 2023
SUPERSEDING
MIL-DTL-83517/8A
w/AMENDMENT 1
21 April 2015


DETAIL SPECIFICATION SHEET

CONNECTOR, RECEPTACLES, ELECTRICAL, COAXIAL, RADIO FREQUENCY, STRIP OR MICROSTRIP TRANSMISSION LINE, SERIES SMA (SOCKET CONTACT, 8 HOLE SURFACE LAUNCH RIGHT ANGLE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83517.





DETAIL
TRANSITION END

Part or Identifying Number (PIN)	"A" dim.	Transmission line thickness
M83517/7-31001	.060 ±.003	.125
M83517/7-31002	.120 ±.003	.250

FIGURE 1. Series SMA, socket contact, surface launch, right angle, receptacle.

AMSC N/A
FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. All undimensioned pictorial configurations are for reference purposes only.

FIGURE 1. Series SMA, socket contact, surface launch, right angle, receptacle – Continued.

ENGINEERING PARAMETERS

Nominal impedance: 50 ohms.

Voltage rating: 335 V rms maximum at sea level.
150 V rms maximum at 70,000 feet.

Frequency range: 0 to 12.4 GHz.

Temperature rating: -65° to 105°C.

REQUIREMENTS:

Design and construction: See figure 1, table I and MIL-STD-348.

Force to engage and disengage:

Torque – 2 inch-pounds maximum.
Longitudinal force – Not applicable.

Coupling proof torque: Not applicable.

Inspection note: For each test of threaded coupling connector where the test is performed on mated pairs, the pairs shall be torqued to 7 to 10 inch-pounds.

Contact gaging: See figure 2.

Contacts with spring members:

Center contact (socket):

Oversize test pin - .0375 +.0001.
Test pin finish – 16 microinches.
Insertion depth - .030/.045.
Number of insertions – 3.

Insertion force test: Steel test pin diameter .0370 + .0001.

Insertion depth - .050/.075.
Test pin finish – 16 microinches.
Insertion force – 3 pounds maximum.

Withdrawal force test: Steel test pin diameter .0355 - .0001.

Insertion depth - .050/.075.
Withdrawal force – 1 ounce minimum.
Test pin finish – 16 microinches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.




FIGURE 2. Test pin data.

TABLE I. PIN and characteristics.

PIN M83517/8-	Connector figure no.	Characteristics
31001	1	Strip transmission line surface launch, right angle receptacle for .125 inch strip transmission line.
31002	1	Strip transmission line surface launch, right angle receptacle, for .250 inch strip transmission line.

Permeability of nonmagnetic materials: Applicable.

Seal:

Hermetic sealed connectors: Not applicable.
Pressurized and weatherproof connectors: Not applicable.

Center contact retention (excluding transition end):

Axial force: 6 pounds minimum.
Torque: 4 inch-ounces minimum.

Corrosion: In accordance with test procedure EIA/ECA-364-26, test condition B.

Voltage standing wave ratio (VSWR): 1.35 +.01F (F in GHz), maximum.

Test frequency range: From .5 to 12.4 GHz. (Using a test method approved by the qualifying activity.)

RF transmission loss: $.07\sqrt{F\ (F\ in\ GHz)}$ tested from 2-12.4 GHz.

RF leakage: Not applicable.

Connector durability:

Interface:

500 cycles minimum at 12 cycles/minute maximum rate.
Connector shall meet contact gaging and force to engage and disengage requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

Contact resistance: In milliohms maximum.

	Initial	After environment
Center contact:	3.0	4.0
Outer contact:	2.0	Not applicable

Thermal shock: Applicable, test condition A.

Moisture resistance: In accordance with MIL-STD-202-106.

No measurements at high humidity.

Insulation resistance: 5,000 megohms minimum in accordance with test procedure EIA/ECA-364-21.

Dielectric withstanding voltage: In accordance with test procedure EIA-364-20, test condition I.

Test voltage 1,000 V rms.

RF high potential withstanding voltage:

At a frequency between 5 to 7.5 MHz.
Leakage current – Not applicable.
RF voltage – 670 V rms.

Coupling mechanism retention force: Not applicable.

PIN: M83517/8-(dash number from table I.)

Group qualification: See table II.

TABLE II. Group qualification.

Group	Submission and qualification of any of the following connectors 1/ 2/ M83517/8	Qualifies the following connectors M83517/8
1	3+001	3+001 3+002

1/ Individual connectors other than listed are self qualifying only.
2/ Qualification of connectors, qualifies connectors of the same material only.
+ Denotes finish.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-83517, this document references the following:

MIL-STD-202-106
MIL-STD-348
EIA-364-20
EIA/ECA-364-21
EIA/ECA-364-26

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – CR
Navy – EC
Air Force – 85
DLA - CC

Preparing activity:
DLA – CC

(Project 5935-2023-043)

Review activities:
Army – AR, AT, CR4
Navy – AS, MC, OS
Air Force – 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:32Z
Check the source to verify that this is the current version before use.