NOT MEASUREMENT SENSITIVE

MIL-R-85111A(AS)
AMENDMENT 7
26 October 1992
SUPERSEDING
MIL-R-85111A(AS)
AMENDMENT 6
31 March 1987

MILITARY SPECIFICATION

RECOVERY ASSIST, SECURING AND TRAVERSING SYSTEM FOR LAMPS MK III HELICOPTER

This amendment forms a part of MIL-R-85111A(AS), dated 10 December 1980, and is approved for use within the Naval Air Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, SPECIFICATIONS, FEDERAL: Following "RR-W-410" listing, add:

"TT-C-490 Cleaning Method and Pretreatment of Ferrous Surfaces for Organic Coatings"

2.1, SPECIFICATIONS, MILITARY: Delete "MIL-C-915 General Specifications for Electrical Cable and Cord for Shipboard Use"

PAGE 2

2.1, SPECIFICATION, MILITARY: Following "DOD-P-17545" listing, add:

"MIL-H-17672 Hydraulic Fluid, Petroleum, Inhibited"

2.1, SPECIFICATIONS, MILITARY: Following, "DOD-P-24555" listing, add:

"MIL-C-24643 Cable, Electrical, 600 Volts"

PAGE 3

2.1, STANDARDS, MILITARY: Following "MIL-STD-831" listing, add:

"MIL-STD-869 Flame Spraying"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:25Z
Check the source to verify that this is the current version before use.

PAGE 5

3.1.1.2, third sentence: Delete.

3.2.2.1, line 5: Delete "MIL-H-83282" and substitute "MIL-H-17672".

PAGE 6

3.2.2.4, line 11: Delete "MIL-H-83282" and substitute "MIL-H-17672".

PAGE 7

3.2.2.6, line 10: Change "150 lbs" to "180 lbs".

3.2.2.7: Delete and substitute:

"3.2.2.7 Control Console. The Control Console shall contain all of the system controls, indicators and switches to be employed in the normal operation of the RAST system. The console shall conform to the installation and interface requirements of Installation Control Drawing, NAEC 700,000 except that provisions for operator voice communications and the connection and control thereof are not required. The console, when combined with other units of the RAST system into a system configuration, shall conform to the system performance requirements of 3.4.1."

3.2.2.8: Delete.

PAGE 11

3.4.1.2a, line 3: Delete "In either the Tail Probe Grid or". In line 14, delete "grid or".

PAGE 12

3.4.1.3a, line 3: Delete "and the Tail Probe engaged in the Tail Probe Grid,".

3.4.1.3d: Delete and substitute:

"d. A capability to reel-out the tailguide cables shall be provided in which the steady state force required at the on-deck ends to unspool the cables does not exceed 75 lbs."

PAGE 13

3.4.1.3g, line 7: Delete "0.2 g" and substitute "0.3g".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:25Z
Check the source to verify that this is the current version before use.

3.4.2.2.2.5.1, add subparagraph e:

"e. For those surfaces normally subjected to abrasive wear a two layer plating system shall be required. This plating system shall consist of a electroless nickel plate and an electrolytic electroless nickel plate. The following components shall be coated with two layer nickel plating system: steel sheaves (above and below deck) including rope accumulator sheaves and tachometer sheaves, drums of the movable sheave gear box, Recovery Assist Winch of the Winch Hydraulic Power Unit (WHPU), Tail Guide Winch (TGW), and traverse winch, and the sheave follower on the Recovery Assist Winch (WHPU)."

3.4.2.2.2.5.1, add subparagraph f:

"The tail guide exit sheave assemblies, down sheave assemblies and traverse track sheave assemblies shall have all manufactured steel components (except sheaves) that are not welded to the deck, coated with a single layer electroless nickel plating."

3.4.2.2.2.5.6a, delete the first line and substitute the following:

a. Steel. "Unless coated in accordance with 3.4.2.2.2.6 or nickel plated in accordance with 3.4.2.2.2.5.1 steel surfaces...".

3.4.2.2.2.5.6a, line 3: Delete ", track through components and tail guide sheave well components".

3.4.2.2.2.5.6, add subparagraph c:

"c. Arresting Beams, Rapid Securing Device. The beams shall be galvanically protected with .005 inch minimum thickness of aluminum flame spray to MIL-STD-869. The topcoat shall consist of .004 to .006 inch dry film thickness of primer followed by .003 to .005 inch fused film thickness of Nylon 11."

3.4.2.2.2.6c(4), delete the last sentence and substitute the following:

"The external surface of the track bolt inserts, when utilized, shall be treated with the ceramic (SermeTel or equal) coating."

3.4.2.2.2.6: Add:

"d. Epoxy powder coatings. Consideration shall be given to the used of epoxy powder coatings for exposed ferrous parts subject to abrasion and impact. Surface preparation for powder coatings shall be abrasice blasting per 3.4.2.2.2.3a with the addition of iron phosphating to TT-C-490 Type II. Dry film thickness shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:25Z
Check the source to verify that this is the current version before use.

Minimum: 3 mils

Maximum: 10 mils (average of 4 measurements. No single measurement greater than 15 mils)

If required, a finish coat to match the surrounding structure may be applied."

3.4.2.2.2.6 , add subparagraph e:

"e. Two layer plating system. The nickel plate-wear resistant plating consists of the sequential application of an electrolytic-electroless nickel two-layer plating. Following these applications, the two-layer plating shall be subjected to final heat treatment to establish the hardening of the surface."

PAGE 21

3.4.5.3: Delete.

3.4.5.5: Delete.

3.4.5.6, lines 3 and 4: Delete "and the enclosure of the Control console".

PAGE 22

* 3.5.5.2, line 3: Delete "MIL-C-915" and substitute "MIL-C-24643".

Add as last sentence: "Connectors that are exposed to the environment before shipboard installation shall have shipping closures of MS90376 protective plastic dust caps."

* 3.5.6: Delete last sentence and substitute:

"Couplings that are exposed to the environment before shipboard installation shall have aluminum alloy closures furnished with a dust and moisture sealing gasket or seal resistant to MIL-H-17672 hydraulic fluid."

PAGE 27

TABLE II: In subject column, line 14, delete "Full". In line 23, delete "Salt Fog, 3.4.5.3, 4.8.3.6, X". In line 27, delete "Dust, 3.4.5.5, 4.8.3.10, X".

PAGE 29

4.8.2.1: Delete and substitute:

"4.8.2.1 System performance test. System equipment, installed in accordance with established installation and interference requirements and combined into a representative system configuration, shall be subjected to a performance test to determine compliance with 3.4.1. The representative system configuration shall include at least one each of the individual items described in 3.2.2 and include the capability to demonstrate the performance of each system functional interface, internal and external; at least one track incorporating both straight and curved sections shall be employed. The test shall be performed as approved in accordance with 4.3."

Source: https://assist.dla.mil Downloaded: 2026-10-23T10:25Z
Check the source to verify that this is the current version before use.

TABLE III, line 10: Delete "4.8.3.6 Salt Fog" and "RSD, CC, ECR, IB for ECR". In line 14, delete "4.8.3.10 Dust" and "CC, ECR, RSD".

4.8.3.2, line 5: Delete "and Control Console are" and substitute "is".

4.8.3.6: Delete.

4.8.3.10: Delete.

The margins of this amendment are marked with an asterisk to indiate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Govenment assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity:
Navy -AS
(Project No. 1710-N051)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:25Z
Check the source to verify that this is the current version before use.