INCH-POUND

MIL-T-83816 (84)
31 Jul 90

MILITARY SPECIFICATION

TRUCK, LIFT, FORK, ELECTRIC, WALKIE REACH, 3000 POUND CAPACITY, 150 INCH MINIMUM LIFT

This specification is approved for use within WR-ALC, CODE 84, Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 SCOPE. This specification covers the requirements for a battery powered, industrial type forklift truck.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 **Specifications, standards, and handbooks.** The following specifications, standards, and handbooks form a part of this specification to the extent specified 'herein. Unless otherwise specified, the issues of' these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

Military

MIL-P-514	Plates, Identification, Instruction and Marking, Blank

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-889	Dissimilar Metals

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMVRG, Robins AFB, GA 31098-5609 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3930

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120 -5099.)

2.2 Non-Government Publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN NATIONAL STANDARDS INSTITUTE, INC (ANSI)

B56.1 - Safety Standards for Powered Industrial Trucks.
B56.11.3- Load Handling Symbols for Powered Industrial Trucks.

(Application for copies should be addressed to the American National Standards Institute Inc, 1430 Broadway, New York NY 10018).

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

NEMA Standards

(Application for copies should be addressed to National Electric Manufacturers Association, 155 East 44th St, New York NY 10017).

SOCIETY OF AUTOMOTIVE ENGINEERS, INC (SAE)

SAE Standards and Recommended Practices

J514	Hydraulic Tube Fittings, Standard
J534	Lubrication Fittings, Standard
J754	Lubrication Types - Construction and Industrial Machinery, Recommended Practice
J1176	External Leakage Classification for Hydraulic Systems, Recommended Practice

(Application for copies should be addressed to the Society of Automotive Engineers Inc, 40() Commonwealth Dr, Warrendale PA 15096).

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also maybe available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The truck shall be a reaching, walking operator, 12 or 24 volt system, electric drive motor, a solid state control, a roller mast, and as specified herein. The forklift shall be equipped with standard instruments, components and accessories normally required for the safe and effective operation of the truck. The truck shall be complete with all components that are standard and with the contractor's products, whether stipulated herein or not, together with such accessories and options, as may be specified herein. The truck shall be equipped with all other components and

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:46Z
Check the source to verify that this is the current version before use.

parts not specifically mentioned but necessary to provide a functional machine and shall conform in quality to that normally provided to the commercial industry.

3.1.1 First article. The supplier shall furnish one truck for examination and testing to prove that his production methods and choice of design detail will produce trucks and comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government. When specified (see 6.2) the Government will conduct any and all of the first article examinations and tests, as specified (see 6.2). Approval of the first article truck by the activity concerned shall not relieve the supplier of his obligation to furnish trucks conforming to this specification. The approved first article truck shall be presented for acceptance as the last unit for delivery under the contract after being rehabilitated to a new appearance. This shall include the furnishing of new tires.

3.1.2 **DESIGN.**

3.1.2.1 Design. The truck shall be designed for 3000 pound minimum capacity at 24 inch load center, up to the maximum lift height of the truck. The load center is measured from the forward vertical load carrying surface of the forks.

3.1.2.2 Safety. The truck shall conform to the applicable requirements of ANSI B56.1 and OSHA standards.

3.1.2.3 Environmental requirements. The truck shall operate in any ambient temperature from 0°F to plus 110°F.

3.1.2.4 Lubrication. Lubrication means shall be provided for all moving parts that require periodic lubrication. The types of lubricants shall be selected from and in accordance with SAE J754. Grease lubrication fittings shall conform to SAE J534.

3.1.2.5 Maintainability. All maintenance and servicing functions shall be capable of being performed using common hand tools. Provision shall be made for adjustment, servicing, and replacement of all electrical assemblies and components, hydraulic system components or assembly where applicable, battery, wearing parts of lift and tilt mechanism, brakes and components, wearing parts of steering assembly, tires, wheels, and horns without removal of any major parts other than covers. There shall be no interference with the servicing or draining of oils and lubricants to or from any assembly or components by frame members or other obstructions. Drain holes with removable drain plugs shall provide for complete drainage without disconnection of lines.

3.1.2.6 Fluid level indicator. All fluid level indicators shall be located where they are readily accessible without danger of burns or injury to the operator. If a panel must be opened to reach a level indicator, it shall open without the need of tools, and shall be hinged to stay on the truck when open.

3.1.2.7 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact. Dissimilar metals are defined in MIL-STD-889.

3.1.2.8 **Recovered** materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the forklift trucks may be newly fabricated from recovered materials to the maximum extent practicable, provided the forklift trucks produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the forklift trucks.

3.1.3 **Electric motors.** Motors shall be industrial type with a high starting torque. The insulation for motors shall be class B, F, or H as defined in NEMA standards.

3.1.4 Battery. The battery shall be 12 volts rated at less than 430 ampere hour capacity, or 24 volts rated at not less than 215 ampere hour capacity. In either case, the battery shall be sufficient for continuous operation of the forklift as described in 4.4.12 for at least 8 hours without recharging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

The battery shall be furnished fully charged by the contractor.

3.1.5 Hydraulic system. The hydraulic system shall consist of all hydraulic components necessary for operation of the forks and mast. It shall not include brake system components. Unless otherwise specified herein, all system components shall withstand a proof pressure that is equal to or greater than 11/2 times the maximum working pressure (1-1/2 time relief valve setting) without external leakage, damage, or permanent deformation. Hydraulic fittings on pumps, valves, and cylinders shall be the o-ring straight thread type as specified in SAE J514. A pipe tap or straight thread o-ring boss test. point shall be located at the outlet of each pump or pressure inlet of each control valve for measuring pressure. The system shall provide for lowering of rated load at not more than 80 feet per minute in the event of failure of or damage to hydraulic hose(s) supplying the lift cylinder.

3.1.5.1 **Hydraulic system** filtration. A system filter shall be furnished in either the suction or return line .

3.1.6 Uprights and carriage assemblies. Uprights shall be the telescopic roller type. Rollers shall be the permanently lubricated for life type. Adequate means shall be provided in the uprights to compensate, by replacement or adjustment, for wear which may develop between lateral rolling contacts. Positive means shall be provided to prevent overtravel of the carriage or channel in both upper and lower positions.

3.1.6.1 Forks. The forks and fork carrier shall conform to ANSI 356.1. Forks shall be 2.5 inches maximum thickness, 5 inches maximum width, and 35 to 42 inches long. Fork thickness shall not exceed 1/2 inch at the tips and the taper shall not be less than 14 inches long. Taper shall be on the under side of the forks. The top of the fork tips shall be chamfered or rounded to break comers and provide smooth edges. The forks shall be capable of being laterally adjusted without the use of hand tools. With the forks at their widest spacing, they shall span at least 27 inches, measured from the outside of the forks. With the forks at their narrowest spacing, they shall measure no more than 16 inches from outside to outside of the forks.

3.1.6.2 Load backrest. A metal backrest, or backrest with extension, shall be provided. There shall be no protruding bolts or appendages beyond the side plane of the load backrest. The load backrest, in conjunction with fork and hanger design, shall provide a vertical rear guard at least 48 inches high measured from the load carrying surfaces of the forks.

3.1.6.3 **Fork extension.** Forks and load backrest shall be able to extend forward at least 24 inches from the rearmost position.

3.1.7 Tires. The tires shall be new, standard commercial type.

3.1.8 Steering. Steering shall be controlled by a steering arm which will rotate in a horizontal plane to steer the truck. The arm shall rotate at least 90° in each direction. The arm shall pivot in a vertical plane from vertical to horizontal position. It shall be spring controlled to return to vertical position when it is released.

3.1.9 Brakes. The brakes shall be applied when the steering arm is in vertical and horizontal position. When the brakes are applied, the power to drive motor shall be automatically disconnected.

3.1.10 Speed Direction controls. Speed and direction controls shall be located on the steering arm handle. The controls shall be operated by thumb or fingertips with selection of at least 2 speeds, or variable speed, for forward and reverse.

3.1.11 Horn. Truck shall be equipped with an electric horn controlled from the steering arm.

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:46Z
Check the source to verify that this is the current version before use.

3.1.12 Controls and instrumentation markings. All controls and instrumentation shall be provided with position markings conforming to ANSI B56.11.3.

3.1.13 **Master s** - A key operated master switch shall be provided. When key is removed control circuits shall be opened or interrupted making it impossible for any electrical control circuit to be activated. Two keys shall be supplied with each truck. All keys shall be identical for every truck on this contract.

3.1.14 Hur meter. An electrically operated hour meter shall be provided. It shall operate when the master switch (3.1.13) is in the "on" position.

3.1.15 Floodlight. There shall be one floodlight mounted on either the right or left mast upright. It shall have a rating of at least 25 watts, and shall be adjustable at least 45 degrees above and below the horizontal plane, and 90 degrees to both sides of the fore and aft longitudinal centerline of the truck.

3.2 Performance.

3.2.1 Lifing speed. Speed of lift with rated load on the forks shall be not less than 12 feet per minute over the entire distance from ground level to maximum fork height.

3.2.2 **Lowering** speed of lowering unloaded forks shall be not less than 25 feet per minute over the entire distance from maximum fork height to ground level. Speed of lowering forks with rated load shall be not more than 80 feet per minute over the entire distance from maximum fork height to ground level. The hydraulic control system shall be damped, metered, or easily manually regulated to reduce shock and prevent the truck from overturning when a rated load is lowered at maximum speed and stopped quickly .

3.2.3 Brake. The brake shall be capable of holding the truck with rated load on a 15 percent grade in both forward and reverse directions.

3.2.4 Right angle stacking. The truck with rated load shall be capable of right angle stacking in an aisle not more than 86 inches wide, into a 56 inch wide space for the load.

3.2.5 Speed. While carrying the rated capacity load on a level surface, truck shall be capable of attaining speed of at least two miles per hour, in both forward and reverse directions.

3.2.6 **Slope ascension forward direction.** The truck shall be capable of ascending a 15 percent grade on a dry concrete surface with and without rated load. The truck shall be able to accelerate from a dead stop on this slope when carrying rated load.

3.2.7 Upright tilt. With no load on the forks, the mast shall have a minimum forward tilt of two degrees and a minimum rearward tilt of four degrees. Positive means shall be furnished to prevent cavitation of the tilt cylinders.

3.2.8 **Collapsed mast** height. Collapsed mast height of unloaded truck with the mast vertical, measured from the ground to the top of the mast, shall not exceed 95 inches.

3.2.9 Lift height. The minimum lift height, with truck bearing rated capacity load and the up-rights fully extended and vertical, shall be 150 inches.

3.2.10 Free lift height. With no load on the forks and the mast vertical, the vertical distance from the ground to the horizontal load carrying surfaces of the forks, without increasing the specified collapsed mast height, shall be not less than 12 inches.

3.2.11 Lift assembly drift. The lift assembly shall be capable of holding the rated load at maximum height not less than 10 minutes with not more than one inch of vertical drift and not more than one

Source: https://assist.dla.mil -- Downloaded: 202610-23T09:46Z
Check the source to verify that this is the current version before use.

degree of rotational drift from the vertical.

3.2.12 Stability. The truck shall conform to stability requirements of ANSI B56.1.

3.3 Painting. All exterior surfaces and surfaces normally painted shall be prepared and primed using material compatible with the final paint. Unless otherwise specified (see 6.2), the truck shall be painted with Polyurethane paint, Color Number 24052 of FED-STD-595. All exterior trim (wheels, rims on lights, etc) shall be the same type and color as the exterior paint.

3.4 **Walkway coating.** Floor plates and step surfaces shall be in accordance with ANSI 1356.1.

3.5 Identification marking. Each truck shall be identified with an identification plate conforming to MIL-P-514, Type I, style 1, composition C, of Type I, grade A, class 1 material which shall be located in a visible and permanent location on the truck. The identifying data shall be stamped in letters in accordance with MIL-P-514. The plate shall be securely attached to the truck with screws, bolts, or rivets and shall be furnished and mounted by the contractor.

3.6 Truck Markings on trucks shall be black, Color Number 37038 of FED-STD-595. Characters shall be block-type capitals and Arabic numerals. Location, information, and character size shall be as follows:

Information	Example	Location	Minimum Character Size (Ht)
Agency	U S Air Force	On each side and rear	1 1/2 inches
Registration No	10D315	On each side and rear	1 1/2 inches
Capacity	3000 pounds	On each side and mast	1 1/2 inches
Safety	No riders	On each side of mast	2 inches

3.7 Identical items. All fork lifts furnished under this specification shall be physically and mechanically identical to the first article that is approved by the Government except that product improvements incorporated in the contractor's standards commercial product lines are permitted at no cost to the Government subject to the following:

a. Physical and performance characteristics defined herein have not been infringed.
b. New components involving Government selected repair parts are directly interchangeable with the superseded component or part.
c. The Government is notified of all changes and alterations a minimum of 15 days in advance of production commitment dates, and production effectivity, by serial number and date, has been identified.
d. Appropriate changes are issued to the Government validating operating, maintenance, and parts manuals.

3.8 Workmanship. The workmanship shall be high quality when compared to industry standards. There shall be no rough surfaces or edges on machined or flame cut pieces.

4. QUALITY ASSURANCE PROVISIONS.

4.1 **Responsibility for inspection.** Unless otherwise specified in the contract or purchase order,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 **Responsibility for compliance.** All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program, The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 **Classification of inspection evaluations and demonstrations.** Inspections, evaluations, and demonstrations shall be classified as follows:

a. First article evaluation and demonstration (see 4.3).
b. Production run-in (see 4.5).
c. Inspection of packaging (see 4.7).

4.3 First article evaluation and demonstratiom Prior to delivery the manufacturer shall make one forklift available, for first article evaluation and demonstration. The forklift and its components shall be compared with this document, calculations, and test data to verify compliance with this Purchase Description. The forklift shall then be subjected to the demonstrations as specified herein. Permanent deformation, overheating, malfunction, failure to meet performance requirements, failure to complete any demonstration, any wear evidenced by removal of material, or leakage of fuel, hydraulic oil in excess of Class 3 or Class 3D of SAE J1176, or lubricants shall be cause for rejection of the forklift.

'4.4 **Demonstrations.**

4.4.1 **Demonstration condition.** Unless otherwise specified herein, demonstration shall be at the ambient temperature and climatic conditions existing at the place of demonstration. Only that maintenance established by the contractor and submitted as a maintenance schedule prior to commencement of the demonstration shall be performed during the demonstration.

4.4.2 Rated load. During the demonstrations specified herein, the rated load shall be a 3000 pound (plus 100, minus O pounds) cube, 48 inches (plus 1/2, minus O inches) on each side, with a center of gravity located at the geometrical center of the cube. The cube shall be provided by the contractor.

4.4.3 **Maximum lift height, collapsed mast height, free lift height.** With no load on forks and mast in true vertical position measure and record collapsed mast height and free lift height. With rated load on the forks, measure and record the maximum lift height. Nonconformance with 3.2.8, 3.2.9, and 3.2.10 shall be cause for rejection.

4.4.4 Lifting speed and lowering speed. Record time in seconds required to raise rated load from floor to maximum fork height. Record time required to lower rated load from maximum fork height to floor at maximum lowering speed. Measure and record distance in inches from floor to top surface of forks in fully lowered position. Record time required to lower unloaded forks from maximum fork

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

height to fully lowered position. The raising and lowering shall be performed three times. Nonconformance to 3.2.1 and 3.2.2 shall be cause for rejection.

4.4.5 Right angle stacking. With rated load and forks raised approximately six inches above the ground and mast vertical demonstrate that truck can meet the right angle stacking dimension specified in 3.2.4. Nonconformance with 3.2.4 shall be cause for rejection.

4.4.6 Travel speed. Operate the truck with rated load in carry position. Truck shall attain speed specified in both forward and reverse directions. The truck shall be driven a distance necessary to attain maximum speed prior to entering a measured distance of not less than 44 feet. The truck shall be driven over the measured course at least two times in each direction. The speed shall be the average of the two runs in each direction. Inability of the truck to attain the minimum speed as specified in 3.2.5, failure of any component, overheating, malfunction, or leakage of fluid shall be cause for rejection.

4.4.7 Slope ascension. Drive truck forward with rated load along a horizontal approach and on to a ramp or slope of specified grade (see 3.2.6) and bring to a complete stop halfway up the ramp. Start from a dead stop and proceed up the ramp to a horizontal surface. Repeat. the procedure without the load.

4.4.8 Brake. Demonstrate capability of the brake to hold truck with the rated load on a grade specified in 3.2.3.

4.4.9 Tilt. Place truck without load on a flat level surface. Raise forks to an elevation of approximately 2 feet and place mast in vertical position. Tilt mast to full forward position and record angle of tilt. Tilt mast to full rearward position and record angle of tilt. Nonconformance to 3.2.7 shall be cause for rejection.

4.4.10 Lift assembly drift. Operate the lift and tilt systems for at least three minutes to heat the hydraulic fluid to normal operating temperature. Raise rated load to maximum fork height with outer channel in true vertical position. Hold for time specified in 3.2.11. Record vertical and rotational drift. Nonconformance to the requirements of 3.2.11 shall be cause for rejection.

4.4.11 Stability. Conduct “forward stacking,” “forward travel,” “lateral stacking,” and "lateral travel” tilting platform tests in accordance with ANSI 1356.1. Nonconformance with ANSI B56.1 shall be cause for rejection.

4.4.12 Forklift operation. The forklift, carrying the rated capacity load, shall be operated for a minimum of 500 cycles over a surface paved with concrete, asphalt, macadam, or equivalent. Each cycle shall consist of the following:

a. Raise the rated load to the carrying position and tilt the mast rearward.
b. Travel forward a sufficient distance to operate a minimum of 50 feet at maximum speed.
c. Slow truck to safe speed and negotiate a 90 degree turn. Travel at least 25 feet, stop truck and raise the load to maximum lift height at maximum lift speed.
d. Lower the load at maximum lowering speed to the ground. Raise to the carry position.
e. Tilt the mast to the full forward position and return to the full rearward position.
f. Drive truck back to initial start point. This constitutes one cycle. Repeat steps 2 through 6 until 500 cycles have been completed.
g. Two-hundred and fifty (250) cycles shall be performed making a right hand 90 degree turn, and 250 shall be performed making a left hand 90 degree turn.
h. The key switch and horn shall be operated once each 50 cycles of operation.

Inability of the forklift to lift the rated load, overheating, leakage of fluid in excess of Class 3 or Class 3D of SAE J1176, malfunction, failure of any component, any wear evidence by removal of material, or failure to complete the operation shall be cause for rejection. Normal battery changes are permit-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

ted, if required, to conduct the test.

4.5 Production run-in. Each forklift carrying a rated load shall be subjected to a production run-in and servicing as specified herein. Inability to complete the run-in, overheating, failure of any components, malfunction of any control, or evidence of leakage of fluids shall be cause for rejection of the forklift by the Government until such deficiencies are corrected.

4.5.1 Travel. Demonstrate starting, ascending and descending a 15 percent ramp, steering, and high speed travel. Operate all lights, horns, and brake system not less than two times during this demonstration.

4.5.2 Mast assembly. Demonstrate maximum lifting and lowering speed and forward and rearward tilt of the forks. Each operation shall be performed at least three times with the rated load on the forks.

4.5.3 Servicing and adjustment. Prior to delivery, the manufacturer shall service and adjust each forklift for proper operational use, including at least the following:

a. Adjustment of mast assembly.
b. Adjustment of solid state control modules.
c. Adjustment of brake system.
d. Adjustment of steering.
e. Continuity check of the electrical system, including filling and charging the battery.

4.6 Inspection of packaging. Each truck shall be completely prepared for shipment and shall be inspected for the correct methods for presentation, packing, and marking as specified in 5.1. Nonconformance to 5.1 shall be cause for rejection of the packaging.

5. PACKAGING.

5.1 Preservation, packaging, and marking. Shall be as specified in the contract.

6. NOTES.

(This section contains information of a general or explanatory nature that maybe helpful, but is not mandatory.)

6.1 Intended use. Trucks described herein are intended for stacking, unstacking, and moving cargo in and around commissary warehouses, and for moving cargo in and out of highway trailers and railroads cars. The trucks are intended for operation over paved and other hard surfaces.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.
b. When Government will conduct tests and to what extent of testing (see 3.1.1).
c. When paint shall be other than as specified (see 33).
d. Time frame for submitting first article test report (see 6.4).

6.3 First article. When first article inspection is required, the item shall be a first article sample to be tested as specified in 4.4. The contracting officer should include specific instructions in acquisition documents regarding time frame for submission of first article test report (see 6.2), approval of first article test results and disposition of the first article unit. The first article test report shall include a detailed description of the examination and demonstration performed. All deficiencies encountered and actions taken to correct the deficiencies shall be included. Invitations

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

for bids should provide that the Government reserves the right to waive the first article inspection to those bidders offering a product which has been previously acquired and tested by the Government, and that bidders offering such products, who wish to reply on such production and test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Subject Term (Key Word) Listing.

Battery Powered
Fork Lift
Material Handling
Reaching
Walk Behind

Preparing activity
Air Force -84

Custodians:
Air Force -99

Project Number
3930-F018

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
3. DOCUMENT TITLE		

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER		
a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY	
a. NAME George Cyphers	b. TELEPHONE (Include Area Code) (1) Commercial (912)926-6171 (2) AUTOVON AV 468-6171
c. ADDRESS (Include Zip Code) WR-ALC/MMVRG Robins AFB, GA 31098-5609	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2025-07-27 07:07:27
Check the source to verify that this is the current version before use.