MIL-C-303C
8 March 1979
SUPERSEDING
MIL-C-303B
17 October 1972
MIL-C-303A
25 May 1959

MILITARY SPECIFICATION

CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nylon, Nonrigid, No. 2

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a nylon cloth case consisting of two parts hinged together and fitted with a slide fastener and a carrying handle. The case contains two interior compartment partitions.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-F-106	- Fastener, Slide, Interlocking.
V-T-285	- Thread, Polyester.
PPP-B-566	- Boxes, Folding, Paperboard.
PPP-B-636	- Boxes, Fiberboard.
PPP-B-676	- Boxes, Setup.

MILITARY

MIL-F-495	- Finish, Chemical, Black, For Copper Alloys.
MIL-W-4088	- Webbing, Textile, Woven Nylon.
MIL-F-10884	- Fasteners, Snap.
MIL-C-43128	- Cloth, Plain Weave, Nylon, Water Repellent, OG-106.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Headquarters, Defense Personnel Support, ATTN: Directorate of Medical Materiel, Code ATT, 2800 So. 20th Street, Philadelphia, PA 19101, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6545

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

Federal Test Method Std. No. 151 - Metal, Test Methods.
FED-STD-595 - Colors.
FED-STD-751 - Stitch, Seam and Stitching.

MILITARY

MIL-STD-105 - Sampling Procedures And Tables For Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MS-27977 - Fasteners, Snap, Style 1 (Large Curtain Type).

DRAWING

DEFENSE PERSONNEL SUPPORT CENTER (DPSC)

2032 - Case, Medical Instrument and Supply Set, Nylon, Nonrigid, No. 2.

(Copies of specifications, standards and drawing, required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposals shall apply.

THE COLOR ASSOCIATION OF THE UNITED STATES, INC.

United States Army Color Card of Standard Shades for Slide Fastener Tapes.

Department of Defense Standard Color Card of Official Standardized Shades for Sewing Threads (1968).

(Application for copies of each should be addressed to the Color Association of the United States, Inc., 200 Madison Avenue, New York, NY 10016).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Component parts. The body of the case shall consist of two major parts hinged together on one side, along with a slide fastener, and a carrying strap. The handle (carrying strap) shall be fitted with four snap fasteners. Partitions within the body of the case shall form compartments.

* 3.2 Materials. The material shall be as specified herein. Metals shall conform to the chemical requirements of their applicable specifications, when tested as specified (see 4.5.1).

3.2.1 Cloth, nylon. The water repellent nylon cloth used for fabrication of the case shall conform to MIL-C-43128. Color shall be Olive Green Number 106.

3.2.2 Webbing, nylon. The 1-1/4 inch nylon webbing for the carrying strap shall conform to type III of MIL-W-4088. Color shall be Olive Drab No. 7.

3.2.3 Thread, polyester. The thread for all stitching, except overedge stitching, shall be type I, class 1, subclass B, size F, of V-T-285. Size B thread shall be used on overedge stitching. Thread shall be dyed Olive Drab Shade S-1, C.I. 66022, except that the colorfastness requirements and test methods shall be limited to weathering only.

3.2.4 Fasteners, snap, curtain style. Snap fasteners shall be the female halves of style 1 fasteners, in accordance with MIL-F-10884. The fasteners shall have a Number 2 Black Finish.

3.2.5 Fastener, slide. The slide fastener shall be a non-separating slide fastener, conforming to V-F-106, type I, style 4, size M. It shall be a single slider with a padlock pull 1 inch long. The metal parts of the fastener shall be brass with a black chemical finish conforming to MIL-F-495.

3.2.5.1 Tape. The slide fastener tape shall be vat dyed Olive Drab, Shade S, conforming to U.S. Army Color Card of Standard Shades for Slide Fastener Tapes, and shall be water repellent and mildew resistant in accordance with V-F-106. Mildew resistance shall be obtained by using copper-8-quinolinolate only.

* 3.2.5.1.1 Water repellence. The finished tape shall pass the water repellence test when tested as specified (see 4.5.2).

* 3.2.5.2 Salt spray resistance. The slide fasteners shall pass the salt spray resistance test requirements as specified (see 4.5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

3.2.6 Stitching sealing. In accordance with the manufacturers directions, exterior stitching shall be sealed by the application of one of the two sealants listed in 6.5 or equal.

3.3 Construction. Design, construction and assembly of the cases, including carrying strap, shall be as specified herein and as shown on Defense Personnel Support Center Drawing 2032.

3.3.1 Stitching, machine. All stitching shall conform to FED-STD-751 as follows:

For all stitching except overedge stitching: type 301, 8 to 10 stitches per inch.

For overedge stitching (single operation optional): type 503 or 504, 8 to 10 stitches per inch.

For closing seams and overedge stitching (simultaneous operation optional): type 301 in combination with 503, 504 or 502, 8 to 10 stitches per inch.

All edges of closing seams shall be overstitched. There shall be no lubrication of the thread, by any means, either prior to, or during sewing. Any of the operations requiring box, box with cross stitch, W stitching, straight line tacking, or any other design of stitching cited in this specification, may be performed with an automatic stitching machine provided that the requirements for stitch pattern, stitches per inch, size, and types of thread are met; and that at least three or more tying, overlapping, or back stitches are used to secure the ends of stitching. Bartacks shall be at least 3/4 inch long with 46 to 52 stitches per inch. The width of zipper stitching shall be 3/16 inch.

3.3.1.1 Type 301 stitching. Thread breaks in stitching shall be overstitched no less than 1 inch at each break. Stitching shall be backstitched no less than 1 inch at the ends, except where ends are turned under in a hem or are held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching, and the lock will be imbedded in the sewn materials.

3.3.1.2 Overedge stitching. Thread breaks in overedge stitching shall be overstitched no less than 3/4 inch at each break. Thread tension shall be maintained so that there will be no loose stitching.

3.3.2 Placement of snap fasteners. The four snap (curtain) fasteners shall be positioned as shown on the drawing and so arranged that all four shall be detachable from above downward. The finished cases shall fit on the test panel without distortion when tested as specified (see 4.5.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

3.3.3 Attachment of curtain fasteners. Holes shall be made in the webbing before insertion of the prongs of the female element. Holes shall be small enough to require prongs to be forced through them. Fastener elements shall be tightly clinched so as not to become detached from the webbing in normal use. Holes in webbing as centers of fasteners shall be large enough so as not to impede insertion of studs into sockets.

3.3.4 Attachment of slide fasteners. Slide fasteners shall be attached as shown on the drawing. Top and bottom stops shall be in proximity with the cross-stitching in order to insure complete closure and to eliminate openings in the tape extension. The cloth body of the case shall be stitched to the fastener tape at a sufficient distance from scoops to permit free movement of slider and pull.

* 3.4 Marking for identification. The case shall be permanently and legibly marked with black waterproof ink or paint in accordance with the drawing, except for the red cross. A Geneva Red Cross on a white background shall be applied to the case as shown on the drawing. Color of the cross shall be Color 11105 (gloss red) as shown in FED-STD-595, and the white background shall be Color 17886 (gloss white) of the same specification.

* 3.5 Workmanship. Workmanship shall be first class throughout. Complete cases (including carrying straps) shall be well made and free from defects which detract from their appearance or impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification to assure supplies and services conform to prescribed requirements.

4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of three years after delivery of the supplies to which such records relate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. Certificates of quality, supplied by the manufacturer of the nylon cloth, webbing, thread, and fasteners, may be furnished in lieu of actual performance of such testing by the contractor, provided lot identity has been maintained and can be demostrated to the Government and provided also that the results obtained comply with those described in this specification. The certificate shall include the name of the contractor, the contract number, the name of the manufacturer or supplier, the NSN, the item identification, the name of the component/material, the lot number, the lot size, the sample size, the date of testing, the test method, individual test results, and the specification requirements.

* 4.2 Sampling.

* 4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and table I. Unit of product for examination purposes shall be one case.

TABLE I. Sampling for examination.

	Inspection level	AQL (percent defective)
For visual examination		
Major defects	II	2.5
Total (Major and Minor combined)	II	6.5
For dimensional examination	S-3	4.0

* 4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105 and table II. Sufficient samples of the component materials shall be selected from each lot of material used in the manufacture of the case, to perform tests as required by the applicable reference specifications, or by tests specified herein. When sample size is not specified, it shall be as indicated for Inspection Level S-1 of MIL-STD-105, except that the acceptance number shall be zero for all sample sizes, and a minimum of three samples shall be taken regardless of lot size. The unit of product for testing shall be the quantity of material necessary to perform all required tests one time each. The same material may be used to perform two or more tests. Lot sizes are express in multiples of the following.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

Cloth, nylon----------Yard or fraction of a yard
Tape----------Yard or fraction of a yard
Thread, polyester--------Cone or spool
Webbing----------Yard or fraction of a yard
Hardware items----------Each

Four ounces of each lot of each metal used in the construction of the cases shall be selected for chemical analysis.

TABLE II. Sampling for tests.

Component	Characteristic	Requirement	Test procedure
Metal samples	Chemical analysis requirements	3.2	4.5.1
Finished tape	Water repellence test	3.2.5.1.1	4.5.2
Slide fasteners	Salt spray resistance	3.2.5.1.2	4.5.3
Case	Test for placement of snap fasteners	3.4	4.5.4

4.3 Examination. The case shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects listed in table III. Examination shall not be restricted to the classified possible defects listed below.

TABLE III. Classification of defects.

Categories	Defects
Major	
101	Any hole, cut, tear, mend, patch or unauthorized splice.
102	Any weakening defect such as smash, multiple float, or loose slub that may develop into a hole.
103	Spots, stains or faded areas.
104	Component part omitted or required operation omitted.
105	Puckered or twisted seam.
106	Seam type other than specified.
107	Stitch type other than specified.
108	Less than 8 stitches per inch.
109	One or more rows of stitching omitted.
110	Seam open 1/4 inch or more.
111	Raw edges.
112	Webbing not size specified.
113	Frayed or scalloped edges of webbing.
114	Webbing not firmly or tightly woven.
115	Any part of case pleated, twisted or caught in any unrelated row of stitching.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (continued).

Categories	Defects
Major	
116	Snap fastener broken or malformed.
117	Burrs or sharp edges.
118	Snap fastener finish omitted or not uniform.
119	Not slide fastener specified.
120	Slide fastener does not operate smoothly.
Minor	
201	Needle chews.
202	Open seam less than 1/4 inch. Broken or skipped stitches occuring twice or more in the same row of stitching.
203	Ends of stitching backstitched less than 3/4 inches.
204	Markings omitted, incorrect, illegible or not size specified.
205	Colors not as specified.
206	Registration of Red Cross on white background not within allowable tolerance.
207	Webbing cut ends not heat sealed.

* 4.3.2 Dimensional examination. The case shall be examined for defects in dimensions. Any dimension not within the tolerances specified herein shall be classified as a defect.

* 4.4 Packaging inspection. The inspection of the unit package, intermediate package, packing and marking for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification and the marking requirements of MIL-STD-129.

* 4.5 Tests. Test shall be conducted to determine compliance with specification requirements.

* 4.5.1 Chemical analysis requirements. Metal samples shall be analyzed in conformance with Method 111 or 112 of Federal Test Method Standard No. 151. In case of dispute, Method 111 shall be used for referee analysis.

* 4.5.2 Water repellence test. The finished tape shall be tested for water repellence as specified in V-F-106.

* 4.5.3 Salt spray resistance. The slide fasteners shall be tested for salt spray resistance as specified in V-F-106.

* 4.5.4 Test for placement of snap fasteners. A metal panel shall be made as shown on drawing 2032. The studs on the panel shall be selected from those shown on MS-27977 and shall fit the specified fasteners referenced in 3.2.4. The finished cases shall be attached to the fasteners.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Unit of issue. One case constitutes a unit of issue.

5.1.2 Level A.

5.1.2.1 Unit package. Each case shall be neatly folded and wrapped in kraft paper. The wrap shall be secured with kraft gummed or pressure-sensitive tape. As an alternate, each folded case may be packaged in a clear polyethylene bag having a minimum wall thickness of 0.00125 inch. A 1/4 inch diameter hole shall be made at one corner of the bag to allow excess air to escape. Closure of the bag shall be by heat sealing or by means of a tuck or reverse flap.

5.1.2.2 Intermediate package. Twelve unit packages shall be packaged in a box conforming to PPP-B-566 or PPP-B-676. Closure shall be as specified in the appendix of the applicable box specification.

5.1.3 Level C. Each case shall be packaged in a manner that will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A. Twelve intermediate packages shall be packed in a shipping container designed for a type 2 load and conforming to PPP-B-636, class weather-resistant. Closure, strapping and waterproofing shall be as specified in the appendix of the box specification.

5.2.2 Level B. Twelve intermediate packages shall be packed in a shipping container designed for a type 2 load and conforming to PPP-B-636, class domestic. Closure shall be as specified in the appendix of the box specification.

5.2.3 Level C. The packaged cases shall be packed in shipping containers in a manner that will afford adequate protection against damage during direct shipment from the supply source to the first receiving activity. These packs shall conform to the carriers' rules and regulations.

5.3 Marking. Each unit package, intermediate package and shipping container shall be marked as specified in MIL-STD-129. Polyethylene bagged items shall have the required information printed on the front of the bag or on a label inserted in the bag in such a manner to permit ready identification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

* 6. NOTES

6.1 Intended use. The case covered by this specification is intended for use as a container for First Aid Kit, General Purpose, Panel-Mounted, NSN 6545-00-919-6650. The assembled kit is installed in naval vessel gun turrets, in aircraft and small watercraft.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) National Stock Number (NSN).
(c) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

6.3 This specification does not cover all types, classes, grades or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the items which are normally procured to meet requirements.

6.4 This specification covers the following item appearing in the Federal Supply Catalog:

National Stock Number	Item Identification
6545-00-912-9860	CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nylon, Nonrigid, No. 2, 7-1/2 inches Long by 4-3/8 inches Wide by 4-1/2 inches High.

6.5 Stitching sealants.

Bostik No. 7058
Bostik Chemical Group, USM Corp.
Middletown, MA 01949

Tite Seal
Eureka Tent Corp.
621 Conklin Highway
Binghampton, NY 13902

6.6 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Logistics Agency - DM

Project Number 6545-0041

Review activity:
DoD - MB

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government Fold on lines on reverse side, staple in corner and send to preparing activity. Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed

NOTE This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-303C CASE, MEDICAL INSTRUMENT AND SUPPLY SET, Nylon, Nonrigid, No.2

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C REASON FOR RECOMMENDED CHANGE(S)

2 REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO
	DATE

DD FORM 1 OCT 78 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.

FOLD

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HEADQUARTERS
DEFENSE PERSONNEL SUPPORT CENTER CODE: ATT
DIRECTORATE OF MEDICAL MATERIEL
2800 SOUTH 20TH STREET
PHILADELPHIA, PA 19101

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T07:00Z
Check the source to verify that this is the current version before use.