MILITARY SPECIFICATION

CONTAINER ASSEMBLY FOR DEMOLITION KIT, BLASTING: XM268

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers molded, high molecular weight polyethylene plastic container assemblies for shipment and storage of the components used in the XM268 Demolition Kit (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Issue of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	-Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1188	-Commercial Packaging of Supplies and Equipment

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

Material-Body, Polyethylene	9329619
Container Assembly	9329679
Cap	9331297
Cap Assembly	9335529
Liner, Cap	9335530
Material-Cap, Polyethylene	9340662
Body	11828918

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D638	-Tensile Properties of Plastics, Standard Test Method for
ASTM-D746	-Brittleness Temperature of Plastics and Elastomers by Impact, Standard Test Method for
ASTM-D790	-Flexural Properties of Plastics and Electrical Insulating Materials, Standard Test Methods for
ASTM-D1238	-Measuring Flow Rates of Thermoplastic by Extrusion Plastometer, Standard Method of
ASTM-D1505	-Density of Plastics by the Density-Gradient Technique, Standard Test Method for
ASTM-D1693	-Environmental Stress-Cracking of Ethylene Plastics, Standard Test Method for
ASTM-D1928	-Preparation of Compression-Molded Polyethylene Test Samples

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Material. The resins used in the manufacture of the container assemblies (Body and Cap) shall be in accordance with drawing numbers 9329619 and 9340662, respectively. In addition, the container assemblies shall be in accordance with the applicable drawings and specifications.

3.2 Mold release agent. The mold release agent(s) used for the body (11828918) and cap (9331297) shall conform to current standard industrial practice. The marking area of the body (11828918) shall be flame treated prior to any marking operation.

3.3 Reworked material. No reworked material or reground scrap (including runners and sprues) shall be utilized in molding container assemblies under this specification. However, initial pelletizing of the molding compositions used shall not be construed as reworking.

3.4 Physical properties. The materials for the caps and bodies shall conform to the physical properties listed in Table I, when tested as specified in 4.5.5.

TABLE I

Physical Properties

Property	Body	Cap
Density, gm/ml	0.948-0.952	0.943-0.947
Melt flow, Condition F, gms/ 10 minutes at 375°F (190°C), 21,600 gms. load	8.0-12.0	1.5-2.5
Environmental Stress-Cracking (Condition A, 50 percent failure point, hours	500-1100	30-80
Tensile strength (2 inches or 5.08 cm per minute), minimum psi, (kg/cm^2)	3,500-4,100 (246-288)	3,200-3,800 (225-267)
Elongation (2 inches per minute, percent	650 min.	200-400
Brittleness temperature, max.	-180 F(-118 C)	-180 (-118 C)
Flexural modulus, psi, (kg/cm)	163,000-187,000 (11,459-13,146)	140,000-160,000 (9,842-11,246)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

3.5 Drop test of container assemblies. The container assembly shall withstand the drop test at ambient and cold temperature of 0° F (-17,8° C) without any evidence of breakage when tested as specified in 4.5.6.

3.6 Air test. The container bodies shall withstand a pressure of three (3) p.s.i. min., as indicated by a readout gage, for a period of ten (10) seconds when tested as specified in 4.5.2.

3.7 First article inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of cracks, burrs, surface defects, flash, air bubbles, holes, blisters, sharp corners, amides, dirt, twists and scrap. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this specification.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First article inspection (see 4.3)
b. Quality conformance inspection (see 4.4)

4.3 First Article Inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. Components shall be selected from each cavity from each mold used to produce the molded part in the quantity specified below and shall be so identified as to permit tracing each item to the cavity in which it was molded. The first article sample shall consist of the following items:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

Part Description	Drawing	Quantity (per cavity)
Body	11828918	5
Cap	9331297	5
Cap Assembly	9335529	5
Container Assembly	9329679	20
Body Material	9329619	30 (see 4.4.3.1)
Cap Material	9340662	30 (see 4.4.3.1)

4.3.2 Inspections to be performed. See MIL-A-48078 and Table II specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
	Container Assembly and Components		See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap (Dwg. 9331297)				
	Examination for Defects	5	-	3.1	4.4.2.1
	Cap assembly (Dwg. 9335529)				
	Examination for Defects	5	-	3.1	4.4.2.2
	Body (Dwg. 11828918)				
	Examination for Defects	5	-	3.1	4.4.2.3
	Container assembly (Dwg. 9329679)				
	A. Examination for Defects	5	-	3.1	4.4.2.4
	B. Drop test at ambient temperature	7	-	3.5	4.5.6.1
	C. Drop test at cold temperature	8	-	3.5	4.5.6.2
	Body material (Dwg. 9329619)				
	A. Density	5	-	3.4	4.5.5
	B. Environmental stress cracking	5	-	3.4	4.5.5
	C. Brittleness temperature	5	-	3.4	4.5.5
	D. Flexural modulus	5	-	3.4	4.5.5
	E. Melt flow	5	-	3.4	4.5.5
	F. Tensile strength	5	-	3.4	4.5.5
	G. Elongation (see Note)	5	-	3.4	4.5.5

NOTES:
The same specimens used for determining tensile strength shall be used for determining elongation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTION (Cont'd)

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
	Container Assembly and Components	2 OF 2	See Below
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cap material (Dwg. 9340662)				
	A. Density	5	-	3.4	4.5.5
	B. Environmental stress cracking	5	-	3.4	4.5.5
	C. Brittleness temperature	5	-	3.4	4.5.5
	D. Flexural modulus	5	-	3.4	4.5.5
	E. Melt flow	5	-	3.4	4.5.5
	F. Tensile strength	5	-	3.4	4.5.5
	G. Elongation (see Note)	5	-	3.4	4.5.5

NOTES: The same specimens used for determining tensile strength shall be used for determining elongation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

4.4 Quality Conformance Inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of container assemblies shall contain:

a. Body material from not more than one lot from one manufacturer.
b. Cap material from not more than one lot from one manufacturer.
c. Material of one color designation.
d. Components from the same manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Delay time in dimensioning examination- No attempt shall be made to determine compliance with dimension and tolerance requirements of the sections before the approved curing time (see 6.4) has elapsed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cap	1 OF 1	9331297
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Pitch diameter of thread		0.40%	3.1	Gage
102	Minor diameter of thread		0.40%	3.1	Gage
103	Internal Depth		0.40%	3.1	Gage
104	Side wall thickness (two readings, 180° apart)		0.40%	3.1	Gage
105	Thickness at top		0.40%	3.1	Gage
106	Interior Radius		0.40%	3.1	Gage
107	Incorrect color		0.40%	3.1	Visual
108	Incorrect embossed Roman numeral		0.40%	3.1	Visual
MINOR					
201	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9335529
4.4.2.2	Cap Assembly				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined				
MAJOR					
101	Cap liner not secure to interior roof of cap		0.40%	3.1	Visual/Manual
MINOR					
201	Evidence of poor workmanship		0.65%	3.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Body	1 OF 1	11828918
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None Defined.				
MAJOR					
101	Total height		0.40%	3.1	Gage
102	Larger width		0.40%	3.1	Gage
103	Smaller width		0.40%	3.1	Gage
104	Larger length		0.40%	3.1	Gage
105	Smaller length		0.40%	3.1	Gage
106	Height of neck		0.40%	3.1	Gage
107	Thickness of neck, minimum (two readings, (180° apart)		0.40%	3.1	Gage
108	Pitch diameter of thread		0.40%	3.1	Gage
109	Major diameter of thread		0.40%	3.1	Gage
110	Color of body		0.40%	3.1	4.5.1
111	Air Test		100%	3.1	4.5.2
112	Side wall thickness (see note)		0.65%	3.1	4.5.3
113	Corner thickness (see note)		0.65%	3.1	4.5.4
114	Incorrect Roman numeral		0.40%	3.1	Visual
MINOR					
201	Weight of body		0.65%	3.1	Scale
202	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:
"Side wall thickness" and corner thickness" inspections shall be performed last.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-63407 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Container Assembly		9329679
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined.				
MAJOR					
101	Color and embossed Roman numeral of cap assembly does not match color and embossed Roman numeral of container body		0.40%	3.1	Visual
102	Cap assembly does not properly assemble to container body		0.40%	3.1	Visual/Manual
MINOR	None defined.				

NOTES:

12

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Physical properties (major defects) of materials for bodies and caps (see 3.4). From each lot of material to be used for the manufacture of bodies and caps, a representative sample shall be taken and specimens shall be prepared (compression molded) in accordance with ASTM-D1928, Procedure C, for testing as specified in 4.4.3.1.1 through 4.4.3.1.3.

4.4.3.1.1 Density. Five specimens shall be sampled at random from each lot and tested in accordance with 4.5.5. The determined values of these specimens shall be averaged. If this average value fails to meet the requirement, the lot shall be rejected.

4.4.3.1.2 Melt flow. Five specimens shall be sampled at random from each lot and tested in accordance with 4.5.5. The determined values of these specimens shall be averaged. If this average value fails to meet the requirement, the lot shall be rejected.

4.4.3.1.3 Tensile strength and elongation. Five specimens shall be selected at random from each lot. If one or more specimen fails to meet either requirement, when tested as specified in 4.5.5, the lot shall be rejected.

4.4.3.2 Drop test of plastic containers.

4.4.3.2.1 Ambient temperature. Fifty (50) container assemblies shall be randomly selected from each lot. The sampling procedure shall be representative of the number of injection molding and blow molding machines used in production. If two or more container assemblies are found defective, the lot shall be rejected. Caps "popping" off bodies causing spillage during drop test shall not be classed defective.

4.4.3.2.2 Cold temperature. The sampling procedure shall be the same as 4.4.3.2.1.

4.4.3.3 Air test. The container bodies shall be checked 100%. Any container body that does not meet the air requirement shall be removed from the lot.

4.4.4 Alternate sampling provisions for dimensional inspection of Container Body and Cap. In place of normal sampling and inspections associated with the Classification of Defects and after a curing time for the parts has been approved (see 6.4), a sample of three (3) parts (as molded) from each

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.2.1 or 4.4.2.3, as applicable, after continuous production of each 4,000 parts or at the end of each week, whichever occurs first. Of the three (3) samples, one (1) sample shall be the last part produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for inspection for each separate type of defect according to MIL-STD-105, using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the contracting officer to substantiate the request.

4.4.5 Qualification of blow molding and injection molding machines. If a molding machine is added to the production line, it must be qualified. A sample of ten (10) bodies or caps, as applicable, shall be randomly selected from the first 30 minutes of production. The bodies or caps, as applicable, shall be assembled to its counterpart which were molded from a qualified machine. Five container assemblies shall be subjected to the drop test as specified in 4.4.3.2.1 and the remaining container assemblies shall be subjected to the drop test as specified in 4.4.3.2.2. If any sample fails to meet the applicable requirement, the molding machine shall be removed from production. The machine may be adjusted or reworked and then returned to production, provided the qualification test is rerun and passed.

4.4.6 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection (see 6.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

4.5.1 Color of container. Examine the specimen container on all sides using daylight illumination to determine compliance with the applicable requirement.

4.5.2 Air test. Seal the filler opening with a test fixture and fit the fixture with a pressure gauge having such range and sensitivity that a change of 1/8 pound per square inch (p.s.i.) can easily be read. Pressurize the container with air to three (3) to five (5) p.s.i. within two (2) seconds and then turn off the air source. After the pressure has been stabilized and corrected for temperature, the pressurized containers shall be considered acceptable if the indicated pressure does not change within ten (10) seconds, minimum.

4.5.3 Side wall thickness. Cut the sample bodies in a direction perpendicular to the mold seam. The location of the cut shall be six (6) inches up from the bottom of the container. Take three (3) measurements of wall thickness for each of the four (4) walls. One measurement shall be near the center of the wall and one approximately two (2) inches to each side of the center measure. If the dimensions are not met in one or more measurements, the sample shall be classed defective.

4.5.4 Corner wall thickness. Gage the above test samples (see 4.5.3) for minimum corner thickness with respect to all the body corners. If the dimensions are not met in one or more measurements, the sample shall be classed defective.

4.5.5 Physical properties. The physical properties of the samples shall be determined as specified in Table III.

TABLE III

Test Methods for Determining Physical Properties

Physical Property	Test Method
Density	ASTM-D1505
Melt flow	ASTM-D1238
Environment stress-cracking	ASTM-D1693
Tensile strength and elongation	ASTM-D638
Brittleness temperature	ASTM-D746
Flexural modulus	ASTM-D790

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

4.5.6 Drop test of container assemblies.

4.5.6.1 Ambient temperature. The body shall be filled to 98 percent of capacity with water after which the cap assembly is affixed and tightened. Each container assembly shall be dropped from a height of 4 feet, onto a solid, unyielding surface, so as to drop diagonally on the top edge or any other part which is weaker. Observation shall be made for compliance with the applicable requirement.

4.5.6.2 Cold temperature. The body shall be filled to 98 percent of capacity with a 1:1 ethylene glycol-water liquid solution after which the cap assembly shall be affixed and tightened. Each container assembly shall be dropped from a height of 4 feet onto a solid unyielding surface, so as to drop diagonally on the top edge or any other part which is weaker. Observation shall be made for compliance with the applicable requirement.

5. PACKAGING.

5.1 Packaging requirements. The container assemblies shall be packaged for shipment per MIL-STD-1188.

5.2 Packing and marking. The packages containing the container assemblies shall be packed and the exterior container marked per MIL-STD-1188.

6. NOTES.

6.1 Intended use. The container assemblies covered by this specification are intended for shipment and storage of blasting agent components.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Cure time. In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g., every 30, 60 etc. minutes) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensionally stability is attained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

The inspection data used in determining the curing time shall be sent to ARRADCOM, ATTN: DRDAR-QAR-Q, Dover, New Jersey 07801. If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time should be established and approved.

6.5 Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-Q, Dover, New Jersey 07801. This description should include, but not be limited to the accuracy and precision of the method, test data demonstrating the accuracy and precision and drawings of any special equipment required.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 8140-A-540

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-63407 Container Assembly for Drmolition Kit, Blasting;XM268

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:48Z
Check the source to verify that this is the current version before use.