MILITARY SPECIFICATION

POWER MODULE ASSEMBLY FOR TEST SET, ELECTRONIC SYSTEM: M137

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and preparation for delivery for Power Module Assembly: used on Test Set, Electronics System: M137.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-T-945	-	Test Equipment for use with Electronic Equipment: General Specification.
MIL-P-19834	-	Plate Identification or Instruction, Metal Foil, Adhesive Backed, General Specification for.
MIL-W-63150	-	Weapons and Support Material, Standard Quality Assurance Provision for.

FSC 1310

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-704A	-	Aircraft Electric Power Characteristics.
MIL-STD-810	-	Environmental Test Methods.
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment
MIL-STD-1235	-	Single and Multi-Level Continuous Sampling Procedure and Tables for Inspecting by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein:

DRAWINGS

US ARMY ARMAMENT MUNITIONS AND CHEMICAL COMMAND

PRODUCT

11834203	-	Power Module Assembly.

PACKAGING

P11834203	-	Power Module Assembly.

(Copies of specifications, standards, handbooks, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 11834203 and associated drawings, MIL-W-63150, and with all requirements specified in applicable specifications and standards.

3.3 Electronic performance characteristics.

3.3.1 Performance. The Power Module Assembly shall have the performance characteristics specified herein.

3.3.1.1 Electrical. The Power Module Assembly shall operate from a nominal 28 volts DC supply and provide outputs of 28 volts DC and 115 volts AC at 400 Hertz.

3.3.1.1.1 Input voltage. The Power Module Assembly shall operate with 24 through 30 volts DC applied to Terminals A (positive) and B (Return) of plug P1. Terminal C shall be connected to ground.

3.3.1.1.2 Input current. The input current through circuit breaker CB1 to the power supply module shall not exceed 10 amps.

3.3.1.1.3 Input transient protection. The unit shall be able to withstand a transient surge voltage in accordance with MIL-STD-704A, Figure 9, Limit 1 (80VDC for 0.1 seconds).

3.3.1.1.4 Output voltages. The voltage across Terminals A and B of Receptacle J1 shall be equal to the input voltage within 0.5 volts. The voltage across Terminals A and B of Receptacle J2 shall be adjustable within the range 108 to 122 VAC. The ouput voltage shall be adjusted by turning the screw on the top of the power supply module case.

3.3.1.1.5 Output currents. The DC output current shall be protected by a 10 amp curcuit breaker. The AC output shall be capable of supplying up to 1.044 amps continuously at rated output voltage.

3.3.1.1.6 Output frequency. The AC output shall have the form of a sine wave of 400 Hertz ± 1 percent. There shall be a maximum of 4 percent harmonic distortion into a resistive load.

3.3.1.1.7 Short circuit protection. The power supply shall be protected against a short circuit condition on the AC output of any duration. The unit must be recycled to restore output.

3.3.1.1.8 Load transient recovery time. The AC output voltage shall return to regulation limits within 5 cycles for a change from no load to full load.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

3.4 Design and construction.

3.4.1 Production drawings. The Power Module Assembly shall be fabricated and assembled in accordance with the associated drawings, parts lists and other documents listed on Drawing 11834203.

3.5 Environmental requirements.

3.5.1 Operating temperature. The unit shall be operable in the range of -65°F (-54°C) to +212°F (+100°C).

3.5.2 Environments. Shall meet the environmental requirements of MIL-STD-810 for altitude, vibration, shock, acceleration, sand, dust, humidity, salt-spray, fungus, and explosive atmosphere.

3.6 First article inspection. This specification contains technical Provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. Finished items and parts shall be fabricated in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. The parts shall not exhibit faulty material and processing such as seams, laps, laminations, cracks, visible steps, sharp edges, nicks, scratches, burrs, deformations, unblended radii, chips, dents, rust, dirt, grease and oil (except where specifically required), corrosion products, flux, other foreign matter, and missing operations which may affect serviceability, operation, or safety. The cleaning agents shall not be injurious to any part or assembly. Exterior surface coatings shall be continuous; however, a few light scratches not exposing base material may be permitted. All required markings and stamping shall be neat and sharply defined. Required packing shall be dry. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing. Cable assemblies and wires shall be neatly dressed and tied in such a manner as to prevent pinching or chafing the wire insulation. Ends of wires shall be free from burrs, sharp edges or points. Castings shall be clean, sound, and free from blowholes, porosity and inclusion. Welds shall be reasonably smooth and free of craters and cracks. They shall exhibit characteristics of good fusion penetration and soundness of weld deposit representative of good welding practice. They shall be free of irregularities which indicate lack of skill or experience on the part of the operator. All scale and splatter shall be completely removed prior to application of protective coatings. There shall be no cracks in or near welded areas.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-W-63150 shall apply and are hereby made a part of this detail specification.

4.2 Certification of provisions. The certification provisions of MIL-W-63150 shall apply.

4.3 Classification of inspection. The following types of inspection shall be conducted on this item.

a. First Article Inspection.
b. Quality Conformance Inspection.

4.4 First article inspection.

4.4.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.4.2. The first article sample shall consist of the following items in sample quatities as indicated.

PART DESCRIPTION	DRAWINGS	QUANTITY
Case	11834204	5
Heat Sink	11834205	5
Receptacle Connector	11834206	5
Bushing	12011794	5
Power Module	12011795	5
Plate	12011796	5
Heat Sink	12011797	5
Plate, Identification	12011798	5
Power Module Assembly	11834203	10

4.4.2 Inspections to be performed. First article assemblies components and test specimens may be subjected by the Government to any or all of the examinations and tests specified in the item detail specification and to any requirements of the applicable drawings. See Table I specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

4.4.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly, component, or test specimen in the sample that fails to comply with any of the stated requirements.

4.5 Quality conformance inspection.

4.5.1 Lot formation. The term "inspection lot" is defined as a homogeneous collection of units of product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which drawn and presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Power Module Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Case (Dwg 11834204) Examination of defects	5		3.2	4.5.2.1
	Heat sink (Dwg 11834205) Examination of defects	5		3.2	4.5.2.2
	Receptacle connector (Dwg 11834206) Examination of defects	5		3.2	4.5.2.3
	Bushing (Dwg 12011794) Examination of defects	5		3.2	4.5.2.4
	Power module (Dwg 12011795) Examination of defects Environmental	5 3		3.2 3.5	4.5.2.5 4.6.3

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2022640-23T03:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE			SHEET 2 OF 2	DRAWING NUMBER
	Power Module Assembly and Components				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plate (Dwg 12011796) Examination of defects	5		3.2	4.5.2.6
	Heat sink (Dwg 12011797) Examination of defects	5		3.2	4.5.2.7
	Plate, identification (Dwg 12011798) Examination of defects	5		3.2	4.5.2.8
	Power module assembly (Dwg 11834203) Examination of defects	10		3.2	4.5.2.9

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

4.5.2 Examination. See MIL-W-63150. Examination for the inspection listed in the following Classification of Defects and Tests paragraphs shall be performed by sampling to the AQL specified unless 100 percent inspection is indicated. Unless otherwise specified sampling shall be in accordance with MIL-STD-105 Level II, except the contractor may request permission from the procuring activity to use an equivalent continuous sampling plan from MIL-STD-1235.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.5.2.1	Case		11834204
			NEXT HIGHER ASSEMBLY 11834203

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Type of material not as specified			3.1	4.2
102.	Case does not meet MIL-T-945 requirements			3.2	4.6.1
103.	Case does not meet automatic relief data		100%	3.2	4.5.4
104.	Maximum working load of latches incorrect		0.65%	3.2	4.5.4
105.	Handle free swing incorrect		0.65%	3.2	Manual
106.	Handle design load incorrect, max without damage or permanent deformation	5	0.65%	3.2	4.5.4
107.	Case damaged (puncture, dented or deformed)		0.65%	3.2	Visual
108.	Component(s) damaged		0.65%	3.2	Visual
109.	Component(s) missing		0.65%	3.2	Visual
MINOR					
201.	Protective finish improper, missing or damaged		1.5%	3.2	4.6.1, Visual
202.	Dimensions and configuration		1.5%	3.2	4.6.1
203.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.5.2.2	Heat Sink				11834205
					NEXT HIGHER ASSEMBLY 11834203
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Surface finish incorrect		0.65%	3.2	4.5.4
102.	Sharp edges and corners not broken		0.65%	3.2	Visual
MINOR					
201.	Dimensions and configuration		1.5%	3.2	4.6.1
202.	Protective finish improper, missing or damaged		1.5%	3.2	4.6.1, Visual
203.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.5.2.3	Receptacle Connector				11834206
					NEXT HIGHER ASSEMBLY 11834203
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Rating incorrect		100%	3.2	4.2
102.	Location of holes incorrect		0.65%	3.2	4.5.4
MINOR					
201.	Evidence of poor workmanship		2.5%	3.5	4.6.1.1

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.5.2.4	Bushing				12011794
					NEXT HIGHER ASSEMBLY
					11834203
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Type of material not as specified			3.1	4.2
102.	Diameter incorrect		0.65%	3.2	4.6.1
103.	Temperature index incorrect			3.2	4.2
104.	Flammability classification incorrect			3.2	4.2
MINOR					
201.	Protective finish missing or damaged		1.5%	3.2	Visual
202.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.5.2.5	Power Module	1 OF 1	12011795
			NEXT HIGHER ASSEMBLY 11834203

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Line regulation incorrect		0.65%	3.2	4.5.4
102.	Load regulation incorrect		0.65%	3.2	4.5.4
103.	Wave form does not meet requirement		0.65%	3.2	4.5.4
104.	Load power factor improper		0.65%	3.2	4.5.4
105.	Temperature coefficient improper		0.65%	3.2	4.5.4
106.	Inputs, outputs, and case not isolated		0.65%	3.2	4.5.4
107.	Environmental requirements			3.2	4.2
MINOR					
201.	Dimensions and configuration		1.5%	3.2	4.6.1
202.	Evidence of poor workmanship		2.5%	3.5	4.6.1.1

NOTES:

Source: https://assist.dla.mil - Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.5.2.6	Plate				12011796
					NEXT HIGHER ASSEMBLY 11834203
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Type of material not as specified			3.1	4.2
MINOR					
201.	Protective finish improper, missing or damaged		1.5%	3.2	4.6.1, Visual
202.	Dimensions and configuration		1.5%	3.2	4.6.1
203.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

DRSMC OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2025-02-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.5.2.7	Heat Sink	1 OF 1	12011797
			NEXT HIGHER ASSEMBLY 11834205

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Type of material not as specified			3.1	4.2
102.	Weight incorrect		0.65%	3.2	4.5.4
103.	Thermal resistance incorrect		0.65%	3.2	4.5.4
MINOR					
201.	Protective finish missing or damaged		1.5%	3.2	4.6.1, Visual
202.	Dimensions and configuration		1.5%	3.2	4.6.1
203.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

DRSMC-OA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil - Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-70449(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.5.2.8	Plate, Identification	1 OF 1	12011798
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Not in accordance with MIL-P-19834, Type I		0.65%	3.2	4.6.1
102.	Lable information missing or incorrect		0.65%	3.2	Visual
103.	Lable marking illegible		0.65%	3.2	Visual
MINOR					
201.	Evidence of poor workmanship		2.5%	3.5	4.6.1.1

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.5.2.9	Power Module Assembly	1 OF 1	11834203
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101.	Surface receiving identification contaminated		100%	3.2	Visual
102.	Soldering improper		0.65%	3.2	4.6.1, 4.5.4
103.	Wires not attached as per manufactures instruction		0.65%	3.2	Visual
104.	Identification plate improperly marked		0.65%	3.2	4.6.1, Visual
105.	Fasteners missing		0.65%	3.2	Visual
106.	Performance not as specified		100%	3.3.1	4.6.2
MINOR					
201.	Dimensions and configuration		1.5%	3.2	4.6.1
202.	Evidence of poor workmanship		2.5%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:27Z
Check the source to verify that this is the current version before use.

4.5.3 Testing. Testing is described in the first article and quality conformance inspection tables.

4.5.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection column in the tables, starting with paragrphs 4.5.2.1 and test methods paragraph (see 4.6). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-W-63150 and 6.3 herein.

4.6 Inspection methods and procedures. Any unit which fails to comply with the specified requirements or evidences degradation of its operational performance shall be classed defective. Test equipment and procedures shall be satisfactory to the contracting officer (see 4.5.4).

4.6.1 Materials, components and processes. Compliance with these requirements shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.6.1.1 Visual and mechanical inspection. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of the applicable drawing and this specification in accordance with 4.5.2 and Table I.

4.6.2 Electronic performance test of the power module assembly. The power module shall be subjected to the electronic performance tests in order to determine conformance to the electronic performance characteristics specified on the applicable drawing. Test equipment and procedures shall be satisfactory to the contracting agency. If any power module assembly fails to comply with any specified electronic performance requirement, it shall be classed defective and rejected. Test equipment and procedures shall be satisfactory to the contracting officer (see 4.5.4).

4.6.3 Environmental tests (first article only).

4.6.3.1 Environmental tests. The tests shall be performed in accordance with MIL-STD-810, Group IE. Operating temperature shall be as specified in 3.5.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation, packaging, packing and marking. The Power Module Assemblies shall be preserved, packaged and marked in accordance with the requirements of the Preservation and ackaging Data Sheet for P11834203 at the level of protection specified in the contract (see 6.2b).

5.1.1 Spare parts or replacement parts. Spare parts or replacement parts shall be cleaned, preserved, packaged as specified in the contract or order.

5.2 Commercial packaging of supplies and equipment. Commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The Power Module Assembly covered by this specification is intended for use with the Electronics System Test Set, M137 on Armament Sybsystem, Helicopter, 20MM: Automatic Gun: M97E1 and M97E2 and its related components.

6.2 Ordering data. Procurement documents shall specify the following:

6.2.1 Procurement requirements

a. Title, number and date of this specification.
b. Quantity required and delivery schedules.
c. Serialization requirements, if applicable.
d. Quality Conformance Inspection, if other than spcified in Section 4 of this specification.
e. First Article sample requirements, if other than specified in Section 4 of this specification.
f. Packaging requirements, if other than specified in Section 5 of this specification.
g. Certificates of conformance for each lot or shipment of product as specified in MIL-W-63150.
h. Spare parts required.
i. Replacement parts schedules.
j. Marking requirements for shipment.
k. QAPS required

6.2.2 Contract data requirements. Contract data requirements for inspection equipment design shall conform to Data Item Description DI-R-1714, Tailored.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

6.3 Submission for inspection equipment design approval. See MIL-W-63150. Equipment designs shall be submitted as required to: Commander, AMCCOM, DRSMC-QAF-I (D), Dover, NJ 07801. Request letter of submittal shall state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraphs.

6.4 Submission of results of contractor-conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commander, AMCCOM, DRSMC-QAF-S (D), Dover, NJ 07801.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A337)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: DRSMC-QA
DOVER, NJ 07801

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-P-70449 (AR)	POWER MODULE ASSEMBLY FOR TEST SET, ELECTRONIC SYSTEM: M137

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil – Downloaded: 2026-10-25T08:27Z
Check the source to verify that this is the current version before use.

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE