MIL-STD-1169B (AR)
20 October 1987
SUPERSEDING
MIL-STD-1169A (AR)
10 November 1977

MILITARY STANDARD

PACKAGING, PACKING AND MARKING FOR SHIPMENT OF INERT AMMUNITION COMPONENTS



AMSC N/A

FSC 8140

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE
Washington, DC 20301

Packing, Packing and Marking for Shipment of Inert Ammunition Components.

1. This Military Standard is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

2. Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Picatinny Arsenal, NJ 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

FOREWORD

This standard provides packaging, packing and marking instructions for shipment of inert ammunition components whenever the detail item specification does not provide packing requirements. This standard includes packaging instructions for the shipment of inert ammunition components for Level A and B (overseas) and Level C (domestic) shipments.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

CONTENTS

Paragraph		Page
1.	SCOPE	1
1.1	Scope	1
1.2	Classification	1
1.3	Restrictions	1
2.	APPLICABLE DOCUMENTS	2
2.1	Government documents	2
2.2	Order of precedence	3
2.3	Sources	3
3.	DEFINITIONS	4
3.1	Level A	4
3.2	Level B	4
3.3	Level C	4
4.	GENERAL REQUIREMENTS	5
4.1	Arrangements	5
4.2	Shipping container content	5
4.3	Item protection	6
4.4	Unit packaging	6
4.5	Intermediate packaging	8
4.6	Packing	8
4.7	Unitization	9
4.8	Testing	10
4.9	Marking for Level A, B, or C	10
5.	DETAILED REQUIREMENTS	11
5.1	Responsibility for inspection	11
5.2	Examination	11
6.	NOTES	14

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This standard establishes general packaging, packing, unitization, and marking instructions for shipment of inert ammunition components. Packaging requirements, based upon U.S. Army packaging policy and procedures, are specified for three levels of protection: Level A - Overseas unknown hazards; Level B - Overseas known hazards and Level C - Domestic limited hazard.

1.2 Classification. Shipping requirements shall be of the following levels and components as specified:

Level A or B. Overseas shipment
- Unit packaging
- Intermediate packaging
- Packing
- Unitization

Level C. Domestic shipment
- Unit packaging
- Intermediate packaging
- Packing
- Unitization

1.3 Restrictions. Any specification called out in this document shall be used with the restrictions, qualifications, and limitations as defined in the specification. Load weight and size of bags, boxes, crates, etc. shall conform to those requirements of the particular specification material used. The use of Military Specifications called out in this document does not absolve the contractor from the requirements to deliver any item in useful undamaged condition.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

NN-P-71	- Pallet, Materials, Handling, Wood, Stringer Construction, 2 Way and 4 Way (Partial)
PPP-B-26	- Bag, Plastic (General Purpose)
PPP-F-320	- Fiberboard, Corrugated and Solid Sheet Stock (Container Grade) and Cut Shapes
PPP-B-566	- Boxes, Folding, Paperboard
PPP-B-585	- Boxes, Wood, Wirebound
PPP-B-587	- Boxes, Wood, Wirebound Pallet-Type
PPP-B-601	- Boxes, Wood, Cleated-Plywood
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	- Boxes, Shipping, Fiberboard
PPP-B-676	- Boxes, Set-up
PPP-C-843	- Cushioning Material, Cellulosic
PPP-C-1797	- Cushioning Material, Resilient, Low Density, Unicellular Polypropylene Foam

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-B-117	- Bags, Sleeves and Tubing-Interior Packaging
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible
MIL-B-2427	- Boxes, Ammuinition Packing: Wood, Nailed
MIL-C-2439	- Containers, Ammunition, Fiber, Spirally Wound
MIL-A-2550	- Ammunition and General Specification for
MIL-C-3955	- Cans, Composite, Spirally Wound
MIL-L-10547	- Liners, Case, and Sheet Overwrap; Water, Vaporproof or Waterproof, Flexible
MIL-P-15011	- Pallets, Material Handling Wood Post Construction, 4 Way
MIL-T-43036	- Tape, Pressure - Sensitive Adhesive, Plastic Film (For Sealing Fiber Containers and Cans)
MIL-B-46506	- Boxes, Ammunition Packing, Wood, Wirebound

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

STANDARDS
FEDERAL

FED-STD-101	- Test Procedures for Packaging Materials

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-147	- Palletized Units Loads
MIL-STD-731	- Quality of Wood Members for Containers and Pallets
MIL-STD-1190	- Minimum Guidelines for Level C Preservation, Packing and Marking
MIL-STD-1235	- Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes, Functional Curves of the Continuous Sampling Plans

2.2 Order of precedence. In the event of a conflict between the text of this document and the reference cited herein, the text of this document takes precedence.

2.3 Sources of government specifications and standards. Copies of the referenced federal and military specifications and standards are available from the Department of Defense Single Stock Point, Commanding Officer, Naval Publications, and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120-5099.

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the currentversion before use.

3. DEFINITIONS

3.1 Level A. This level of protection provides maximum protection to materials shipped under the most severe worldwide shipment, handling and storage conditions.

3.2 Level B. This level of protection provides intermediate protection to materials under anticipated favorable environmental conditions of worldwide shipment, handling and storage.

3.3 Level C. This level of protection provides minimum protection to materials under known favorable conditions. It should be specified for domestic (interplant) shipment where use or consumption of the item at the first destination is anticipated within 18 months.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

4. GENERAL REQUIREMENTS

4.1 Arrangements.

4.1.1 Items. Items with their parts may be temporarily assembled and handled as an item for packaging when approved by the contracting officer.

4.1.2 Bulk packaging. Parts packaged directly in shipping containers shall be separated with pads, liners, partitions or dividers as required to protect the parts, strengthen the container and to distribute the load 1/.

4.1.3 Semi-bulk packaging. Large quantity items, such as lead washers, plastic discs, lightweight round stampings or nesting pieces shall be stacked. Stacks shall be packaged by wrapping (coin wrap), by placing in chipboard tubes, or by placing within vertical partitions 1/.

4.1.4 Single item packaging. Items shall be packaged singly in separate cells or unit containers when they can be easily handled individually or when they have critical surfaces, such as silver or chromium plate, highly machined surfaces, external threads, sharp projections or other easily damaged surfaces 1/.

4.1.5 Small items. Special precautions shall be taken for items that are extremely small or for some other reason have a tendency to be easily lost when handled. For such items, sealed envelopes, fiber cans, or similar positive closure containers shall be used. When the total quantity of an item being shipped is of such small volume as to be less than 500 cubic inches, two or more item packs shall be placed in one shipping container 1/.

4.1.6 Bagged items. If appropriate, items may be packaged directly into bags. Cushioning may be required to protect the items from damage or the bags from puncturing. Bags shall be closed by heat sealing, cold sealing, taping, or stapling as required to protect the items against the affects of moisture 1/.

4.2 Shipping container content. The quantity of an item or items, as described in 4.1 to be packed in the shipping container shall be governed first, by weight limitations as specified in 4.6 second, by count, and third, by lot size, convenience factors or other circumstances which may be considered of major importance by the contracting officer. The number of items packed is preferred in multiples of 5, or quantities of 10 or more such as 10, 25, 100, 500, 1000. Multiples of 2 and 3 may be used, particularly in small quantities such as 6, 9, 12, 24 when these quantities will permit

1/ Special precautions shall be taken to prevent chemical damage, that is, the effect of moisture, acidity, and sulphurous compounds in the packing material or the atmosphere.

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the currentversion before use.

better package design or better adjustment to weight limitation. Any doubts regarding the proper count shall be resolved with the contracting officer prior to packaging of the items being shipped.

4.3 Item protection. Unless otherwise specified on the item drawing, cleaning and drying of all items with applicable procedures and methods in accordance with MIL-P-116 is mandatory. In addition, protection from corrosion shall be included as part of the packaging requirements. The item manufacturer shall use appropriate preservatives whether P-type metal preservatives, volatile corrosion inhibitors, etc. listed in MIL-P-116 or any other equivalent preservative type materials to eliminate the affects of the normal environment expected. The selection of preservatives shall be based upon need, ease or need for removal, availability, item surface finish, compatability with the energetic material it may come in contact with, etc.

4.4 Unit packaging.

4.4.1 Level A. Items shall be packaged by one of the methods described in 4.1.2, 4.1.3, 4.1.4, 4.1.5 or 4.1.6. The method and the arrangement of the items being packaged shall be selected in accordance with the characteristics of the item, protection required, and so as to facilitate removal and handling on the assembly line of the receiving facility. Containers and parts designed for interior protection shall be dimensioned so as to provide a close fit and limit as much as possible the need for filler material.

4.4.1.1 Filler and cushioning material. Cushioning material is that material which will protect an item against the adverse affects of shock and vibration caused by external forces. Cushioning material shall be used to control item movement, protect fragile or delicate components, prevent rupture of barriers and containers, distribute forces, prevent abrasion, and absorb shock. Any materials used as cushioning should be as dry as practical, be non-corrosive, and not absorb any grease or preservative when in intimate contact with an item. Filler and cushioning material shall not have shreds, lint, dirt or other objectionable deposits on the items being packed. Cushioning shall comply with PPP-C-843, PPP-C-1797, or comparable material. Partitions, pads, liners or fillers when made from corrugated fiberboard shall be at least 125 pound test board complying the PPP-F-320. Corrugated liners and partitions inserted parallel to the depth of the carton shall have the corrugations parallel to the depth. Partitions and pads for small or very light parts may be made from chipboard. Thickness, weight and strength of chipboard shall be selected in accordance with the requirements of the package. Chipboard .030 inch thick, commercial No. 2 finish, is suitable for use.

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the current version before use.

4.4.1.2 Containers. Fiberboard or paperboard boxes shall comply with one of the following specifications; PPP-B-636, PPP-B-676 or PPP-B-566. Closures shall be as specified in the applicable box specification. Alternatively, fiber containers complying with MIL-C-2439 may be used. They shall be closed with one and one quarter turns of tape complying with MIL-T-43036. A one inch pull tab shall be made at the end of the tape by folding the tape back on itself. Heat sealed bags complying with MIL-B-117 may be used if deemed adequate.

4.4.1.2.1 Waterproof packages. When a waterproof package is required, the boxes described in 4.4.1.2 shall be placed in a heat sealed barrier bag complying with Class C of MIL-B-117. The seal shall meet the heat seal test of MIL-P-116. When waterproof unit packages are small, the items may be placed directly into bags without boxes. Alternatively, fiber containers complying with Type I or Type II, Class 1 of MIL-C-2439, or Type II, Grade B of MIL-C-3955, may be used. When intermediate packs are not used, unit packages shall be waterproof. If deemed satisfactory, items with appropriate cushioning can be placed directly inside a heat sealed bag, Class B or C, MIL-B-117.

4.4.1.2.2 Moistureproof packages. Items sensitive to damage from moisture vapor shall be packaged as described in 4.4.1.2.1 except that barrier bags shall comply with Class E of MIL-B-117. Alternatively, fiber containers complying with Type IV, Class 1 of MIL-C-2439 may be used. Moisture content of any fillers, partitions, pads or cushions shall not exceed 9 percent when tested in accordance with Method 5024 of FED-STD-101. If deemed satisfactory, items with appropriate cushioning can be placed directly inside a heat sealed bag, Class E, MIL-B-117.

4.4.1.2.3 Greaseproof packages. Items coated with an easily transferable preservative coating shall be wrapped in a greaseproof paper complying with Type I or II, Grade A of MIL-B-121 prior to being placed in a barrier bag described in 4.4.1.2.1 or 4.4.1.2.2. Alternatively, the fiber containers specified in 4.4.1.2.2 may be used. If deemed satisfactory, items with any appropriate cushioning can be placed directly inside Class E, MIL-B-117 bag with or without the wrap.

4.4.2 Level B. Items shall be packaged as specified in 4.4.1, 4.4.1.1, and 4.4.1.2. Taping of fiber containers may be omitted if fiber containers are tightly overpacked provided waterproofness or moistureproofness is not required. Bags for small plastic parts can be fabricated in accordance with PPP-B-26 if moistureproofness and greaseproofness is not required.

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the currentversion before use.

4.4.2.1 Additional requirements. When required by the nature of the item or when specifically called for waterproofness, moisture-proofness and greaseproofness shall comply with 4.4.1.2.1, 4.4.1.2.2 or 4.4.1.2.3 as applicable.

4.4.3 Level C. Items packaged for Level C can be arranged as specified in 4.1.2, 4.1.3, 4.1.4, 4.1.5 or 4.1.6. Packaging requirements in all other respects shall conform to MIL-STD-1190. Any fiberboard box developed in accordance with MIL-STD-1190 shall not carry more than 65 pounds.

4.5 Intermediate packaging.

4.5.1 Level A. When unit packages are not waterproof or are less than five (5) pounds in weight or less than 500 cubic inches in size, except for fiber containers, they shall be packaged in W-board or V-board boxes made and closed in accordance with PPP-B-636. Alternatively, domestic class fiberboard boxes, each enclosed in a heat sealed liner complying with Type I, Grade A or B or MIL-L-10547 may be used. Intermediate packages shall not exceed 30 pounds net weight or 2 cubic feet in volume.

4.5.2 Level B. Intermediate packages may be used, if desired to consolidate small unit packages or to facilitate packaging and assembly line handling. Intermediate boxes shall meet the requirements for domestic class fiberboard boxes of PPP-B-636. Closure shall be accomplished by stapling, stitching, taping, gluing or a combination of these methods.

4.5.3 Level C. Intermediate packaging, if required, shall be in accordance with MIL-STD-1190. Any fiberboard box developed in accordance with MIL-STD-1190 shall not carry more weight than is authorized by the box specification.

4.6 Packing.

4.6.1 Level A. Exterior containers for Level A use, shall be nailed wood or wirebound boxes. Boxes shall comply with the overseas requirements of PPP-B-585, PPP-B-621, PPP-B-601, MIL-B-2427, or MIL-B-46506. Unless otherwise specified by the contracting officer, the gross weight of loaded wood boxes shall not exceed 150 pounds except for MIL-B-2427 and MIL-B-46506 boxes which are limited to 100 pounds. Individual shipping containers shall be not less than 1 cubic foot. Small quantities of items in unit or intermediate packages may be consolidated with the above requirements for shipment to a single destination. The gross weight of wood boxes fabricated in accordance with PPP-B-601 or PPP-B-621 shall not exceed 150 pounds without skids nor 1000 pounds without nominal 4" x 4" skids attached to the bottom. Container

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the currentversion before use.

closure shall be in accordance with the applicable specification. The use of pallet type boxes, as specified in PPP-B-587, is also permitted when due to the nature of the items to be packed, it is more economical or results in a more efficient pack than the use of individual wood boxes. Testing to verify package performance shall be in accordance with MIL-P-116 and as modified by 4.8.

4.6.2 Level B. Exterior containers shall be so constructed as to give assurance that the items being shipped will remain in prime condition after being shipped to an overseas location. The containers shall be sufficiently rigid to withstand transportation and permit storing in tiers at least 10 feet high without damage to containers or contents. Shipping containers shall be fabricated from solid or corrugated fiberboard or wood. Boxes selected shall comply with PPP-B-636, PPP-B-621, PPP-B-601, MIL-B-2427, PPP-B-585 or MIL-B-46506. Only waterproof, water vapor proof, or weather resistant fiberboard shall be used to fabricate boxes per PPP-B-636. The gross weight of fiberboard shipping containers shall not exceed authorized weight or size limitation of the box specification. The gross weight of wood boxes with and without skids shall be as specified for 4.6.1. Closure of fiberboard boxes or wood boxes shall be in accordance with the applicable box specification.

4.6.3 Level C. Exterior containers shall be in accordance with MIL-STD-1190. Any fiberboard box developed in accordance with MIL-STD-1190 shall not carry more weight or cube than authorized by the box specification. Any wood box developed shall have skids when loads exceed 150 pounds.

4.7 Unitization.

4.7.1 Level A. Shipping containers that are not on skids shall be unitized. Pallets shall comply with MIL-P-15011 or NN-P-71. Unitization procedures shall be in accordance with MIL-STD-147 with the following exceptions:

a. Pallet sizes may be 40" x 48" (NN-P-71 or MIL-P-15011), 35" x 45 1/2" (MIL-P-15011) or 42" x 53" (MIL-P-15011). Pallets will be constructed from MIL-STD-731 Group III or IV wood.

b. Gross weight of loaded pallet shall not exceed 4,000 pounds.

c. Strapping shall be metallic.

d. Shrink-film or stretch wrap bonding shall not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the currentversion before use.

4.7.2 Level B. Shipping containers may be unitized at the contrctor's option, unless otherwise directed. Pallets shall be in accordance with MIL-P-15011 or NN-P-71. Unitization procedures and strapping illustrations are in accordance with MIL-STD-147 except:

a. Pallet sizes may be 40" x 48" (NN-P-71 or MIL-P-15011), 35" x 45 1/2" (MIL-P-15011) or 42" x 53" (MIL-P-15011). Pallets will be constructed from MIL-STD-731, Group III or IV wood.

b. Gross weight of loaded pallet shall not exceed 4,000 pounds.

c. Shrink film and stretch wrap bonding shall not be used for loads weighing more than 3,000 pounds.

4.7.3 Level C. Unitization shall be in accordance with MIL-STD-1190. Gross weight of loaded pallet shall not exceed 4,000 pounds.

4.8 Testing. Any package testing required by MIL-P-116 as it pertains to small containers, under 150 pounds, shall use Procedure G, Method 5007 in lieu of Procedure E and B, Method 5007 of FED-STD-101.

4.9 Marking for Level, A, B or C. For each unit, intermediate, and exterior container or unitized configuration, as applicable, marking shall be in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the currentversion before use.

5. DETAILED REQUIREMENTS

5.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the standard where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 in order to define the terms used herein. The provisions of MIL-A-2550 shall apply.

5.1.1 Responsibility for compliance. All items must meet all requirements of sections 4 and 5. The inspection set forth in this standard shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the standard shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

5.2 Examination. Inspection for critical defects (and major defects when so specified) shall be 100 percent. Sampling plans and procedures for major and minor defects shall be in accordance with special inspection Level S-3, Table 1 of MIL-STD-105 except that continous sampling plans in accordance with MIL-STD-1235 may be used, if approved by the procuring activity. Also at the option of the procuring activity, AQLs and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each minor defect, and an AQL of 0.40 percent for each major defect except where 100 percent inspection is specified. Lot formation shall be in accordance with the end item specification.

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

5.2.1 Unit container. 1/

Categories	Defects	Method of Inspection
Critical	None defined	
Major	AQL 0.40 percent	
101	Container punctured, crushed or torn	Visual
102	Container interior contaminated with dirt, lint or other foreign matter	Visual
103	Incorrect number of items packed.	Visual
104	Moisture/corrosion protection missing (when specified)	Visual
Minor	AQL 0.65 percent	
201	Container improperly closed or sealed	Visual
202	Container markings, illegible, missing incorrect or incomplete	Visual

5.2.2 Intermediate container.

Categories	Defects	Method of Inspection
Critical	None defined	
Major	AQL 0.40 percent	
101	Container punctured, crushed or torn	Visual
102	Container interior contaminated with dirt, lint or other foreign matter	Visual
103	Incorrect number of items packed	Visual
104	Moisture/corrosion protection missing (when specified)	Visual
Minor	AQL 0.65 percent	
201	Container improperly closed or sealed	Visual
202	Container markings illegible, missing incorrect or incomplete	Visual

5.2.3 Exterior container

Categories	Defects	Method of Inspection
Critical	None defined	
Major	AQL 1.0 percent	
101	Marking, missing, incomplete or illegible	Visual
102	Container punctured, crushed, or torn	Visual
103	Container interior contaminated with dirt, lint or other foreign matter	Visual
104	Container improperly sealed or closed	Visual
105	Container packing, partitions, pads separators missing, torn or crushed	Visual
106	Strapping missing or loose	Visual
107	Incorrect number of items packed	Visual
Minor	None defined	

1/ A unit container may be a box, bag, fiber tube, etc.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

5.2.4 Unitization.

Categories	Defects	Method of Inspection
Critical	None defined	
Major	AQL 0.40 percent	
101	Pallet damaged or members insecure	Visual
102	Strapping loose or insufficient	Visual
Minor	AQL 2.5 percent	
201	Marking incorrect	Visual
202	Splinters projection	Visual
203	Nails or fasteners projecting	Visual
204	Load not tightly stacked	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202640-23T23:22Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Issue of DODISS. When this standard is used in acquisition, the applicable issue of the DODISS must be cited in the solicitation (see 2.1.1).

6.2 Subject term (key work listing).
Inert ammunition components
Level A, B and C
Marking
Packaging
Packing
Unitization

6.3 Changes from previous issue. Vertical lines or asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 8140-A733)

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-STD-1169B	PACKAGING, PACKING AND MARKING FOR SHIPMENT OF INERT AMMUNITION COMPONENTS

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:22Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202610-23T23:22Z
Check the source to verify that this is the current version before use.