INCH-POUND

MIL-T-52953/3B
27 October 1989
SUPERSEDING
MIL-T-52953/3A
27 May 1980

MILITARY SPECIFICATION

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES, 4000-POUND CAPACITY, 180-INCH LIFT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-52953.

REQUIREMENTS

1. Capacity: 4000 pounds at 24 inches load center.
2. Tire Type: Solid Rubber.
3. Collapsed mast height: 83 inches maximum.
4. Maximum fork height: 180 inches minimum.
5. Free lift height: 50 inches minimum.
6. Fork size: 1-13/16 inches maximum thickness X 5-1/16 inches maximum width X 42 inches long, plus 0 inch minus 0.5 inch.
7. Fork spacing: 10 inches to minimum 30 inches.
8. Overhead guard height: 83 inches maximum.
9. Right-angle turn dimensions: 142 inches maximum. (Add 4 inches when side shift is used).
10. Travel speed: 6 mph minimum.
11. Upright tilt: 5 degrees, plus or minus 1 degree, forward; 5 degrees minimum rearward.
12. Lifting speed (loaded): 43 feet per minute (minimum).
13. Battery: 850 AH @ 6 hr. rate (minimum).
14. Underclearance: 3.25 inch minimum.

Custodian:
Army - ME
Navy - SA
Air Force - 99

Preparing activity:
Army - ME

Project 3930-0636-3

Review activities:
Army - AT, SM, MT
Navy - MC
DLA - CS
Air Force - 84

AMSC N/A

FSC 3930

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:41Z
Check the source to verify that this is the current version before use.