MIL-T-60506A(MU)
AMENDMENT 2
15 December 1971
SUPERSEDING
AMENDMENT 1
22 July 1970

MILITARY SPECIFICATION

TELESCOPE ASSEMBLY: 10540506

This amendment forms a part of Military Specification MIL-T-60506(MU), dated 18 June 1970.

Page 3, paragraph 3.4.6: Sealing.- Delete second sentence and substitute the following:

"The interior of each cavity shall be capable of maintaining 5 pounds per square inch gage (psig) for a period of 2 hours ± 10 minutes at a temperature of 75° ± 2°F. At the end of the 2 hour period, the leakage shall not have exceeded 0.2 psig."

* Page 9, Paragraph 4.4.2: Change 70' to 70°.

Page 13, paragraph 4.6.2: Sealing.- Delete fifth and sixth sentences and respectively substitute the following:

"Subsequent to reaching the pressure specified, the source of pressure to the cavity shall be shut off. At the conclusion of the specified time period, the leakage shall not have exceeded the requirements of 3.4.6 as indicated on the pressure gage of the testing equipment."

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing Activity:

Army - MU

Project No. 1240-A327

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:39Z
Check the source to verify that this is the current version before use.