AA-C-001402(GSA-FSS)
June 4, 1968

INTERIM FEDERAL SPECIFICATION

CABINET, PROTECTIVE STORAGE AND FILING, UNINSULATED, WITH COMBINATION PADLOCK

This Interim Federal Specification was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C., 20405, based upon currently available technical information. It is recommended that Federal agencies use this document in procurement and forward any recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers an uninsulated, steel filing cabinet having an internal locking mechanism which is secured by an externally attached changeable combination, padlock. The cabinet affords 20 man-minutes protection against entry by surreptitious attack. It has no forced entry requirements.

1.2 Classification. The filing cabinets shall be of the following sizes, as specified (see 6.2).

Size I - Legal size, 5 drawers high, 1 drawer wide.
Size II - Letter size, 5 drawers high, 1 drawer wide.

2. APPLICABLE DOCUMENTS.

2.1 Specifications and standards. The following specifications and standards of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

FF-P-110 - Padlock, Changeable Combination (Resistant to Opening by Manipulation and Surreptitious Attack).
QQ-P-416 - Plating, Cadmium (Electrodeposited).
QQ-Z-325 - Zinc Coating, Electrodeposited, Requirement For.
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple-Wall.
PPP-B-1055 - Barrier Material, Waterproofed, Flexible.
PPP-C-650 - Crates, Wood, Open and Covered.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

Military Specifications:

MIL-L-10547 - Liners, Case and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

Military Standards:

MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Qualification. The filing cabinets furnished under this specification shall be products which have been tested, and passed the qualification tests specified in section 4, and have been listed on or approved for listing on the applicable qualified products list.

3.1.1 Qualification suspension.

3.1.1.1 Development of entry techniques. Continous tests of qualified cabinets will be conducted by the Government to determine whether the surreptitous entry protection afforded by the cabinet should or can be improved. If, at any time techniques are developed within the framwork of the specification which affect the security integrity of the qualified cabinet, it shall be removed from the qualified products list and and manufacturer shall be required to modify his product to the extent necessary to defeat the technique and have it requalified.

3.1.1.2 Change in specification requirements. This specification will be continually reviewed by the Government to determine whether requirements should or can be changed to increase the quality of the product. If, at any time it is determined that the specification's requirements should be changed, and such changes affect the qualification status of the cabinet, it shall be removed from the qualified products list and the manufacturer shall be required to modify his product to the extent necessary to comply with specification changes and submit it for requalification.

3.2 Material. Material used in the cabinet's construction shall be as stated herein. Material not definitely specified shall be of good commercial quality, suitable in all respects for the purpose intended.

3.2.1 Steel. Steel used in the cabinet case, drawers, and drawer suspensions shall be of a type, thickness, and strength to meet the test requirements of this specification. The steel used shall be free from rust, scale, pits, buckles, and other imperfections which might adversely affect the appearance or serviceability of the finished product.

3.2.2 Face hardware. Face hardware shall be satin-finished anodized aluminum, type 430 corrosion-resistant steel, brushed chromium on steel, or on die-cast zinc, brass or bronze, or electroless nickel coating. The exposed surfaces of all hardware used on a single unit shall be finished to match each other within the limits of the base material and protective plating used. The exposed surfaces of all face hardware shall be free of sharp edges, burrs, or nicks. The attachment of face hardware shall not affect the cabinet's security protection.

3.2.2.1 Drawer pulls. The drawer pulls shall be of one of the materials specified in 3.2.2. The material used shall be of sufficient thickness and strength to withstand hard daily usage. The drawer pulls shall be securely and firmly attached to the drawer head to withstand loosening in testing and in operation during the service life of the cabinet.

3.2.2.2 Label holders. The label holders may be sand-cast, die-cast, or stamped and formed. Stamped and formed label holders shall be not less than 22 gage (0.0359-inch) steel or 0.040-inch thick aluminum. All surfaces of the label holder shall be free from roughness and sharp edges. The holders shall readily accommodate and retain, without binding, label cards not less than [illegible] by 1-3/4 inches.

3.2.2.3 Drawer latch and release mechanism. In addition to the locking device specified in 3.4, each drawer shall have an automatic latch which is released by a finger activated button or lever so located that it can be operated when the user's hand is in position on the drawer pull. The latch shall automatically hold the drawer in a closed position, even when the loaded cabinet is in a forward tilted position. It shall not be possible to open the drawer by hand-shaking, jerking, or moving the closed drawer up or down or from side to side unless the latch is released by its control mechanism.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.2.3 Finishing materials.

3.2.3.1 Enamel and lacquer. The finish coat shall be either an enamel of the baking type or an air-dry, textured finished, nitrocellulose lacquer. The quality of the final coat and its application shall be in accordance with good commercial standards and practices. The color shall be as specified in 3.2.4.

3.2.3.2 Zinc coating. Zinc coating shall be in accordance with type I, class 2, of QQ-Z-325.

3.2.3.3 Cadmium plating. Cadmium plating shall be in accordance with class 1, type I, of QQ-P-416.

3.2.4 Color of finish. The color of finish shall be gray, color No. 26134, of Fed. Std. No. 595. (Sample panels of the standard color are obtainable, without charge, from the Buinesss Service Center, Federal Supply Service, General Services Administration, Washington, D.C. 20407, or from the Business Service Center of the nearest GSA Regional Office.)

3.3 Construction.

3.3.1 Design. The filing cabinet shall be 5 drawers high and 1 drawer wide. It shall have the same general appearance as the standard, vertical, Government-type filing cabinet and shall be constructed to meet all requirements of this specification.

3.3.2 Dimensions. The maximum overall outside dimensions of the cabinet, exclusive of external hardware; and the minimum available clear filing capacity of the drawers, not including follower block, shall be as specified in table I.

TABLE I. Dimensions (in inches).

Size	Cabinet Outside-maximum (without hardware)			Drawers Inside-minimum (without follower)		
	Height	Width	Depth	Height	Width	Depth
I	57-1/2	20-13/16	28	10-1/4	19-1/2	24
II	57-1/2	17-9/16	28	10-1/4	16-1/2	24

3.3.3 Weight. The net weight of the cabinet, complete with drawers, shall not exceed the pounds per square-foot of base area specified hereunder. The cabinets base and top area shall be of the same dimensions. The weight of the cabinet shall be clearly and permanently marked on the cabinet base so as to be visible from the front.

Size I - 120 pounds per sq. ft. of base area.
Size II - 100 pounds per sq. ft. of base area.

3.3.4 Assembly of cabinet. The top, sides, back, bottom, and case frame members shall be assembled into a rigid unit. All welding and mechanical attachments shall accomplish secure and rigid joints in proper alignment. Welding and brazing shall be sound without porosity. All protruding or depressed welds on the cabinet exterior shall be filled and sanded or ground smooth. The end item shall provide a cabinet which is well finished and has sufficient strength to withstand daily usage.

3.3.4.1 Cabinet bottom. The cabinet shall be fabricated in such a manner to accommodate the attachment of casters by means of machine screws at each of the four corners of the cabinet bottom. The provision for the attachment of casters shall not weaken the security protection of the cabinet.

3.3.5 Drawers, general. Each drawer shall be equipped with a drawer pull specified in 3.2.2.1, a label holder specified in 3.2.2.2, a drawer latch specified in 3.2.2.3, and a movable follower block specified in 3.3.7. The travel of the drawer shall be such that when the drawer is in its fully opened position, the drawer back shall be not more than 4 inches within the front face of the cabinet. The drawer shall travel easily, quietly, and smoothly on its suspension and shall be easily removed from the cabinet for service purposes.

3.3.5.1 Drawer construction. The drawer body shall be formed from a single sheet of steel of the quality specified in 3.2.1. The drawer back and sides shall be of not less than 20 gage (0.0359-inch) steel. The drawer head and back shall be securely attached to the drawer body by suitable and effective methods. The height of the drawer back shall be not less than the drawer sides. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

The upper edge of the back shall be formed in a flat fold, or a side bead, or ground and sanded. The inside corners of the drawer front shall be neatly closed in a manner to present no external rough edges or sharp corners.

3.3.5.2 Drawer stops. Each drawer shall be provided with a heavy duty stop which will prevent the drawer from hitting the back of the cabinet on the inward movement and with a positive stop that will prevent the drawer from falling out when fully extended. The stops shall be designed to permit the drawer to be readily removed and replaced.

3.3.6 Guide rods. Guide rods are not permitted.

3.3.7 Movable follower block. The thickness of the steel used for the follower block shall be not less than 20 gage (0.0359-inch). The follower block shall be as specified in 3.3.7.1 or 3.3.7.2. Its upper edge shall have a completely closed formation and all other exposed surfaces shall be finished in a manner which completely eliminates roughness. The follower block shall be easy to adjust and removable.

3.3.7.1 Friction locking type. The friction locking type follower block shall be held in place by means of pressure exerted against the drawer sides and shall be held securely in a right angle position to the drawer sides at any point along the drawer depth except for a maximum of 5 inches at the front of the drawer. The follower block shall be spring controlled and activitated at one point near the upper edge of the follower by a device designed for this purpose. The follwer block shall withstand the test specified in 4.4.8.5 without damage or creeping in excess of 1/2-inch.

3.3.7.2 Positive locking type. The positive locking type follower block shall be held in place by engaging slots along the drawer sides or bottom and shall be held securely in a right angle position to the drawer sides at no greater than 1 inch increments except for a maximum of 5 inches at the front of the drawer. The locking method shall be such as to prevent disengaging by pressure of filing material in the drawer. When the locking method does not incorporate spring action, the locking shall be accomplished solely by the weight of the follower block.

3.3.7.3 Follower block support. The follower block support shall be constructed of not less than 11 gage (0.1196 inches) steel and shall be made corrosion resistant by zinc or cadmium plating. The support shall be held securely and shall move freely within the formation provided in the drawer side. The support arm extending along the drawer side shall be not more than 5 inches or less than 4-1/2 inches in length.

3.3.8 Drawer suspension. The drawer suspensions shall be equal in all respects to either the type specified in 3.3.8.1 or in 3.3.8.2. Suspensions shall be equipped with bumpers or shock absorbers of rubber or other comparable material to prevent metal to metal contact between the back of the suspension or drawer track and the back of the cabinet. Suspensions shall withstand the test in 4.4.8.2.

3.3.8.1 Progressive suspension, side-arm type. The steel used in the construction of the neutral members shall be not less than 16 gage (0.0598-inch) and shall be cadmium or zinc plated to a minimum thickness of .0004-inch, except for areas burned during the welding process. Alternatively, a black oxide coating may be used provided the entire member is then coated with a clear organic finish which dries to a hard film. The slides shall travel easily, quietly, and smoothly with the drawer.

3.3.8.2 Progressive suspension, cradle-type. There shall be two neutral members and not less than two tie members, all of which shall be not less than 16 gage (0.0598-inch) steel. The neutral members and tie member shall be joined by not less than two spot welds at each connection. All members shall be cadmium or zinc plated to a minimum thickness of .0004-inch, except for area burned during the welding process. Alternatively, a black oxide coating may be used provided the entire member is then coated with a clear organic finish which dries to a hard film. The slides shall travel easily, quietly, and smoothly with the drawer.

3.3.8.3 Rollers and ball bearings. Free rolling rollers, balls, or fixed journal rollers of the ball-bearing or floating type shall be used to support the suspensions and drawers. There shall be at least three main bearing rollers in each side arm slide that shall be not less than 3/4-inch thickness and slightly chamfered at both edges, and not less than 7/8-inch in diameter. Rollers shall be accurately turned from cold rolled steel and shall be case-hardened. When used, the housing or retainer for the free rolling rollers shall be of cold rolled steel not less than 16 gage (0.0598-inch) and welded to the side arm at each end by not less than two spot welds. When journal rollers are used, each suspension shall have at least six of the ball bearing type and two of the stud bearing type. When free rollers or balls are used, there shall be not less than two to a suspension. Balls shall be not less than 3/8-inch diameter, hardened and polished, and so retained in concave races to prevent dislocation or removal of balls unless the suspension is dismantled.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.3.9 Drawer and case track. The drawer and case track shall be of hot- or cold-rolled steel of not less than 14 gage (0.0747-inch) thickness. After forming to shape, the drawer and case track shall have a Rockwell hardness of not less than 70 nor more than 85 on the "B" scale, or equivalent hardness on a comparable scale. All outer surfaces of the drawer and case track shall be finished in accordance with 3.2.3.2 or 3.2.3.3. Case tracks shall be secured to at least the front and rear interior reinforcing members by interlocking of lugs on the case track into appropriate openings in the reinforcing members. The interlocking shall provide secure connections without vertical or horizontal movement. The bottom edge of the case track shall rest on the cross rail. Alternatively, the case track may be bolted or welded to at least the front and rear interior reinforcing members to provide a comparable connection. The drawer tracks shall be attached to the drawer sides by two rows of spot welds on not more than 4-inch centers, or, alternatively, by one row of spot welds on not more than 3-inch centers, diagonally measured.

3.4 Locking mechanism and padlock. A built-in, interior locking mechanism, of a design which can be secured by the attachment of a changeable combination padlock on the outside front of the cabinet, shall control the locking of the entire cabinet. It shall not be possible, in normal operation, to secure the locking mechanism and leave any drawer unlocked. Exposed parts of the locking mechanism shall not interfere in normal use of the cabinet. The padlock shall be a class I, concealed shackle type specified in FF-P-110. The padlock shall be tested as an integral part of the cabinet, and it shall be furnished on the sample cabinet submitted for qualification.

3.4.1 Drawings. Complete, exploded-view drawings of the locking mechanism and lock mounting, with parts indexed, shall be furnished by the manufacturer upon specific written request of the purchaser.

3.5 Pretreatment and finishing.

3.5.1 Pretreatment. All exterior and interior ferrous metal surfaces shall be treated for painting in accordance with any of the types in TT-C-490.

3.5.2 Finishing. The finish coat specified in 3.5.3.1 shall be applied to all exterior and interior metal surfaces except plated metal. The minimum total finished film thickness of the final coat shall be not less than 1.0 mil. The finish shall level out to produce uniform exposed surfaces without runs, wrinkles, grit, areas of thin film or no film, and separation of color. Special attention shall be given to the base and to the interior to insure that all surfaces are adequately protected against rust. The final finish shall withstand the test in 4.4.8.9 without evidence of cracking, flaking, or loss of adhesion of the finish. Two test panels of 20 gage (0.0359-inch) in 3- by 5-inch size shall be furnished with the sample cabinet. One prepared to reflect the inner coating used and one to simulate the outer case. Both panels shall withstand the test in 4.4.8.9.

3.5.2.1 Optional finish. A crinkle finish may be used on the exterior surfaces of the cabinet.

3.5.3 Bolts, screws, nuts, and accessories. The bolts, screws, nuts, and similar accessories shall be made to resist rust by electrogalvanizing or by zinc, chromium, or cadmium plating. Zinc and cadmium finishes shall be in accordance with 3.2.3.

3.6 Lubrication. All of the cabinet's moving parts requiring lubrication shall have a permanent-type lubricant applied which is suitable to the varied climatic conditions likely to be encountered during the service-life of the cabinet.

3.7 Resistance to entry techniques. The cabinet, including its attached padlock shall withstand the surreptitious and radiographic tests in 4.4.8.6, 4.4.8.6.1, and 4.4.8.7 for the times specified hereunder.

20 man-minutes surreptitious entry.
30 man-minutes radiographic techniques.

3.7.1 Shielding for radiographic protection. When shielding, additional to that provided in the padlock, is necessary to obtain the required radiographic protection, the inside depth dimension of the drawer on which the padlock is mounted may be 1/2-inch less than the depth dimension specified in table I.

3.8 Resistance to damage by dropping. The cabinet shall be subjected to the drop tests in 4.4.8.8, and shall withstand damage to the extent specified in the test requirement.

3.9 Replacement of component parts. The cabinet's components such as drawers, follower blocks, suspensions, padlock, and external hardware shall be capable of identical replacement in the field without use of specialized tools or specially qualified personnel. Such replacements shall be possible without affecting the security protection afforded by the cabinet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.10 Identification markings.

3.10.1 External marking. The cabinet shall have a metal label affixed to the outside face of the top drawer which shall show the manufacturer's name.

3.10.2 Internal marking. Cabinets furnished in accordance with this specification shall have affixed to the side of the top drawer, a metal label or labels showing the manufacturer's name, cabinet model and serial numbers, year of manufacture, and Government contract number.

3.10.3 Protection certification marking. Cabinets furnished in accordance with this specification shall have a metal label externally affixed to the side of the top drawer. The label shall be clearly visible when the drawer is in the half open position and shall show in easily read letters not less than 1/8-inch in height, the following certification:

PROTECTION

This cabinet has been tested by an agency of the Government under the test requirements specified in Interim Federal Specification AA-C-001402, and affords protection for:

20 man-minutes against surreptitious entry;
30 man-minutes against entry by radiographic techniques; and 30 man-minutes against entry by manipulation of the padlock. The cabinet has no forced entry requirements.

3.11 Workmanship. The workmanship shall be of a quality to produce a serviceable and well finished item of office furniture able to withstand hard daily usage. The edges of all parts and sheets shall be protected by folding, beading, flanging, or grinding to eliminate burrs, roughness, and sharp edges. The bending of channels and flanges shall be straight and smooth. Welding and brazing shall produce secure and rigid connections. Lock washers, cotter pins, clips, retainers, or built-in features shall be used to prevent loosening of screws, bolts, and nuts, which may cause disengagement of parts and possible lockout. Moving parts shall operate smoothly without binding or jamming. The cabinet shall be free of any defects or features which may affect its appearance and serviceability, or which may cause personal injury.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. Except that testing for qualification shall be performed by an agency designated by General Services Administration, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facility or service acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

4.2 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.3 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the preservation, packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.4 Testing procedures and tests.

4.4.1 Testing agency. Qualification tests accomplished on cabinets submitted for approval for inclusion on applicable Qualified Products Lists (QPL) and any retesting that may be required shall be performed by a testing agency specifically designated by the General Services Administration.

4.4.2 Testing costs. All testing costs entailed in determining the qualification of the supplier's product, including costs or retesting of a qualified product if subsequently disqualified under 3.1.1.1 or 3.1.1.2, shall be borne by the supplier, and shall be payable to the General Services Administration as directed by Standardization Division, Federal Supply Service.

4.4.3 Testing procedures. The following procedures shall govern the testing of all cabinets submitted for qualification under this specification:

(a) Samples shall be submitted for qualification only after the supplier has obtained written authorization from the General Services Administration.

(b) A qualification test may be discontinued at the Government's testing facility at any time the product fails to meet any one or more of the requirements set forth in this specification. The manufacturer may be permitted to make modifications on the sample during the testing phase where such modifications, in the judgement of the General Services Administration and the testing facility, are clearly in the interest of the Government.

(c) In case of failure of the sample, consideration will be given to the request of the manufacturer for resubmission for retest only after it has been clearly shown that changes have been made in the product which the Government considers sufficient to warrant retest.

(d) The manufacturer or his representative will not be permitted to observe the actual tamper resistance tests conducted on his product at the testing facility. However, when samples tested fail to comply with the requirements of this specification, the sample may be examined by the manufacturer or his representative and full details of the failure may be made known to them in a manner which, for reasons of security, will be in the best interest of the Government.

4.4.4 Test samples. Two qualification test samples shall be forwarded at a time and to a place designated by the General Services Administration. In the event the two samples are destroyed or damaged to such an extent during testing that testing cannot be completed, the Government reserves the right to require the manufacturer to furnish additional samples to complete the testing.

4.4.5 Drawings and material specifications. The manufacturer shall furnish two complete sets of construction and assembly drawings and material specifications with the sample cabinets submitted for qualification. When samples have been tested and are approved for inclusion on the applicable QPL, the manufacturer shall furnish three additional sets of the drawings and material specifications to the General Services Administration for the Government's use in inspection and acceptance of the product after award of contract. All material so furnished by the manufacturer will be held in proprietary confidence.

4.4.5.1 Changes in drawings and material specifications. Once the cabinet has been tested and approved for QPL , no change of any kind shall be made in its construction or in the construction drawings unless prior written authorization to make the change is obtained from Standardization Division, Federal Supply Service.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.4.6 Qualification testing. Qualification testing shall consist of the following tests described under Test methods in 4.4.8. Failure of the sample to withstand any one or more of these tests shall provide reason to consider the product as having failed to comply with the testing requirements.

(a)	Rack test	- 4.4.8.1
(b)	Service test	- 4.4.8.2
(c)	Drawer pull test	- 4.4.8.3
(d)	Moving test	- 4.4.8.4
(e)	Follower block test	- 4.4.8.5 (if friction type)
(f)	Tamper resistance test	- 4.4.8.6 and 4.4.8.6.1
(g)	Radiographic test	- 4.4.8.7
(h)	Drop test	- 4.4.8.8

4.4.7 Acceptance after award of contract. The Government reserves the right to inspect and test each cabinet, including all component parts thereof, delivered for acceptance under this specification after award of contract.

4.4.8 Test methods.

4.4.8.1 Rack test. Each drawer of the size I cabinet shall be loaded with material weighing 80 pounds (60 pounds if size II). The weight load shall be equally distributed from front to back of cabinet drawers. Examination shall be made to determine ease of operation of the cabinet's movable parts, under condition of loaded level, uniform support. The drawer pull test in 4.4.8.3 shall be conducted at this time. The drawer operating force shall not exceed 10 pounds. The loaded cabinet shall then be raised not less than one inch to a position of being supported at two diagonally opposite corners. The area of support shall be not greater than 6 inches from each corner. Two hundred and fifty pounds of additional weight shall be still-loaded on the top of the cabinet at each of the two unsupported corners. The cabinet shall remain in this position for not less than 24 hours. The cabinet shall be returned to its normal position at the end of this period and reexamined to determine ease of operation of its movable parts. The drawer pull test shall be conducted. The cabinet shall be considered to have failed the test if the drawer pull operating force exceeds ten pounds or if other movable parts of the cabinet fail to function as intended.

4.4.8.2 Service test. The cabinet shall be bolted or otherwise secured in proper position. The drawer selected for test, loaded as specified in 4.4.8.1, shall be connected by its drawer pull to a machine which will operate the drawer. The machine shall have a positive means (no springs) for adjusting the length of its stroke so that the drawer will travel the full distance, not more than 1/2-inch clearance at the end of each stroke, from back stop to front stop. The machine shall drive the drawer at a rate of 20 cycles per minute ± 2 cycles per minute. The machine shall in no way contribute to the support of the drawer. The suspension of the drawer being tested shall be cleaned and lubricated at the end of 10,000 cycles and shall have no further attention until the test is completed. At the beginning of the test and at each increment of 10,000 cycles, the drawer test in 4.4.8.3 shall be conducted to determine the force required to start the loaded drawer forward to move it to its full outward limit. The cabinet shall be considered to have failed the test if the drawer operating force exceeds 10 pounds to complete the forward stroke before, or at 50,000 cycles. Should failure be perceptible during the increment of 10,000 cycles, the machine shall be stopped and the drawer pull test shall be conducted at that point.

4.4.8.3 Drawer pull test. The drawer pull test shall be conducted on the loaded drawer by passing a limp cord, attached to the center of the drawer pull, over a sheave with a weight applied to the free end. The force required to start the loaded drawer forwarded and to move it to its full outward limit shall be recorded. The drawer operating force shall not exceed 10 pounds.

4.4.8.4 Moving test. The cabinet, loaded as specified in 4.4.8.1 and with the follower block in each drawer drawn up tight against the loaded material, shall be tipped over on its back on a furniture moving dolly. It shall remain in that position for not less than 3 hours. It shall then be returned to normal position and examined. There shall be no damage to the cabinet or its component parts or displacement of the drawer's contents as a result of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.4.8.5 Follower block (friction-type) test. A drawer of the size I cabinet shall be loaded with material weighing 60 pounds (50 pounds for size II). The material shall be held against the front of the drawer by the follower block. The location of the follower block shall be indicated by a mark placed on the bottom of the drawer. The machine specified in 4.4.8.2 for operating the drawer shall be connected to the drawer and set in motion and made to operate 500 cycles. Upon completion of the 500 cycles, the position of the follower block shall again be indicated by a second mark on the bottom of the drawer. The rearward movement of the follower block, as indicated by the distance between the two marks, shall not exceed 1/2-inch.

4.4.8.6 Surreptitious entry test. There shall be no limit on the number of surreptitious entries (see 6.5.1) attempted. There shall be sufficient time allowed to study the design of the cabinet and related drawings and to develop testing methods prior to the start of the test. Not more than two people will be used simultaneously during an attempt at entry. The man-minute working time shall cover the period during which an entry test is in progress on the cabinet, and shall be exclusive of time required for safety first precautions and rest periods. The test tools and devices used in the test shall be limited to those powered by hand such as, but not limited to, metal cutters, hammers, wedges, chisels, and drills. Tools and devices shall be not more than 20 inches in length when disassembled or folded. Tools and devices shall be capable of being carried in a case not exceeding 1.5 cubic feet in volume and nine inches in thickness, and which do not exceed a total weight of 25 pounds, exclusive of weight of case. Neither explosives not the application of heat such as from a blow torch or electric arc shall be used. The test tools and devices selected for the test shall be weighed and packed in the carrying case specified prior to commencement of the test. The time clock shall be started when the test equipment carrying case is opened and shall not be stopped during a test, except as specified above. Any change or repair of tools taken from the carrying case during a test shall only be done while the clock is running. Simulated test actions shall not serve in place of an actual test on the item at hand. And, where successful entry is achieved, test shall be complete in detail. Any surreptitious entry made under the above conditions within less than the time specified in 3.7 shall provide reason to consider the cabinet as having failed to meet requirements of the test.

4.4.8.6.1 It shall not be possible, within the time and tool limitations specified in 4.4.8.6, to extract material from the cabinet through a gap or crevice made by spreading an opening of any dimension (The 5-sq. inch opening in 6.5.1 does not apply to this test. between the edges of the drawer head and the front frame of the drawer compartment without leaving evidence of the act which would be readily discerniable in normal use of the cabinet.

4.4.8.7 Radiographic test. The test in intended to simulate surreptitious entry within the specification's limit of time, utilizing practicable and feasible procedures and equipment readily available to the Government testing agency conducting the tests. For example, the drawer head or cabinet structure on which the cabinet's padlock is mounted shall be radiographed, and the resulting radiographs shall not permit determination of the padlock's combination. Radioactive material shall be used in the test. Any entry made under the above conditions within less than the time specified in 3.7 shall provide reason to consider the cabinet as having failed to meet the requirements of the test.

4.4.8.8 Drop test. Each drawer of the cabinet shall be loaded with 60 pounds of weight which shall be compacted and held in place by the follower block. The locked cabinet shall then be subjected to the tests in 4.4.8.8.1 and 4.4.8.8.2.

4.4.8.8.1 Thirty-six inch drop test. The cabinet shall be slowly tilted backward from its normal upright position until overbalanced and allowed to free-fall on its back to a hard, level concrete surface or equal surface. With the cabinet on its back, the top end shall be raised and allowed to rest on a 4-inch ledge or support. The base end shall then be elevated to a height of 36 inches and allowed to free fall to the concrete surface or equal surface. Any damage to the cabinet which results in a lockout requiring destructive force to reduce shall provide reason to consider the cabinet as having failed to withstand the conditions of the test.

4.4.8.8.2 Thirty-foot test. The cabinet shall be raised while in its normal upright position until the base of the cabinet is 30-feet above the floor. The cabinet shall then be allowed to free-fall, base down, onto a hard, level concrete surface or equal surface. Any damage to the cabinet which releases or makes accessible without further force, any part of the stored contents shall provide reason to consider the cabinet as having failed to withstand the conditions of the test.

4.4.8.9 Finish test. The steel panels prepared in accordance with 3.5.2 shall be bent at room temperature around 1/4-inch rod to an angle of 180 degrees. The panels shall then be examined for compliance with 3.5.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.4.8.10 Inspection. The sample cabinet shall be inspected for compliance with applicable requirements of this specification for dimensions, weight, color and finish, and workmanship.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be levels A, B, or C, as specified (see 6.2).

5.1.1 Levels A and B. Filing cabinets, with drawers closed, shall be protected from marring or surface abrasion by cushioning with fiberboard pads, cellulose wadding or comparable fiberboard pads of sufficient width and thickness to afford maximum protection against stresses of shipment and storage. The fiberboard pads and cushioning material shall be secured with tape conforming to PPP-T-60, class 3.

5.1.2 Level C. Filing cabinets shall be cushioned and protected in accordance with the manufacturer's commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Cabinets weighing 1,000 pounds or less. Each cabinet, cushioned as specified in 5.1.1, shall be packed in a close-fitting box conforming to PPP-B-585, class 3; PPP-B-591, overseas type; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-640, class 2, grade A respectively. Each shipping container shall be provided with a sealed case liner conforming to MIL-L-10547. Closure and strapping shall be in accordance with the appendix to the applicable box specification.

5.2.1.2 Cabinets weighing over 1,000 pounds. Each cabinet, cushioned as specified in 5.1.1, shall be packed in a crate conforming to PPP-C-650. The cabinet shall be blocked, braced, and anchored to prevent movement within the crate during transit and shall be shrouded with material conforming to PPP-B-1055, class B-2, B-3, or B-5. The shroud shall completely enclose the cabinet and shall extend to the base of the crate.

5.2.2 Level B. The cabinets shall be packed as specified in 5.2.1, except that the containers shall be class domestic and case liners and waterproof shrouds shall not be required. Closures, strapping, blocking, and bracing shall be in accordance with the appendix to the applicable container specification.

5.2.3 Level C. The cabinets, packaged as specified in 5.1.2, shall be packed to insure carrier acceptance and safe delivery at destination at lowest rates, in containers complying with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The cabinets furnished under this specification are intended for the protective storage and filing of certain categories of classified material where and when authorized by the using agency.

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, symbol, and date of this specification.
(b) Size required (see 1.2).
(c) Level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

6.3 Qualification. With respect to products requiring qualification, awards will only be made for such products as have, prior to the time set for opening of bids, been tested and approved for inclusion on the applicable Federal Qualified Products List, whether or not such products have actually been so listed by that date. The attention of suppliers is called to this requirement and manufacturers are urged to arrange to have the products they propose to offer to the Federal Government tested for qualification so that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20405, and information pertaining to qualification may be obtained from that activity.

6.4 Samples. All sample cabinets required for testing purposes shall be furnished at no expense to the Government and the manufacturer shall pay all transportation charges to and from the point where the tests are conducted. All tested samples shall become the property of the Government but may be released to the manufacturer at the option of the Government. Upon request, the manufacturer shall furnish to the Government testing facility, a cabinet equal in every respect to that of the qualified sample for use of inspection and test during the term of qualification. The cabinet shall be furnished at no expense to the Government and will be returned to the manufacturer should his product be removed from the qualified products list.

6.5 Definitions of terms used in this specification.

6.5.1 Surreptitious entry. For the purpose in 4.4.8.6, "surreptitious entry" means provisions of an opening in the cabinet of not less than 3 square inches in area from which material can be withdrawn with the minimum for any one dimension being 1/4-inch. It is further defined as an entry made in such a manner as to leave no evidence of the act which would be readily discernible in normal use of the cabinet (see 6.5.2).

6.5.2 Normal use. For the purpose of this specification, "normal use" means opening the padlock, releasing the cabinet's locking mechanism, opening a drawer to the extent necessary for the extraction or reception of filing material, closing the drawer, and relocking the cabinet. During this operation it is considered that the top and front of the cabinet is exposed to view and touch; the rear and sides exposed to view only; and the base bottom neither exposed to view nor to touch.

6.5.3 Manipulation of the lock. For the purpose of this specification "manipulation" is defined as the opening of the padlock without alteration of the physical structure of the padlock or disarranging of parts. Ordinarily manipulation is accomplished by movement of the padlock dial.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.