[Metric]
AA-C-1779E
November 20, 1991
SUPERSEDING
AA-C-001779D
July 20, 1990

FEDERAL SPECIFICATION

FILING CABINET, STEEL LATERAL AND FRONT TO BACK FILING, LEGAL AND LETTER SIZE MATERIAL, GENERAL OFFICE

This specification is approved by the Commissioner, Federal Supply Service, General Services Administration, for use by all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The filing cabinets covered by this specification are of contemporary style, and they are designed to be compatible with other standard contemporary style, steel, general office furniture (see 6.1).

1.2 Classification.

1.2.1 Sizes. The filing cabinets shall be of the following sizes (see 6.1).

Size 1 - 910 mm wide
Size 2 - 1070 mm wide
Size 3 - 760 mm wide

1.2.2 Types and styles. The filing cabinets shall be of the following types and styles (see 6.2).

Type I - Two tiers high.

Style A - With two drawers.
Style B - With two shelves.
Style C - With one drawer and one top shelf

Type II - Three tiers high

Style A - With three drawers.
Style B - With three shelves
Style C - With two drawers (bottom) and one top shelf.
Style D - With one drawer (bottom) and two top shelves.

Type III - Four tiers high.

Style A - With four drawers.
Style B - With four shelves.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the currentversion before use.

Style C - With three drawers (bottom) and on top shelf.
Style D - With two drawers (bottom) and two top shelves.
Style E - With one drawer (bottom) and three top shelves.

Type IV - Five tiers high.

Style B - With five shelves.
Style C - With four drawers (bottom) and one top shelf.
Style D - With one drawer (bottom) and four top shelves
Style E - With two drawers (bottom) and three top shelves.
Style F - With three drawers (bottom) and two top shelves.

1.2 3 Models. The filing cabinets shall be of the following models (see 6.2).

Model 1 - Without laminated plastic top.
Model 2 - With laminated plastic top (Types I and II only).

1.2.4 Classes. The filing cabinets shall be of the following classes (see 6.2).

Class A - With lock.
Class B - Without lock.

2. APPLICABLE DOCUMENTS

2.1 Government publications. The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein

Federal Standards:

Fed Std. No 595 - Colors.

Fed Std. No. 123 - Marking for Domestic Shipment (Civil Agencies)

(Activities outside the Federal Government may obtain copies of Federal specifications, Standards, and Commercial Item Descriptions, as outlined under General Information in the Index of Federal Specifications, Standards, and Commercial Item Descriptions. The Index, which includes cumulative bimonthly supplements, as issued, is for sale on a subscription basis by the Superintendent of Document, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification, other Federal specifications, and commercial item descriptions required by activities outside the Federal Government for bidding purposes

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:41Z
Check the source to verify that this is the current version before use.

are available without charge from General Services Administration Business Service Centers in Boston, MA, New York, NY; Philadelphia, PA; Washington, DC; Atlanta, GA; Chicago, IL; Kansas City, MO, Fort Worth, TX, Houston, TX; Denver, CO, Los Angeles, CA; San Francisco, CA; and Seattle, WA.

(Federal Government activities may obtain copies of Federal specifications, standards, commercial item descriptions, and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-129 - Marking for Shipment and Storage

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2. Other publications The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply

American Society for Testing and Materials, Publications.

ASTM D-999 - Method for Vibration Testing of Shipping Containers
ASTM D-880 - Method for Incline Impact Test for Shipping Containers

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. All materials used shall be free from defects which affect serviceability or appearance of the finished product. The manufacturer shall utilize recovered material to the maximum extent practicable.

3.1.1 Steel. The steel shall be smooth and free from rust, scale, pits, scratches, laps, and buckles affecting strength or appearance.

3.1.2 Fastening devices. Unless otherwise specified herein, all bolts, nuts, screws, washers, and other fastening devices shall be of the type, style, and size normally used commercially for the purpose intended and shall be made corrosion resistant in accordance with the manufacturer's commercial practice. The use of paint or lacquer as the sole corrosion inhibitor is prohibited.

3.1.3 Face hardware. The face hardware shall be stainless steel or satin finished chromium plating on steel, aluminum, or on die-cast zinc, brass or bronze. The exposed surfaces of all face hardware used on a single unit shall be finished to match each other.

3.1.4 Laminated plastic.

3.1.4.1 Decorative laminate sheets. Unless otherwise specified, the color, pattern, and finish of the decorative plastic laminate shall be simulated walnut wood grain per GSA Standard Sample No. FSS-L-01002.

3.1.5 Finishing materials.

3.1.5.1 Primer. The primer, when used, shall be compatible with the finishing enamel.

3.1.5.2 Enamel. The enamel shall be of the baking type in accordance with the manufacturer's commercial product.

3.1.5.3 Color. Unless otherwise specified, the color of the enamel finish shall be one of the following colors from Fed. Std. No. 595.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:41Z
Check the source to verify that this is the current version before use.

Black No. 27040
Parchment No. 27769

3.1.5.4 Plated finish. The material used in the plating process shall be as normally used commercially to accomplish the quality specified.

3.1.6 Caution label and instruction sheet. The adhesive backed caution label shall be legibly marked with a statement advising the user to adjust the glides so that the cabinet is level from side to side and where applicable the front is slightly higher than the back. The label should also advise the user that bottom compartments should be loaded first. The adhesive and ink used shall both be the permanent type. The label shall also reference an instruction sheet which shall include instructions for installation of accessories and conversion from letter size to legal size filing and vice versa. The label shall be affixed to the interior surface of the top compartment, prominently visible to the user when the compartment is open.

3.2 Construction. All details shall be consistent with quality production. All elements of construction shall be free of any conditions which hinder the proper function of any part of the units or which constitute a potential hazard to personnel or their clothing.

3.3 Dimensions. The outside overall width and depth of the cabinets shall be as specified in table I. The minimum clear inside dimensions of drawers and shelves shall be as specified in table II. These outside and inside dimensions apply to all cabinets regardless of the drawer and shelf arrangement furnished in the various styles specified in 1.2.2.

TABLE I. Outside overall width and depth

Size	Width and depth
1	910 mm ± 15 mm wide by 460 mm ± 15 mm deep.
2	1070 mm ± 15 mm wide by 460 mm ± 15 mm deep.
3	760 mm ± 15 mm wide by 460 mm ± 15 mm deep.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE II. Minimum clear inside dimensions of drawers and shelves in millimeters

Size		Height	Width	Depth
1	Full height drawer and shelves	254	825	381
2	Full height drawer and shelves	254	977	381
3	Full height drawer and shelves	254	673	381

3.4 Assembly of cabinets. The general exterior appearance of the cabinet covered by this specification shall be as shown in figures 1 through 6. The illustrations identify the basic styling required but do not represent specific requirements unless so stated herein. All welding and mechanical attachments shall accomplish secure and rigid joints in proper alignment. Welding and brazing shall be sound and without porosity and shall prevent the loosening of any part or cause any other defect which might affect the lifetime serviceability of the cabinet. All flanges which are to be welded to another piece shall be positioned to provide maximum welding area, strength, and rigidity to the welded assembly. Interior welds shall be finished to eliminate sharp edges and rough surfaces which might cause personal injury.

3.5 Cabinet case and supporting members. The cabinet case shall consist of front, sides, back, top, bottom, and interior supporting members. All parts of the cabinet case shall be formed, assembled, and finished so that there are no exposed, raw, metal edges which might cause personal injury or might damage floors. The cabinet's case shall be designed to hold both fixed front drawers and roll out shelves with receding doors. The cabinet's bottom shall have easily adjustable glides at each corner.

3.6 Filing drawers and filing shelves. The drawers and shelves shall be of the dimensions specified. All drawers and filing shelves shall have an interlocking mechanism, a gang locking mechanism for class A cabinets, stops and bumpers, and suspensions. Drawers and shelves shall fit squarely in their openings and shall be formed and finished to eliminate roughness and sharp edges that might come into contact with the users during normal operation of the compartments. Drawers and filing shelves shall be easily converted without the use of tools to the filing configurations specified in 3.7.2 and 3.8.2 below. Accessories needed to make these conversions shall be furnished with each drawer and shelf.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.7 Drawers.

3.7.1 Drawer fronts. All drawers shall be fixed, solid front type.

3.7.2 Hanging drawer frames. All drawers shall be equipped with hanging folder frames to support both legal and letter size material filed in both the lateral and front-to-back manner. The hanging folder frames may be an integral part of the drawer or they may be separate, easily installed components (without the use of tools), furnished with each drawer.

3.7.3 Dividers. Each drawer shall be furnished with three snap-in or slide-in dividers which shall securely support both legal and letter size material filed in a lateral manner. No dividers are required for front to back filing in full height drawers.

3.7.4 Depth. Each drawer shall be equipped with a component part which enables the user to easily convert the drawer to legal and letter size filing depth.

3.8 Filing shelves and doors.

3.8.1 Shelves. All shelves shall be the roll-out type with receding doors.

3.8.2 Hanging folder frames. All shelves shall have provisions for conventional filing of both legal and letter size material in a lateral manner. Each shelf shall be equipped with hanging folder frames to support both legal and letter size documents filed in a lateral manner. The frames may be integral with the shelves or they may be separate, easily installed components furnished with each shelf.

3.8.3 Dividers. Each shelf shall be furnished with three snap-in dividers which shall support both legal and letter size material filed in a lateral manner.

3.8.4 Depth. Each shelf shall be equipped with a component part which enables the user to easily convert the shelf to legal and letter size filing depth. An adjustable shelf back may be used for this purpose, or it may be a snap-in component.

3.9 Drawer and shelf interlock mechanism. The cabinet shall have an interlock mechanism to control the opening and closing of each drawer and shelf in the cabinet. The interlock mechanism shall prevent opening of two drawers simultaneously (reference shelf may be excepted).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.10 Drawer and receding door locks for class A cabinets. All class A cabinets shall be equipped with a locking mechanism to control the locking of all cabinet compartments. The locking mechanism, when activated, shall hold the drawers and doors positively locked and secured against any forward tilting of the cabinet and against hand pressure applied to the drawer or door. The locking mechanism shall secure each side of the drawers and doors and shall be activated by a key-operated lock which shall have not less than 125 key changes, keyed differently in groups of 125 units. The face of the lock shall be secured to the inside of the cabinet in such a manner as to retain the lock in the prescribed operating position and to provide ease in operating the lock and the locking mechanism. The lock shall not be removable without the use of tools. The lock shall be lubricated with a lubricant recommended by the lock manufacturer and shall be operated by a grooved key. Two identical keys shall be supplied for each lock and they shall operate easily and smoothly in locking and unlocking the cabinet

3.11 Out stops and bumpers. The cabinet drawers and shelves shall have two noise reducing out-stops (one on each side) which shall prevent drawers and shelves from falling out of the cabinet when they are fully extended. All stops and bumpers shall be installed in a manner to withstand a normal rebound without damage. The use of adhesive as the only method of securing the stops or the noise absorbing material is not permitted.

3.12 Drawer and shelf suspensions. The drawers and shelves of each cabinet shall be equipped with full progressive side arm suspensions. Alternatively, suspensions may be the precision ball bearing, telescoping type. The drawer and shelf suspensions shall incorporate in their design a retaining or anti-rebound feature which shall retain the drawer or shelf in their closed position without creeping or moving forward. Dimensional clearances between all suspension members shall be so controlled that the drawers or shelves shall operate smoothly, and evenly without any binding or drag and shall limit the horizontal and vertical movement of the drawers or shelves. All exterior metal surfaces of the suspension members shall be plated. Drawers and shelves shall extend to the fully open position, far enough to allow unobstructed insertion and removal of hanging files. Suspensions shall be designed to permit the drawers or shelves to be closed by pressure applied at any point on the drawer or shelf front from side to side and top to bottom without binding or dragging.

3.13 Vertical dividers for drawers and shelves. The material used in the dividers shall be of steel formed or reinforced so that the finished item will have a stiffness at least equal to that of an uncoated flat sheet of steel. All exposed surfaces

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the currentversion before use.

shall be smooth and free of burrs and rough edges. The dividers shall retain both legal and letter size documents adequately without excess overlap and shall be designed to snap securely in the drawers and shelves without the use of tools or attaching devices. The dividers shall be cadmium plated or zinc plated as specified herein or they may be painted. When painted a color other than the color specified for the unit, they may be used provided color harmony is maintained.

3.14 Hanging folder frames for drawers and shelves. The hanging folder frame attachment for drawers and shelves shall be formed metal capable of supporting fully loaded standard legal and letter size folders to the maximum capacity of the filing compartment. The frames shall be installed in such a manner that they shall not twist from the true vertical position in excess of 1.6 mm. Attachments for front to back filing should be designed to prevent dislodgement or movement out of position during insertion or removal of filing material. The frames shall have a smooth surface with no rough edges exposed to contact the sliding supports of the hanging folders

3.15 Doors. Doors for the roll out filing shelves shall be the receding type, receding fully into the cabinet when opened. All edges shall be formed and doors shall be reinforced as necessary to assure a sturdy component which will not easily dent, bulge, or bend out of square in use. All exposed surfaces shall be finished to eliminate burrs and roughness. Door tracks shall be formed so that the door is securely retained in the tracks against accidental removal. The door shall be easily removable (use of simple hand tools is permitted). Doors shall have rear bumpers of rubber or other resilient material to cushion the door when it is fully receded into the cabinet. Cushioning bumpers shall be provided to prevent metal-to-metal contact between the door and the cabinet when the door is closed. The outside face of the door shall not act as a bearing surface when the door is receded into the case or is protected from damage when receded into the case.

3.16 Face hardware. Hardware shall be securely retained and shall be of the recessed design, with the outer frame projecting no more than 2.4 mm from the face of the drawer. The pull portion shall provide a comfortable natural hand hold. The exposed surface of the frame face shall be free of sharp surfaces or edges. The inside of the grip area, except for the front opening, shall be completely encased, and the enclosure shall be finished the same color as the end item. The face hardware shall include a clear, rigid or flexible plastic label holder which shall securely hold the label in place.

3.17 Cabinet tops. The tops for the Model 2 cabinets shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

have a top surface and four sides and shall have self-edged decorative plastic laminate firmly and permanently adhered thereto. The edges of the laminated plastic shall be slightly chamfered, smooth, and shall not be chipped. The simulated grain in the decorative laminate on the top surface, front edge, and rear edge of the tops shall extend from side to side (as viewed from the front of the unit). The simulated grain of the laminate on the side edges (right and left side) of the top shall run vertically (as viewed from both sides). The core material for the tops shall be plywood, particleboard, formed steel with steel reinforcements, or a combination steel and honeycombed material sandwich construction. When formed steel is used, extreme care must be exercised to assure that formed edges have minimum possible radii to assure as secure a bond between the laminated plastic and the horizontal and vertical edges of the top as could be accomplished if one of the other core materials was used. The formed steel tops shall be rigidly reinforced and any of the other cores specified above shall be so constructed as to assure conformance with all tests. Tops having plywood or particleboard cores shall have a non-decorative laminated plastic backing sheet permanently adhered to the underside of the top. The top shall be securely attached to the cabinet.

3.18 Pretreatment and finishing.

3.18.1 Paint finish.

3.18.1.2 Pretreatment. All exterior and interior unplated ferrous metal surfaces shall be treated for painting in accordance with the manufacturer's commercial practice.

3.18.1.3 Paint. All pretreated surfaces shall be coated with the baked enamel or electrostatically applied powder base paint. The finish shall be baked at a time-temperature cycle recommended by the enamel manufacturer. The total dry film thickness on all exterior surfaces shall be not less than 0.027 mm. The finish shall level out to produce smooth, uniform surfaces without runs, wrinkles, grits, areas of thin film or no film, tackiness, and separation of color.

3.18.2 Plated finish.

3.18.2.1 Pretreatment. The components to be plated shall be cleaned and otherwise pretreated in accordance with the standard commercial practice for the type of plating specified.

3.18.2.2 Chromium plating. The chromium plating shall not peel, chip, or crack and shall be free of pits, blisters, stains, powder film, and brush or grind marks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.19 Workmanship. A high degree of craftsmanship shall be exercised while performing the various operations of manufacture to eliminate the possibility of personal injury due to burrs and sharp edges; to assure that the occurrence of defects will not exceed the acceptable quality level (AQL) specified herein; and to produce a finished commodity that is satisfactory in function, serviceability, and appearance.

3.20 Identification label. There shall be an identification label affixed to the inside wall of the top drawer in the cabinet so as to be readily visible and readable when the drawer is open. The label shall bear the contractor's name or trademark, contract number, item stock number, month and year of manufacture.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies or services conform to prescribed requirements. Cabinets shall be inspected for the defects in table III and for dimensional defects using the inspection levels and AQL,s in 4.1.2.

4.1.1 Application of First Article samples. Two cabinets of each size, type, style, model, and class and their applicable components and accessories, as designated by the contracting officer, shall be provided for First Article examination.

TABLE III. Classification of Defects

Examine	Para. No.	Defect	Classification	
			Major	Minor
Steel	3.1.1	Rust, scale, pits, laps, & buckles		x
Face hardware	3.1.3	Not material or finish as specified.		x
		Rough or sharp edges.	x	
		Not design specified.		x

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of Defects

Examine	Para. No.	Defect	Classification	
			Major	Minor
		Not identical in appearance.		x
Cabinet color	3.1.5.3	Wrong color.	x	
Welding	3.4	Burnt through, cracked, fractures not fused.	x	
		Flash or splatter on drawer interiors and exposed surfaces.		x
		Welds on exterior surfaces not smooth as specified.		x
Cabinet case	3 5	Exposed raw metal edges.	x	
Leveling glides		Abrade floor surface.	x	
		Not adjustable or accessible as specified.	x	
Drawers and shelves	3.6	Not adjustable or accessible as specified	x	
		No provisions for hanging folder frames.	x	
Interlock	3 9	Not positive and automatic	x	
Drawer & door locks	3 10	Does not require a grooved key to operate lock.		x
		Lock mechanism does not secure both sides of drawer and doors.		x

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of Defects

Examine	Para. No.	Defect	Classification	
			Major	Minor
Stops & bumpers	3.11	Not as specified	x	
		Metal-to-metal contact with cabinet back.	x	
		Do not prevent cabinet compartment from falling out.	x	
Suspensions & tracks		Not securely attached.	x	
		Not as specified.	x	
		Do not extend compartment outward as specified.	x	
		Do not operate easily, quietly and smoothly.		x
		Binds or drops while opening and closing.	x	
Dividers	3.13	Finish not as specified.		x
		Rough or sharp edges.	x	
		Do not snap in compartment as specified.	x	
Hanging folder frame	3.14	Do not fit compartment.	x	
		Finish not as specified.		x
Door	3.2 6.1 1	Does not recede into cabinet as specified	x	
		Does not travel easily, quietly, and smoothly.		x
		Jams while closing and opening.	x	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of Defects

Examine	Para. No.	Defect	Classification	
			Major	Minor
		Leading edge not formed as specified.		x
		Not finished as specified.		x
		Metal-to-metal contact with cabinet back or front.	x	
		Front face of door is bearing surface.	x	
Laminated plastic top	3 17	Material not as specified.	x	
		Top covering not properly adhered to top.	x	
		Top buckled, bulged, or warped.	x	
		Not color or pattern specified.	x	
Pretreatment	3.18	Indication of rust under coating.	x	
Finish	3.18.1	Poor adhesion, tacky, color separation, stains, runs, or foreign matter in coating.		x
		Scratches or unpainted areas.	x	
		Abrasion or areas of thin coating.		x
		Film thickness on exterior surfaces less than specified.		x

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of Defects

Examine	Para. No.	Defect	Classification	
			Major	Minor
		Film thickness on interior surfaces less than specified.		x
Bolts, nuts, screws	3 1.2	Not finished as specified.		x
		Threads stripped.		x
Caution label	3.1.6	Missing.	x	
Instruction sheet	3.1.6	Missing.	x	
Workmanship	3.19	Part missing, affecting appearance or serviceability.	x	
		Part malformed, damaged, buckled, or warped, affecting serviceability.	x	
		Sharp edged or roughness which may cause injury.	x	
		Design or construction features which may cause injury to the user.	x	

4.1.2 Dimensional inspection. Inspection shall be made to determine the cabinet's compliance with dimensions specified in table I and table II. Any dimension not within tolerance shall be classified as a defect.

4.1.3 Inspection levels and acceptable quality levels. The inspection levels and AQL's expressed in percent defective shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE IV. Inspection Levels and AQLs

	Inspection level	AQL
For examination in table III (major)	I	4.0
For examination in table III (total)	I	10 0
For examination in 4.1.2 (one class)	I	4.0
For examination in 4.2	S-2	4.0

4.2 Examination of preparation for delivery. An examination shall be made to determine compliance with the requirements of section 5. The sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105D.

4.3 Testing of First Article and production line cabinets. Testing shall be repeated whenever a change is made in material, construction, or method of production during the course of a contract. The Government reserves the right to subject any cabinet from any production lot to the tests in 4.4.

4.4 Tests and test methods. Cabinet testing shall be performed in accordance with test methods described in paragraphs 4 4.1 through 4.4.12. This does not preclude the use of other test fixtures if the mechanics of the system are duplicated for similar tests. Points or reference lines shall be provided as applicable so that accurate measurement may be taken to determine if any permanent distortion has taken place in any cabinet component under test. Failure of a cabinet to pass a test shall be considered as failing to comply with specification requirements.

4.4.1 Tilt test The cabinet shall be placed on a hard, level surface in its operating position. The top compartment shall be evenly loaded with typical filing material with the weight of 0.471 g/cubic centimeter. All other compartments shall be empty and closed. The loaded top compartment shall be fully extended and a horizontal force (pull) of 44.5 N shall be applied at the center point of the compartment front The cabinet shall have failed the test if it tips over.

4.4.2 Receding door cycling test. The cabinet shall be placed on a hard, level surface in its operating position, and the base shall be restricted from vertical and lateral movement. The test door shall be connected to the cycling device 150 mm

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

from the right side on the leading edge. One cycle shall cause the door to travel inward from the extended position to its receded position and outward to the extent of its horizontal travel. The cycle rate shall be 10 ± 5 cycles per minute continuous till test is complete The door shall be cycled 20,000 times on the right side and 20,000 times with the cycling device attached 150 mm from left side on the leading edge. The cabinet shall have failed the test if a pull force of over 13.3 N is required to move the door from the receded position to a distance of 150 mm to 176 mm outward, and at any time during the test if the door drags or binds during operation, opening, receding, extending, and closing of door.

4.4.3 Out stop test. The cabinet shall be placed on a hard, level surface in its operating position, and the base shall be restricted from vertical and lateral movement. The test drawer or shelf shall be loaded as specified in 4.4.1 and then held closed. A small cable shall be attached to the center of the drawer or shelf and extended horizontally to a pulley. The opposite end of the cable shall extend downward, and a weight equal to 20 percent or 44.5 N, (whichever is greater) of the drawer or shelf load shall be attached to the free end. The weight shall be allowed to free fall, causing the drawer or shelf to impact the out stops. The test shall be repeated five times. The cabinet shall have failed the test if the outstops fail, distort, or become damaged.

4.4.4 Shelf retention test. The cabinet shall be placed on a hard, level surface in its operating position. An empty drawer or shelf shall be fully extended. A 110 N force shall be applied to the front center in a vertical upward direction The cabinet shall have failed the test if the drawer or shelf becomes detached from the suspension or has resulting damage affecting its operation or serviceability.

4.4.5 Lock test. The cabinet shall be placed on a hard, level surface in its operating position, and all drawers and shelves shall be loaded as specified in 4.4.1. Drawers and doors shall be closed, locked and the key removed. Apply a horizontal outward pull of 220 N at the center of each drawer or door pull. The cabinet shall have failed the test if any drawer or door opens during the pull test or if the locking mechanism fails to operate properly after the test

4.4.6 Interlock mechanism test.

4.4.6.1 Interlock mechanism service test. Part 1: The cabinet shall be placed on a hard, level surface in its operating position. Only the bottom shelf shall be fully loaded as specified in 4.4.1. Apply a horizontal force (pull) of 44.5 N to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

the top shelf at the center of the shelf. When it is fully extended, the unsecured unit shall not tip over. Counterweights or other stability devices may be used for compliance if these are an integral part of the cabinet. Part 2: All compartments shall be fully loaded with the applicable weight specified in 4.4.1. One randomly selected drawer or shelf shall be opened not less than 150 mm nor more than 200 mm from the fully closed position. All other drawers and shelves, loaded as specified in 4.4.1, shall be fully closed. A horizontal pull force of 133.4 N shall then be applied to the drawer pull or center point on the shelf of each of the closed compartments one at a time. The cabinet shall have failed the test if the opening of the closed drawers or shelves is more than 12.5 mm beyond the front face of the cabinet on the side that the interlock is attached. If the interlock mechanism is located on the side of the drawer or shelf, the drawer opening shall be measured on the side where the interlock is attached. For interlocks that attach at the rear of the cabinet, the drawer or shelf opening shall be measured at the center point of the drawer or shelf.

4.4.6.2 Interlock mechanism tip test. The cabinet shall be evenly loaded as specified in 4.4.1. All of the drawers or shelves shall be in the fully closed position. The cabinet shall be tilted forward 15° so that the drawers or shelves will be restrained from opening only by the interlock mechanism. If the interlock mechanism is located on the side of the drawer or shelf, the drawer opening shall be measured on the side where the interlock is attached. For interlocks that attach at the rear of the cabinet, the drawer or shelf opening shall be measured at the center point of the drawer or shelf. The cabinet shall have failed the test if more than one drawer or shelf extend more than 12.5 mm beyond the face of the cabinet on the side that the interlock is attached. For interlocks that attach at the rear of the cabinet, the drawer or shelf opening shall be measured at the center point of the drawer or shelf.

4.4.7 Drawer or shelf cycling test. The test shall be performed on the top drawer or shelf. The cabinet shall be placed on a hard, level surface in its operating position, and the base shall be restricted from vertical and lateral movement. The test drawer suspensions shall be cleaned or lubricated at the start of the test only. The test drawer or shelf shall be loaded as specified in 4.4.1 with hanging folders loaded with steel shot or other typical filing material and connected to the cycling device at the center of pull area. One cycle shall cause the drawer shelf to travel inward until the interlock mechanism is activated and outward to within 6 mm of the fully extended position. The cycle rate shall be not less than 15 cycles per minute and shall be ran continuously until the test is complete. The cycling device shall not support nor add to the load on the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

suspensions nor shall the test shall be performed on the drawer or shelf after 100 cycles suspension be cleaned or lubricated during the test. The pull and at intervals of 10,000 cycles. After 125,000 cycles attach the cycling device 150 mm from the right side of the drawer or shelf and cycle 10,000 cycles and perform the pull test. Attach the cycling device 150 mm from the left side and after 10,000 cycles perform the pull test. For cabinets with center pulls, the drawer or shelf shall be cycled at 145,000 cycles. The cabinet shall have failed the test if the ~~drawer or shelf does not operate properly during or after the~~ cycling test, if the interlock or locking mechanisms fail to operate properly or if the drawer or shelf fails to pass the pull test.

4.4.8 Pull and interlock test. 1a) Attach a limp cable or force gage to the shelf at a point not more than 100 mm from the left or right edge (side) on the front, with the weight applied to the loose end which shall overcome any anti-rebound feature that may be built into the cabinet or suspension. A force gauge may be used instead of the cable. Record this force. 1b) Apply a weight to the loose end, with the drawer or shelf past the antirebound, which shall open the drawer or shelf to its full extension or against the outward stops. Record this force. The cabinet shall have failed the test if the pull force to open over the anti-rebound is more than 26.7 N.

2) Extend one drawer away from cabinet. Apply a 220 N static load to other pulls. Apply 44.5 N static loads simultaneous to combinations of two drawers. No more than one drawer may open more than 19 mm at any time.

4.4.9 Cabinet shock test. This test is to be performed on prior to any other tests. The cabinet shall be placed 12.7 mm above a hard, surface resting on its leveling glides in their retracted position. All drawers and shelves shall be loaded with typical filing material with a weight of 0.471 g/cubic centimeter and the cabinet locked with the key removed. The cabinet shall be tilted to one side until the opposite side bottom edge is 200 mm from the floor or to its balance point, whichever is less. A 200 mm long block shall be placed under the center of the raised side and then knocked loose, allowing the cabinet to fall on the leveling dome supporting that side. The test shall be conducted on one side. The cabinet shall then be emptied. Following the same set-up procedures the cabinet shall be raised 300 mm from the floor. A 300 mm long block shall be placed under the center of the raised side and then knocked loose, allowing the cabinet to fall on the leveling dome supporting that side. The test shall be conducted on both sides.

The cabinet shall have failed the test if any permanent damage to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

the lock or interlock mechanisms is detected; failure of rivets or welds; damage (except case) or loosening of components; or failure of the drawers and shelves to pass the pull test. (Note: In all probability, there will be visible case damage. This is not a criteria for rejection).

4.4.10 Finish test for steel panels. A 0.91 mm steel panel, prepared in accordance with 3.2.7 shall be bent at room temperature around a 3.175 mm diameter rod at 180 degrees. Any evidence of cracking, flaking, or loss of adhesion of the enamel shall be considered as a failure

4.4.11 Spot weld test. A spot weld assembly of at least two parts of the end item cabinet shall be produced under production conditions. A chisel shall be driven between the welds or one part shall be bent back until failure occurs. Failure around the periphery of the weld(s) shall be considered as complying with the requirements. Failure of the weld(s) shall be considered as failing to comply with specification requirements.

4.4.12 Rebound test. The file shall be leveled in its normal operating position and secured. The test drawer or shelf shall be uniformly loaded as specified in 4 4.1 and connected to a cycling device in a manner that causes the drawer to travel within 6.4 mm of the closed position and 6.4 mm of full extension without supporting or adding to the load on the suspensions and cycled 100 cycles. A force gage with a spring rate of 44.5 N inch shall be mounted and the drawer or shelf shall be opened to a force within 1 kg of the drawer or shelf load or 177.9 N, whichever is less. The drawer or shelf shall be released, allowing the force gage to close the drawer or shelf. This procedure shall be repeated 10 times for each drawer or shelf tested. The drawer or shelf shall have failed test if the rebound position of the drawer or shelf exceeds 38 mm average after ten closings.

4.4.13 Shipping shock test. The test equipment shall comply with ASTM D-880. A complete fully assembled unit (cartoned) shall be submitted for test. Prior to cartoning, the unit shall be inspected for visual or functional damage and documented. The cartoned unit shall be placed onto the impact machine dolly flush against the back stop and parallel to the leading edge of the dolly. The catch mechanism located on the side of the dolly shall be tripped to allow the dolly to move up the incline at a 10° angle. Once the dolly hits the automatic trip mechanism, the dolly will freely roll down the incline at a distance of 1219 mm and impact the back stop. This procedure shall be performed on 5 sides of the cabinet, excluding the top of the pack. The carton shall have failed the test if there is

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

visual, structural or functional damage to the unit.

4.4.14 Shipping Vibration Test. The test equipment shall comply with ASTM D-999. 1) A complete fully assembled unit shall be submitted for test. Prior to cartoning the unit shall be inspected for visual and functional damage. The packaged product shall be placed on the vibration platform in its normal shipping position. Set the vibration frequency at a minimum speed sufficient to cause the packaged product to leave the platform ~~momentarily so that a 1.6 mm shim may be inserted at least 100 mm~~ between the packaged product and the surface of the platform. Vibrate the packaged product for a total of one hour. A single 90° horizontal rotation should be accomplished after the first one half hour of vibration, (if the size of the product makes a 90° rotation impractical, a 180° horizontal rotation is permissible. 2) Place the packaged product on the platform in its normal shipping position. Follow the same procedure as section 1. 3) Using the same vibration frequency, vibrate the packaged product for one half hour on all sides except the top (two and one half hours total). Inspect the carton for visual, structural or functional damage. Remove the product from the carton and inspect it for visual, structural or functional damage to the unit.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Unless otherwise (see 6.2) specified, preservation and packaging shall be in accordance with the manufacturer's standard practice and meet the requirements in 4.4.13 and 4.4.14.

5.2 Packing. Unless otherwise specified (see 6.2), files, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Containers shall be in accordance with Uniform Freight Classification Rules and Regulations of other carriers applicable to the mode of transportation

5.2.1 File accessories. Accessories shall be secured to prevent movement within the pack and to prevent the accessories from damaging the files or the pack

5.3 Marking.

5.3.1 Civilian agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Federal Standard No. 123 and as specified in 5.3.3.

5.3.2 Military requirements. In addition to any special

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:41Z
Check the source to verify that this is the currentversion before use.

marking required by the contract or order, shipping containers shall be marked in accordance w3 1, 4dditional marking. In addition to the marking specified herein, arrows or prominent marks shall be placed on all 4 sides of each shipping container to indicate the position in which the container shall be handled during shipment. The word "UP" shall be placed at the point of the arrows in letters at least 50 mm in height on all four sides. The side panels of each shipping container shall be plainly marked as follows:

UP
FURNITURE
FRAGILE, HANDLE WITH CARE

6. NOTES

6.1 Intended use. The files covered by this document are intended to be used for heavy duty filing.

6.2 Ordering data. Purchasers should exercise any desired options offered herein and the procurement documents should specify the following information:

(a) Title, number, and date of this document.
(b) Type, Group, Class, Style, and Size of the files and accessories required.
(c) First Article sample is not required (see 3.1).
(d) The color desired.
(e) Level of packaging and packing and type of marking required (see section 5).

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the currentversion before use.