AMENDMENT TO INTERIM FEDERAL SPECIFICATION

FURNITURE, CONTEMPORARY, OAK (GENERAL SPECIFICATION)

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information The General Services Administration August 23, 1977

Page 3

Paragraph 3.2.2 Plastic laminate Line 5, delete "0 050" insert "0 030"

Page 4

Paragraph 3 2.8 Dowels Under "Dowel Diameter" delete "chuck dowel" under "Application" delete "chuck"

Page 8

Paragraph 3 3 5 Edging Delete entire paragraph Insert new paragraph "3 3 5 Edging Edges and corners of the case pieces shall be eased approximately 1/16 inch All edges of exterior frames of tables, beds, mirrors, desk and vanity legs, and top edges of drawer bodies shall have a 1/4 inch radius profile Except for the Type V side chair, the two outer edges of each seating piece A frame shall be profiled with a 1/4 inch radius The side frames of the Type V side chair shall have a 1/4 inch radius profile only on the edge which is exterior to the chair All other edges of seating pieces shall be eased approximately 1/16 inch to prevent sharp edges and splinters

4 3 2 Inspection of end item Line 2 after "assembled units " insert "except for the Types VII, VIII, and IX which shall be in knockdown condition prior to inspection "

4 3 3 Inspection levels and acceptable levels (AQL's) Table IV under "For examination in' add new paragraph number "4 3 7" "Inspection level" add new inspection level "I" Under "Major' add "2" Under "Total" add "6"

Page 15

Add new paragraph "4.3 7 Examination of knockdown construction and assembly An examination shall be made to determine if the Type VII, VIII, and IX units are constructed as specified in 3 1 4 and 3 1 4 1 of AA-F-001873/1a (GSA-FSS) Defects shall be scored as specified in Table VIII The sample units shall be those selected for examination in 4 3 3 herein The lot size shall be those selected for examination in 4 3 3 herein The lot size shall be the number of containers in the inspection lot (see 4 3 3 herein) The selected units shall be assembled according to the assembly instructions with the exception that one A frame, a seat and two back rails from another package shall be used in assembly of each unit The manufacturer shall supply all those tools needed for the assembly of the items The examination of the knockdown construction and assembly shall be conducted first and the units shall then be examined as specified in 4 3 4, and 4 3 5 herein "

TABLE VIII Knockdown construction and assembly defects

Examine	Defect	Classification Major	Minor
Prebored holes	Not present where specified	X	
	Do not align with holes in mating parts	X	
K-D fasteners	Do not align with prebored holes	X	
	Not flush as specified		X
	Not dimension specified		X
	Capped nut bottoms out on hanger bolt, joint not tightenable	X	
	Not number specified		X
	Not packed as specified		X
	Gap in K-D joint counterbore exceeds that specified		X

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE VIII Knockdown construction and assembly defects (cont'd)

Examine	Defect	Classification	
		Major	Minor
T nuts	Not secure in hole-pushed out during assembly	X	
Other fasteners	Not packed as specified		X
	Not number specified	X	
Assembly	Requires tools other than those specified	X	
Instruction sheet	Not present	X	
	Not packed as specified		X
Assembled unit	Not rigid-joints loose	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.