AA-F-001873/1A(GSA-FSS)
AMENDMENT-1
November 9, 1978

AMENDMENT TO INTERIM FEDERAL SPECIFICATION

FURNITURE, CONTEMPORARY OAK SEATING PIECES (DETAILED SPECIFICATION)

This amendment was developed by the General Services Administration Federal Supply Service, Washington, DC 20406, based upon currently available technical information The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification AA-F-001873/1A(GSA-FSS) dated August 23, 1977

Page 1

1 2 Classification At end of type listing add the following

"Type VII - Chair, lounge, with arms, upholstered seat and back Same as Type I except with knockdown construction

Type VIII - Sofa, two seat, with arms, upholstered seat and back Same as Type II except with knockdown construction

Type IX - Sofa, three seat, with arms, upholstered seat and back Same as Type III except with knockdown construction"

Page 3

Add new paragraph

"3 14 Construction of the Type VII Chair, Type VIII Sofa, and Type IX Sofa The construction of these items shall be identical to that of the Type I Chair, Type II Sofa and Type III Sofa respectively with the following exceptions They shall utilize knockdown construction to the extent that the back, seat A frame, and cross rails (upperback rail lower back rail and front rail) are disassembled from each other when packaged When set up the A frames and the cross rails shall be joined by knockdown fasteners as specified in 3 14 1 The other fastenings required to fully assemble the seating pieces shall be the same as required for the Type I, II, and III units except that the loose hardware shall be packed in the same bags as the KD hardware The cross rails shall have a minimum of two, three inch long hanger bolts inserted in each end The hanger bolts shall correspond to holes bored and counterbored in the A frames When the capped nuts (see 3 14 1) are fully tightened they shall seat flush, minus 1/64 No more than 1/64 inch of the edge of the counterbore shall be visible The gap between the capped nut and the edge of the counterbore shall not exceed 1/64 inch All lead and thru holes for wood screws and thru holes for machine screws shall be pre-bored in such a way that all seating pieces in a lot shall have interchangeable parts All T-nuts shall be inserted in the back rail of the seat frame to ensure that they do not fall out during shipment and assembly All hanger bolts and counterbored holes for K-D fasteners shall be positioned so that all chairs in a lot shall have interchangeable parts The only tools needed for assembly shall be a power screwdriver, a ratchet wrench, and a hex wrench An instruction sheet shall be prepared with simple illustrated assembly directions The instruction sheet shall list all tools necessary for assembly The instruction sheet shall stress that power screwdrivers are essential when assembling the seat-back assembly to the cross rails It shall be available for use and approval at the time of the preproduction inspection The approved assembly instruction sheet shall be packed with each unit and placed in the package with the hardware

Add new paragraph

3 14 1 Knockdown fastener The knockdown fastener shall consist of a 3 inch 1/4-20 hanger bolt and a 1/4-20 flat head capped nut The nut shall have a hex broach to accommodate a 1/8 inch hex wrench The nut shall have a cap .110 inch thick and .625 inch wide The overall length of the nut shall be .725 inch The outside diameter of the threaded barrel of the nut shall be .34 inch Commercial tolerances shall apply to the dimensions of the capped nut The capped nuts shall have a dark finish which is compatible with the finish of the wood grain. All fasteners not permanently attached to the subunits at time of packing shall be packed in a clear polyethylene bag An 1/8 inch hex wrench for each chair shall be placed in the hardware bag One extra fastener of each type required shall be placed in the hardware bag "

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

5 2 Packing Add new sentence to end of paragraph "All knockdown parts for an individual Type VII, VIII and IX seating unit shall be packed in one container " Two complete Type VII units may be packed in a single container

Add new paragraph

6 6 Sources of supply The following manufacturer/distributers are known sources of supply for the item indicated

3 14 1 Knockdown fastener

Goe Engineering
City of Industry, CA

Most screw manufacturers with a screw machine will be able to manufacture this product as a special item

Page 8 and 9

Figures 4 and 5 Note B add the end of note "Upper back rail shall be positioned 1/4 inch from rear edge of the rear leg in lieu of 1/8 inch as indicated in the Figure "

Page 16

Figure 8, change "15-1/8 inches" to "15 5/8 inches"

Page 20

Figure 12, Type V Side Chair, Note F, delete "x 3/4 inch chuck"

Figure 12 Type V Side Chair delete "1/4 inch" dimension indicating distance rails are recessed from edge of legs Insert '3/8 inch'

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.