AA-0-001628(GSA-FSS)
AMENDMENT-1
June 14, 1974

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

CHAIRS, WOOD, GENERAL OFFICE

This amendment was developed by the Federal Supply Service, General Services Administration, Washington, D. C., 20406, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a part of Interim Federal Specification AA-0-001628(GSA-FSS), dated September 1, 1971.

PAGE 2

Paragraph 2.2 Other publications.

Commercial Standards: Delete "CS 35 - Hardwood Plywood", and substitute the following:
"PS-51 - Hardwood and Decorative Plywood.
PS-13 - Uncored Slab Urethane Foam for Bedding and Furniture Cushioning."

American Society for Testing and Materials (ASTM) Standards: Add the following citation after "ASTM D-905-49":

"ASTM D-1564-71 - Testing Slab Flexible Urethane Foam."

PAGE 3

Paragraph 3.2.1 Adhesives. Table I, second column, line 9, delete "Commercial Standard CS 35 for Hardwood Plywood" and substitute "Product Standard PS 51 for Hardwood and Decorative Plywood".

Paragraph 3.2.2 Wood. Table II, first column, line 10, delete "Philippine hardwood 2/" and line 13, delete "2/ Red luan group only."

Paragraph 3.2.2.2 Plywood. Delete entire paragraph and substitute the following:

3.2.2.2 Plywood. Plywood shall be hardwood plywood, veneer core construction conforming to the requirements of Product Standard PS 51 for Hardwood and Decorative Plywood."

PAGE 4

Paragraph 3.2.7 Glides. Line 4, delete "7/8" and substitute "3/4".

Paragraph 3.2.9 Rotary mechanism. Delete entire paragraph and substitute:

"3.2.9 Rotary mechanism. All type II chairs shall have a suitable metal rotary mechanism having four contact points (spider or plate) for attaching to the underside frame of the seat frame, a spiral spring tension adjustment or a rubber torsion unit adjustment for back tilt, and a positive stop to prevent the seat from going over backwards should there be any failure of the tilt mechanism, and an adjustment for height of seat over a range of not less than 2 inches. In addition to the above requirements, the type II, Style A chairs shall have a positive adjustment for height of back independent of the seat and an adjustment for pitch of the back. The material used shall be free from rough surfaces, rust, and other defects which may affect the safety of the user, the durability, serviceability, or appearance of the finish mechanisms. Adjustments for tilting shall be by means of a suitable hand wheel conveniently located at the front of the chair swivel and tilt mechanism. Adjustment for raising shall be by means of a suitable hand wheel located concentrically on the pivotal axis of the chair and shall be self-locking and permit swiveling."

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

Paragraph 3.2.11.2 Polyurethane. Delete entire paragraph and substitute the following:

"3.2.11.2 Polyurethane foam. The prime urethane foam shall not contain any filler material and shall be grade USU 34 for the chair backs and grade USU 44 for the chair seats as defined in PS 13, Uncored Slab Urethane and shall conform to the requirements of Table IX when tested as specified in the applicable sections of ASTM D-1564-71. The urethane foam shall be slab stock and of sufficient thickness to comply with the requirements specified herein.

TABLE IX. Physical properties of urethane foam

Property	Requirement Chair Back	Chair Seat
25 percent Indentation load deflection; lbs.	34 ± 3	44 ± 4
Indentation load ratio (65 percent/25 percent); minimum	1.9	1.9
Compression set 22 hours/158 degrees F., 90 percent deflection, percent max.		
Steam autoclave test (condition B)		
Percent change in 25 percent comp. load deflect; percent maximum.	-20%	-20%
Comp. set 22 hour/158 degrees F., 90 percent deflect; percent max.	20%	20%
Fatigue test		
25 percent indentation load ratio loss; percent max.	25%	25%
Thickness loss percent max.	5%	5%
Rebound Resilience	45%	45%
Prime Urethane Density, pounds/cu. ft.	2.2 ± .2	3.0 ± .3

NOTE: The preceding physical properties are based upon the use of a 4 inch thick test slab.

PAGE 5

Paragraph 3.3.2 Dimensions.

Table III - Column Type II Style A
Height - change "30-1/2 - 31-1/2" to "29-3/4 - 31-1/2"
Seat height - change "17" to "16-1/4"

Paragraph 3.3.3 Joinery. Line 7, delete sentence beginning "Corner blocks" and substitute "Corner blocks shall be fitted carefully, glued and screwed by not less than two screws in each side. They shall be not less than one inch thick and 1/16 to 1/8 inch less in height than the width of the smaller of the rails being joined, at the point of joining."

Line 9, after "two screws in each side" add, "When curved seat pans are used, the corner blocks shall fit close to seat pan and may be 1/4 inch less in height than the side rails."

Line 10 and 11, delete the last two sentences and substitute "The seat shall have a pitch of 2 to 4 degrees and the back pitch (from the vertical) shall be 10 to 12 degrees with an included angle between seat and back of not less than 97 degrees."

PAGE 6

Paragraph 3.3.4.3 Seat. Delete the last sentence in subparagraph (a) and substitute "A 2-inch layer of polyurethane shall be glued to the plywood pan, followed by a layer of polyester fiberfill batting sewn between cheesecloth or alternatively, non-woven synthetic fabric weighing not more than 1.2 ounces per square yard and then the final upholstery fabric cover. The front edge of the plywood pan shall be protected by polyurethane foam. Welts are not required on the seat."

Paragraph 3.3.4.3, subparagraph (b), add the following to the end of the subparagraph: "Welts are not required on the seat."

Source: https://assist.dla.mil -- Downloaded: 20260-26T11:41Z
Check the source to verify that this is the current version before use.

Paragraph 3.3.5.5 Seat, Style A. Delete the last sentence in subparagraph (a) and substitute "A 2-inch layer of urethane shall be glued to the plywood pan, followed by a layer of polyester fiberfill batting sewn between cheesecloth or alternatively, non-woven synthetic fabric weighing not more than 1.2 ounces per square yard and then the final upholstery fabric cover. The front edge of the plywood pan shall be protected by polyurethane foam. Welts are not required on the seat."

Paragraph 3.3.5.5, subparagraph (b), add the following to the end of the subparagraph: "Welts are not required on the seat."

Paragraph 3.3.5.7 Back assembly. Delete the paragraph in its entirety and substitute the following:

"3.3.5.7 Back assembly. The completed back shall be fastened to two tapered hardwood posts made from one piece or built-up stock. Each post shall extend from the backplate of the rotary mechanism to a point approximately two thirds up the back rest. The post shall be 7/8 inch minimum thick, 2-1/2 inches minimum wide at the seat, tapering uniformly to a 2 inch width at the top. Alternatively, the post may be 2-1/2 inches minimum at the point of attachment to the back plate, then shaped to approximately 1-3/4 inches wide and uniformly tapered to 1-5/16 inches at the top. The posts shall be secured to the back plate of the rotary mechanism by bolts with lockwashers and nuts and screws. The back shall be secured to the posts by side hinges to provide proper support. There shall be a cross back rail between the posts located so that its top surface is approximately 1/4 inch below the top of the posts. Rail shall be 7/8 inch (minimum) thick and 2-1/4 inches wide, and shall be double-doweled to the posts."

PAGE 7

Paragraph 3.3.5.8 Base. Line 2, after "Figure" add "2".

PAGE 14

Delete section 5 in its entirety and substitute the following:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. All surfaces of the chair that come in contact with the shipping container shall be cushioned. The cushioning shall be in the form of pads, not less than 1/4 inch in thickness, extending not less than two inches above, below and to each side from the point of contact and secured in place with tape or twine.

The cushioning may be any of the following:

Macerated paper	Creped cellulose wadding
Wood wool packing	Polypropylene foam conforming to
Wood fiber felt	PPP-C-1797

Alternatively, the chair shall be blocked and braced in the container to insure a minimum of 1 inch clearance between the chair and the inside of the shipping container. The cushioned or blocked and braced chair shall be completely covered with kraft paper, 30 pounds basis weight (24" x 36' x 500) or with a plastic film not less than 2 mils in thickness.

5.1.1.1 Casters. The casters shall be removed from the chairs and placed in a single bag. The bag shall be a cotton drawstring type or heat sealed polyethylene type, and shall be secured to the rotary base assembly to preclude movement or damage during shipment and storage. Alternatively, the chair with casters attached shall be suspended on a wood or fiberboard suspension system that will maintain a minimum 1-1/2 inch clearance between the bottom edge of the casters and the closet points on the inside surface of the bottom of the shipping container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. The chairs shall be packaged as specified in 5.1.1 and 5.1.1.1.

5.1.3 Level C. The chairs shall be packaged in accordance with the manufacturer's standard commercial practice provided that this will insure protection during shipment and safe delivery at destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Type I, style A & B chairs. Each chair, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, grade V13c, style RSC. The box shall be provided with a bottom pad made of fiberboard conforming to PPP-F-320, grade V13c. The pad shall be of equal length and width of the box. The box shall be closed, sealed and reinforced in accordance with the appendix to the box specification.

5.2.1.2 Type II, style A & B chairs. Each chair, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, grade V13c, style RSC. The box shall be provided with a bottom pad made of fiberboard conforming to PPP-F-320, grade V13c. The pad shall be of equal length and width as the inside length and width of the box except when the casters are assembled to the chair and the chair is suspended off the bottom of the box as specified in 5.1.1.1, the bottom pad may be omitted. The box shall be closed, sealed and reinforced in accordance with the appendix to the box specification.

5.2.2 Level B.

5.2.2.1 Type I, style A & B chairs. Each chair, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, class domestic, type CF, variety DW, grade 275 minimum except when the gross weight exceeds 65 pounds, the box shall conform to PPP-B-636, class domestic, type CF, variety DW, grade 350 minimum. The box shall be provided with a bottom pad made of the same fiberboard as the box. The pad shall be of equal length and width as the inside length and width of the box. The box shall be closed and reinforced in accordance with the appendix to the box specification.

5.2.2.2 Type II, style A & B chairs. Each chair, packaged as specified in 5.1, shall be packed in a close-fitting box conforming to PPP-B-636, class domestic, type CF, variety DW, grade 275 minimum except when the gross weight exceeds 65 pounds, the box shall conform to PPP-B-636, class domestic, type CF, variety DW, grade 350 minimum. The box shall be provided with a bottom pad of equal length and width as the inside length and width of the box except when the casters are assembled to the chair and the chair is suspended off the bottom of the box as specified in 5.1.1.1, the bottom pad may be omitted. The box shall be closed and reinforced in accordance with the appendix to the box specification.

5.2.3 Level C. Chairs packaged as specified in 5.1.3, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification or the National Motor Freight Classification.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to the markings required by 5.3.3, the shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to the special markings required by 5.3.3, the shipping containers shall be marked in accordance with MIL-STD-129.

5.3.3 Special marking. In addition to the markings required by 5.3.1 or 5.3.2, the front and back panels of each shipping container shall be marked in each upper corner with the word "UP" and an arrow pointing to the direction in which the container should be shipped and stored. "UP" shall be in characters a minimum of 2 inches high. Additionally, the top and one side and one end of the container shall be marked as follows in characters a minimum of two inches high. Top of container:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TOP
THIS SIDE UP
FURNITURE, FRAGILE-HANDLE WITH CARE

One side and one end of container:

FURNITURE
FRAGILE-HANDLE WITH CARE

PAGE 15

Paragraph 6.2, line (d), delete "3.3.6.1" and substitute "3.4.2".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.