INTERIM FEDERAL SPECIFICATION

OFFICE FURNITURE: EXECUTIVE, CONTEMPORARY FULL PANEL

GENERAL SPECIFICATION

This Interim Federal Specification was developed by the National Furniture Center, Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification describes the GENERAL requirements for executive, contemporary full panel office furniture. The items are of all wood construction. Specific requirements, figures, drawings, and other information pertaining to any individual piece of furniture in this group, will be found in the applicable DETAILED specification. A complete index of the paragraph numbers and titles herein will be found on the last page of each DETAILED specification.

1.2 Classification. The types and sizes of the furniture covered by this specification shall be as specified in the applicable DETAILED specifications, AA-0-1959/1 through AA-0-1959/3 as follows:

/1 - Desks, Desk Attachments, Executive Contemporary full panel
/2 - Credenza, Executive Contemporary full panel
/3 - Tables, Conference and Occasional, Executive Contemporary full panel

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on the date of Invitation For Bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications

P-W-158 - Wax, General-Purpose, Solvent-Type
TT-F-336 - Filler, Wood Paste
TT-L-57 - Lacquer, Rubbing, Clear (for Wood Furniture)
TT-S-720 - Stain: Wood, Nongrain Raising, Solvent-Dye Type

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402 .

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, Handbooks, and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes.
MIL-STD-1363 - Measurement of Wood Moisture Content.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of Invitation For Bids or request for proposal shall apply.

American Society for Testing and Materials (ASTM) Standards:

D-905 - Standard Method of Test for Strength Properties of Adhesives in Shear by Compression Loading.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

U.S. Department of Commerce (CS) Publications:

Commercial Standard CS-236	- Mat-Formed Particleboard.
Product Standard PS-51	- Hardwood and Decorative Plywood.

(Copies of the Commercial Standards and Product Standards referenced above, which are Department of Commerce Publications, may be obtained upon application, accompanied by money order, coupon, or cash, to the Superintendent of Documents, Government Printing Office, Washington, DC. Prices may be obtained from the Superintendent of Documents.)

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Traffic Department 1616 P. Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Preproduction sample. A sample of each finished commodity and each kind of accessory on contract and each component part thereof shall be submitted or made ready for the contracting officer or his authorized representative to examine and test to determine compliance with this document. Approval of the preproduction sample authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all other provisions of the document. Production units shall not vary from the approved preproduction sample in design or construction without written approval of the contracting officer.

3.2 Material. All materials used shall be as hereinafter specified. They shall be free from defects which affect serviceability or appearance of the finished product.

3.2.1 Adhesives. Adhesives used in the construction of the furniture and their permitted application shall be as shown in Table I.

TABLE I. Adhesives

Application	Kind Adhesives
All glue blocks, assembly joints, glued laminated stock, and edge joining of lumber-core panels.	Any adhesive that will develop an average block shear strength of not less than 2800 pounds per square inch when tested as specified in 4.5.2 herein. For assembly joints the adhesive will conform to or exceed the test requirements of the Type II bond, as described in the Product Standard PS-51 for Hardwood Plywood.
All plywood gluing, edge-joining of veneer plies, cross-banding, and edge banding, and plastic laminating.	Any adhesive that will conform to or exceed the test requirements of the Type II bond, as described in the Product Standard PS-51 for Hardwood Plywood.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.2.2 Particleboard. The particleboard shall be in accordance with any of the following types, grades, and classes in CS-236:

Type I, grade A (high density), class 1.

Type I, grade B (medium density), class 2, except that panels less than one inch thick shall have a minimum average screw holding capacity of 235 pounds on the faces and edges.

Type II, grade A (high density), class 2.

The thickness of the particleboard shall be as hereafter specified. The moisture content of the particleboard shall not exceed 9 percent at time of laminating.

3.2.3 Wood.

3.2.3.1 Wood Varieties and parts. Wood parts including solid wood and veneers shall be of the kind of wood listed in Table II and of the quality hereinafter specified. Exposed parts include all parts and surfaces of each item of furniture which are exposed in their normal use position. All exposed woods on one piece shall be of same species.

TABLE II. Varieties of Wood

Face Veneer	Exposed Solid Parts	Unexposed Solid and Plywood Parts	
White Oak	White Oak	Poplar	Magnolia
Walnut	Walnut	Sweetgum	Oak
		Maple	Pecan
		Mahogany	Red Alder
		Walnut	Ash
		Andiroba	
		Beech	
		Birch	
		Cherry	
		Hackberry	

3.2.3.2 Characteristics. The wood used on the exposed surfaces shall be bright, well sanded, and free from brashness, discoloration, worm holes, splits, shakes, or other defects as indicated in 3.2.3.5 herein. The wood used on the unexposed parts of the furniture may contain defects as indicated in 3.2.3.6 herein.

3.2.3.3 Veneers.

3.2.3.3.1 Species. The species of the surface veneers shall be narrow-heart flat-cut white oak with a minimum of sap wood, and quarter cut walnut with a minimum of figure and flaking.

3.2.3.3.2 Matching. Veneer faces shall be book-matched for figure and color, with invisible joints. The veneers shall be carefully selected, and all faces of any one panel or top shall have the same grain patterns. There shall be no patches or other imperfections except that if there are pin-knots, there shall be no more than two on any 36 inches of length of the piece. The grain pattern of the drawer fronts on any one pedestal shall be continuous. The grain pattern on the drawer fronts of double pedestal desks shall be matched. All face veneers shall be edge-glued before application.

3.2.3.4 Seasoning. All wood shall be uniformly kiln-dried to a moisture content of from 5 to 8 percent as determined by MIL-STD-1363 dependent upon the manufacturer's best commercial practice. After kiln-drying it shall be held in properly controlled warm, dry storage for a sufficient period of time to insure a uniform distribution of moisture among the individual pieces. After gluing, lumber cores shall be permitted to cure out or conditioned to insure a uniform distribution of glue joint moisture and the elimination of sunken joints, spring back, and stresses that impair serviceability or finished appearance, before planing and sanding for crossbanding.

3.2.3.5 Solid exterior parts. All solid exposed parts shall be free of defects which impair appearance or which might impair serviceability except as follows:

(a) Sound, tight knots of not over 1/8 inch in average diameter provided they are not in clusters.

(b) Figured grain or discoloration provided the wood is such as to permit a uniform color when finished.

Source: https://assist.dla.mil -- Downloaded: 202640-26T11:41Z
Check the source to verify that this is the current version before use.

3.2.3.6 Solid interior parts. Wood shall be free from defects which might impair serviceability or appearance except as follows:

(a) Sound, tight knots of not over 1/2 inch in average diameter provided they are not in clusters.

(b) Holes not over 1/16 inch in diameter.

(c) Surface checks with barely perceptible openings not over 3 inches long.

(d) Bark, gum or pitch pockets not over 1/8 inch wide and 2 inches long, except drawer parts exposed when open.

3.2.3.7 Hardwood plywood. The hardwood plywood shall be a minimum of 5 plies and shall be constructed according to the requirements of PS-51 and as specified herein. Bondage shall be Type II or better. Face and back veneers shall be not less than 1/28 inch thick with exception of walnut which shall be 1/36 inch thick before sanding and when face and back veneers are not of the same species, the two veneers shall be of the same density and thickness. Face veneers shall be of the wood specified in Table II and shall be grade 1 (good). All face veneers in one panel shall be matched for color and grain to present a uniform appearance. The above requirements shall apply to all paneled surfaces viewed in normal use position and in addition, shall apply to exposed faces and backs of modesty panels, inside face of exposed back panel, door panels, top side of shelves, and the interior of various other visible compartments and surfaces. Crossbands shall be not less than 1/24 inch thick and shall be grade 2 or better under grade 1 veneers and grade 3 or better under grade 2 veneers. Veneers cores shall be grade 3 or better and any voids at panel edges shall be filled. Particleboard cores shall be as specified in 3.2.2 herein. The entire exposed edge of the core shall be self-edged or banded with the same kind of wood as other exposed parts. Lumber core panels shall be regular grade except that no butt joints or knots in excess of 1/2 inch diameter will be permitted. All knots will be filled prior to the application of the veneer. Crossbands, veneer cores, and lumber cores shall be of medium or low density wood as defined in PS-51. At time of assembly, the moisture content shall be from 5 to 9 percent.

3.2.4 Finishing materials.

3.2.4.1 Stain. Stain shall conform to TT-S-270.

3.2.4.2 Filler, wood paste. The lacquer shall conform to TT-F-336.

3.2.4.3 Lacquer, spray, clear. The lacquer shall conform to Type I or II, TT-L-57.

3.2.4.4 Wax. The wax or polish shall conform to Type I or II, P-W-158.

3.2.5 Hardware.

3.2.5.1 Screws. The screws used in the assembly of the furniture items shall be according to the manufacturer's best practices and shall be of the size and kind to insure the level of quality intended by this specification.

3.2.5.2 Door catches. The catches used on the doors shall be magnetic, molded plastic, self-alignment type, which have a commercial release rating of 6 to 8 pounds. The color shall be dark brown or black.

3.2.5.3 Hinges. The hinges used on doors shall be semi-invisible knife hinges of not less than 0.083 inches thick material. The hinge shall be secured by not less than 6 flathead screws, and shall have a statuary bronze finish. The hinge used on the stationery pedestal door shall be a 270^0 opening type.

3.2.5.4 Glides. The glides shall be adjustable leveling glides of not less than 3/4 inch adjustment, capable of adjustment by hand, without the use of any tools. The glide base will be of high impact ABS black plastic, and shall be a minimum of 1-1/16 inch in diameter. All metal surfaces of the glides shall be made corrosion resistant by plating, in accordance with glide manufacturer's commercial practice for high quality glides. The receptacle for the glides shall be a threaded insert imbedded or screwed into the base of the panel and shall allow the glide to be adjusted to 3/4" from its retractable position.

3.2.5.5 Locks. The file drawers in all single and double pedestal desks and desk attachments shall have a statuary bronze finish, flush mounted, 4 pin tumbler lock of die cast zinc or brass, operated by a paracentric key. Each lock on any order up to 100 units shall be of a different key change, with no key opening more than one of the one hundred or less locks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.2.5.6 Drawer suspensions. All drawer suspensions shall be a precision ball telescoping type. Slide members and ball retainers shall be C.R.S (cold rolled steel) zinc plated. Balls shall be nickel plated, carburized steel, or polished and hardened steel captively held in ball retainer. Slides shall have a progressive movement such that the intermediate member moves at 1/2 the speed of the moving member. Movement shall be a smooth and even telescoping action. Slides shall have a positive stop in the opened and closed positions. In-stops shall incorporate a sound dampening feature and shall prevent metal-to-metal contact between the suspensions and the pedestal or drawers. Out-stops shall have a sound dampening feature, which may be a metal spring securely held in the suspension raceway to provide sound dampening. Suspension shall be lubricated with a high-low temperature grade lubricant sufficient for the normal life of the slide. The drawer will open to within a maximum of 2 inches of its full extension.

3.2.5.7 Attachment bracket. The attachment brackets for attaching the desks to the desk attachment shall be constructed as shown in Figures 7, 8 and 9. They shall be constructed of not less than 14 gauge (0.075 steel) and shall be secured as shown in the figures by the use of threaded inserts with attaching screws (1/4 - 20, truss HD by 5/8" long). The finish color shall be dark brown or black.

3.3 Construction. The construction requirements specified herein are minimum. The contractor will exceed these requirements (without altering the general configuration, basic design concept or primary construction specified or illustrated herein) wherever necessary to assure the high level of quality intended. Any detail not specified herein shall be consistent with good quality production of similar commercial products. All elements of construction shall be free of any conditions which hinder the proper function of any part of the unit or which constitute a potential hazard to personnel or their clothing.

3.3.1 Design. The design of the furniture shall be full panel contemporary design as shown in the figures of the detailed specifications.

3.3.2 Tolerances and dimensions.

3.3.2.1 Tolerances. Unless otherwise specified, the following tolerances are permissible:

(a)	Dimensions of any solid wood part	- plus or minus 1/16 inch.
(b)	Dimensions of any plywood part	- plus 1/16 inch, minus 1/32 inch.
(c)	Any overall dimension	- plus or minus 1/8 inch.
(d)	All flush conditions specified	- plus 0, minus 1/16 inch.

3.3.2.2 Dimensions. All overall dimensions shall be as specified in 1.2.1 of the Detailed Specification. Height for the various dimensions shall be measured without glides. Other dimensions shall be as specified in the applicable paragraphs.

3.3.3 Gluing. All joints shall be milled true and even and all structural joints shall be thoroughly glued and held under proper pressure until the glue has set sufficiently to handle. Nails, brads or staples will not be permitted on the outside and shall not be used to hold glue joints. Excess glue shall be neatly cleaned from exposed surfaces. Clamp nails shall not be used.

3.3.4 Joining and assembly. Unless otherwise specified all joints shall be splined, mortised-and-tenoned, tongue-and-grooved, or doweled, with a sufficient quantity of the glue specified in 3.2.1 herein applied to the joint which shall be held under pressure until the glue has set. Starved or insufficiently glued joints will not be acceptable. The joining of all components covered by this specification shall result in compact units of sufficient strength to prevent distortion, breakage, or loosening of any part of the units during rough handling when shipping, during heavy daily usage, and when moving the units when loaded from office to office.

3.3.5 Direction of grain. The grain pattern on the tops shall run parallel to the length. The grain pattern on the butt ends, when self-edged, shall run vertical, when banded the grain pattern shall run parallel to the width of the end panel. The grain direction on the end panels, back panels, and drawer and door fronts shall be vertical.

3.3.6 Top panels, end panels, and back panels. All panels shall be self-edged or banded as specified in the detailed specifications. All panels shall be of either particleboard core as specified in 3.2.2, overlaid with veneer as specified in 3.3.5 and Table II, or lumber core plywood, a minimum of 5 ply, as specified in 3.2.3.7 and Table II herein. All veneer plies shall be in full length pieces and shall be applied in a balanced construction form. All exposed edges, of the panels shall be self-edged veneered or banded with 1/4 inch solid wood. Edging and banding shall be of the same species used for the face veneers. All full panels and desk and desk attachment back panels shall be face veneered on two sides. The end panels shall have provisions for two adjustable glides as specified in 3.2.5.4 herein. The panel thickness, including the tops, shall be as indicated in Table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE III. - Minimum panel thickness (including drawer and door fronts)

Panel	1-1/4"	3/4"	1/2"
Desk, desk attachment, and credenza tops	X		
Desk, desk attachment, and credenza side panels	X		
Desk attachment back panel	X		
Desk, back panels		X	
Desk and desk attachment pedestal units		X	
Drawer and door fronts		X	
Credenza sectional inserts			X

3.3.7 Drawer and door fronts. Drawer and door fronts shall be constructed as specified in 3.3.5, 3.3.6, 3.3.8 and Table III of the General Specification. All exposed edges, including the bottom shall be banded or self-edged as specified in 3.3.6 herein. The drawer and door fronts shall have concealed shaped self-pulls of 1/2 inch radius as follows:

Storage drawer	- Continuous both sides.
File drawer	- Continuous both sides and minimum 5 inch center in bottom edge.
Door front, secretarial	- Minimum 5 inch self pull, centered on botton edge of the door.
Door front, credenza insert	- Continuous on the opening edge of the door and in addition a minimum 5 inch self-pull centered on the bottom edge.

3.3.8 Drawers. Drawers shall be constructed with two sides and one back of 1/2 inch minimum thickness solid oak. The drawer sides shall be dovetailed and glued to the drawer back and shall be French dovetailed and glued to the drawer front as specified in 3.3.3 herein. The dovetails shall be machined true and even. Any open, poorly milled, glued, or unevenly assembled dovetails shall not be acceptable. The drawer bottoms shall be constructed of minimum 3 ply 3/16 inch thickness oak plywood as specified in 3.2.3.7 herein. The sides, back and front shall be grooved to receive the drawer bottom. The drawer bottom shall be reinforced with at least 6 rubbed-in-place glue blocks or staples and hot melt glue. Drawer sizes shall be as specified in the applicable detailed specification. The drawer fronts shall fit square in the pedestal, the sides shall be parallel with the end panel and the top and bottom of the fronts shall be parallel with the top of the unit. Each side of the storage drawers shall have 3 vertical grooves 3/16 inch deep cut at 4 inch, 8 inch, and 12 inch increments from the inside of the drawer front to allow for the insertion of dividers. Each storage drawer shall be provided with two adjustable dividers 3/16 inch minimum 3 ply oak plywood specified in 3.2.3.7 herein. Steel bars to accommodate hanging folders shall be furnished with the file drawers to accomplish the filing arrangement specified in the detailed specifications. In addition each desk file drawer shall have a 3/16 inch deep groove in each side located 13-1/2 inches from the inside of the drawer front to allow for the insertion of a partition. The drawer partition shall be constructed from 3/16 inch minimum 3 ply oak plywood specified in 3.2.3.7 herein.

3.3.9 Convenience tray. A removable oak convenience tray, having three compartments, with sufficient capacity to hold the normal use miscellaneous items such as pencils, paper clips, etc., shall be furnished in one storage drawer in each desk.

3.3.10 Reveal strips. All items, except the Type IV desk attachment, shall have a reveal strip securely attached to the underside of the top. The reveal strip shall be secured on the underneath front, back, and two sides and shall be recessed 1/16" from flush to the top edges. The strip shall be a minimum of 1-1/8" wide by 3/16" thick and shall be mitered at all four corners. The strip shall be constructed of firm semi-gloss black plastic material.

3.3.11 Panel base trim. A base trim shall be securely attached to the bottom of all end panels and to the back panels of the desk attachments. The material for the trim shall be identical to the material used in the reveal strip as specified in 3.3.10 herein, and shall be attached to the bottom of the panel flush minus 1/16 inch on four sides.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.4 Methods of finishing. The color of the finish shall be walnut or oak as specified. Sample panels will be supplied to the bidder by the procuring officer. All surfaces normally exposed to view shall be finish sanded smooth and all corners and edges eased, thoroughly cleaned, and finished as herein specified. The finish shall match the sample for color and patina and shall meet the test requirements as specified in 4.5 herein. When requesting samples the FSS numbers are FSS W 01005 (Walnut) and FSS W 01006 (Oak).

3.4.1 Procedure for clear wood finish on open pore wood:

1. Sap stain to equalize wood color.
2. Apply selected colorant to wood to produce color specified.
3. Wash coat with adhesive sealer.
4. Scuff sand, using fineness of sandpaper grit needed to produce proper surface.
5. Fill to degree necessary to match sample.
6. Seal with adhesive type sealer.
7. Sand, using fineness of sandpaper grit needed to give proper surface.
8. Shade to tie in color variation, if necessary.
9. Top coat with lacquer.
10. Top coat with lacquer. The lacquer and finish shall be of a quality to meet the requirements specified in 4.4.1 and subparagraphs thereunder.
11. Rub and wax, if required.

NOTE: Operation number 8 may be performed where shown or after operation number 5.

3.4.2 Appearance of finish. The natural grain of the wood shall not be clouded by the finishing materials. Bleaching agents or materials shall not be used. The application of materials, the drying time, sanding, cleaning and rubbing shall be controlled to produce items of smooth, uniform exposed surfaces without blisters, pits, wrinkles, runs, tackiness or more than a trace of orange peel.

3.5 Identification marking. Each item shall be permanently and clearly marked in an inconspicuous place, with the Federal Stock Number, this specification number, the year of manufacture, and the contractor's or manufacturer's name or trademark so that the source of manufacturer may be readily determined.

3.6 Workmanship. The methods of construction, veneering, joining, assembly, and finishing shall be in strict accordance with the minimum requirements of this specification. Each item shall be free from any defects that affect the appearance or that might affect the serviceability for the lifetime of the furniture.

3.7 Conflict of text and drawings. In any case where there is a conflict between the text of the specification and drawings, illustrations, or figures, the text shall prevail.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, (see 6.2 herein), the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Lot acceptance tests. Lot acceptance tests shall be conducted under the supervision of the Government Inspector at the manufacturer's plant. In the event the manufacturer does not have the facilities to perform the required tests, he shall engage the services of a commercial testing laboratory acceptable to the Government. Copies of the laboratory report shall be submitted to the Government inspector upon receipt from the laboratory. All examination and testing shall be in accordance with Section 4 of this specification.

4.3 Sampling for inspection and acceptance. Sampling for inspection and acceptance shall be performed in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

4.4 Inspection (end item).

4.4.1 Visual examination. Examination of the end item(s) shall be in accordance with the classification of defects specified in Table IV and acceptable quality levels (AQL's) specified in 4.4.3 herein. The lot size shall be expressed in the number of complete units for the purpose of determining the sample size in accordance with MIL-STD-105. The sample unit for this examination shall be one complete item.

TABLE IV. Classification of end item defects

Examine	Defects	Classification Major	Classification Minor
Finish and appearance of exposed wood parts visible in normal use position.	Does not match standard reference panel with respect to color, texture, and gloss.	X	
	Discoloration (Bleeding) over 1 square inch.		X
	Spotted, affecting appearance.		X
	Light or dark colored area affecting appearance.	X	
	Area of no lacquer film over 1 square inch in area.	X	
	Glue stain or glue line clearly showing, affecting appearance.		X
	Excess glue not removed.		X
	Finish peeling, flaking, blistered, cracked, checked or wrinkled.	X	
	Finish cut or rubbed through to wood.		X
	Open grain. Finishing material not filling pores.		X
	Orange peel, affecting appearance.		X
	Damage or scratch, less than 1 inch long, or 1 inch square.		X
	Damage or scratch over 1 inch square or 1 inch long.	X	
	Finish tacky, i.e., not completely dry.		X
	Rough or gritty surface or foreign matter imbedded in finish.		X
	Light colored edge not touched up.		X
	Burn-in or repairs not neatly accomplished.		X
	Unstained (white) wood visible when item is in normal use position.		X
	Not polished where required.		X
Finish of exterior wood parts not visible in normal use.	Finish not applied where required.		X
	Stain or sealer coat omitted where required.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of end item defects (con.)

Examine	Defects	Classification Major	Classification Minor
Finish of interior and concealed wood surfaces.	Top edge of drawer front scratched, bruised, or not finished same as exterior wood surfaces.		X
	Stain or sealer coat omitted from bottom edge of drawer.		X
	Opening or top edge of door scratched or bruised, or not finished as the exterior wood surfaces.		X
Quality of solid wood or build-up stock on exposed and unexposed surfaces.	Species of wood not as specified.	X	
	Component not fabricated of one piece solid wood where required.		X
	More than 1 species of wood used for exposed wood components of any one item.		X
	Direction of grain not as specified.	X	
	Check or split over 1 inch in length.	X	
	Wood warped, affecting appearance or serviceability.		X
	Loosened grain or shake on exposed surface.		X
	Loosened grain or shake on unexposed surface.		X
	Honeycomb.		X
	Loose or unsound knot.		X
	Hole on exterior surface, affecting appearance.	X	
	Glue line in built-up stock open over 1 inch in length.		X
	Glued up pieces uneven in built-up stock.		X
	Wave of uneven sanding.		X
	Machine mark on exposed surface, affecting appearance.		X
	Any mineral streak on exposed surface over 1/8 inch by 4 inches or 1/4 inch by 2 inches.		X
	Wood chipped or splintered on exposed surface of drawer interior.		X
	Any manufacturing defect or defect native to the wood filled in with plastic wood or other filler material.	X	
Quality of plywood on unexposed surfaces.	Species of wood not as specified.	X	
	Number of plies not as specified.	X	
	Veneer delaminated.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of end item defects (con.)

Examine	Defects	Classification Major	Minor
Quality of plywood on unexposed surfaces	Any manufacturing defect or defect native to the wood filled with plastic wood or other filler material.		X
Construction, assembly and attachment of unexposed and exposed parts	Not as specified or not as shown on drawings or figures.	X	
	Component not size or shape specified.	X	
	Component not type or design specified.	X	
	Component not assembled as specified.		X
	Component missing.	X	
	Component in wrong location, except attaching implements.	X	
	Component loose or insecurely fastened where rigidity is required.		X
	Component out of alignment or out of square affecting serviceability.		X
	Poor fit of component part or on mating part.		X
	Wood component not glued as specified.		X
	Solid wood used in place of veneer or vice versa.		X
	Wood component damaged or not properly machined.		X
	Edges not "eased off" where required.		X
	Any loose or unsound glued joint.	X	
	Wood joint not as specified.	X	
	Glue joint open over 1/16 inch on exposed part.		X
	Glue joint open over 1/8 inch on unexposed part.		X
	Top panels warped over 1/4 inch in width or length.		X
	Self-pulls on drawer and door fronts not as specified.		X
	Bar for hanging folders not furnished.		X
	Dividers not furnished with storage drawers.		X
	Glides omitted.	X	
	Glides improperly positioned.		X
	Glides not proper size.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE IV. Classification of end item defects (con.)

Examine	Defects	Classification Major	Classification Minor
Identification marking	Missing, incorrect, or illegible.		X
	Text incomplete.		X
	Marking in wrong location.		X

4.4.2 Dimensional examination. Inspection will be made for compliance with dimensions specified. Any dimension not within tolerance specified shall be classified as a defect.

4.4.3 Inspection levels and AQL's. The acceptable quality levels (AQL's) expressed in defects per hundred units, and inspection levels shall be as follows:

	Inspection Levels	AQL's
For examination in Table IV Major	II	4.0
For examination in Table IV Total	II	10.0
For examination in 4.4.2 (1 class)		4.0

4.4.4 Inspection for preparation for delivery requirement.

4.5 Tests.

4.5.1 Test of finish system. The following tests shall be made on panels produced in accordance with the production procedures used in producing the furniture.

4.5.1.1 Working properties. Working properties shall conform to the requirements of 4.3.4 of TT-L-57.

4.5.1.2 Spot test. Spot test shall conform to 4.3.7 of TT-L-57.

4.5.1.3 Alcohol. Alcohol test shall conform to 4.3.7.1 of TT-L-57.

4.5.1.4 Print resistance test. Print resistant test shall conform to the requirements of 4.3.8 of TT-L-57.

4.5.1.5 Cold check resistance. Cold check resistance test shall conform to the requirements of 4.3.7.4 of TT-L-57.

4.5.1.6 Boiling water. The boiling water test shall conform to the requirements of 4.3.7.3 of TT-L-57.

4.5.1.7 Ultra-violet light resistance. Ultra-violet light resistance shall be as specified in 4.3.9 of TT-L-57 except that panel preparation as specified shall be disregarded, and tests shall be made on complete finished wood panel of the same wood as used in production. The finish shall be produced in accordance with production procedures used in producing the furniture.

4.5.1.8 Toughness and adhesion. The test for toughness and adhesion shall be made by using Bell Laboratories Adhesion Tester, U.S. Testing Company, Model Number 1001, in accordance with instructions for using, as provided by manufacturer of the tester. The panel shall be marred both parallel and perpendicular to the grain. The resulting indentation shall show no whitening which is evidence of film separation. The film shall conform to the contour of the indentation and shall not crack in a brittle manner in or along the indentation. The test shall be made on completely finished wood panels of the same wood as used in production. The finish shall be produced in accordance with production procedures used in producing the furniture.

4.5.2 Test for adhesives. Test for adhesives shall be as shown in Table V.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

TABLE V. Test for adhesives

Component	Characteristic	Requirement Reference	Test Method	Sample unit
Adhesive	Block shear test	3.2.1	ASTM D 905 1/ 2/ 3/	1/2 pint

1/ The following modifications apply when testing casein-type adhesive. The test blocks shall be placed under pressure between 10 and 20 minutes after spreading the adhesive, the adhering pressure shall be 175 ± 25 pounds per square inch, and the test blocks shall be held under pressure for at least four hours.

2/ The following modifications apply when testing animal adhesive. The moisture content of the wood shall be from 6 to 9 percent. The joints shall be conditioned at a relative humidity of 40 ± 4 percent.

3/ Whenever a specimen fails at a load of less than 2,800 pounds per square inch and the failure occurs 50 percent or more in the wood, the specimen shall be disregarded in computing the average. In case the shearing strength of one or more specimens is 2,800 pounds per square inch or higher, the variation among individual specimens is 10 percent or more (based on the strongest joint) the test shall be run again, provided the average is less than the required 2,800 pounds per square inch.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level C.

5.1.1 Level C. Each item shall be packaged in accordance with the manufacturer's standard commercial practice.

5.2 Packing. Packing shall be level C.

5.2.1 Level C. Each item, packaged as specified in 5.1, shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification or the National Motor Freight Classification.

6. NOTES

6.1 Intended use. The executive units covered by this specification are designed for use in executive offices of the Federal Government.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, name, and date of this specification.
(b) Options exercised in credenza, desk, and desk attachment assemblies, (see applicable detailed specification).
(c) Marking requirements.

GSA DC 78-1702

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.