AA-S 1518A
June 1, 1970
SUPERSEDING
Int. Fed. Spec. AA-S-001518(GSA-FSS)
October 7, 1968

FEDERAL SPECIFICATION

SAFE, TOOL-RESISTANT, UNINSULATED, SECURITY

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers a tool-resistant safe designed to meet the protective storage criteria for classified material set forth in Executive Order 10501, as amended, "Safeguarding Official Information in the Interest of the Defense of the United States." The safe affords protection to its contents as specified in 3.9.

1.2 Classification.

1.2.1 Types. Safes shall be of the following types, as specified (see 6.1).

Type I - With hand-change designed combination lock.
Type II - With key-change designed combination lock.

1.2.2 Styles. Safes shall be of the following styles, as specified (see 6.1).

Style A - With channel base assembly (see 3.5).
Style B - Without channel base assembly.

1.2.3 Sizes. Safes shall be of the following sizes, as specified (see 6.1).

Size I (see 3.3.3).
Size II (see 3.3.3).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

Federal Specifications:

QQ-P-416 - Plating, Cadmium (Electrodeposited).
QQ-Z-325 - Zinc Coating, Electrodeposited, Requirement for.
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings.

Federal Standards:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civilian Agencies).
Fed. Std. No. 595 - Colors.

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402.

(Single copies of this specification and other Federal specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, D.C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Washington.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issues in effect on date of invitation for bids or request for proposal shall apply.

Underwriters' Laboratories, Inc. (UL) Publications:

Subject No. 140 - Relocking Devices.
Subject No. 768 - Combination Locks.

(Application for copies should be addressed to Underwriters' Laboratories, Inc. 207 East Ohio Street, Chicago, Illinois 60611).

3. REQUIREMENTS

3.1 Qualification. The safes furnished under this specification shall be products which have been tested, and passed the qualification tests and inspections specified in section 4, and have been listed on or approved for listing on the applicable Federal qualified products list (QPL).

3.1.1 Qualification suspension.

3.1.1.1 Development of entry techniques. Continuous tests of qualified safes will be conducted by the Government to determine whether the surreptitious or forced entry protection afforded by the safe should or can be improved. If at any time techniques are developed within the framework of the specification which affect the security integrity of the qualified product, it shall be removed from the qualified products list and the manufacturer shall be required to modify his safe to the extent necessary to defeat the techniques and have it requalified.

3.1.1.2 Change in specification requirements. This specification will be continually reviewed by the Government to determine whether requirements should or can be changed to improve the quality of the product. If, at any time the specification's requirements are changed, and such changes affect the qualification status of the safe, it shall be removed from the qualified products list and the manufacturer shall be required to modify his product to the extent necessary to comply with the specification changes and submit it for requalification.

3.2 Material. Material used in the safe's construction shall be as stated herein. Material not definitely specified shall be of good commercial quality, suitable in all respects for the purpose intended.

3.2.1 Steel: Steel used in the case and door of the safe shall be not less than 1 inch in thickness and shall have not less than 50,000 pounds per square inch tensile strength. Steel shall be free from rust, scale, pits, buckles, and other imperfections which might adversely affect the appearance or the serviceability of the finished product.

3.2.2 Face hardware. The face hardware, excluding the door stop and combination lock, shall be satin finished, anodized aluminum, type 430 corrosion resistant steel, brushed chromium on steel, or on die cast zinc, brass or bronze, or electrolysis nickle coating.

3.2.3 Finishing materials.

3.2.3.1 Enamel and lacquer. The finish coat shall be either enamel or lacquer of good commercial quality. The color shall be as specified in 3.2.4.

3.2.3.2 Zinc coating. Zinc coating shall be in accordance with type I, class 2 of QQ-Z-325.

3.2.3.3 Cadmium plating. Cadmium plating shall be in accordance with class 1, type I, of QQ-P-416.

3.2.4 Color of finish. The color of finish used on the exterior shall be gray, color No. 26134, of Fed. Std. 595. The color of finish used on the interior shall be the manufacturers' standard, commercial white or aluminum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.3 Construction.

3.3.1 Assembly of unit. The safe's top, sides, back, and bottom shall be assembled and joined in a manner to provide the required strength. All welding and mechanical attachments shall be of a type and quality to accomplish secure and rigid joints in proper alignment. Welding and brazing shall be sound without porosity. All protruding or depressed welds on the unit's exterior shall be filled and sanded or ground smooth. Interior welds shall be finished so as to present no sharp edges or rough surfaces which might cause personal injury.

3.3.2 Safe door. The safe shall have a round, lug-type door with not less than three lugs. The door shall provide a clear opening into the safe interior of not less than 12 inches in diameter. The clearance between the door and jamb shall be not more than 0.006-inch. The door shall have a detent or other suitable feature to hold the locking bolts in a retracted position when the door is open. The door head shall be in perfect alignment with the door frame and operation of the lock-mechanism, including the locking bolts, shall be smooth and positive without binding or jamming of parts. The door, in any open position, shall not overbalance the empty safe. The door shall be subjected to the test in 4.4.8.2.

3.3.2.1 Door stop. A stop or bumper shall be mounted on the front face of the safe in a manner to protect the combination lock and door handle against damage. The stop or bumper shall be of rubber or other comparable material and shall be attached so as to withstand hard daily usage.

3.3.2.2 Door handle. The door handle shall be of one of the materials in 3.2.2 and of sufficient thickness and strength to withstand hard daily usage. The handle shall be securely and firmly staked to the door to prevent accidentally loosening during the service life of the safe. The handhold for the handle shall be not less than 1 by 3 inches and shall easily accommodate the users hand. The handle shall be well finished and shall be free from sharp edges, nicks, scratches, and rough surfaces.

3.3.3 Dimensions. The outside and inside dimensions of the safe shall be as specified in table I. Tolerance for the outside dimensions shall be ± 1/4-inch. Inside dimensions shall be not less than specified.

TABLE I. Dimensions (in inches)

Outside (± 1/4-inch) (without face hardware)				Inside (minimum clear opening) (excluding door inward projection)		
Size	Height	Width	Depth	Height	Width	Depth
I	19-3/4	35-1/2	26-1/2	17	33	24
II	20	20	17-3/4	18	18	12-3/4

3.4 Combination lock. A changeable combination lock of the type described herein shall be installed as an integral part of the safe. The lock shall be of top-reading design with its dial and ring protected by a standard, snap-on dust cover. At the option of the purchaser, the lock shall be a hand-change or a key-change type (see 6.1). The lock shall resist opening by manipulation and special techniques for not less than 20-man-hours (see 6.3.3 and 6.5). The lock shall be afforded protection against radiological attack for not less than 20-man-hours (see 4.4.8.3.2). The lock shall meet group 1 or group 1R requirements of UL Publication No. 768. The UL's group 1 or group 1R lock label shall be affixed to the lock and it will be accepted as evidence of compliance with the UL Standard (see 3.4.4).

3.4.1 Combination lock installation. The lock's dial ring shall be mounted so as to be flush with the front surface of the safe door and its attachment to the door shall be firm and secure without movement or side play. The lock case shall be securely attached to the door with screws. Screws shall be retained by lock washers or other suitable and effective means so that there is no movement or side play to the lock case. The lock's spline key shall not be defaced in any manner and shall be inserted to within 1/32-inch of the top of the lock drive cam. The lock's outer spindle shall be threaded not more than 4 threads from the top of the lock drive cam. The formation of the drive cam operating spring shall not be changed or altered in any manner from the formation supplied by the lock manufacturer. Neither the lock bolt nor the drop lever shall be filed, abraded, or otherwise deformed from the formation supplied by the lock manufacturer. Metal plates, housing, or other barriers used around the lock case shall be installed in a manner so as not to abrade or otherwise damage the lock spindle. No lubricant other than that applied by the lock manufacturer shall be used within the lock case.

3.4.2 Relocking device. The safe locking mechanism shall incorporate a relocking device which shall be in accordance with UL Publication No. 140. The UL relocking label shall be affixed to the safe and will be accepted as evidence of compliance with the UL requirement.

3.4.3 Locking mechanism and lock mounting drawings. Complete, exploded-view drawings of the locking mechanism and the lock mounting, with individual parts indexed, shall be furnished by the manufacturer upon the specific request of the purchaser.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.4.4 Government testing. The Government testing facility for the General Services Administration reserves the right of testing the combination lock in accordance with standards that are priviledged to the Government. The UL's testing of the lock and the relocking device shall not in itself constitute final approval.

3.5 Channel base assembly. At the option of the purchaser (see 6.1), the safe shall have a channel base assembly permanently attached to its bottom. The assembly shall consist of two channel formed, steel bases. One base shall extend from front to back on the left underside of the safe; the other from front to back on the right underside. The base shall be 4 inches high and 5 inches wide, ± 1/4-inch. The side of the bases which bears on the floor shall have a return flange from each side so as to provide a lengthwise slot approximately 2 inches wide. The slot may extend the full length of the base or it may run to within approximately 2 inches from each end of the base. The outer edges of the bases shall be recessed approximately 1/2-inch in from the side, front, and back edges of the safe base. The front and rear ends of the bases shall have removable caps to facilitate anchoring the safe to the floor when desirable. Attachment of the base assembly shall not weaken the tamper resistance of the safe, and the assembly shall withstand the test in 4.4.8.1.

3.6 Weight. The net weight of the safe shall not exceed 250 pounds per square foot of its base area. The total minimum weight shall be not less than 750 pounds. The base and top area of the safe shall be of the same dimensions. The weight shall be clearly and permanently marked on the base of the unit in letters not less than 1/2-inch in height so as to be visible from the front.

3.7 Pretreatment and finish.

3.7.1 Pretreatment. All exterior and interior ferrous metal surfaces shall be treated for painting in accordance with any of the types in TT-C-490.

3.7.2 Finish. The finish coating specified in 3.2.3.1 shall be applied to all exterior and interior metal surfaces except plated metal. The minimum total finished film thickness of the final coat shall be not less than 1.0 mil. The finish shall level out to produce uniform exposed surfaces without runs, wrinkles, grit, areas of thin film or no film, or separation of color. Special attention shall be given to the base and interior to insure that all surfaces are adequately protected against rust. The final finish shall withstand the test in 4.4.8.5 without evidence of cracking, flaking, or loss of adhesion of the finish. Two 3 x 5 inch test panels of 20 gage (0.0359-inch) steel shall be furnished with the sample safe for the purpose of the test in 4.4.8.5. One panel shall be prepared to reflect the inner coating and one to reflect the outer coating used.

3.7.3 Plating. Bolts, screws, nuts, and similar accessories shall be made to resist rust by electro-galvanizing or by zinc, cadmium or chromium plating.

3.8 Lubrication. The safe's moving parts requiring lubrication shall have a permanent type lubricant applied which is suitable to the varied climatic conditions likely to be encountered in areas where the safe is used.

3.9 Resistance to entry techniques. The safe shall withstand the entry tests in 4.4.8.3 for not less than the periods of time specified hereunder.

30 man-minutes surreptitious entry.
10 man-minutes forced entry.
20 man hours radiological entry.

3.10 Drop tests. The safe shall be subjected to the drop tests in 4.4.8.4.1 and 4.4.8.4.2 and shall withstand damage to the extent specified in the test requirements..

3.11 Replacement of parts. The safe's combination lock and face hardware shall be capable of identical replacement in the field without use of specialized tools or specially qualified personnel. Replacement of parts shall be possible without affecting the safe's security integrity.

3.12 Identification labels. Each safe furnished in accordance with this specification shall bear the metallic labels specified hereunder.

3.12.1 External label. A label affixed to the outside face of the safe which shall show in easily read letters not less than 1/8-inch in height, the following data:

GENERAL SERVICES ADMINISTRATION
APPROVED SECURITY CONTAINER
MANUFACTURER'S NAME

3.12.2 Manufacturer and contract identification label. A label affixed to the outside face of the safe showing the safe model and serial number, date of manufacturer, and Government contract number.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

3.12.3 Certification label. A label internally affixed so as to be visible when the safe door is open. The label shall bear the following certification:

This is a U.S. Government security container, approved by GSA under Fed. Spec. AA-S-1518A. It affords the following security protection:

30 Man-minutes against surreptitious entry.
10 man-minutes against forced entry.
20 man-hours against manipulation of the lock.
20 man-hours against radiological attack.

3.13 Workmanship. The workmanship shall be of a quality to produce a serviceable and well finished. product able to withstand hard daily usage. The edges of all exposed parts and sheets shall be protected by folding, beading, flanging, or grinding to eliminate burrs, roughness, and sharp edges. The bending of channels and flanges shall be straight and smooth. Welding and brazing shall produce secure and rigid connections. Lock washers, cotter pins, clips, retainers, or built-in features shall be used to prevent loosening of screws, bolts, and nuts, which may cause disengagement of parts and possible lockout. The door and other moving parts shall operate smoothly without binding or jamming. To assure strict compliance with 3.4.1, particular attention shall be given to the quality of workmanship and method used in the installation of the combination lock in the safe door. The safe shall be free of any defects or features which may affect its appearance and serviceability, or which may cause personal injury.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. Except that testing for qualification shall be performed by an agency designated by General Services Administration, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facility or service acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

4.1.1 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.2 Inspections and tests for acceptance.

4.2.1 Inspections. Cabinets delivered for acceptance under contract or order shall be inspected for compliance with 4.4.9. Any defect shall provide reason to reject the cabinet. Rejected cabinets may be reworked to correct defects and resubmitted for acceptance. Reworked cabinets shall be so indicated to the Government inspector.

4.2.2 Tests. Periodically, during the term of contract, the Government inspector will select samples of the manufacturer's production and have them tested in accordance with 4.4.8. Testing shall be performed by a Government agency designated by the General Services Administration. Failure to meet any one or more of the tests shall provide reason to suspend acceptance of the manufacturer's product until the Government inspector is satisfied that all defects have been corrected.

4.3 Inspection of preparation for delivery requirements. An inspection shall be made to determine that the preservation, packaging, packing, and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior)	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping inadequate stapling.
	Distortion of container.

4.4 Testing procedures and tests.

4.4.1 Testing agency. Qualification tests accomplished on safes submitted for approval for inclusion on the applicable Qualified Products List (QPL) and any retesting that may be required for requalification shall be performed by a testing agency specifically designated by the General Services Administration. 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.4.2 Testing costs. All testing costs entailed in determining the qualification of the supplier's product, including costs of retesting of a qualified product if subsequently disqualified under 3.1.1.1 or 3.1.1.2, shall be borne by the supplier, and shall be payable to the General Services Administration as directed by Standardization Division, Federal Supply Service.

4.4.3 Testing procedures. The following procedures shall govern the testing of all safes submitted for qualification under this specification:

(a) Samples shall be submitted for qualification only after the supplier has obtained written authorization from the General Services Administration.
(b) A qualification test may be discontinued at the Government's testing facility at any time the product fails to meet any one or more of the requirements set forth in this specification. The manufacturer may be permitted to make modifications on the sample during the testing phase where such modifications, in the judgement of the General Services Administration and the testing facility, are clearly in the interest of the Government.
(c) In case of failure of the sample, consideration will be given to the request of the manufacturer for resubmission for retest only after it has been clearly shown that changes have been made in the product which the Government considers sufficient to warrant retest.
(d) The manufacturer or his representative will not be permitted to observe the actual tamper resistance tests conducted on his product at the testing facility. However, when samples tested fail to comply with the requirements of this specification, the sample may be examined by the manufacturer or his representatives and full details of the failure may be made known to them in a manner which, for reasons of security, will be in the best interest of the Government.

4.4.4 Test samples. Two qualification test samples shall be forwarded at a time and to a place designated by the General Services Administration. In the event the samples are destroyed or damaged to such an extent during testing that testing cannot be completed, the Government reserves the right to require the manufacturer to furnish additional samples to complete the testing.

4.4.5 Drawings and material specifications. The manufacturer shall furnish two complete sets of construction and assembly drawings and material specifications with the samples submitted for qualification. When samples have been tested and are approved for inclusion on the applicable QPL, the manufacturer shall furnish three additional complete sets of the assembly and construction drawings and material specifications lists to the General Services Administration for the Government's use in inspection and acceptance of the product after award of contract. All material so furnished by the manufacturer will be held in proprietary confidence.

4.4.5.1 Changes in drawings and material specifications. Once the safe has been tested and approved for QPL, no change of any kind shall be made in its construction or in the construction drawings unless prior written authorization to make the change is obtained from the Federal Supply Service, General Services Administration.

4.4.6 Qualification testing and inspection. Qualification testing and inspection shall consist of the following tests and inspections. Failure of the sample to meet any one or more these requirements shall provide reason to consider the product as having failed to meet requirements for qualification.

(a)	Channel base test	- 4.4.8.1
(b)	Door test	- 4.4.8.2
(c)	Resistance to entry tests	- 4.4.8.3
(d)	Drop tests	- 4.4.8.4
(e)	Inspections	- 4.4.9

4.4.7 Acceptance after award of contract. The Government reserves the right to inspect and test each safe, including all component parts there of, delivered for acceptance under this specification after award of contract.

4.4.8 Test Methods.

4.4.8.1 Channel base test. The safe, loaded with 60 pounds of weight shall be locked and then raised from its normal upright position until the bottom of the channel bases are approximately 6 inches above the floor surface. The safe shall then be allowed to free fall, base down, onto a hard level concrete surface or equal surface. Any resulting distortion or weakening in the structural strength of the bases, or weakening in their attachment to the safe shall be considered as failing to comply with the requirements of the test.

4.4.8.2 Door test. The safe shall be tested empty and shall not be anchored to the floor during this test. The safe door shall be opened 90 degrees from its closed position and 150 pounds of weight shall be loaded on the top edge of the door. The safe shall be allowed to remain in this condition for not less than 24 hours. The safe shall be considered to have failed the test if tipping occurs of if the door and locking bolts fail to operate smoothly.

4.4.8.3 Resistant to entry tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

4.4.8.3.1 Surreptitious and forced entry. There shall be sufficient time and opportunity to study the design and construction of the safe and to develop testing methods prior to the start of the tests. There shall be no limit on the number of methods of entry attempted. Not more than two men shall be used simultaneously during each attempt at entry. The man-minute working time shall cover the period during which a surreptitious or forced entry test is in progress on the safe and shall be exclusive of time required for safety first precautions and rest periods. The test tools and devices used in the test shall be limited to those powered by hand such as, but not limited to, cutters, hammers, wedges, chisels, and drills. Tools and devices shall be not more than 20 inches in length when dis-assembled or folded. Tools and devices shall be capable of being carried in a case not exceeding 1.5 cubic feet in volume and nine inches in thickness, and which do not exceed a total weight of 25 pounds, exclusive of weight of case. Neither explosives not the application of heat such as from a blow torch or electric arc shall be used. The test tools and devices selected for a test shall be weighed and packed in the carrying case specified prior to commencement of the test. The time clock shall be started when the test equipment carrying case is opened and shall not be stopped during a test, except as specified above. Any change or repair of tools taken from the carrying case during a test shall only be done while the clock is running.

4.4.8.3.2 Entry by radiological techniques. The safe shall successfully meet the following test to demonstrate resistance to entry by radiological techniques. For example, the safe structure including the mounted lock shall be radiographed, and the resulting radiographs shall not permit determination of the lock combination to the extent that entry is made into the safe in less than the time specified. Radioactive isotopes such as Cobalt 60 will be used in the test. Any effective radiation shielding provided in the safe will be included in the test. The test is intended to simulate attempted entry into the safe within the specification limits of time and equipment, utilizing practicable and feasible procedures and equipment available to Government testing agencies performing the tests.

4.4.8.4 Drop tests. The safe shall be loaded with 60 pounds of weight and then locked. The loaded safe shall then be subjected to the drop test specified hereunder.

4.4.8.4.1 Thirty-six inch test. The safe shall be raised until the base of the safe is 36 inches above the floor surface. The safe shall then be allowed to free fall onto a hard, level, concrete surface or equal surface. Except for a lockout caused by activation of the relocking device, any resulting lockout requiring destructive force to reduce shall provide reason to consider the safe as having failed to withstand the conditions of the test.

4.4.8.4.2 Thirty foot test. The safe shall be raised until its base is 30-feet above the floor surface The safe shall then be allowed to free fall, base down, onto a hard, level, concrete surface or equal surface. Any damage which results in the releasing or making accessible without further force, any part of the stored material shall provide reason to considered the safe as having failed to withstand the test.

4.4.8.5 Finish test. The steel panels prepared in accordance with 3.7.2 shall at room temperature be bent around a 1/4-inch rod to an angle of 180 degrees. The panels shall then be examined for compliance with 3.7.2.

4.4.9 Inspections. Visual inspections shall be made to determine compliance with the following paragraphs:

3.2	-	Material.
3.2.4	-	Color and finish.
3.3.1	-	Assembly.
3.3.2	-	Door.
3.3.3	-	Dimensions.
3.4	-	Combination lock.
3.5	-	Channel base assembly.
3.6	-	Weight.
3.7	-	Pretreatment and finish.
3.8	-	Lubrication.
3.12	-	Labels (safes delivered under contract).
3.13	-	Workmanship.

In addition, products delivered under contract for acceptance shall be examined to determine whether construction and assembly details are in accordance with the approved construction and assembly drawings.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Unless otherwise specified, commercial packages are acceptable under this specification.

5.2 Packing. Unless otherwise specified, the subject commodity shall be packed in substantial commercial containers of the type, size and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate at the point of delivery.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

5.3 Marking. In addition to marking required by the contract or order, the shipping container shall marked in accordance with Fed. Std. No. 123 or MIL-STD-129.

6. NOTES

6.1 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, symbol, and date of this specification.
(b) Type, style, and size required (see 1.2.1, 1.2.2, and 1.2.3).
(c) Levels of packaging, packing, and marking required (see 5.1, 5.2, and 5.3).

6.2 Qualification. With respect to products requiring qualification, awards will be made only for such products as have, prior to the time set for opening of bids, been tested and approved for inclusion on the applicable Federal Qualified Products List, whether or not such products have actually been so listed by that date. The attention of suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification so that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is Standardization Division, Federal Supply Service, General Services Administration, Washington, D.C. 20406, and information pertaining to qualification may be obtained from that activity.

6.3 Definition of terms used in this specification.

6.3.1 Surreptitious entry. For the purpose of this specification, "surreptitious entry" means provisions of an opening into the safe of not less than 3 square inches in area from which material can be withdrawn with the minimum for any one dimension being 1/4-inch. It is further defined as an entry made in such a manner or by such a means as to leave no evidence of the act which would be readily discernible in normal use of the safe.

6.3.2 Forced entry. For the purpose of this specification, "forced entry" means provisions of an opening in the safe of not less than 9 square inches in area for access into the safe with the minimum of any one dimension being 1/2-inch. It is further defined as an entry made in such a manner which may leave evidence of the act which would be readily discernible in normal use of the safe.

6.3.3 Lock manipulation. For the purpose of this specification, "lock manipulation" is defined as the opening of the combination lock without alteration of the physical structure, or disarranging of parts. Ordinarily manipulation would be accomplished by movement of the lock dial.

6.3.4 Normal use. For the purpose of 6.3.1 and 6.3.2, "normal use" is defined as the opening of the lock, releasing the locking mechanism, opening the door to the extent necessary for the reception or withdrawal of the contents; and closing the door and relocking the safe with the top and front of the safe exposed to view and touch; the rear and sides exposed to view only; and the base neither exposed to view nor touch.

6.4 All samples required for test purposes shall be furnished at no expense to the Government and the manufacturer shall pay all transportation charges to and from the point where tests are performed. All tested samples shall become the property of the Government but may be released to the manufacturer at the option of the Government. Upon request, the manufacturer shall furnish to the Government testing facility a safe equal in every respect to that of the qualified sample for use of inspection and test during the term of qualification. The safe shall be furnished at no expense to the Government and will be returned to the manufacturer upon removal of his product from the qualified products list.

6.5 Information relating to the requirements of 3.4 in respect to special techniques will be disclosed to qualified suppliers and personnel of the Federal agencies on a need to know basis.

Preparing activity:

GSA

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price of this specification 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.

GENERAL SERVICES ADMINISTRATION - FEDERAL SUPPLY SERVICE

SPECIFICATION COMMENT SHEET

BUDGET BUREAU NO. 29-R0175

INSTRUCTIONS

This form provides a way for users of this specification to inform the originator of problems encountered in its use. It is not to be used to request changes to accommodate proprietary features. All comments will be considered and appreciated, but please do not expect a reply. To comment: detach, complete, and mail to General Services Administration, FSS(FMSO), Washington, D. C. 20406.

NOTE: Comments on this form do not constitute or imply authorization to waive any part of the document or serve to amend contractual requirements.

1. SPECIFICATION

AA-S-1518A Safe, Tool-Resistant, Uninsulated, Security

2. CONTRACT NO. *(If any)*	3. QUANTITY ON CONTRACT *(Optional)*	4. DOLLAR VALUE *(Optional)*

5. GENERAL NATURE OF PROBLEM *(e.g., inspection difficulties, manufacturers unable to meet tolerances, containers collapse under normal warehousing conditions, etc.)*

6. SPECIFIC REQUIREMENTS AFFECTED *(Include paragraph number and lines of wording)*

7. SPECIFIC PROBLEMS *(e.g. tests in 4.2.2 will not assure that the battery will last required time; temperature ranges in table 2 do not conform to commercially available items.)*

8. RECOMMENDATIONS

9. NAME OF MANUFACTURER, ASSOCIATION, GOVT., AGENCY, ETC.	10. ADDRESS *(Number, Street, City, State and Zip Code)*

11. NAME AND TITLE OF SUBMITTER	12. DATE

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.