AA-T-001197(GSA-FSS)
AMENDMENT-3
January 29, 1969
SUPERSEDING
Amendment-2
June 18, 1968 and
Amendment-1
June 30, 1967

AMENDMENT
TO
INTERIM FEDERAL SPECIFICATION

TABLES, WOOD OR METAL, BASE

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this amendment as a valid exception to Interim Federal Specification AA-T-001197(GSA-FSS) dated May 19, 1967.

PAGE 3

Paragraph 3.2.4. Delete last line and substitute the following:

"(a) Formica, white No. 949, or equal;
(b) Pioneer 5-PR-2 Gunstock Savcy Walnut, standard finish, or equal;
(c) Formica 91-132-33, Walnut Textured Finish, or equal. (see 6.2)."

PAGE 4

Paragraph 3.2.8. Delete entirely, and substitute new paragraph:

"3.2.8 Chromium plating (satin). Steel frame members shall be chrome plated as in class 1 (decorative plating) and type II (satin) in accordance with Federal Specification QQ-C-320. The copper plus nickel undercoat on steel base metal shall conform to class 1 (decorative plating), type III (KS) on steel base metal, 0.00075 inch copper plus nickel as specified in Federal Specification QQ-N-290. When nickel alone is used for the undercoat, it shall be not less than 0.001 inch thick. The chrome plating shall not peel, or crack and it shall be free of uneven color, pits, stain and powder film.

Paragraph 3.3.3. In second sentence delete "CS326" and substitute "CS236". In third sentence delete "CS263" and substitute "CS236".

PAGE 5

Add new paragraph:

3.3.4.1 Table, Type I, Knock-down construction. When specified (see 6.2), the table shall be constructed for knock-down shipment in the following manner:

Each leg shall be assembled to the aprons by a machined snug-fitted dovetail joint. A 1/4 inch hanger bolt with washer and wing nut shall penetrate the leg a minimum of 7/8 inch and a metal corner bracket shall be the attaching implements. (see Figure 2). The aprons shall be notched at an angle to receive the corner brackets. The aprons shall be secured to top with No. 10 sheet metal screws 3/4 inch from each end and a maximum span of 12 inches apart between the end screws. The dovetail joint shall receive one coat of sealer and shall then be waxed for ease of assembly. A detailed easy to use, illustrated assembly instruction sheet shall be packed with each table. Table tops with attached aprons and the detached legs, selected by the Government inspector, shall be fully assembled by the contractor. The inspector shall witness the assembly of the legs to the table aprons and shall observe the ease of assembly, fit of components and rigidity of assembled table.

Paragraph 3.4.1 Wood. Line 3 between "the" and "plastic" insert "Walnut."

FSC 7105

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:41Z
Check the source to verify that this is the current version before use.