MILITARY SPECIFICATION

LOUDSPEAKER, PERMANENT MAGNET (UNENCASED, 3-INCH AND 4-INCH DIAMETER CONE, 2-WATT; FUNGUS-, GUNBLAST-, AND IMMERSION-RESISTANT), TYPE LS-445/U, M12606-01, and M12606-02

This amendment forms a part of Military Specification MIL-L-12606D, dated 25 October 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 16

Paragraph 4.7.7, delete and substitute.

"4.7.7 Harmonic distortion (see 3.4.6). The loudspeaker shall be mounted in its appropriate test cabinet. A constant voltage having a rms value of 4.00 ± .1 volts at discrete frequencies of 400, 2,000 and 4,000 Hz ± 10% shall be applied to the voice coil terminals of loudspeaker types LS-445/U and M12606-02. A constant voltage having a rms value of 4.00 ± .1 volts at discrete frequencies of 500, 2,000 and 4,000 Hz ± 10% shall be applied to the voice coil terminals of loudspeaker type M12606-01. Harmonic distortion shall be determined by one of the methods specified in 4.7.7.1 or 4.7.7.2."

Paragraph 4.7.7.2, line 3, following "determined by the following formula:", insert:

"Percent distortion = $100 \times \sqrt{\frac{p_2^2 + p_3^2 + \ldots p_n^2}{p_1^2 + p_2^2 + p_3^2 + \ldots p_n^2}}$ "

Paragraph 4.7.8, line 1, delete "mounted in a test cabinet (figure 4)" and substitute "mounted in its appropriate test cabinet".

Custodians
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy -
Air Force - 99
DLA - ES

User activities:
Army - AR, AV
Navy - MC

Preparing activity
Army - CR

Agent:
DLA - ES

(Project 5965-0173)

FSC 5965

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:04Z
Check the source to verify that this is the current version before use.