INCH-POUND

MIL-I-12597C(AR)
AMENDMENT 2
11 February 1993
SUPERSEDING
AMENDMENT 1
6 December 1977

MILITARY SPECIFICATION

IGNITER, BLASTING FUSE, FRICTION TYPE, M3A1
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-I-12597C(AR), dated 23 May 1975, and is approved for use by the US Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.2: Change "Industrial Checmicals" to "Industrial Chemicals".

PAGE 3

* 2.1, Add the following:

"MIL-B-117 - Bag, Sleeve and Tubing - Interior Packaging"
MIL-STD-129 - Marking for Shipment and Storage"

3.3 Delete in its entirety and substitute the following:

"3.3 Tumble. The igniter shall not disassemble or ignite when subjected to the Tumbling Test."

PAGE 8

* 4.4.2.2 Clip Safety, Minor 201: Delete "Diameter of Eyelet" and substitute "Outside dimension of eyelet".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:03Z
Check the source to verify that this is the current version before use.

PAGE 22

4.5.3:

Change "Approximately 500" to "400 plus or minus 50".

Change "... segregate those igniters which ignited during tumbling" to "reject and remove from the lot those igniters which lost safety clips, disassembled or ignited during tumbling."

PAGE 23

* 5.1.2: Add paragraph as follows:

"5.1.2 Level C. Four hundred Igniter, Blasting Fuze shall be packed in a domestic class, fiberboard box of Spec PPP-B-636. They shall be arranged, on end, in 10 rows of 20 each with a fiberboard spacer between rows. A fiberboard filler shall be placed on top of the bottom layer of 200 igniters and a second layer of 200 igniters shall be packed on top as above except the position of the ends of the igniter shall be alternated. Add additional fillers, as required, to insure tight packing. Seal the box, blunt all corners and place into a barrier bag, Type I, Class E of Spec MIL-B-117. Exhaust excess air within bag and seal in accordance with manufacturer's instructions. If required by the contract, the sealed package shall comply with the quick leak test of Spec MIL-P-116."

* 5.2.2: Add paragraph as follows:

"5.2.2 Level C. Twelve boxes (total 4800 Igniters), packaged and sealed as cited in 5.1.2, shall be packed in an overseas class (waterproof), fiberboard box meeting the requirements of Code of Federal Regulations (CFR), Title 49, Parts 100-199. Fillers shall be added around and on top of the inner boxes to insure tight packing. The box shall be securely sealed to meet the requirements of the Code of Federal Regulations."

* 5.3: Delete paragraph and substitute the following:

"5.3 Marking.

5.3.1 Level A. The boxes and bags shall be marked as specified on dwgs. 8835011 and 8835012.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:03Z
Check the source to verify that this is the currentversion before use.

5.3.2 Level C. The boxes and bags shall be marked in accordance with MIL-STD-129 and CFR Title 49, Parts 100-199."

* 6.2: Change address to: "Commander, US Army Research, Development and Engineering Center, ATTN: SMCAR-QAT-I, Picatinny Arsenal, NJ 07806-5000.

* 6.3: Change address to: "Commander, US Army Research, Development and Engineering Center, ATTN: SMCAR-QAT-M, Picatinny Arsenal, NJ 07806-5000.

The margins of this amendment are marked with a asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to eveluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A503)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:03Z
Check the source to verify that this is the current version before use.