NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/277B
16 February 2021
SUPERSEDING
MIL-DTL-11484/277A
21 April 2016

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN CAREER SERVICE, DEFENSE CONTRACT MANAGEMENT AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Oxidized, Relieved, Matte Finished and shall match The Institute of Heraldry Metal Finish Chip Number 4.

DIMENSION:
HEIGHT: 13/16 inch (REF)
WIDTH: 25/32 inch (REF)
THICKNESS (At thickest point): 0.115 inch $\pm$ 0.010 inch

ATTACHING DEVICE:
1. Attaching device shall be prong with pick and flat ball type clutch

2. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:45Z
Check the source to verify that this is the current version before use.

NOTE:
The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2021-281)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:45Z
Check the source to verify that this is the current version before use.