NOT MEASUREMENT SENSITIVE

MIL-L-11484/141B
9 June 1992
SUPERSEDING
MIL-L-11484/141A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, DECORATION, JOINT SERVICE ACHIEVEMENT MEDAL, DOD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.




MATERIAL: Gilding Metal

DIMENSIONS:
HEIGHT (Overall): 9/64 inch (0.36 cm) (REF)
WIDTH (Overall): 21/32 inch (1.67 cm) (REF)
THICKNESS (At edge): 0.065 inch ± .005 inch (0.165 cm ± 0.012 cm)

*FINISH: Hard Enameled, Gold Plated, Mirror-like Polished*

NOTES:
1. Attaching devise shall be prong with pick and wing type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.


Source: https://assist.dla.mil -- Downloaded: 202610-17T16:58Z
Check the source to verify that this is the current version before use.

2. Enameled colors shall be as indicated. The colors shall conform to the TIOH chip numbers listed below or the standard sample:

| COLOR | CHIP NO. |
|---|---|
| Red | 1 |
| Green | 12 |
| Dark Blue | 20 |
| White | 28 |
| Light Blue | 33 |

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of the manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85 and incorporate an ultraviolet inhibitor.

4. The term (REF) refers to measurements taken from the Government furnished hub or die.

Custodians:
Army - IH
Air Force -11
Navy - NU

Review activities:
Air Force - 82, 99
Navy - MC, CG
DLA - CT

User activities:
Air Force - 45

Preparing activity:
Army - IH

(Project No. 8455-0671)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T16:58Z
Check the source to verify that this is the current version before use.