NOT MEASUREMENT SENSITIVE

MIL-L-11484/146B
14 January 1994
SUPERSEDING
MIL-L-11484/146A
27 June 1988

MILITARY SPECIFICATION SHEET

LAPEL BUTTON, OFFICE OF THE INSPECTOR GENERAL IDENTIFICATION BADGE, DOD

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-L-11484.

MATERIAL: Red Brass

DIMENSIONS:
DIAMETER: 5/8 inch (1.59 cm) (REF)
THICKNESS (At Thickest Point): 0.080 inch ± 0.010 inch (0.203 cm ± 0.025 cm)

FINISH: Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:00Z
Check the source to verify that this is the current version before use.

2. Attaching device shall be prong with pick and flat ball type clutch. The prong shall be centered on the reverse side and fused or soldered to the lapel button.

3. Each lapel button shall be mounted and centered on a polyethylene pad and placed in a rigid hinged plastic box having a transparent lid and opaque bottom section. The box shall have two plastic hinges and catches and shall be approximately 1-1/8 inches (2.86 cm) square and 5/8 inch (1.59 cm) in overall depth. The pad shall be of sufficient depth to restrict movement of the lapel button when the lid is closed.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other - DOD

Preparing activity:
Army - IH

(Project No. 8455-0745)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T17:00Z
Check the source to verify that this is the current version before use.