MILITARY SPECIFICATION

GAGE, FRUIT AND VEGETABLE SIZING

This Limited Coordination Military Specification has been prepared by the Defense Personnel Support Center based upon currently available technical information, but it has not been approved for promulgation as a coordinated document. It is subject to modification. However, pending its promulgation as a coordinated Military Specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers a gage suitable for verifying grade and size of fresh fruits and vegetables by veterinary personnel.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Federal

MMM-A-250	Adhesive Water Resistant (For Sealing Waterproofed Paper).
PPP-B-566	Boxes, Folding, Paperboard.
PPP-B-585	Boxes, Wood, Wirebound.
PPP-B-601	Boxes, Wood, Cleated-Plywood.
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.
PPP-B-676	Box, Setup.
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, (For Carton Sealing).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

Air Force-Navy Aeronautical Standard

AN24-12A	Bolt-Clevis

DRAWING

Defense Personnel Support Center (DPSC)

24223 Gage, Fruit and Vegetable Sizing

(Copies of specifications, standards, and drawing required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Material shall be of the highest quality throughout and as specified herein.

3.2 Construction. Gage shall consist of a series of seven (7), 6061-T6 aluminum alloy plates, held together by a bolt-clevis, nut and two (2) washers and shall be in accordance with DPSC Drawing 24223. The bolt-clevis shall be made of cadmium plated steel and shall be constructed in accordance with Air Force-Navy Aeronautical Standard AN24-12A. Nut and washers shall be made of 300 series corrosion resisting steel. The unit gage shall provide twenty (20) circular openings ranging in size from 1/4 inch to 3 inches in diameter and shall be suitable for verifying grade and size of fresh fruits and vegetables by the veterinary personnel. Openings shall be effected so that there shall shall be no bending or warping of the plates, nor distortion of edges surrounding the holes which would scratch adjacent plate surfaces in the assembled unit. Plates in unit shall be properly assembled and adequately secured with a bolt-clevis and a thin self-locking hex nut as shown in drawing. The securing hardware shall provide that degree of tightness, to the assembled plates in the unit, as to facilitate selection of any one (1) gage plate for ready use and yet not be so loose as to cause the plates to swing freely from the bolt axis. Each gage opening shall be identified by stamping the size in close proximity to the pertinent opening.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

3.3 Marking.

3.3.1 Sizing marking. Sizing numerals of 1/4 inch height shall be stamped on one side of the plate as shown in the drawing and shall be not less than 1/8 inch from the openings or edges. Stamping shall be effected so as not to cause metal to protrude from the opposite side of the plate surface.

3.3.2 Identification marking. Each unit shall be permanently marked on the back side of the last plate, with the manufacturer's name or registered trademark.

3.4 Finish. Unit shall be finished smoothly. Circular openings and edges of plates shall be free of slivers, burrs and sharp edges. Each plate shall receive a clear oxidize finish after punching out the gage openings and stamping of numerals.

3.5 Workmanship. Workmanship shall be first class throughout. The unit gage, in the close position, shall have even sides and shall be free of defects which detract from its appearance or may impair its serviceability. Bolts, nuts and washers in unit shall be free from rough or sharp edges and plate surfaces shall be free of roughness, gouge marks or indentations.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual, or auditory, investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

4.1.2 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the aluminum alloy, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with Military Standard MIL-STD-105. The inspection levels and acceptable quality levels shall be as indicated in Table I. Unit of product for examination purposes shall be the gage.

Table I. Sampling for Examination

Type Defect	Inspection level	AQL (percent defective)
For visual examination		
Major defects	II	4.0
Minor defects	II	6.5
For dimensional examination	S-3	4.0

4.2.2 For tests. Sampling for tests shall be conducted in accordance with MIL-STD-105.

4.3 Examination. The gage shall be examined to determine compliance with all requirements contained in this specification. Unit item shall be examined for defects including, but not limited to, those listed in Table II.

Table II. Classification of Defects

Categories	Defects
Major	
101	Unit gage not finished smoothly.
102	Circular openings and plate edges not free of slivers, burrs or sharp edges.
103	Unit gage, with plates in closed position, not with even sides.
104	Marking of sizing numerals missing, illegible or incomplete.
105	Plate surfaces not free of roughness, gouge marks or indentations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

Table II. Classification of Defects (Cont'd)

	106	Plates not free of bends or warpage.
	107	Clear oxidized finish not applied as specified.
	108	Plate surfaces not free of metal protrusions resulting from stamping of numerals.
	109	Bolts, nuts and washers in unit gage not free of rough or sharp edges.
	110	Edges surrounding holes not free of distortion..
Minor		
	201	Identification marking illegible incomplete or missing.
	202	Gage plates not secured so as to facilitate selection of any one plate for ready use.
	203	Plates not secured sufficiently to keep from swinging freely around the bolt axis.
	204	Gage plates not assembled as shown in drawing.

4.3.1 Dimensional examination. The gages shall be examined for defects in dimensions. Any dimension not within the tolerance specified herein (see drawing) shall be classified as a defect.

4.4 Tests. Tests shall be conducted to determine compliance with specification requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Unit of issue. One gage, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in the following table shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

Table III. Packaging Quantities

Unit package	Intermediate package	Exterior container
1 unit	12 units	144 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units may be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

5.1.3.1 Unit package. Unit package shall be a box of appropriate size and design constructed in accordance with PPP-B-566 or PPP-B-676, except commercial colors will be acceptable, or PPP-B-636, type CF, class domestic. Closure shall be adequate to prevent accidental opening under normal handling.

5.1.3.2 Intermediate package. Intermediate package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class weather-resistant. Boxes shall be closed by taping the top and bottom flaps with 2 inch wide adhesive conforming to MMM-A-250 or metal stitches is permitted.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest reate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

5.3.1 Interior packages. Each unit package and each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.2 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Gage is used by the Veterinary Corp. Food Inspection Personnel to verify grade and size of fresh fruits and vegetables.

6.2 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packing (see 5.1 and 5.2).

6.3 This specification covers the following item appearing in the Federal Supply Catalog.

FSN	Item Identification
6695-762-5930	Gage, Fruit and Vegetable Sizing, Aluminum Alloy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

6.4 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet requirements.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DM

Project No. 6095-0073

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

CAUTION

NOTICE TO BIDDERS/OFFERORS

DO NOT CONDITION OR BASE YOUR BID/OFFER ON ANY CURRENT PROCUREMENT ON THE INFORMATION SUBMITTED ON THIS FORM SINCE ANY CHANGES OR DELETIONS IN THE SPECIFICATIONS MAY RENDER YOUR BID/OFFER NON-RESPONSIVE IN WHICH CASE IT CANNOT BE CONSIDERED FOR AWARD.

Fold

DEFENSE PERSONNEL SUPPORT CENTER
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

DEFENSE SUPPLY AGENCY
OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEFENSE SUPPLY AGENCY

HEADQUARTERS, DEFENSE PERSONNEL SUPPORT CENTER
ATTN: DIRECTORATE OF MEDICAL MATERIEL, CODE ATT
2800 SOUTH 20TH STREET
PHILADELPHIA, PA. 19101

Fold

DPSC FORM 2418
MAR 68

EDITION AUG 66, WILL BE USED UNTI EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

MIL-G-36683(DSA-DM) FSN:

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64, WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T09:01Z
Check the source to verify that this is the current version before use.