The documentation and process conversion measures necessary to comply with this amendment shall be completed by 15 January 1996

INCH-POUND

MIL-S-19500/182D
AMENDMENT 1
15 October 1995

MILITARY SPECIFICATION

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW-POWER
TYPES 2N720A, 2N1893, 2N1893S, JAN, JANTX AND JANTXV

This amendment forms a part of MIL-S-19500/182D, dated 22 April 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.3 Maximum ratings, T_J and T_{STG} column, delete "-65" (three places) and substitute "-55" (three places).

1.4 $V_{CE(SAT)}$ column; delete "0.2".

PAGE 3

4.3.2 Thermal impedance, delete and substitute as follows:

"4.3.2 Thermal impedance $Z_{\theta JC}$ measurements (for qualification only). The $Z_{\theta JC}$ measurements shall be performed in accordance with MIL-STD-750, method 3131.

a. I_H measurement current . . . . . 10 mA.

b. I_H forward heating current . . . . . 28 mA for 2N720A
47 mA for 2N1893 and 2N1893s.

c. t_H heating time . . . . . 10 ms.

d. t_{HD} measurement delay time . . . . . 100 μs maximum.

e. V_{CE} collector - emitter voltage . . 10 V dc.

The maximum limit for $Z_{\theta JC}$ in group A, subgroup 2 for 2N720A = 97°C/W, for 2N1893 and 2N1893s = 58°C/W."

4.3.2.1 delete paragraph.

4.4.1 delete and substitute as follows:

"4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with MIL-S-19500, and table I herein."

PAGE 4

4.4.2 at end of paragraph, add the following:

"B3 2037 Test condition A"

4.4.4, group E2, method column; delete "1038" and substitute "1039".

4.5.2, a; delete "47 mA dc" and substitute "50 mA dc".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:34Z
Check the source to verify that this is the current version before use.

PAGE 5

Table I, subgroup 2, delete Thermal impedance testing entirely.

Table I, subgroup 2, conditions column $V_{(BR)CER}$, delete "I_C = 100 mA dc" and substitute "I_C = 10 mA dc",

Table I, subgroup 2, symbol column $V_{CE(sat)}$, minimum limits column; delete ".3".

Table I, subgroup 2, delete Forward-current transfer ratio, symbol h_{fE4} testing entirely.

PAGE 6

Table I, subgroup 4 open-circuit output capacitance, conditions column; delete "100 kHz ≤ f ≤ <Hz" and substitute "100 kHz ≤ f ≤ MHz".

End of table I, delete note 2/ entirely.

PAGE 17

Delete in its entirety and substitute "CONCLUDING MATERIAL" as printed herein.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 17

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19, 85, 99

Preparing activity:
DLA -ES

(Project 5961-1726-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:34Z
Check the source to verify that this is the current version before use.