This documentation process conversion measures necessary to comply with this revision shall be completed by 30 August 2000.

INCH-POUND

MIL-PRF-19500/182E
AMENDMENT 2
3 July 2000
SUPERSEDING
AMENDMENT 1
16 June 2000

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, TRANSISTOR, NPN, SILICON, LOW-POWER
TYPES 2N720A, 2N1893, 2N1893S, JAN, JANTX, AND JANTXV

This amendment forms a part of MIL-PRF-19500/182E, dated 29 July 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 1.3 Maximum ratings. Delete table in it's entirety and replace with;

Type	P_T 1/ T_C = +25°C	P_T 2/ T_A = +25°C	V_{CBO}	V_{EBO}	V_{CEO}	I_C	V_{CER} R_{BE} = 10 Ω	T_J and T_{STG}	$R_{\theta JA}$
	W	W	V dc	V dc	V dc	mA dc	V dc	°C	°C/W
2N720A	1.8	0.5	120	7	80	500	100	-65 to +200	325
2N1893	3.0	0.8	120	7	80	500	100	-65 to +200	175
2N1893S	3.0	0.8	120	7	80	500	100	-65 to +200	175

1/ Derate linearly at 10.3 mW/°C for type 2N720A and 17.2 mW/°C for type 2N1893 and 2N1893S for T_C > +25°C.
2/ Derate linearly at 3.08 mW/°C for type 2N720A for T_A > +37.5°C and 5.7 mW/°C for type 2N1893 and 2N1893S for T_A > +60°C.

PAGE 3

Figure 1, Dimensions table, Delete the CH dimensions "inches .065 min, .085 max, metric 1.65 min, 2.16 max", replace with "inches .170 min, .210 max, metric 4.31 min, 5.33 max".

PAGE 4

Note 11. Delete in it's entirety and substitute with, "For transistor type 2N1893, dimension LL shall be 1.5 inches (38.1) mm minimum and 1.75 inches (44.4 mm) maximum."

Note 12. Delete in it's entirety and substitute with, "For transistor type 2N1893S, dimension LL shall be 0.5 inches (12.7) mm minimum and 0.75 inches (19.0 mm) maximum."

PAGE 5

4.3.1. Power burn-in conditions. Delete 4.3.1 completely and replace with;

"4.3.1. Power burn-in conditions. Power burn-in conditions are as follows: V_{CB} = 10 - 30 V dc. Power shall be applied to achieve T_j = +135°C minimum and a minimum P_D = 75% of P_T maximum rated as defined in paragraph 1.3 herein."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:34Z
Check the source to verify that this is the current version before use.

PAGE 8

Table I, subgroup 2, Collector to base cutoff current, Delete the I_{CBO1} value of “10 μA dc” and substitute a value of “100 μA dc”.

Table I, subgroup 2, Emitter to base cutoff current, Delete the I_{EBO1} value of “10 μA dc” and substitute a value of “100 μA dc”.

PAGE 9

Table I Subgroup 3, Forward-current transfer ratio, delete “h_{FE1}” and replace with “h_{FE4}”.

NOTE: The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, CG, MC
Air Force - 13, 19, 99

Preparing activity:
DLA - CC

(Project 5961-2349)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:34Z
Check the source to verify that this is the current version before use.