MILITARY SPECIFICATION

SEMICONDUCTOR DEVICES, THYRISTORS

TYPES 2N1870A, 2N1871A, 2N1872A AND 2N1874A

This amendment forms a part of Military Specification MIL-S-19500/198A(NAVY) dated 17 January 1969.

Page 1

Paragraph 1.3: In the V_{GT} column, delete "R_e = 100 ohms" and substitute "R_e = 1,000 ohms", and in the I_{GT} column, delete "R_e > 10K" and substitute "R_e > 1K".

Page 2

Add paragraph 3.5.1 as follows:

"3.5.1 Polarity. The polarity shall be indicated as shown on figure 4."

Page 3

Table I, Group A inspection, Subgroup 2, Forward on voltage, Details column: Delete "i_{FM} = 4a(pk) pulse" and substitute "i_{FM} = 2a(pk) pulse".

Table I, Group A inspection, Subgroup 2, Exponential rate of voltage rise: Delete and substitute:

" Exponential rate of voltage rise	4231	Bias Cond. B; repetition rate=60pps; 50Ω ≤ R_L ≤ 400Ω; C=.001 ufd min; test duration=15 sec; R_3=1,000 ohms	V_{FBX}	---	---	---
2N1870A		dv/dt=100V/usec; V_{AA}=30Vdc		25		
2N1871A		dv/dt=60V/usec; V_{AA}=60Vdc		55		
2N1872A		dv/dt=40V/usec; V_{AA}=100Vdc		95		
2N1874A		dv/dt=30V/usec; V_{AA}=200Vdc		190		

FSC 5961

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:38Z
Check the source to verify that this is the current version before use.

Page 5

Table II, Group B inspection, Subgroup 2, Gate trigger current, Details column: Delete "R_L > 10,000 ohms" and substitute "R_L = 100 ohms".

User activities:
Navy - SH, AS, OS, MC, CG

Preparing activity:
Navy - EC
(Project 5961-N250)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:38Z
Check the source to verify that this is the current version before use.