MILITARY SPECIFICATION

BENCHES, WORK, GENERAL PURPOSE

This amendment forms a part of Military Specification MIL-B-4173B(USAF) dated 6 February 1969

Page 6

Add paragraph 2.2 - "Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

National Fire Protection Association (NFPA) Standard

No. 70 - The National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

American National Standards Institute (ANSI) Standard

No. C1-1971 - National Electrical Code

(Application for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018.)

Underwriters' Laboratories, Inc. (UL) Standards

(Application for copies of applicable standards should be addressed to the Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, IL 60611; 1285 Walt Whitman Road, Melville, LI, New York 11746; 1655 Scott Boulevard, Santa Clara, CA 95050.)

Factory Mutual Engineering Associates (FMTL)

(Application for copies should be addressed to Factory Mutual Testing Laboratories, 1151 Providence Highway, Norwood, MA 02062.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)"

Source: https://assist.dla.mil -- Downloaded: 20260-17T03:26Z
Check the source to verify that this is the current version before use.

Add paragraph 3.2.1 - "Material thickness. The nominal thickness of the steel sheet used in the fabrication of the various parts of the work bench shall be the manufacturer's standard thickness corresponding to the required gage as long as the thickness approximates the current industry standard relating gage and thickness."

Page 7

Paragraph 3.5.1 - delete and substitute:

"3.5.1 Leg section. The leg section shall consist of two uprights made of heavy formed steel channels with a cross member welded between the uprights approximately 9 inches from the bottom and a rolled pressed steel channel or tie section at least 3 inches wide and not less than 1-3/8 inches deep, welded to the top of uprights. Uprights and cross members shall be of not less than 14 gage steel. Leg top section shall not be less than 12 gage steel. Lower portion of the uprights shall be flared to form an integral foot approximately 2-1/2 inches by 6 inches or otherwise provided with a foot not less than 12 gage steel welded to bottom of uprights approximately 3-3/4 inches by 5-1/2 inches. Uprights, cross member, and top section shall be provided with holes for attachment of top, stringers, and shelf or foot rest as required. Foot shall have holes for attaching uprights to floor."

Paragraph 3.5.2 - line 4, delete "U.S.S. (.0781) metal" and add "steel."

Paragraph 3.5.3 - lines 4 and 5, delete "U.S.S. (.0781) metal" and add "steel."

Paragraph 3.5.4 - line 3, delete "U.S.S. (.0500) inch" and add "steel."

Page 8

Paragraph 3.6.2 - line 2, delete "U.S.S. (.1094) inches in thickness."

Page 9

Paragraph 3.7.1 - lines 3 and 4, delete "U.S.S. (.0375) inch."

Add paragraph 3.8.5 "Codes and Standards. The work benches with electrical outlets shall comply with the applicable requirements of the National Electrical Code, NFPA 70-1971; ANSI C1-1971. Compliance shall be indicated if the bench is accepted, certified, listed, or labeled by a nationally recognized testing laboratory such as, but not limited to: Underwriters' Laboratories, Inc. or Factory Mutual Engineering Corp."

Custodian:
Air Force-84

Preparing Activity:
Air Force-84

Project Number:
7195-F078

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:26Z
Check the source to verify that this is the current version before use.