MILITARY SPECIFICATION

CASE, INTELLIGENCE OFFICER'S SET

1. SCOPE

1.1 This specification covers one type of intelligence officer's field set, designated type M-1.

2. APPLICABLE DOCUMENTS

* 2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

C-F-206	Felt, Sheet. Cloth, Felt, Wool, Pressed
P-D-680	Dry Cleaning Solvent
V-T-276	Thread, Cotton
QQ-S-698	Steel, Sheet And Strip, Low-Carbon
TT-C-490	Cleaning Methods And Pretreatment Of Ferrous Surfaces For Organic Coatings
TT-E-529	Enamel, Alkyd, Semi-Gloss
TT-P-636	Primer Coating, Alkyd, Wood And Ferrous Metal
MIL-A-181	Adhesive, Phenol, Resorcinol, Or Melamine Base
PPP-B-636	Box, Fiberboard

Military

MIL-P-116	Preservation, Methods Of
MIL-D-1000	Drawings, Engineering And Associated List
MIL-E-5272	Environmental Testing Aeronautical And Associated Equipment, General Specification For
MIL-T-5661	Tape And Webbing, Textile, Cotton Reinforced, Woven
MIL-W-6110	Wood, Determination Of Moisture Content Of
MIL-S-7947	Steel, Sheet And Strip (1095) Aircraft Quality
MIL-F-10336	Fiber Sheet Vulcanized
MIL-C-20696	Cloth, Coated, Nylon, Waterproof
MIL-M-46032	Mildew-Resistant Treatment (For Fabric) Copper Processes

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-175	Adhesives. Methods Of Testing
FED-STD-595	Colors
FED-STD-751	Stitches, Seams, And Stitchings

Military

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking And Waterproofing, With Appropriate Test Methods
MS35822	Hinge, Continuous Piano

DRAWINGS

Air Force

43B17006	Handle Assembly-Shipping Case Flush Type
44K19042	Case Assembly-Intelligence Officer's Field Kit, Type M-1

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNITED STATES DEPARTMENT OF COMMERCE

Product Standard PS1-Softwood Plywood-Construction And Industrial

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2) before production is commenced, four sample cases covered by this specification shall be submitted or made available to the contracting officer or his authorized representative for approval in accordance with 4.2. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the supplier of responsibility for compliance with all applicable provisions of this specification. The preproduction sample shall be manufactured in the same facilities to be used for manufacture of the production items.

* 3.2 Materials. The materials specified shall conform to the applicable specifications and requirements specified herein. Materials not definitely specified shall be of the quality normally used for the purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.2.1 Fiber sheet, vulcanized. Vulcanized fiber shall be 0.060 thick conforming to MIL-F-10336.

* 3.2.2 Plywood. Plywood used in the fabrication of the cases shall be 1/4 inch thick. Each of the panels for the cases shall be one piece of plywood conforming to Softwood Plywood, Group 1 or 2, Exterior Type, Grade A-A, sanded two sides, conforming to Product Standard PS 1.

* 3.2.3 Adhesive. Room temperature and intermediate temperature setting adhesive shall conform to type I or II of MMM-A-181, as applicable. High temperature setting adhesive shall conform to the requirements for type II of MMM-A-181 except that the requirements for shear strength by compression loading and for intermediate temperature cure cycle need not apply.

* 3.2.4 Felt, sheet, wood, pressed. The felt shall be 1/4 inch thick conforming to Type I, Classification 16R1, mildew-resistant treated, of C-F-206.

3.2.5 Cloth, coated, nylon, waterproof. The cloth, coated, nylon, waterproof shall conform to Type I, Class 1 of MIL-C-20696. The color shall approximate olive drab 23087 of FED-STD-595.

* 3.2.6 Webbing. The webbing tape for the strap shall be 1-1/2 inches wide, conforming to Type II of MIL-T-5661. The webbing shall be mildew resistance treated in accordance with Type III, Method 3 of MIL-M-46032. The strap shall be mounted securely in a manner to provide free movement in removing and replacing paper sheet material. It shall be attached in the location indicated in Drawing 44K19042.

* 3.2.7 Thread. The thread for seaming and stitching the pocket assembly and webbing strap shall be thread, cotton, machine, soft finish, type IA3, ticket No. 50, 3-ply, conforming to V-T-276. The thread shall be dyed to a shade approximating the color of the coated nylon and webbing

* 3.2.8 Steel, sheet and strip, low carbon. The steel for the angles, partitions, brackets and cleats shall conform to any quality or temper, thickness .032 conforming to QQ-S-698.

* 3.2.9 Steel, sheet and strip, aircraft quality. The steel for the spring clips shall conform to MIL-S-7947.

* 3.2.10 Primer. Primer shall conform to TT-P-636.

* 3.2.11 Enamel. The enamel shall conform to Class A or B of TT-E-529. The color shall be olive drab conforming to Color No. 24087 of FED-STD-595.

* 3.2.12 Hardware. All items of hardware shall be as shown in 44K19042 and 43B17006. Except as otherwise specified herein, commercial tolerances shall apply for metal thicknesses.

* 3.2.13 Rivets and washers. Rivets shall conform to 44K19042. Commercially available washers, compatible with the size of the applicable rivets, shall be used in all locations where rivets are to be peened or curled against fiber. As an alternate, oval head bifurcated (split) rivets, without washers, may be used to attach the right angle bindings only.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.2.14 Wood, solid. Solid wood used in the fabrication of the separators shall be hardwood, any species. The wood shall be uniformly dried without brashness, casehardening, or honeycombing to a moisture content of from 8 to 12 percent when tested as specified in 4.3.3.2. The wood shall be free from knots, warp, decay, hole, split, twist, or other defect affecting appearance or serviceability.

* 3.3 Design and construction. The case shall conform to the design and construction shown in 44K19042 and shall conform to the requirements and dimensions specified herein. The case panels shall be fabricated of fiber covered plywood, with the plywood portion conforming to 3.2.2. The plywood for the case panels shall be covered on both sides with the vulcanized fiber specified in 3.2.1. The top edges of the fiber covered plywood shall be rounded as shown in 44K19042. The case panels shall be aligned and assembled tightly so that the body, lid cover, hardware, supports, drawbolts, guides, and hinges shall mate and function properly.

* 3.3.1 Fiber covering. All plywood case panels, prior to covering with fiber, shall be cleaned of all dust and foreign matter to assure a smooth surface. The vulcanized fiber specified in 3.2.1 shall be bonded to the surfaces of the plywood to present clean, smooth surfaces, free from waves or irregularities. Each surface shall be covered by a single sheet of fiber The thickness of the fiber shall be .060 plus or minus .005 inches. The adhesive bond of fiber to plywood shall show a fiber failure of not less than 95 percent minimum, before panels are primed or enameled, when tested as specified in 4.3.3.1. Application of adhesive to the surfaces, assembly periods, pressing time, pressure and curing temperature shall be in accordance with the adhesive manufacturer's recommendations. The fiber covered plywood panels shall be fabricated by either of the following processes

a. Unit process. The vulcanized fiber and wood veneers shall be glued with the same adhesive, and assembled, pressed and cured in one position.

b. Two step process. The vulcanized fiber shall be bonded to the plywood specified in 3.2 2 with any of the adhesives specified in 3.2.3.

* 3.3.2 Partitions. The partitions shall be fabricated of plywood specified in 3.2.2 and of steel specified in 3.2.8, as applicable, and shall be as shown on 44K19042. Each of the metal to metal partitions shall be fastened with either not less than 4 tubular rivets or 4 spot welds, with one rivet or spot weld approximately 1/2 inch from each end and the other two rivets or spot welds (as applicable) equally spaced. The direction of grain of the face and back veneers of the plywood shall be parallel to the case sides and ends. At time of assembly, the adhesive specified in 3.2.3 shall be applied to the surface of the faying edges of the plywood partitions, except the plywood to metal surfaces which shall be riveted with 4 tubular rivets to each holding side, with one rivet 1/2 inch from each end and the other 2 equally spaced.

* 3.3.3 Angles, brackets, and cleats. The angles, brackets and cleats shall be fabricated of steel specified in 3.2.8 and shall be as shown on 44K19042.

* 3.3.4 Gluing of felt. The sections shall be neatly lined with felt specified in 3.2.4 in the locations shown on 44K19042. Except as otherwise indicated on the drawing, all felt panels shall be securely glued with adhesive specified in 3.2.3. Adhesive shall be applied to the joint surfaces in an adequate and uniform manner as recommended by the glue manufacturer. Clamping or pressing time shall be in accordance with the glue manufacturer's instructions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.3.5 Pocket assembly. The pocket assembly as specified in 44K19042 shall be fabricated of coated nylon cloth specified in 3.2.5. The pocket assembly shall consist of two pockets attached to a backpiece. Hem top of upper and lower pockets 5/8 inch and double stitch 1/4 to 3/8 inch gage, EFb-2. Stitch upper pocket to backpiece at sides and bottom 1/8 inch gage, SSa-1 (sides) and SSaa-1 (bottom). Stitch lower pocket to the backpiece at sides and bottom 1/8 inch gage, SSa-1. Hem sides, top and bottom of pocket assembly 5/8 inch and stitch 1/4 inch gage, EFa-1. The coated nylon cloth for the pockets shall be cut in a manner to permit approximately 1 inch looseness at the top of each pocket and the pocket assembly shall meet the dimensions specified in 44K19042. The head of each rivet shall be on the exterior surface of the case cover and each rivet shall be clinched on a zinc or cadmium plated washer of adequate size

* 3.3.6 Strap. The webbing used for the strap shall conform to 3.2.6. The ends of the webbing shall be hemmed 1/2 inch and stitched with stitching type EFb-1 as shown on 44K19042. One end of the strap shall be riveted in the location shown in 44K19042.

* 3.3.7 Machine stitching. All stitching shall conform to type 301 of FED-STD-751, 10 to 12 stitches per inch for the pocket assembly and 6 to 8 stitches per inch for the strap. Thread shall be as specified in 3.2.7 Thread breaks in stitching shall be overstitched not less than 1/2 inch at the ends, except where held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching. All thread ends shall be trimmed. Seam allowance shall be maintained with seams properly sewn so that no runoffs, twists, pleats, puckers or open seams will result

* 3.3.8 Driving of rivets. The holes for rivets in fiber, plywood, and hardware shall be not more than 0.015 inch greater than the diameter of the applicable rivets. Rivet length of tubular rivets shall be sufficient to permit a minimum of 1/16 inch clinch to securely set or head the rivet ends by peening or curling. The length of split rivets, when used to attached the right angle bindings (see 3.2.12), shall be sufficient to provide a minimum of 1/8 inch clinch. Split rivet legs shall be clinched over into the fiber covered plywood and no leg ends of rivets shall be exposed.

* 3.3.9 Hardware. All hardware shall be attached in the locations shown in 44K19042.

* 3.3.9.1 Lid supports. Two lid supports as specified in 44K19042 shall be installed, one on each side of the case, to act as stops holding the cover securely at an angle of approximately 85 degrees with the top of the case when the cover is open and fastened to case with split rivets and washers so case cover will open and close properly.

* 3.3.9.2 Handles. One flush type handle conforming to 43B17006 shall be mounted on each end of the case.

* 3.3.9.3 Continuous hinges. The case body and lid shall be equipped with continuous hinges MS35822-3C, extending the length of the case and lid as shown in 44K19042, and riveted in place with tubular rivets (with washers) clinched on the inside. The hinge shall have a fairly stiff action.

* 3.3.9.4 Guides. Four guides shall be provided to keep the cover correctly aligned with the body of the case when the cover is closed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.3.9.5 Glides. Four glides shall be provided on the bottom of the case, which shall elevate the bottom of the case 3/8 inch above the surface on which the case rests and fastened securely with split rivets.

* 3.3.9.6 Bolts. The cover and case body shall each be further secured with ten hexagonal head slotted bolts with ferrules. The bolts shall be locked as specified in 44K19042.

* 3.3.10 Plastic boxes. The case shall be provided with eight ribbed plastic boxes with plastic partitions in accordance with 44K19042. The boxes and partitions shall be constructed of a clear transparent plastic material which shall not be less than 0.050 inch or more than 0.060 inch thick. The boxes shall be provided with covers that snap securely closed. Each box shall be provided with a leather tab on one end to permit easy removal of the box from its location in the case.

* 3.3.11 Wood separators. The finished wood separators shall be of a size to fit tightly in their respective compartments and shall be removable.

* 3.4 Interchangeability. All parts having the same manufacturer's part number shall be directly and completely interchangeable with each other with respect to dimensions, installation and performance. Changes in manufacturer's part numbers shall be governed by the drawing number requirements of MIL-D-1000.

* 3.5 Finish.

* 3.5.1 Metal surface preparation. Prior to priming, the surfaces of steel components (except rivets, washers, and bolts) shall be given a cleaning and surface preparation conforming to type I or II of TT-C-490.

* 3.5.2 Preparation of fiber covered plywood panels. The edges of the fiber covered plywood panels shall be treated with a protective fungicide. The protection fungicide shall consist of a 5 percent solution of pentachloraphenol in solvents conforming to P-D-680. There shall be no water repellents in the solution. The solution shall be applied after all cuts and holes have been made in the panels, but before assembly of the case. Two coats of the fungicide solution shall be applied to all exposed edges of the fiber covered plywood panels.

* 3.5.3 Priming.

* 3.5.3.1 Fiber covered surfaces and spot welded metal partitions (when applicable). Prior to attachment of bindings, corners, felt, strap, and hardware, a coat of primer specified in 3.2.10 shall be applied to all inside and outside surfaces of the case. The prime coat shall level out to produce a dry film without runs, wrinkles, streaks or areas of no film, and shall be free from grit or coarse particles. Forced drying is permitted, providing that a surface temperature of 140° Fahrenheit (F) is not exceed and the relative humidity of surrounding air is maintained at 30 to 50 percent.

* 3.5.3.2 Metal parts. Prior to attaching, all metal parts including metal partitions which are to be riveted, when applicable, except rivets, washers, screws, and bolts, shall be given a coat of primer specified in 3.2.10. Baking of the primer is permissible and the dry film shall level out to a smooth uniform film.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.5.3.3 Plywood for partitions. Prior to priming, all visible voids in the core of the plywood components shall be filled with a commercial wood filler and sanded smooth.

* 3.5.4 Enameling. After attachment of all hardware, the complete case (excluding the lid supports, wood blocks, plastic boxes, pocket assembly, felt, and strap shall be given a full hiding coat of enamel specified in 3.2.11. All surfaces shall be thoroughly dry prior to attaching the lid supports, pocket assembly, felt, strap, or inserting the plastic trays and wood separators.

* 3.5.5 Finish of wood separators. All wood separators, prior to installation, shall be sanded smooth and cleaned of dust and foreign matter. All surfaces of the separators shall then be given two coats of commercially available clear lacquer or varnish. The coated wood separators shall be thoroughly dry before installation in the case.

* 3.6 Identification of product. The case shall be permanently and legibly marked in center of outside top surface of the lid by stenciling in letters 1/4 inch with black No. 17038 of FED-STD-595 with the following information

Case, Intelligence Officer's Set
Type M-1
Specification MIL-C-4004B
Part No.
Mfr's Serial No. _____
Order No. _____
Stock No. _____
(Mfr's Name or Trademark)
US Property

* 3.6.1 Order number. The contract number shall be placed on the identification listing in the place designated "Order Number."

* 3.6.2 Stock number. The stock number marked in the space provided in the nameplate shall be as specified by the procuring agency.

3.7 Workmanship.

3.7.1 General. The case, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness and thoroughness of marking, welding, finishing and riveting. Metal components shall be free from tears and scuffs. There shall be no splits in the wood or plywood. Enamel shall be dry, free from runs, drops, wrinkles, orange peel, streaks, area of thin or no film, and grit or coarse particles imbedded in the finish. All surfaces shall be thoroughly dry before stacking and packing. The lid shall not stick to the body, and there shall be no splintering of plywood or exposed bare wood surfaces, when opened from the closed position. The lid shall not require the use of a tool in opening. Parting agents, such as beeswax, may be applied to contacting surfaces to assist in meeting this requirement.

3.7.2 Riveting. Riveting operations shall be carefully performed to insure that the rivets are tight and satisfactorily clinched.

* 3.7.3 Welding. Spot welds, when applicable, shall be sound, smooth, and free from pits, burns or flashes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 3.7.4 Cleaning. The finished case shall be cleaned of metal chips, dust and other foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 First article sample inspection. When a preproduction sample is required, it shall be examined for defects listed in Table III, dimensions specified on drawing 44K19042 and tested in accordance with 4.4.

* 4.3 Sampling for inspection. Sampling for inspection shall be made in accordance with the provisions set forth in MIL-STD-105, except where otherwise indicated hereinafter.

* 4.3.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

* 4.3.2 In-process inspection. Inspection shall be made during the manufacturing process for the requirements specified in Table I to establish that no deviation is made from indicated requirements. Whenever nonconformance is noted, correction shall be made to affected items and process.

TABLE I - In-Process Inspection

Requirement, operation, or assembly	Requirement Paragraph
Direction of grain of plywood partition	3.3.2
Gluing of felt	3.3.4
Sewing of pocket assembly	3.3.5 and 3.3.7
Driving of rivets	3.3.8
Metal surface preparation	3.5.1
Protective fungicide treatment	3.5.2
Primer application	3.5.3.1 and 3.5.3.2

* 4.3.3 Intermediate testing.

* 4.3.3.1 Vulcanized fiber adhesion test. The test specified in FED-STD-175, Method 1041, shall be performed on fiber covered plywood to determine compliance with 3.3.1. The inspection lot shall be all the fiber covered plywood offered for inspection at one time. The sample unit shall be five (5) specimens, 4 inch square, each selected from a different piece and from different locations on the fiber covered plywood. The inspection level shall be S-2. Failure of any specimen shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 4.3.3 Moisture content tests shall be performed on each lot of wood at time of fabrication for moisture content in accordance with MIL-W-6110 to determine compliance with 3.2.14. Three determinations shall be taken on each sample unit and the results shall be the average of the three determinations. The sample unit shall be one piece of wood. The inspection level shall be S-2 with an acceptable quality level (AQL) of 2.5 expressed in terms of defects per hundred units.

* 4.3.4 End item inspection. The inspection lot shall consist of all completely fabricated cases offered for inspection at one time. The sample unit shall be one completely fabricated case.

* 4.3.4.1 Visual examination. Examination of the cases shall be in accordance with the classification of defects in Table III The inspection level shall be level II with an AQL of 2.5 for major defects, 6.5 for major and minor A, and 25.0 total, expressed in terms of defects per hundred units.

* 4.3.4.2 Dimensional examination. Dimensional examination shall be made of completed case, to determine compliance with this specification and applicable drawings. Any dimension that is not within the specified requirements shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 defects, expressed in terms of defects per hundred units.

* 4.3.5 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing and marking requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with Table II. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 with an AQL of 2.5, expressed in terms of defects per hundred units.

TABLE II - Examination of Packaging, Packing and Marking

Examine	Defect
Preservation	Missing, not as specified or improperly applied
Marking (exterior)	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application
Materials	Any component missing or damaged
Workmanship	Inadequate application of component, such as incomplete locking, cushioning, closure of container flaps, inadequate stapling.

4.4 Preproduction testing.

* 4.4.1 Test sample. Three first article cases shall be tested by the procuring activity in accordance with 4.4.2, or, when so specified in the contract, at the contractor's plant or an approved testing laboratory under the supervision of the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III - Classification of Defects

Examine	Defect	Classification Major	Minor A	Minor B
Finish of enameled surfaces (All components	Not finished	X		
	Wrong type			X
	Not a close match to specified color or discolored			X
	Not adherent, e.g., blistered, peeled or flaked		X	
	Not smooth and uniform, e.g., run, drop, streak or evidence of think coat (prime coat shows through):			
	Exterior		X	
	Interior			X
	Not clean		X	
	Area of no film	X		
	Wet or tacky		X	
	Foreign matter imbedded			X
Construction and workmanship (General)	Any component not fabricated of the specified material	X		
	Component not as specified	X		
	Fiber covering contains bubble, gouge, tear, hole, wave, ripple or seam		X	
	Case not square, e.g., panels not assembled at right angles	X		
	Any operation missing, or is improperly performed	X		
	Any functioning component or assembly will not operate as intended	X		
	Component or assembly will function but requires undue force to operate		X	
	Lid binds in opening and closing		X	
	Any component missing, broken, cracked, split, torn, or is not specified type or size (except as otherwise indicated herein)	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III - Classification of Defects (Cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Construction and workmanship (General)	Component not in specified location, is misaligned or will not mate with its mating component	X		
	Any component not securely attached (where required)	X		
	Any knot, hole, decay, warp, or split in wood or plywood		X	
	Burr or sharp edge in metal component		X	
	Machine or die mark in metal		X	
	Component malformed or bent out of shape		X	
	Metal on case exterior dented or damaged		X	
	Metal in case interior dented or damaged			X
	Contains hole, where hole is not required	X		
	Hardware not flush fit to surface		X	
Plastic Box	Missing, wrong type or size	X		
	Not clear, transparent plastic		X	
	Not provided with hinged cover	X		
	Cover will not snap securely closed		X	
	Leather tab missing from any box		X	
	Split, cracked, or otherwise impaired		X	
	Discolored or dirty			X
	Not ribbed as required		X	
	Any plastic partition missing		X	
	Plastic partition excessively loose in ribs			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of defects (Cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Webbing Strap	Missing	X		
	Wrong color		X	
	Abrasion mark resulting in weak place	X		
	Broken or missing end or pick			X
	Hole, cut, tear or frayed edges	X		
	Multiple float		X	
	Not secured as specified		X	
	Wrong stitching type		X	
	Open seam		X	
	Needle chews		X	
	Number of stitches per inch less or more than specified		X	
	Spot or stain in fabric			X
	Thread ends not trimmed			X
	End of stitching not backstitched			X
Pockets	Any missing	X		
	Wrong color		X	
	Coating spotted or stained			X
	Any uncoated area		X	
	Coating blistered or delaminated			X
	Not mounted in specified location	X		
	Stitches missing, broken or not secure		X	
	Wrong color thread			X
	Wrong seam or stitch type		X	
	Open seam		X	
	Needle chews		X	
	Number of stitches per inch less or more than specified		X	
	Seam twisted, pleated, or puckered			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III - Classification of Defects (Cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Pockets	Thread ends not trimmed			X
	End of stitching not caught in other seam or stitching not backstitched			X
Felt	Any missing	X		
	Wrong color		X	
	Spotted or stained			X
	Hole, cut, or tear	X		
	Waviness or inability to lay flat		X	
	Not glued, where required		X	
	Glued, where not required		X	
	Evidence that insufficient glue has been used		X	
	Does not fit neatly and evenly in or on applicable compartment		X	
Plywood Partitions	Not constructed of 1/4 inch thick, 3-ply plywood	X		
	Not reinforced as specified	X		
	Not secured as specified	X		
	Knothole		X	
	Knot showing through finish		X	
	Veneer chipped or splintered		X	
	Veneer delaminated			X
	Partition warped			X
	Edge of partition not smooth			X
	Faying parts not flush with each other at top		X	
	Machine mark or gouge in plywood			X
	Open joint over 1/32 inch at any point		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III - Classification of Defects (Cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Metal Partitions	Not attached as specified	X		
	Faying parts not flush with each other at top		X	
	Not trimmed neatly or evenly			X
Hardware	Wrong type, e.g., supports not left hand and right hand as required	X		
	Not attached as specified	X		
	Loose or insecurely attached		X	
Solid Wood separators	Not fabricated of hardwood		X	
	Split, check, shape, honeycomb or hole		X	
	Warped, twisted or otherwise out of required shape			X
	Loose or unsound knot		X	
	Sound, tight knot			X
	Not coated on all surfaces with clear varnish or lacquer			X
	Not smooth			X
	Poor fit in compartment		X	
Rivets & riveting	More than one rivet missing	X		
	One rivet missing		X	
	Rivet wrong size or wrong type			X
	End of rivet not properly peened e.g., results in sharp edge or is inadequately secured		X	
	Washer missing, where required			X
	End of bifurcated rivet protrudes in sharp point or results in rough surface		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

TABLE III - Classification of Defects (Cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Rivets & riveting	Plywood splintered by rivets or riveting			X
	Any rivet loose, i.e., can be removed by hand		X	
	Any rivet loose but cannot be removed by hand			X
	Head of rivet on wrong side of component			X
	Rivet head broken off		X	
	More than two rivet heads cocked more than 1/32 inch			X
Bolts & screws	Missing, where required	X		
	Head broken off		X	
	Cocked			X
	Thread damaged			X
	Not drawn tight			X
Spot welding	Missing or not fused where required		X	
	Metal damaged by welding		X	
	Pitted			X
	Metal burnt through		X	
Identification marking	Missing, illegible, incomplete, wrong text, not specified type or size, or not applied in specified location			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

* 4.4.2 Tests. The preproduction test shall consist of the following tests.

* 4.4.2.1 Environmental. The case shall be subjected to the following tests conducted in accordance with MIL-E-5272. There shall be no damage as a result of each test.

* 4.4.2.1.1 High temperature.

* 4.4.2.1.2 Low temperature.

* 4.4.2.1.3 Humidity. No corrosion shall result.

* 4.5 Inspection of the preservation, packaging, packing and marking for shipment and storage. Sample items or packs and the inspection of the preservation, packaging, packing and marking for shipment and storage shall be in accordance with the requirements of Section 5, or the documents specified therein.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Each case shall be preserved and packaged in accordance with MIL-P-116, Method III. Interior cushioning shall be in accordance with MIL-STD-1186.

5.1.2 Level C. Each case shall be preserved and packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving activity. This level may be the supplier's commercial practice when it meets the requirements of this level.

5.2 Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A and B. Each case preserved and packaged as specified in 5.1.1 shall be packed in a class weather resistant container conforming to PPP-B-636, grade V3c. Closure and strapping shall be in accordance with the appendix of the referenced specification. Containers shall be of uniform size and shape and of minimum tare and cube.

5.2.2 Level C. Packages that require overpacking for acceptance by the carrier shall be packed in exterior type shipping containers in a manner that will insure safe transportation to the point of delivery. Containers shall conform to carrier rules and regulations as applicable to the mode of transporation.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The case covered by this specification is intended for storage and transporting the items comprised in the intelligence officer's field kit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following

a. Title, number, and date of this specification.

b. Selection of applicable levels of preservation, packaging and packing (see 5.1 and 5.2).

c. Preproduction test conditions (see 4.4).

d. Whether first article is required (see 3.1).

6.2.1 Preproduction test samples. Four cases will be submitted to the contracting officer as a preproduction sample to be subjected to the preproduction test to determine compliance with the requirements of this specification. The point of inspection for these tests should be specified.

* 6.3 The margins of this specification are marked with an asterisk to indicate where changes (additons, moidifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian
Air Force - 82

Review Activity
Air Force - 82

Preparing Activity
Air Force - 82

Project No. 8460-F041

*U S GOVERNMENT PRINTING OFFICE 1970 - 393-098/8-8682

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No 22-R255

INSTRUCTIONS This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

DEPARTMENT OF THE AIR FORCE

OFFICIAL BUSINESS

SAN ANTONIO AIR MATERIEL AREA
SERVICE ENGINEERING DIVISION (SANEOB)
KELLY AFB, TEXAS 78241

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T03:18Z
Check the source to verify that this is the current version before use.