MIL-C-60996A (PA)
15 August 1974
SUPERSEDING
MIL-C-60996 (MU)
11 March 1968

MILITARY SPECIFICATION

CHARGE, DEMOLITION ROLL, M186
PARTS, LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the parts, loading, assembling and packing for one type of demolition charge designated as Charge, Demolition Roll, M186.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

*MILITARY

MIL-P-116 - Preservation, Packaging, Methods of

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

FEDERAL

FED-STD-151 - Metals; Test Methods

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-1168- Lot Numbering of Ammunition

DRAWINGS

*U.S. ARMY PICATINNY ARSENAL

9216715 - Box, Wirebound, Packing, Ammunition for Charge, Demolition Roll, M186
9297231 - Charge, Demolition Assembly M186

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

*(For meaning of asterisk see paragraph 6.4)

3. REQUIREMENTS

3.1 Material. - Materials and parts shall be in accordance with applicable drawings and specifications.

3.1.1 Reclaimed material. - A blend of reclaimed and virgin plastic material may be used provided the requirements of this specification are met. The blend shall be limited to 70 percent minimum virgin material. The reclaimed material shall be clean scrap, free from any type of foreign material not related to the blend. Floor sweepings will not be accepted as clean scrap.

*3.2 Assembly. - The assembly shall comply with all requirements specified on drawing (dwg.) 9297231 and with all requirements specified in applicable specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

3.3 Susceptibility to cracking. - The reel parts assembly (see dwg. 9211461) shall not crack or separate when subjected to temperature conditioning at minus 65 degrees Fahrenheit, plus or minus 5 degrees, for a period of 24 hours, plus or minus 1/2 hour.

3.4 Workmanship. - All parts and assemblies shall be fabricated and loaded in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), holes, tears, voids, porosity, warpage, excess flush, cracks, chipped edges, blisters, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.5 First article inspection. - The specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - The responsibility for inspection shall comply with MIL-A-48078 (PA).

4.1.1 Submission of product. - At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agents authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Classification of inspections. - See MIL-A-48078

4.3 First article inspection. - Prior to the start of regular production the contractor shall submit a first article sample to a Government approved facility (see 6.2b) as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample will consist of 25 complete sets of parts and sub-assemblies (i.e. 25 each of every component and sub-assembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

TABLE 1

Part Description	Drawings	Quantity
Inert Parts Assembly	9211461	25
Blasting Cap Holder M8	8887302	25

4.3.2 Inspections to be performed. - The First Article parts submitted in accordance with paragraph 4.3.1 will be submited by the Government to any or all the requirements of the applicable drawings and to the inspections of Table I. All inspections listed in Table I shall be classifiied Major unless otherwise specified.

4.3.3 Rejection. - (see MIL-A-48078 (PA)

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. - See MIL-A-48078 (PA) Lot numbering as required shall be in accordance with MIL-STD-1168 Each lot of demolition charges shall contain (a) Parts of one kind from one supplier (b) Flexible explosive from not more than one lot.

4.4.2 Examination. - See MIL-A-48078 (PA). The examinations listed in the following tables and subparagraphs shall be performed on inspection lots of the components or assemblies designated in the Classification of Defects and Test tables or paragraphs. Sampling plans for major or minor defects shall be in accordance with MIL-STD-105, Inspection Level II, unless otherwise specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9214256
4.4.2.1	Core				NEXT HIGHER ASSEMBLY 9211461
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major:B					
131.	Outside diameter across web, maximum (max.)		0.40	3.2	Gage
132.	Length of web pilot (min)		0.40	3.2	Gage
133.	Crack or split		0.40	3.2	Visual
Minor:					
201.	Thickness of rim		0.65	3.2	Gage
202.	Inside diameter of hub		0.65	3.2	Gage
203.	Length of rim		0.65	3.2	Gage
204.	Width of slot		0.65	3.2	Gage
205.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Disk		9214259
			NEXT HIGHER ASSEMBLY 9211461

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:B					
131.	Crack or split		0.40	3.2	Visual
132.	Length of hub		0.40	3.2	Gage
133.	Width of slit of hub		0.40	3.2	Gage
134.	Thickness of hub		0.40	3.2	Gage
135.	Perpendicularity of hub with respect to base		0.40	3.2	Gage
Minor:					
201.	Outside diameter		0.65	3.2	Gage
202.	Inside diameter		0.65	3.2	Gage
203.	Thickness of base		0.65	3.2	Gage
204.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

8

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211460
4.4.2.3	Explosive, Flexible				NEXT HIGHER ASSEMBLY 9211459
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:A					
101.	Pressure sensitive tape missing or improperly applied		0.40	3.2	Visual
Minor:					
201.	Total length (min)		0.65	3.2	Gage
202.	Width		0.65	3.2	Gage
203.	Thickness (min.)		0.65	3.2	Gage
204.	Markings misleading or unidentifiable		0.65	3.2	Visual
205.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211461
4.4.2.4	Parts Assembly, Charge Demo Roll, M-186				NEXT HIGHER ASSEMBLY 9211459
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:A					
101.	Parts improperly or inadequately secured		0.40	3.2	Visual
Minor:					
201.	Distance between disks (min.)		0.65	3.2	Gage
202.	Perpendicularity of sides of disk with hub		0.65	3.2	Gage
203.	Rope missing		0.65	3.2	Visual
204.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
*4.4.2.5	Holder, Blasting Cap, M-8	1 OF 1	8887302
			NEXT HIGHER ASSEMBLY 9211459

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major:B					
131.	Small width of explosive charge opening		0.40	3.2	Gage
132.	Blasting cap retaining dimples missing or inadequate		0.40	3.2	Visual
133.	Raised nibs missing or deformed		0.40	3.2	Visual
Minor:					
201.	Width of clip opening (max.)		0.65	3.2	Gage
202.	Length of blasting cap clip		0.65	3.2	Gage
203.	Diameter of blasting cap clip		0.65	3.2	Gage
204.	Overall width of explosive charge		0.65	3.2	Gage
205.	Overall length of holder		0.65	3.2	Gage
206.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9211459
4.4.2.6	Charge, Demolition Roll, M-186				NEXT HIGHER ASSEMBLY 9297231 9277231
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:	None defined				
Minor:					
201.	Explosive improperly coiled		0.65	3.2	Visual
202.	Carrying rope knot improper		0.65	3.2	Visual
203.	Markings misleading or unidentifiable		0.65	3.2	Visual
204.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 9216714
4.4.2.7	Bag, Packing, Ammunition, For Charge Demo Roll, M186		NEXT HIGHER ASSEMBLY 9297231

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:	None defined				
Minor:					
201.	Snap fasteners missing, improperly located or inadequately attached		0.65	3.2	Gage
202.	Pull tabs missing or improperly attached		0.65	3.2	Visual
203.	Carrying strap improperly attached		0.65	3.2	Visual
204.	Stitching improper or incomplete		0.65	3.2	Visual
205.	Improper thread		0.65	3.2	Visual
206.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9297232
*4.2.2.8	Bag, Packing For Holder Blasting Cap, M8				NEXT HIGHER ASSEMBLY 9298299
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:	None defined				
Minor:					
201.	Bag Height		0.65	3.2	Gage
202.	Bag Width		0.65	3.2	Gage
203.	Location of lettering from base of bag		0.65	3.2	Gage
204.	Lettering height		0.65	3.2	Gage
205.	Marking missing, misleading or unidentifiable		0.65	3.2	Visual
206.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS MIL-C-60996A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
*4.2.2.9	Bag Assembly, with Blasting Cap Holder		9298299
			NEXT HIGHER ASSEMBLY 9297231

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:A					
101.	Heat Seal Test	13	-	9298299	MIL-P-116
102.	Incorrect number of blasting cap holders		0.40	3.2	Visual
Minor:					
201.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
*4.2.2.10	Charge Demolition Assembly M186				9297231
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:	None defined				
Minor:					
201.	Any component missing from bag		0.65	3.2	Visual
202.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60996A (PA)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Box, wirebound, packing (prior to closing)		9216715
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:B					
131.	Sealing strip incomplete or badly wrinkled		0.40	3.2	Visual
132.	Bag punctured, torn or cut		0.40	3.2	Visual
133.	Incorrect number of demolition charges		0.40	3.2	Visual
134.	Blasting cap holders in bag assembly missing from canvas bag		0.40	3.2	Visual
135.	Snap fasteners improperly secured		0.40	3.2	Visual
Minor:					
201.	Marking misleading or unidentifiable		0.65	3.2	Visual
202.	Any packing material missing		0.65	3.2	Visual
203.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

SARPA-QA FORM 2567 FEB 74

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Box, wirebound, packing sealed				9216715 NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical:	None defined				
Major:B					
131.	Box damaged to extent that contents are exposed or liable to become exposed		0.40	3.2	Visual
Minor:					
201.	Car seal missing, unsealed or improperly positioned		0.65	3.2	Visual
202.	Contents loose		0.65	3.2	Visual
203.	Marking misleading or unidentifiable		0.65	3.2	Visual
204.	Evidence of poor workmanship		0.65	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Susceptibility to cracking (see 3.3). - Major B defect - Samples of 15 parts assemblies (see dwg. 9211461) shall be selected from each lot for these tests. The tests shall be performed as specified in 4.5.1. If one or more assemblies fail to comply with the specified requirements, the lot shall be rejected. Samples complying with the requirement may be returned to the lot.

4.4.3.2 Hardness of M8 blasting cap holder (see dwg. 8887302). Major B defect - Twenty (20) blasting cap holders shall be selected from each heat treated batch for test. If any holder fails to comply with the applicable requirement, the heat treated batch represented by the sample shall be rejected. The test shall be performed as specified in 4.5.2 using equipment in accordance with 4.4.4. Samples complying with the requirement may be returned to the lot.

4.4.3.3 Heat seal test of sealed bag (see dwg. 9298299). - Major B defect - Sampling, acceptance criteria and test procedures for this test shall be as required in MIL-P-116.

4.4.4 Inspection Equipment. - The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.4). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Test Methods and Procedures

4.5.1 Susceptibility to cracking at cold temperature. - The reel parts assembly shall be placed in a cold temperature chamber in such a manner that no external mechanical stresses are applied. The assembly shall be maintained at a temperature of minus 65 degrees Fahrenheit, plus or minus 5 degrees, for a period of 24 hours, plus or minus 1/2 hour. Observation shall be made for evidence of cracks, including hairline cracks, as evidence of noncompliance with 3.3. Test equipment shall be in accordance with 4.4.4.

4.5.2 Hardness of M8 blasting cap holder. - The blasting cap holder shall be tested for hardness as specified in Federal Standard No. 151, Method 243.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

*5. PREPARATION FOR DELIVERY

5.1 Packaging Level A. - The demolition charge shall be packaged in accordance with dwg. 9216715.

5.2 Packing Level A. - The demolition charge shall be packed in accordance with dwg. 9216715.

5.3 Marking. - Markings shall be in accordance with dwg. 9216715.

6. NOTES

6.2 Ordering Data. - Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Provisions for submission of first article samples.
c. Provisions of MIL-A-48078.

6.2 Submission of designs for approval. - (see 6.2.3 of MIL-A-48078 (PA). Designs shall be submitted for approval to Commander: Picatinny Arsenal, ATTN: SARPA-QA-T Dover, New Jersey 07801.

6.3 Distribution of ammunition data cards. - Distribution of data cards shall include the following: Commander, Picatinny Arsenal, ATTN: SARPA-QA-A-M Dover, New Jersey 07801.

Asterisks -

6.4 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-104

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:08Z
Check the source to verify that this is the current version before use.