MILITARY SPECIFICATION

PRIMER, STAB, T103E1
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of stab primer designated as Primer, Stab T103E1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-116 – Preservation, Method of.

MIL-A-2550 – Ammunition and Special Weapons; General Specification for.

MIL-I-45607 – Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 – Sampling Procedures and Table for Inspection by Attributes (ABC-STD-105).

MIL-STD-109 – Quality Assurance Terms and Definitions.

MIL-STD-650 – Explosives: Sampling, Inspection and Testing.

MIL-STD-1235 – Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

7548103 – Box, Set-up, Packing, Ammunition, Outer for Small Explosive Components.

7548104 – Box, Set-up, Packing, Ammunition, Inner for Small Explosive Components.

7548118 – Box, Packing, Ammunition, for Primer, Stab.

8787058 – Primer, Stab. T103E1 Assembly.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

ORDNANCE CORPS

IEL-8787058 — Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Primer. The primers shall comply with all requirements specified on Drawing (dwg.) 8787058 and with all requirements specified in applicable specifications.

3.3 Moisture content of primer mixture. The moisture content of the primer mixture used in loading the primers shall not exceed 0.30 percent when tested as specified in 4.3.1.

3.4 Functioning.

3.4.1 *Sensitivity.* The primers shall function on the first attempt under an applied energy of 11.85 inch ounces, and shall cause an audible report when fired against a standard lead disc, the test shall be as specified in 4.3.3.1.

3.4.2 *Waterproofness.* The primers shall be waterproof as evidenced by normal functioning after being immersed under a minimum (min.) of 2 in. of water for a min. of 48 hours when tested as specified in 4.3.3.2.

3.5 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all of the quality assurance provisions specified within this specification.

(b) Number of units of product inspected.

(c) Results obtained, by defect code, for all inspections performed.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Statement of findings on the primer mixture and associated ingredients and a certificate of conformance on all material purchased by the contractor when such material is controlled by Government specification referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records .

4.2 Inspection provisions.

4.2.1 *Lot formation.* A lot shall consist of primers produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification, and process changes not affecting safety, performance, or fit, as determined by the Government, shall not necessitate changing the lot interfix number. Lots shall be submitted for inspections in accordance with Standard MIL-STD-105 (or Standard MIL-STD-1235 when applicable). Each lot shall contain:

(a) Parts bearing the same lot interfix number from one manufacturer.

(b) Primer mixture from one batch or blending of batches which results in homogeniety of all primer mixture used in loading the entire primer lot.

4.2.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL-STD-1235 may be used, for defects other than critical, if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Assembly, prior to loading and closing (see dwg. 8787058).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:29Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of inspection	Code No. (see 6.2)
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Interior coating incomplete or inadequate	Visual	01001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01002

4.2.2.2 Assembly (see dwg. 8787058).

Categories	Defects	Method of inspection	Code No.
Critical:			
1.	Cup split or cracked	Visual	02001
Major:	AQL 0.40 percent		
101.	Length, minimum (min.)	Gage	02002
102.	Outside diameter, maximum (max.)	Gage	02003
103.	Identification color missing or incorrect	Visual	02004
104.	Not crimped full 360 degrees	Visual	02005
105.	Lacquer seal incomplete or inadequate	Visual	02006
Minor:	AQL 1.00 percent		
201.	Disc bulged above top of crimp	Visual	02007
202.	Evidence of poor workmanship (see 3.5)	Visual	02008

4.2.2.3 Box, set-up, inner (see dwg. 7548104).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Box damaged	Visual	03001
102.	Number of primers incorrect	Visual	03002
Minor:	AQL 1.00 percent		
201.	Marking misleading or unidentifiable	Visual	03003
202.	Any packing material missing	Visual	03004

4.2.2.4 Box, set-up, outer (see dwg. 7548103).

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Number of inner set-up boxes incorrect	Visual	04001
102.	Sealing strip torn, badly wrinkled, incomplete or otherwise fails to seal the box completely	Visual	04002
Minor:	AQL 1.50 percent		
201.	Box torn, cut or punctured	Visual	04003
202.	Marking misleading or unidentifiable	Visual	04004
203.	Contents move when box is shaken	Manual	04005

4.2.2.5 Outer set-up packing box in barrier bag (when applicable) (see dwg. 7548103).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Barrier bag punctured or torn	Visual	05001
102.	Marking missing, misleading or unidentifiable	Visual	05002
103.	Barrier bag seal incomplete or improperly positioned	Visual	05003
Minor: None defined.			

4.2.2.6 Sealed packing box (see dwg. 7548118).

Categories	Defects	Method of inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Box damaged to extent that contents are exposed or liable to become exposed	Visual	06001
102.	Strapping missing, broken or loose	Visual-Manual	06002
Minor:	AQL 1.50 percent		
201.	Strapping improperly engaged, positioned, or assembled	Visual	06003
202.	Contents loose	Manual	06004
203.	Marking missing, misleading or unidentifiable	Visual	06005

4.2.3 *Testing.*

4.2.3.1 *Primer mixture.*

4.2.3.1.1 *Moisture content (see 3.3) — Major defect — Code No. 07001.* The moisture content of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.1 shall be selected and tested as specified in 4.3.1. If the moisture content is in excess of the percentage specified and if loading has not begun, the batch or blend of batches of the primer mixture shall be rejected. If loading has begun, action on the unloaded primer mixture shall be as specified above and all detonators loaded with

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:29Z
Check the source to verify that this is the current version before use.

the questionable primer mixture shall be rejected.

4.2.3.1.2 *Composition (see dwg. 8787058) Major defect – Code No. 08001.* The composition of the primer mixture shall be determined for each batch or blend of batches at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.3.2, shall be selected and tested as specified in 4.3.2. If the composition of the primer mixture fails to conform to the requirements specified on the applicable drawing and if loading has not begun, the batch or blend of batches of primer mixture shall be rejected. If loading has begun, detonators loaded with the questionable primer mixture shall be rejected.

4.2.3.2 *Functioning.*

4.2.3.2.1 *Sensitivity (see 3.4.1) – Major defect – Code No. 02009.* A sample of 750 primers shall be selected at random from each lot. If 5 or more primers fail to comply with the requirement specified the lot shall be rejected. The test shall be performed as specified in 4.3.3.1, using test equipment as specified in 4.2.4.

4.2.3.2.2. *Waterproofness (see 3.4.2) – Major defect – Code No. 02010.* A sample of 25 primers shall be selected at random from each lot. If one or more primers fail to comply with the requirement specified the lot shall be rejected. The test shall be performed as specified in 4.3.4.2 using test equipment as specified in 4.2.4.

4.2.3.3 *Heat seal test of sealed bag (see dwg. 7548103) Major defect – Code No. 05004.* Sampling, acceptance criteria and test procedures for this test shall be specified in Specification MIL-P-116.

4.2.4 *Inspection Equipment.* Index of Inspection Equipment Number IEL-8787058 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement of parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and wherever inspection equipment drawings are needed.

4.2.4.2 *Supply and maintenance.* Supply add maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL-I-45607.

4.2.4.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of it's accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures.

4.3.1 *Moisture content of primer mixture.* A sample of 0.7 grams shall be accurately weighed to the nearest milligram and dried to a constant weight at 60 degrees C. plus or minus 5 degrees C., or in a desiccator containing calcium chloride. The loss in weight shall be calculated as the percentage of moisture.

4.3.2 *Composition.*

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

4.3.2.1 *Potassium chlorate.*

4.3.2.1.1 *Preparation of solutions.*

4.3.2.1.1.1 *Solution No. 1.* To approximately 800 ml of distilled water in a 1-liter amber glass reagent bottle, 40 gm of potassium sulfocyanate shall be added. The reagent bottle and contents shall be sealed with a rubber stopper and shaken until the solid material has been dissolved. To this solution, 1.0 gm of lead thiocyanate, 1.0 gm of antimony sulfide, and 1.0 gm of lead azide shall be added. Again the reagent bottle shall be stoppered, and the contents vigorously shaken for several minutes, then allowed to stand overnight. Portions of the saturated solution shall be filtered before use.

4.3.2.1.1.2 *Solution No. 2.* To approximately 400 ml of distilled water in a ½-liter amber glass reagent bottle, 1.0 gm of lead thiocyanate, 1.0 gm of antimony sulfide, and 1.0 gm of lead azide shall be added. The reagent bottle shall be sealed with a rubber stopper, and the contents vigorously shaken for several minutes, then allowed to stand overnight. Portions of the saturated solution shall be filtered before use.

4.3.2.1.2 *Procedure.* A portion of approximately 1.0 gm of the sample shall be accurately weighed directly into a tared 30-ml sintered glass crucible of medium porosity. From a burette, 3.0 ml of Solution No. 1 shall be added to the crucible. The solution shall be swirled for exactly 1 minute, care being taken that no liquid be spilled, then aspirated with suction, and the bottom of the crucible wiped dry with tissue paper. The washing shall be continued, using one more 3.0 ml portion, two 2.0 ml portions, and two 1.0 ml portions, making a total of 12.0 ml in all. The crucible shall be removed, and the bottom of the crucible, the funnel, the adapter, and the suction flask washed with water. The test tube shall be placed in the flask and the stem of the filtering funnel inserted into it. As above, the crucible and contents shall be washed with one 1.0 ml portion of Solution No. 1. The solution shall be aspirated with suction, and the filtrate caught in the test tube. The test tube shall be removed, 1.0 ml of distilled water added, then tested for the chlorate ion, as follows:

The tube shall be inclined at an angle of about 45 degrees. About 0.5 ml of a solution containing 1.0 gm of diphenylamine in 100 gm of concentrated sulfuric acid shall be run down the side of the tube from a dropper so that there will be two distinct layers. If an appreciable amount of chlorate ion is present, a distinct blue ring shall be visible at the border of the two layers. On shaking the tube, the ring disappears, but the contents assume a blue coloration, which shall last several seconds, depending on the amount of chlorate ion present. If only a trace of chlorate ion is present, the blue ring may not form, but upon shaking the test tube, a slight bluish coloration shall appear momentarily throughout the solution, and last for only a fraction of a second. If a definite blue ring forms, the washing shall be repeated as before, using one 1.0 ml portion of Solution No. 1, and finally a 0.5 ml portion of the same solution, as needed, depending upon the outcome of the tests for the chlorate ion. (Usually a total of 14.0 or 14.5 ml of Solution No. 1 shall be sufficient.) After the removal of potassium chlorate has been completed, the inside of the crucible shall be washed with 1.0 ml of Solution No. 2, and aspirated immediately. The bottom of the crucible shall be wiped dry with tissue paper, and the crucible dried in an oven at 80 degrees plus or minus 1 degree C. for 30 minutes, cooled in a desiccator, and weighed. The percentage of potassium chlorate shall be calculated as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

$$\text{Potassium chlorate, percent} = \frac{B \times 100}{W}$$

where:

B = Loss in weight of the contents of the crucible.

W = Weight of the sample on a moisture-free basis.

4.3.2.2 *Antimony sulfide.*

4.3.2.2.1 *Preparation of solution of ferric ammonium sulfate.* To approximately 120 ml of distilled water in a ½-liter reagent bottle, 125 gm of ferric ammonium sulfate shall be added. The reagent bottle shall be stoppered, vigorously shaken for several minutes, and then allowed to stand overnight. Portions of the saturated solution shall be filtered before use.

4.3.2.2.2. *Procedure.* A portion of approximately 1 gm of the sample shall be accurately weighed directly into a tared 30 ml sintered glass crucible of medium porosity. A 5.0 ml portion of 1 percent nitric acid shall be added, and the crucible constantly swirled for 1 minute, in order that all the ingredients of the powder except antimony sulfide be dissolved. Care shall be taken that none of the liquid be spilled. The mixture shall be filtered by applying suction. employing a vacuum flask. The crucible shall be removed from the adapter, and the bottom wiped dry with tissue paper. The washing operation shall be repeated, using 5.0 ml of 1 percent nitric acid each time, and the contents swirled for exactly 1 minute. After a total of 40 ml of 1 percent nitric acid has been used, the crucible shall be removed, and the bottom of it washed with water. The funnel, the funnel adapter, and the vacuum flask shall be washed with water, and the filtrate and washings discarded. About 1 ml of a saturated solution of ferric ammonium sulfate shall be placed in the flask. The contents of the crucible shall be treated as before with 5.0 ml of 1 percent nitric acid, and filtered by means of suction into the flask. If the liquid in the flask turns red, due to the presence of the thiocyanate ion *in the filtrate, the washing of the contents* in the crucible shall be repeated with additional 5.0 ml portions of 1 percent nitric acid, until a negative test for the thiocyanate ion has been affected. (Usually a total of 50 ml shall be sufficient.) The crucible and contents shall be rinsed with alcohol, and then with ether. The solution shall be aspirated until the odor of ether can no longer be detected. The crucible and contents shall be dried in an oven at 80 degrees plus or minus 1 degree C. for 30 minutes, cooled in a desiccator, and weighed. The percentage of antimony sulfide shall be calculated as follows:

$$\text{Antimony sulfide, percent} = \frac{A \times 100}{B}$$

where:

A = Weight of residue in the crucible.

B = Weight of sample on a moisture-free basis.

4.3.2.3 *Lead azide.* The lead azide content shall be determined using the (Eudiometer) method and apparatus in MIL-STD-650 Method No. 407.1.

4.3.2.4 *Lead thiocyanate.* The percentage of lead thiocyanate in the sample shall be calculated on a moisture free basis by subtracting from 100 the sum of the percentages of potassium chlorate, antimony sulfide, and lead azide.

4.3.3 *Functioning.*

4.3.3.1 *Sensitivity.* The primer shall be assembled to the applicable test fixture specified in 4.2.4, so that the firing pin will strike the sensitive end of the primer. A steel ball

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:29Z
Check the source to verify that this is the current version before use.

weighing 3.95 ounces maximum shall be dropped on the firing pin to function the primer from a height of 3 inches, maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A primer that fails to fire with an audible report shall be classed defective.

4.3.3.2 *Waterproofness.* The primer shall be immersed under water maintained between 60 degrees F. and 90 degrees F. at the required depth for the time specified. Within one hour after removal from the water the primer shall be subjected to the sensivity test specified in 4.3.3.1. Any primer which fails to fire with an audible report shall be classed defective.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 *Level C.* Packaging shall be as specified on dwg. 7548104.

5.1.2 *Intermediate packaging.* The primers shall be packaged in accordance with dwg. 7548103.

5.2 Packing

5.2.1 *Level C.* The containers shall be packed in accordance with dwg. 7548118.

5.3 Marking. Inner, outer and exterior containers shall be marked in accordance with dwgs. 7548103, 7548104 and 7548118.

5.4 Data cards. Data cards shall be prepared for each lot in accordance with the information specified in Specification MIL-A-2550.

6. NOTES

6.1 Ordering data. Procurement documents shall specify title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 *Inspection equipment lists.* Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection equipment list codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the IEL by the following codes:

CDAF	– Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF	– Contractor's design responsibility on contractor format.
AD	– Army design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:29Z
Check the source to verify that this is the current version before use.

ADMU – Army design, mandatory for use.

CE – Commercial equipment.

SCD – Specification control drawing.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and nonmandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with nonmandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawing.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be nonreproducible diaz or electrostatic prints of top quality full size with black lines on white background and shall provide a legible print produced via the 35-mm microfilm process. Contractor shall submit one copy of the final approved design as a rolled set or flat set.

Source: https://assist.dla.mil -- Downloaded: 202610-23T00:29Z
Check the source to verify that this is the current version before use.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 **Check test for possible deterioration.** If the total time between original acceptance of the primer lot, and the assembly of that lot into the item for which it is intended exceeds 2 years, or if the primers have been subjected to adverse conditions however brief, at any time, the primer lot shall be subjected to and must satisfactorily pass the check test for deterioration immediately before the primers are assembled into the end item. This test shall be performed on primers selected by the Government inspector at the facility assembling the primers into the end item. The test shall be conducted at Government expense without cost to the contractor who loaded the primers, or the contractor assembling the primers into the end item and shall not constitute a basis for rejection against either contractor except when deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor. A sample of 750 primers shall be selected at random from each lot. If 7 or more primers fail to comply with the requirement specified the lot shall be rejected. The sample shall be tested as specified in 4.3.3.1 using test equipment specified in 4.2.4.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1375-A841

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:29Z
Check the source to verify that this is the current version before use.