MIL-S-52317B(ME)
21 September 1983
SUPERSEDING
MIL-S-52317A(ME)
3 November 1970

MILITARY SPECIFICATION

SLING, MULTIPLE LEG, AND CHAIN ASSEMBLY, SINGLE LEG;

FOR MEDIUM CABLEWAY

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is Available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers a multiple-leg chain sling and a single-leg chain assembly.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5420

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

1.2 Classification. The sling and chain assembly shall be the following types as specified (see 6.2):

Type I - With spreader bar.
Type III - Chain assembly.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-G-20241	-	Gasket Material, Wool Felt, Impregnated, Adhesive, Pressure-Sensitive.
MIL-P-23377	-	Primer Coatings: Epoxy-Polyamide, Chemical and Solvent Resistant.
MIL-S-81733	-	Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-889	-	Dissimilar Metals.
MIL-STD-1188	-	Commercial Packaging of Supplies and Equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

Digital Appliances.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13208E5003	-	Sling, Multiple Leg, With Spreader Bar.
TA13212E3254	-	Chain, Single Leg.

(Copies of specifications, standards, and drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI).

ANSI/ASME	-	Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
ANSI/AWS D1.1	-	Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, NY 10018.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The sling and chain assembly shall be as shown on Top Assemblies TA13208E5003, and TA13212E3254 and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the sling or chain assembly. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3).

3.3 Material. Material shall be as specified herein and as shown on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification. Material shall be new and unused.

3.3.1 Material deterioration and control. The sling and chain assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environment to which the item may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, shall be electrically insulated from one another to minimize or prevent galvanic corrosion. Insulation may be provided by an insulating barrier such as a coat of epoxy primer conforming to MIL-P-23377, or corrosion inhibiting sealant conforming to MIL-S-81733 or chromate tape conforming to MIL-G-20241. Protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or designated representative.

3.4 Identification marking. The sling and chain assemblies shall be identified as shown on the drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

3.5 Type I, with spreader bar. The multiple-leg sling shall be as shown on TA13208E5003 and as specified herein. The sling shall lift a load of 6,000 pounds without failure or permanent deformation of any component.

3.6 Type III, chain assembly. The chain assembly shall be as shown on TA13212E3254 and as specified herein. The chain assembly shall lift a load of 8,000 pounds without failure or permanent deformation of any component.

3.7 Workmanship.

3.7.1 Steel fabrication. Steel used in the fabrication of the slings shall be free from laminations and bends. Bent material shall be straightened by methods that will not change the physical properties of the material. Steel may be sheared, sawed, or flame cut. Burned surfaces of flame-cut material shall be ground or machined to remove ash and cooling checks. All burrs and projections shall be removed from edges of components.

3.7.2 Welding and welders.

3.7.2.1 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are subjected to proof and service loadings. Welding shall be done by the shielded metal-arc or gas metal-arc method and shall conform to the ANSI/AWS D1.1 Structural Welding Code-Steel. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part.

3.7.2.2 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

ANSI/ASME Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.
ANSI/AWS D1.1, Structural Welding Code, Section 5, Qualification.

Contractors who make only horizontal welds need not qualify welders for "all position welding". Subject to approval by the Government, the contractor's standard welder qualification may be substituted in lieu of the above codes provided that the contractor's procedure is equivalent to the above codes. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

contractor shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with ASME or AWS codes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the Quality assurance provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.4 and 6.5).

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows.

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article sling or chain assembly shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article sling or chain assembly shall be tested as specified in 4 5.2. Failure of any test shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and test shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. AQL shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The sling and chain assemblies shall be examined as specified herein for the following defects:

Major

101. Materials not as specified.
102. Materials are not corrosion resistant or treated to be made corrosion resistant for the applicable storage and operating environment.
103. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
104. Contractor does not have documentation available for identification of material, material finishes or treatments.
105. Workmanship not as specified.
106. Incomplete or incorrect assembly.
107. Any part or component not in accordance with the QAP requirements as shown on the drawings.

Minor

201. Dimensions other than those identified by QAP data not as specified.
202. Identification marking incorrect, missing or illegible.

4.5.2 Tests.

4.5.2.1 Type I sling. Suspend a load of 6,000 pounds, 1,500 pounds per hook, from the hooks of the sling assembly for a period of 5 minutes. Support

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:14Z
Check the source to verify that this is the currentversion before use.

the sling assembly by the lifting bar in the center of the spreader bar. Breakage, weld failure, or permanent deformation of any component shall constitute failure of this test.

4.5.2.2 Type III chain assembly. Suspend a load of 8,000 pounds from the hook of the chain assembly for a period of 5 minutes. Failure or permanent deformation of any part of the chain assembly shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

108.	Boxes not as specified for level A or B.
109.	Quantities packed together exceed limitations of the box for level A or B.
110.	Packing not in accordance with the referenced document as specified for commercial.
111.	Marking, missing, illegible, incorrect, or incomplete for level A, B, or commercial.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.1.1 Level A. Sling and chain assemblies of like description shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional, in quantities not to exceed the weight limitation of the box. The contents shall be blocked and braced to prevent free movement. Box closure and strapping shall be in accordance with the appendix of the applicable box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

5.1.2 Level B. Packing shall be as specified in 5.1.1 for level A except boxes shall be domestic type or class as applicable.

5.1.3 Commercial. The sling and chain assemblies shall be packed in accordance with MIL-STD-1188.

5.2 Marking (see 6.7).

5.2.1 Military. Marking for military levels of protection (level A or B) shall be in accordance with MIL-STD-129.

5.2.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The sling and chain assemblies are intended to be used in lifting components of a cableway and in transporting cargo on a cableway.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type of sling required (see 1.2).

c. When a first article is required for inspection and approval and the number of units required (see 3.2).

d. Level of packing required (see 5.1).

6.3 First article. When a first article inspection is required the item shall be examined and should be a first produced sling or chain assembly. The contracting officer should include specific instructions in the acquisition documents regarding arrangements for examinations and approval of the document's first article.

6.4 Quality assurance provisions (QAP) records. The contracting officer should require the contractor to maintain records of all QAP inspections. A suggested paragraph is as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

"The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include as a minimum, lot size, sample size, drawing requirement, actual measurement, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.5 Definitions.

6.5.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.6 Classification change. Type II slings, without spreader bar, have been discontinued since they are no longer required.

6.7 Packaging. Preservation is not required, but for purposes of preservation/packing level marking, preservation shall be designated as level A.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5420-A333

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-52317B(ME)	Sling, Multiple Leg, and Chain Assembly, Single Leg: for Medium

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
Cableway	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use i submitting comments and suggestions for improvements. All users of military standardization documents are invited to provid suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, an mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, w too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTA
NECESSA
IF MAILE
IN THE
UNITED STA

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Mobility Equipment Research & Development
Command
Attn DRDME DS
Fort Belvoir VA 22060

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.