MILITARY SPECIFICATION

TRACER ASSEMBLY, 12525043

This specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies for the Department of Defense.

1. SCOPE

1.1 Scope. - This specification covers the requirements and quality assurance provisions for the Tracer Assembly, 12525043. The Tracer Assembly covered by this specification is intended for use in Cartridge, 120mm, TPCSDS-T, M865.

2. APPLICABLE DOCUMENTS

2.1. Government documents.

2.1.1 Specifications, standards, and handbooks. - Unless otherwise specified, the following specifications, standards and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-1167	Ammunition Data Card
MIL-STD-1234	Pyrotechnics: Sampling, Inspection and Testing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army ARDEC, Attn: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC-1370

Distribution Statement A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

FEDERAL

FED-STD-101 Packaging Materials, Test Procedures for

(Unless otherwise indicated, copies of federal and military specifications, standards, and hard books are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, Pennsylvania 19111-5094.)

2.1.2 Order documents, other GOVERNMENT documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those listed in the solicitation.

DRAWINGS See 6.8

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

12525043	Tracer Assembly
12525041	Tracer Charge Composition
12524919	Igniter Composition
12525044	Charge Tracer
12525045	Charge Igniter
12525039	Cup Tracer

PUBLICATIONS

CODE OF FEDERAL REGULATIONS

Title 49	Transportation

(The Interstate Commerce Commission Regulations are now a part of the Code of Federal Regulations, available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders for the above publication should cite, "49 CFR 100-199 latest revision.)

(Copies of drawings and publications required by suppliers in connection with specific acquisition functions, should be obtained from the contracting activity or as directed by the Contracting Officer.)

2.2 Order of precedence. – In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. – Materials shall be in accordance with drawings in paragraph 2.1 and the applicable drawings and specifications referenced thereon.

3.2 Components. – Components shall be in accordance with paragraph 2.1 and the applicable drawings and specifications referenced thereon.

3.3 Tracer performance.

3.3.1 Static performance.

3.3.1.1 Burn time. – The minimum static burn time shall be 3.0 seconds.

3.3.2 Performance.

3.3.2.1 Tracer function. – Tracer for each cartridge shall ignite within approximately 250 meters of the muzzle and shall show visible evidence of burning to a minimum distance of 750 meters.

3.4 First article. – When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3).

3.5 Workmanship. – The tracer charge shall be free of cracks, chips, broken edges, striations, capping and laminations. The tracer charge and igniter composition shall be free of dirt, grease and foreign material. Packaging shall be free of dirt and grease.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. – Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use their own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. – All items must meet all requirements of Sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections.- The following types of inspection shall be conducted on this item:

a) First article inspection

b) Quality conformance inspection.

4.3 First article inspection.

4.3.1 The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing/Specification	Quantity
Charge, Tracer	12525044	100 pellets
Composition, Igniter	12524919	400 grams
Cup Tracer	12525039	10 pieces
Charge Igniter	12525045	100 pellets
Tracer Assembly	12525043	50 pieces
Tracer Charge Composition	12525041	400 grams

A first article sample or portion thereof as directed by the procuring agency shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacture processes, material used, drawing, specification or source of supply, such as to significantly affect product uniformity as determined by the Government.

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. - See MIL-A-48078. Unless otherwise specified in the classification of defects, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II or continuous sampling in accordance with MIL-STD-1235 may be used if approved by the Government. Inspection shall be in accordance with the applicable Quality Conformance Inspection table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Tracer Assembly, 12525043				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Tracer Assembly (DWG 12525043)	10		3.2 and 3.5	4.4.2.6
	Examination for Defects				
	Static Tests Burn Time	10		3.3.1.1	4.5.1.1
	Operational Tests				
	Hot Temperature (+52°C - 3°C) Tracer Function	10			4.5.1.2
	Ambient Temperature (21°C ± 1.5°C) Tracer Function	10		3.3.2.1	4.5.1.2
	Cold Temperature (-32°C + 3°C) Tracer Function	10			4.5.1.2
	Tracer Charge Composition (DWG 12525041)	400 grams		3.1.	4.4.2.3
	Charge, Tracer (DWG 12525044) Examination for Defects	100 pellets		3.2.	4.4.2.2

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF CHARACTERISTICS AND TESTS

PARAGRAPH	TITLE TRACER ASSEMBLY, 12525043		SHEET 2 OF 2		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Charge Igniter (DWG 12525045)	100 pellets		3.2.	4.4.2.4
	Igniter Composition (DWG 12524919)	400 grams		3.1	4.4.2.1
	Tracer Cup (DWG 12525039)	10		3.2	4.4.2.5

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.1	TITLE Igniter Composition		SHEET 1 OF 1		DRAWING NUMBER 12524919
					NEXT HIGHER ASSEMBLY 12525044
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture content maximum	1/		3.1	4:5.2
102	Composition	2/		3.1	Certification
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1/ One sample from each batch or 8 hours production, whichever occurs sooner.

2/ Each batch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Charge, Tracer				12525044
					NEXT HIGHER ASSEMBLY 12525043
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pellet diameter		0.40%	3.2	Gage
102	Pellet weight		100%	3.2	Scale
103	Composition	1/		3.1	Certification
104	Moisture content	2/		3.1	4.5.2
105	Density	3/		3.2	Gage/4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1/ Each batch.
2/ One sample from each batch or 8 hours production, whichever occurs sooner.
3/ Ten samples from each batch run, or from each eight hours of production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Tracer Charge Composition				12525041
					NEXT HIGHER ASSEMBLY 12525044
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture content max.	1/		3.1	4.5.2
102	Composition	2/		3.2	Certification
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES:
1/ One sample from each batch or 8 hours production, whichever occurs sooner.
2/ Each batch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.4	TITLE Charge, Igniter		SHEET 1 OF 1		DRAWING NUMBER 12525045
					NEXT HIGHER ASSEMBLY 12525043
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pellet diameter		0.40%	3.2	Gage
102	Pellet weight		0.40%	3.2	Scale
103	Composition	1/		3.1	Certification
104	Moisture content	2/		3.1	4.5.2
105	Pellet density	3/		3.2	Gage/4.5.3
Minor					
201	Evidence of poor workmanship		0.65%	3.5	Visual

NOTES: 1/ Each batch.
2/ One sample from each batch or 8 hours production, whichever occurs sooner.
3/ Ten samples from each batch run, or from eight hours of production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH 4.4.2.5	TITLE Cup, Tracer		SHEET 1 OF 1		DRAWING NUMBER 12525039
					NEXT HIGHER ASSEMBLY 12525043
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%	3.2	Gage
102	Length		0.40%	3.2	Gage
103	Primer coating missing		0.40%	3.2	Visual
104	Threads in Zone A		0.40%	3.2	Gage
Minor					
201	Inside diameter		0.65%	3.2	Gage
202	Thickness through bottom		0.65%	3.2	Gage
203	Burrs		0.65%	3.5	Visual
204	Foreign matter		0.65%	3.5	Visual
205	Crack, puncture, or other damage		0.65%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION.

CLASSIFICATION OF DEFECTS AND TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Tracer Assembly				12525043
					NEXT HIGHER ASSEMBLY 12525001
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter, maximum		0.40%	3.2	Gage
102	Total Length, maximum		0.40%	3.2	Gage
103	Charge missing or less than minimum, required depth from shoulder		0.40%	3.2	Visual
104	Igniter charge chipped or broken on any one step in excess of 1/3 of the total area of the step, or total aggregate of chipped or broken area of all steps in excess of 1/3 of the total area of the largest step		0.40%	3.5	Visual
105	Static burn time	n = 10 c = 0	N/A	3.3.1.1	4.5.1.1
106	Operational Test				
	Tracer Function (21°C ± 1.5°C)	n = 10 c = 1	N/A	3.3.2.1	4.5.1.2
	Tracer Function (-32°C + 3.0°C)	n = 10	N/A		4.5.1.2
	Tracer Function (+52°C - 3.0°C)	n = 10	N/A		4.5.1.2

NOTES:
n = Number of samples
c = Number of allowable failures, additional failures are cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. – The inspection equipment required to perform the examinations and test prescribed herein is described in the "Paragraph reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Methods of Inspection.

4.5.1 Tracer performance.

4.5.1.1 Static performance. – The tracer assembly shall be loaded into fins or simulator mounts with the same process used in production of fin and tracer assemblies as specified in Drawing 12525001. Test units shall then be secured in a vertical or horizontal position. A quickmatch, M100 electric match or equivalent, shall be attached to the closure plug in such a manner as to ignite the igniter composition. The electric match shall then be ignited remotely and test instrumentation observed to verify proper tracer static function. In case of failure of the igniter compound, the ignition process may be repeated. Test equipment shall be in accordance with 4.4.3.

4.5.1.2 Operational performance. – The tracer assembly shall be loaded into fins using the same processes as apply in production per drawing 12525000 and 12525001. The appropriate number of test cartridges shall be assembled.

4.5.1.2.1 Testing. - A total of 30 cartridges shall be tested and evaluated for tracer performance. The 30 cartridges shall consist of ten cartridges each conditioned to 21 ± 1.5°C, 52 - 3°C and -32 + 3°C. The test cartridges shall be temperature conditioned for 24 hours minimum. All cartridges shall be fired from a M256 gun.

4.5.1.2.2 Tracer function. - Tracer performance of each cartridge shall be monitored for conformance to the tracer function requirements as follows:

a. All tests requiring verification of proper tracer function shall be performed during daylight hours.

b. Verification of proper tracer function shall be performed visually by three observers. A tracer shall be considered to have met requirements if at least one observer confirms that the tracer functioned properly.

c. The three observers shall be positioned within 50 meters to the rear of the gun and shall be situated approximately 30 meters to either side of the gun. All three observers shall utilize binoculars with 7x by 50mm magnification.

d. A video camera shall be located at the line of fire and shall record tracer functioning from approximately 250 meters to 750 meters. In addition a video camera shall be located to record proper functioning at 750 meters. The videotape recordings from these cameras shall be utilized, whenever necessary, to assist the observers in their decision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

e. A video camera shall be located downrange so as to record tracer functioning at the 2500 meter target. This recording shall be utilized for informational purposes only. All videotape recordings shall be analyzed to determine the rate of tracer functioning at 2500 meters. This information shall be provided to the technical agency to support a government data base on tracer functioning.

4.5.1.2.3 Tracer performance shall be considered acceptable if no more than one tracer fails to meet the tracer functioning requirements specified in paragraph 3. If more than one tracer fails to meet requirements, the lot shall be referred to the technical agency for disposition. Performance of tracers fired at -32°C and +52°C will be noted but shall not be considered for acceptance of the lot.

4.5.2 Moisture and total volatile content of tracer and igniter charge. – The contractor shall provide adequate controls to ensure the compliance of each lot with the applicable requirement. The contractor shall test a minimum of one randomly selected sample from each batch or from each 8 hours production, whichever is the lesser amount. Composite samples shall not be used for determining compliance. Failure to comply with the applicable requirement shall be cause for rejection of the parent quantity represented by the sample. The test shall be performed in accordance with MIL-STD-1234 Method 102.2.1.

4.5.3 Density of tracer and igniter charge. – The density of the tracer and igniter charge pellets shall be determined by the following method. The contractor shall calculate density on a minimum of 10 randomly selected samples from each batch run, or from each 8 hours of production. Each pellet shall be weighed and measured for length and diameter. Volume and density shall then be calculated using these measurements. Tracer pellet density shall be per drawing 12525043. Igniter pellet density shall be per drawing 12525045. Failure to comply with the applicable requirement shall be cause for rejection of the parent quantity represented by the sample.

5. PACKAGING

5.1 Preservation and packaging.

A. The tracer assembly, 12525043 shall be preserved and packaged to comply with the minimum requirements of (DOT) CFR 49, Part Number 173.105, entitled, Percussion, Tracer, Combination, Time Fuzes and Tracers. Preservation per Section 5.2.1, this specification.

5.2 Packing.

A. Tracer assembly shall be packed to provide:

B. Protection against normal transportation/vibration shock (Federal Test Method Standard 101, Method 5019.1).

C. Protection against internally/externally imposed stacking pressures.

D. Relative humidity protection during shipping/storage (10 percent R.H. until assembled).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

E. Strong, tight, outside wooden or DOT Specification 23F Shipping Container, per CFR 49, Part Number 173.105.

5.3 Marking.

A. Marking of inner and outer containers to be per MIL-STD-129 and CFR 49, Part Number 173.105.

B. Labeling of shipping container per CFR 49, Part Number 173.105, and MIL-STD-129.

5.4 Data card. – Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Intended use. – The items covered by this specification are intended for use in the 120mm ammunition.

6.2 Ordering data. – See MIL-A-48078.

6.2.1 Acquisition requirements. See MIL-A-48078.

6.2.2 Data requirements. – When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, subpart 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Paragraph	Data Requirement	Applicable DID No.
4.4.3	Inspection Equipment Design Approval	DI-R-1714
6.2.3	Ammunition Data Cards	DI-MISC-80043

(Data Item Descriptions related to this specification, and identified in Section 6 will be approved and listed as such in DOD 5000.19L, Vol. II, AMSDL. Copies of Data Item Descriptions required by contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.2.3 Submission of test data and ammunition data cards. – In addition to the normal distribution of records when the projectile is procured by the U.S. Army Armament, Materiel and Chemical Command, one copy of all ballistic tests data and ammunition data cards shall be forwarded to each of the following: Commander, ARDEC, ATTN: SMCAR-CCH-V, and AMSMC-QAT-A(D), Picatinny Arsenal, New Jersey 07806-5000; and Commander, AMCCOM, ATTN: AMSMC-QAD(R), Rock Island, Ilinois, 61299-6000.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

6.3 Tracer definition. – The tracer as referred to in this specification consists of two tracer charge pellets and a igniter pellet compressed in a tracer cup.

6.4 Moisture. – The igniter and tracer compositions, and the pellets formed thereof, are hygroscopic and will deteriorate rapidly when exposed to moisture. Small amounts of moisture present in or absorbed by the compositions or pellets, will eventually result in unsatisfactory functioning. It is highly desirable that the ingredients, compositions, and pellets be carefully safeguarded from exposure to moisture and humid atmospheres. For insurance of a satisfactory tracer function, it is recommended that the blending and pelleting buildings be air conditioned in a manner which will hold the humidity of the atmosphere less than 60 percent.

6.5 Alternate testing procedures. – Alternative testing procedures may be proposed by the contractor when such testing and procedures provide as a minimum the quality assurance provisions specified herein. Prior to applying alternative procedures, the contractor shall describe them in a written proposal and shall demonstrate that their effectiveness is equal to or better than the quality assurance provisions specified herein. Alternative testing procedures must have the approval of the Government Contracting Officer prior to use.

6.6 Shipping.– If shipment is necessary, Department of Transportation (DOT) Class and Marking cited on the affected item drawings is applicable. Material must be adequately and properly packaged in accordance with applicable DOT Packaging Requirements (paragraph 173.61, CODE OF FEDERAL REGULATIONS (CFR) Title 49).

6.7 Hazard notice. – The tracer and igniter charge and the tracer and igniter charge composition described herein are flammable and/or explosive and consequently present hazards in manufacture, handling, storage and shipment. The contractor should recognize these hazards and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling, and electrically induced incidents.

6.8 Drawings. – Drawings listed in Section 2 of this specification in the heading U.S. Army Armament Research and Development Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or U.S. Army Armament and Development Center drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.9 Subject term (keyword) listing. –

Ammunition
Ballistic Testing
Cannon (120mm)
Cartridge (120mm)
Tank
Tracer

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

Custodian
Army (AR)

Preparing activity
Army (AR)

Project Number:1370-A316

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-70988	900815

3. DOCUMENT TITLE

Tracer Assembly, 12525043

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)
COMMANDER, U.S. ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER	(1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code) ATTN: AMSMC-QAA(D) PICATINNY ARSENAL, NEW JERSEY 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:16Z
Check the source to verify that this is the current version before use.