The documentation and process conversion measures necessary to comply with this document shall be completed by 6 April 2023.

INCH-POUND

MIL-PRF-19500/726E
w/AMENDMENT 1
6 January 2023
SUPERSEDING
MIL-PRF-19500/726E
25 September 2017

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, SCHOTTKY RECTIFIER,
TYPES 1N6940, 1N6941, 1N6942
JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

* 1.1 Scope. This specification covers the performance requirements for silicon, Schottky power surface mount rectifier diodes in a low profile package. Three levels of product assurance (JANTX, JANTXV, and JANS) are provided for each device type as specified in MIL-PRF-19500.

1.2 Package outlines. The device package outline is as follows: Surface mount in accordance with figure 1 for all encapsulated device types.

1.3 Maximum ratings. Unless otherwise specified T_C = +25°C.

Column 1	Column 2	Column 3	Column 4	Column 5	Column 6
Types	V_{RWM}	I_O T_C = +100°C	I_{FSM} t_p = 8.3 ms, T_C = +25°C	$R_{\theta JC}$	T_{STG} and T_J
	V dc	A dc	A (pk)	°C/W	°C
1N6940UTK3, CS, AS	15	150	2,000	.35	-65 to +150
1N6941UTK3, CS, AS	30	150	2,000	.35	
1N6942UTK3, CS, AS	45	150	2,000	.35	

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil/.

AMSC N/A

FSC 5961

* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

1.4 Primary electrical characteristics. Unless otherwise specified, T_C = +25°C.

Column 1	Column 2					Column 3		Column 4			Column 5
Types	V_F Maximum forward voltage at T_C = +25°C V dc at I_F					V_F Maximum forward voltage T_C = +125°C V dc at I_F		I_R Maximum reverse current (see column 2) mA at V_{RWM}			C_J Maximum junction capacitance f = 1MHz V_R = 5 VDC
	25A	50A	75A	110A	150A	110A	150A	T_J = +25°C	T_J = +125°C	V_R	pF
1N6940UTK3, CS, AS			.43		.50		.43	5	1,200	15	10,000
1N6941UTK3, CS, AS	.42	.50					.50	5	1,200	30	7,500
1N6942UTK3, CS, AS	.40	.46	.48	.55	.59	.50	.57	5	500 1,500	30 45	7,000

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for PIN construction example and 6.5 for a list of available PINs.

1.5.1 JAN certification mark and quality level for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: “JANTX”, “JANTXV” and "JANS".

1.5.2 Device type. The designation system for the device types of diodes covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The diodes of this specification sheet use the first number and letter symbols "1N".


1.5.2.2 Second number symbols. The second number symbols for the diodes covered by this specification sheet are as follows: "6940", "6941", and "6942".

1.5.2.3 Suffix letters. The following suffix letters are incorporated in the PIN for this specification sheet:

UTK3	Indicates a surface mount package of figure 1 with no copper strap.
UTK3AS	Indicates a surface mount package of figure 1 with the copper strap attached to the anode.
UTK3CS	Indicates a surface mount package of figure 1 with the copper strap attached to the cathode.

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.



Ltr	Dimensions			
	Inches	Inches	mm	mm
	Min	Max	Min	Max
BL	.420	.440	10.67	11.18
BLT		.125		3.18
BT		.115		2.92
C	.469	.509	11.91	12.93
E	.038	NOM	.97	NOM
F	.331	.341	8.41	8.66
LC	.040	NOM	1.02	NOM
LF	.055	.075	1.40	1.91
LT	.005	.015	.127	.381
LW	.185	.215	4.70	5.46

NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. For anode, cathode, and strap connections, see 3.4.1 and 3.4.3.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil).

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturer's list (QML-19500) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. The interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 herein.

3.4.1 Diode construction. These devices shall be constructed utilizing double plug construction with eutectic bonding between both sides of the silicon die and terminal pins (see MIL-PRF-19500). Metallurgical bond shall be in accordance with the requirements of category II in MIL-PRF-19500. The diode body is ceramic. All seals are eutectic solder. Strap material is a copper alloy or copper sandwich. The 1N6940UTK3, 1N6941UTK3 and 1N6942UTK3 have no strap. The strap connects to the cathode on 1N6940UTK3CS, 1N6941UTK3CS, and 1N6942UTK3CS and to the anode on 1N6940UTK3AS, 1N6941UTK3AS, and 1N6942UTK3AS.

3.4.2 Lead formation and finish. Unless otherwise specified, lead finish (pads, bottom pad and strap foot) shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750 and herein. Where a choice of lead finish or formation is desired, it shall be specified in the acquisition document (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

3.4.3 Polarity. Polarity shall be marked with the appropriate diode symbol on the strap or with a dot on the cathode side of the seal ring on "no strap" devices (see figure 1).

3.5 Marking. Marking shall be in accordance with MIL-PRF-19500 and herein. All marking may be omitted from the device except for the polarity marking. When present, part number may be abbreviated (ex: JS6940 for JANS1N6940UTK3). All marking that is omitted from the body of the device shall appear on the label of the initial container.

3.6 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4 and table I.

3.7 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table I herein.

3.8 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and table I, II, and III).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 Construction verification. Cross sectional photos from three devices shall be submitted in the qualification report.

4.2.2 Group E qualification. Group E qualification shall be performed herein for qualification or requalification only. In case qualification was awarded to a prior revision of the specification sheet that did not request the performance of table II tests, the tests specified in table II herein shall be performed on the first inspection lot to this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

* 4.3 Screening. Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	Measurements for JANS level	Measurements for JANTX and JANTXV levels
(1) 3b	Condition A, one pulse, I_O = 0, V_{RWM} = 0, I_{FSM} = see 1.3, column 4 herein.	Condition A, one pulse, I_O = 0, V_{RWM} = 0, I_{FSM} = see 1.3, column 4 herein.
3c	Thermal impedance (see 4.3.1)	Thermal impedance (see 4.3.1)
4	Not applicable	Not applicable
5	Not applicable	Not applicable
7b	Optional	Optional
8	Serialization required.	Not applicable
9	Not applicable	Not applicable
10	Not applicable	Not applicable
11	V_{F1} and I_{R1}	V_{F1} and I_{R1}
12	Method 1038 of MIL-STD-750, test condition A; T_C = +80°C, t = 240 hours, V_{RM} = 80 percent of rated V_{RWM} = see 1.3, column 2 herein V (pk), I_O = 0, f = 60 Hz; alternate test: V_{RM} = 80 percent of rated V_{RWM} (see 1.3, column 2 herein for V_{RWM}), T_C = +80°C	Method 1038 of MIL-STD-750, test condition A; T_C = +80°C, t = 48 hours, V_{RM} = 80 percent of rated V_{RWM} = see 1.3, column 2 herein V (pk), I_O = 0, f = 60 Hz; alternate test: V_{RM} = 80 percent of rated V_{RWM} (see 1.3, column 2 herein for V_{RWM}), T_C = +80°C
13	Subgroup 2, of table I herein, and subgroup 3 of table I herein, V_{F1} and I_{R1}; ΔV_{F1} = ±50 mV (pk); ΔI_{R1} = ±1 mA dc or 100 percent from the initial value, whichever is greater. Scope display evaluation (see table I, subgroup 7)	Subgroup 2, of table I herein excluding thermal impedance; V_{F1} and I_{R1}; ΔV_{F1} = ±50 mV (pk); ΔI_{R1} = ±1 mA dc or 100 percent from the initial value, whichever is greater. Scope display evaluation (see table I, subgroup 7)
14b	Required	Required
15	Not applicable	Not applicable

(1) Surge shall precede thermal impedance. These tests shall be performed anytime after screen 3 and before screen 10.

4.3.1 Thermal impedance. The thermal impedance measurements shall be performed in accordance with method 3101 of MIL-STD-750. See table E-IX, group E, subgroup 4 of MIL-PRF-19500.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500 and table I herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables E-VIA (JANS) and E-VIB (JANTX and JANTXV) of MIL-PRF-19500 and 4.4.2.1 and 4.4.2.2 herein. Delta measurements shall be in accordance with table III herein.

4.4.2.1 Quality level JANS, table E-VIA of MIL-PRF-19500.

	Subgroup	Method	Condition
*	B4	1037	ΔT_C = +85°C minimum, I_F = 2 A minimum.
	B5	1038	Condition B, I_F = 1 A dc minimum, adjust T_A and I_F to achieve T_J = +150°C, +0°C, -35°C, t = 240 hours min; (heat sinking allowed).

4.4.2.2 Quality levels JAN, JANTX and JANTXV, table E-VIB of MIL-PRF-19500.

Subgroup	Method	Condition
B3	1037	ΔT_C = +85°C minimum, I_F = 2 A minimum.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500. Delta measurements shall be in accordance with table III herein.

Subgroup	Method	Condition
C5	3101	I_H = 20 A to 50 A, I_M = 10 mA to 250 mA, t_H = thermal equilibrium; t_{MD} = 200 μs maximum.
C6	1037	ΔT_C = +85°C minimum, I_F = 2 A minimum for 6,000 cycles.

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-IX of MIL-PRF-19500 and table II herein. Delta measurements shall be in accordance with table III herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables as follows.

4.5.1 Pulse measurements. Conditions for pulse measurement shall be as specified in section 4 of MIL-STD-750.

4.5.2 Avalanche energy test. The Schottky rectifier shall be capable of absorbing the reverse energy of 350 rectangular pulses, t_p =1 μsec, I_R = 2 A at 1 kHz. This will be performed during wafer or die level prior to device assembly.

* 4.5.3 Scope display evaluation. The reverse breakdown characteristics shall be viewed on an oscilloscope with display calibration factors of 2-mA/division and 10 to 20 V/division. Reverse current over the knee shall be at least 10 mA. Each device may exhibit a slightly rounded characteristic and any discontinuity or dynamic instability of the trace shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance 2/	3101	I_M = 10 mA to 250 mA, I_H = 200 A, t_H = 2 ms, t_{md} = 200 μs maximum	$Z_{\theta JX}$			
1N6940UTK3, CS, AS					.12	°C/W
1N6941UTK3, CS, AS					.12	°C/W
1N6942UTK3, CS, AS					.12	°C/W
* Forward voltage	4011	Pulsed test (see 4.5.1) t_p = 300 μs Condition B.	V_{F1}			
1N6940UTK3, CS, AS		I_F = 75 A (pk)			.43	V
1N6941UTK3, CS, AS		I_F = 25 A (pk)			.42	V
1N6942UTK3, CS, AS		I_F = 25 A (pk)			.40	V
* Forward voltage	4011	Pulsed test (see 4.5.1) t_p = 300 μs Condition B.	V_{F2}			
1N6940UTK3, CS, AS		I_F = 150 A (pk)			.50	V
1N6941UTK3, CS, AS		I_F = 50 A (pk)			.50	V
1N6942UTK3, CS, AS		I_F = 50 A (pk)			.46	V
* Reverse current leakage	4016	DC method, Condition A or B.	I_{R1}			
1N6940UTK3, CS, AS		V_R = 15 V			5.0	mA
1N6941UTK3, CS, AS		V_R = 30 V			5.0	mA
1N6942UTK3, CS, AS		V_R = 45 V			5.0	mA
Breakdown voltage	4021	Pulsed test (see 4.5.1) t_p = 35 ms	V_{BR1}			
1N6940UTK3, CS, AS		I_R = 50 mA (pk)		16.5		V
1N6941UTK3, CS, AS		I_R = 50 mA (pk)		33		V
1N6942UTK3, CS, AS		I_R = 50 mA (pk)		50		V

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection – Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 3						
High temperature operation:		T_C = +125°C				
Forward voltage	4011	Pulsed test (see 4.5.1) tp = 300 µs Condition B.	V_{F3}			
1N6940UTK3, CS, AS		I_F = 150 A (pk)			.43	V
1N6941UTK3, CS, AS		I_F = 150 A (pk)			.50	V
1N6942UTK3, CS, AS		I_F = 110 A (pk)			.50	V
1N6942UTK3, CS, AS		I_F = 150 A (pk)	V_{F4}		.57	V
Reverse current leakage	4016	DC method, Condition A or B.	I_{R2}			
1N6940UTK3, CS, AS		V_R = 15 V			1,200	mA
1N6941UTK3, CS, AS		V_R = 30 V			1,200	mA
1N6942UTK3, CS, AS		V_R = 30 V			500	mA
Reverse current leakage	4016	DC method, Condition A or B.	I_{R3}			
1N6942UTK3, CS, AS		V_R = 45 V			1,500	mA
Low temperature operation:		T_C = -55°C				
Breakdown voltage	4021	Pulsed test (see 4.5.1) t_p = 35 ms	V_{BR2}			
1N6940UTK3, CS, AS		I_R = 50 mA (pk)		15		V
1N6941UTK3, CS, AS		I_R = 50 mA (pk)		30		V
1N6942UTK3, CS, AS		I_R = 50 mA (pk)		45		V
Subgroup 4						
Junction capacitance	4001		C_J			
1N6940UTK3, CS, AS		V_R = 5 V dc, f = 1 MHz,			10,000	pF
1N6941UTK3, CS, AS		V_{SIG} = 50 mV (p-p)			7,500	pF
1N6942UTK3, CS, AS					7,000	pF
Subgroup 5						
Not applicable						

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

* TABLE I. Group A inspection – Continued.

Inspection 1/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 6						
Surge	4066	I_{FSM} = see 1.3, column 4, ten surges of 8.3 ms each at 1 minute intervals. Condition A: T_C = 25°C				
Electrical measurements		See table I, subgroup 2 herein				
Subgroup 7						
* Scope display evaluation	4023	See 4.5.3				
Electrical measurements		See table I, subgroup 2 herein				

1/ For sampling plan, see MIL-PRF-19500.
2/ For end-point measurements, this test is required for the following subgroups:
Group B, subgroups 3, 4, and 5 (JANS).
Group B, subgroups 2 and 3 (JANTX and JANTXV).
Group C, subgroups 2 and 6.
Group E, subgroup 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) – for qualification and requalification only.

Inspection	MIL-STD-750		Qualification
	Method	Conditions	
Subgroup 1			n = 45, c = 0
Thermal shock (liquid to liquid)	1056	Test condition A, 0°C to +100°C	
Temperature cycling (air to air)	1051	Test condition C, 500 cycles	
Hermetic seal	1071		
Electrical measurements		See table I, subgroup 2 and table III herein	
Subgroup 2			n = 45, c = 0
Life test	1038	Condition A, t = 1,000 hours, V_R = 80 percent V_{rated} (see 1.3, column 2 herein)	
Electrical measurements		See table I, subgroup 2 and table III herein	
Subgroup 4			
Thermal impedance curves		See MIL-PRF-19500.	
Subgroup 5			
Not applicable			
Subgroup 7			n = 22, c = 0
Forward surge	4066	I_{FSM} = see 1.3, 110 percent of column 4; ten surges of 8.3 ms each at 1 minute intervals, condition A: T_C = 25°C	
Electrical measurements		See table I, subgroup 2 except for thermal impedance	

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

TABLE III. Groups B, C, and E delta requirements. 1/ 2/ 3/ 4/ 5/

Step	Inspection 1/	MIL-STD-750		Symbol	Limit	Limit	Unit
		Method	Conditions		Min	Max	
* 1.	Forward voltage	4011	Condition B	ΔV_{F1}	±50 mV		
* 2.	Reverse current leakage	4016	DC Method, Condition A or B.	ΔI_{R1}	±1 mA or 100 percent of initial value whichever is greater.		

1/ The delta measurements for table E-VIA (JANS) of MIL-PRF-19500 are as follows: Subgroups 4 and 5, see table III herein, steps 1 and 2.
2/ The delta measurements for table E-VIB (JANTX and JANTXV) of MIL-PRF-19500 are as follows: Subgroup 3, see table III herein, steps 1 and 2.
3/ The delta measurements for table E-VII of MIL-PRF-19500 are as follows: Subgroup 6, see table III herein, steps 1 and 2.
4/ The delta measurements for table E-IX of MIL-PRF-19500 are as follows: Subgroups 1 and 2, see table III herein, steps 1 and 2.
5/ Devices which exceed the table I limits for this test shall not be accepted.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.2).


d. The complete PIN, see 1.5 and 6.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QPDSIS-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 PIN construction example.

6.4.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



6.5 List of PINs.

6.5.1 List of PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for devices of the "TX" quality level	PINs for devices of the "TXV" quality level	PINs for devices of the "S" quality level
JANTX1N6940UTK3	JANTXV1N6941UTK3	JANS1N6942UTK3
JANTX1N6940UTK3AS	JANTXV1N6941UTK3AS	JANS1N6942UTK3AS
JANTX1N6940UTK3CS	JANTXV1N6941UTK3CS	JANS1N6942UTK3CS

6.6 Request for new types and configurations. Requests for new device types or configurations for inclusions in this specification sheet should be submitted to: DLA Land and Maritime, ATTN: VAC, Post Office Box 3990, Columbus, OH 43218-3990 or by electronic mail at Semiconductor@dla.mil or by facsimile (614) 692-6939 or DSN 850-6939.

* 6.7 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

(Project 5961-2022-080)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T05:13Z
Check the source to verify that this is the current version before use.